

Integrations

Alert Rules

V5.4.11

CONTENTS

1	Alert Rules	2
2	MITRE ATT&CK Analytics	3
2.1	LP_High Severity EPP Alert	3
2.2	LP_Host Generating Multiple Medium Severity EPP Alert	3
2.3	LP_Host Generating Multiple High Severity EPP Alert	4
2.4	LP_Medium Severity EPP Alert	4
2.5	LP_Windows Service Stop or Delete	5
2.6	LP_Suspicious Hack Tools Execution	5
2.7	LP_Suspicious Execution of XORDump Utility for LSASS Memory Dump .	6
2.8	LP_Suspicious Execution of Createdump Utility for Memory Dump	6
2.9	LP_Suspicious DsInternals Get-ADReplAccount Activities	7
2.10	LP_Suspicious Activities Associated with NTDS Exfiltration	7
2.11	LP_Possible LSASS Memory Dump Via Windows Task Manager	8
2.12	LP_Possible LSASS Dump Via SilentProcessExit Technique	8
2.13	LP_NTDS or SAM Database Copy Operation	9
2.14	LP_Microsoft IIS Service Account Password Dumped	9
2.15	LP_Dumpert Process Dumper Execution	10
2.16	LP_Credential Dump Via NPPSpy	10
2.17	LP_Malicious PowerShell Commandlets Detected	11
2.18	LP_Code Execution Via Diskshadow Detected	11
2.19	LP_Image Mount Indicator in Recent Files	12
2.20	LP_Disk Image File Created	12
2.21	LP_PowerShell Execution via DLL Detected	13
2.22	LP_Suspicious Windows Defender Registry keys Modification	13
2.23	LP_Executable Files Created and Executed by Office Applications	14
2.24	LP_WMI Backdoor in Exchange Transport Agent	14
2.25	LP_Suspicious Msiexec Usage Detected	15
2.26	LP_Suspicious Usage of Advanced IP Scanner	15
2.27	LP_Persistence through Port Monitor Registry modification	16
2.28	LP_File Dropped in Suspicious Location	16
2.29	LP_Alternate PowerShell Hosts via Powershell Module	17
2.30	LP_Suspicious Usage of Where Binary	17

2.31	LP_MSHTA - Activity Detected	18
2.32	LP_Alternate PowerShell Hosts via Named Pipe	18
2.33	LP_Suspicious File Execution Using Wscript or Cscript	19
2.34	LP_Suspicious Child Process Spawned by Microsoft Office Product	19
2.35	LP_Windows Login Attempt on Disabled Account	20
2.36	LP_RClone Utility Execution	20
2.37	LP_UAC Bypass via SDCLT	21
2.38	LP_Credential Dumping - Registry	21
2.39	LP_Suspicious Binary Execution in User Directory	22
2.40	LP_Suspicious WMIC Child Process	22
2.41	LP_Suspicious File Execution Using Wscript or Cscript	23
2.42	LP_BCDEdit Safe Mode Command Execution	23
2.43	LP_Suspicious Encoded PowerShell Command Line	24
2.44	LP_Persistence Attack through Accessibility Process Feature	24
2.45	LP_Suspicious DLL Added to Applnit DLL Registry	25
2.46	LP_Firewall Rule Addition via Netsh Detected	25
2.47	LP_MSHTA Spawned by SVCHOST Detected	26
2.48	LP_Exploitation of CVE-2019-1388 Detected	26
2.49	LP_Sophos EPP Registry Modification	26
2.50	LP_Office365 Inbox Rule with Special Characters Created	27
2.51	LP_Suspicious WerFault Process Creation	27
2.52	LP_Suspicious WerFault File Creation	28
2.53	LP_Snake Malware Covert Store Registry Key Detected	28
2.54	LP_Suspicious WerFault Service Creation	29
2.55	LP_Suspicious Named Pipe Connection to Azure AD Connect Database	29
2.56	LP_Suspicious Driver Loaded	30
2.57	LP_AADInternals PowerShell Cmdlet Execution	30
2.58	LP_Suspicious Scheduled Task Creation via Masqueraded XML File	30
2.59	LP_Suspicious Microsoft Equation Editor Child Process	31
2.60	LP_Windows Error Process Masquerading	31
2.61	LP_Bypass UAC via CMSTP Detected	32
2.62	LP_Application Whitelisting Bypass via Dxcap Detected	32
2.63	LP_Suspicious WMIC XSL Script Execution	33
2.64	LP_Suspicious File Execution via MSHTA	33
2.65	LP_Regsvr32 Anomalous Activity Detected	34
2.66	LP_Remote File Execution via MSIEXEC	34
2.67	LP_Execution of Trojanized 3CX Application	35
2.68	LP_Msbuild Spawned by Unusual Parent Process	35
2.69	LP_Suspicious Files Designated as System Files Detected	35
2.70	LP_Bypass User Account Control using Registry	36
2.71	LP_LSASS Process Access by Mimikatz	36
2.72	LP_Unsigned Image Loaded Into LSASS Process	37
2.73	LP_Usage of Sysinternals Tools Detected	37
2.74	LP_Microsoft SharePoint Remote Code Execution Detected	38
2.75	LP_DenyAllWAF SQL Injection Attack	38

2.76	LP_Windows CryptoAPI Spoofing Vulnerability Detected	39
2.77	LP_Malicious use of Scriptrunner Detected	39
2.78	LP_Suspicious process related to Rundll32 Detected	39
2.79	LP_Javascript conversion to executable Detected	40
2.80	LP_Suspicious Execution of Gpscript Detected	40
2.81	LP_Proxy Execution via Desktop Setting Control Panel	41
2.82	LP_Credentials Dumping Tools Accessing LSASS Memory	41
2.83	LP_Xwizard DLL Side Loading Detected	43
2.84	LP_DLL Side Loading Via Microsoft Defender	43
2.85	LP_ZIP File Creation or Extraction via Printer Migration CLI Tool	44
2.86	LP_Credentials Capture via Rpcping Detected	44
2.87	LP_Suspicious ConfigSecurityPolicy Execution Detected	45
2.88	LP_C-Sharp Code Compilation Using Ilasm Detected	45
2.89	LP_Process Dump via Resource Leak Diagnostic Tool	45
2.90	LP_Suspicious DLL execution via Register-Cimprovider	46
2.91	Accessibility features - Process	46
2.92	LP_Accessibility Features-Registry	47
2.93	LP_Active Directory DLLs Loaded By Office Applications	47
2.94	LP_DCSync detected	48
2.95	LP_Active Directory Replication User Backdoor	48
2.96	LP_Activity Related to NTDS Domain Hash Retrieval	49
2.97	LP_AD Object WriteDAC Access Detected	49
2.98	LP_AD Privileged Users or Groups Reconnaissance Detected	50
2.99	LP_Addition of SID History to Active Directory Object	50
2.100	LP_Admin User Remote Logon Detected	51
2.101	LP_Adwind RAT JRAT Detected	51
2.102	LP_Apache Struts 2 Remote Code Execution Detected	52
2.103	LP_AppCert DLLs Detected	52
2.104	LP_Application Shimming - File Access Detected	52
2.105	LP_Application Whitelisting Bypass via Bginfo Detected	53
2.106	LP_Application Whitelisting Bypass via Dnx Detected	53
2.107	LP_Audio Capture Detected	54
2.108	LP_Authentication Package Detected	54
2.109	LP_Autorun Keys Modification Detected	55
2.110	LP_Bloodhound and Sharphound Hack Tool Detected	55
2.111	LP_BlueMashroom DLL Load Detected	56
2.112	LP_Remote Thread Creation via Cactustorch	56
2.113	LP_Call to a Privileged Service Failed	57
2.114	LP_Capture a Network Trace with netsh	57
2.115	LP_CEO Fraud - Possible Fraudulent Email Behavior	58
2.116	LP_Certutil Encode Detected	58
2.117	LP_Change of Default File Association Detected	59
2.118	LP_Citrix ADC VPN Directory Traversal Detected	59
2.119	LP_Clear Command History	59
2.120	LP_Clearing of PowerShell Logs Detected	60

2.121LP_Clipboard Data Access Detected	60
2.122LP_Cmdkey Cached Credentials Recon Detected	61
2.123LP_CMSTP Detected	61
2.124LP_CMSTP Execution Detected	62
2.125LP_CMSTP UAC Bypass via COM Object Access	62
2.126LP_CobaltStrike Process Injection Detected	63
2.127LP_Windows Command Line Execution with Suspicious URL and AppData Strings	63
2.128LP_Compiled HTML File Detected	63
2.129LP_Console History Discovery Detected	64
2.130LP_Control Panel Items - Registry Detected	64
2.131LP_Copy from Admin Share Detected	65
2.132LP_Copying Sensitive Files with Credential Data	65
2.133LP_Copyright Violation Email	66
2.134LP_CreateMiniDump Hacktool Detected	66
2.135LP_CreateRemoteThread API and LoadLibrary	66
2.136LP_Command Obfuscation via Character Insertion	67
2.137LP_Command Obfuscation via Environment Variable Concatenation Reassembly	67
2.138LP_Credential Access via Input Prompt Detected	68
2.139LP_Credential Dump Tools Dropped Files Detected	68
2.140LP_Credential Dumping - Process Creation	69
2.141LP_Credential Dumping - Process Access	69
2.142LP_Credential Dumping - Registry Save	70
2.143LP_Credential Dumping with ImageLoad Detected	70
2.144LP_Credentials Access in Files Detected	71
2.145LP_Registry Enumeration for credentials Detected	71
2.146LP_Default Account privilege elevation followed by restoration of previous account state	72
2.147LP_Default Blocked Inbound Traffic followed by Allowed Event	72
2.148LP_Default Blocked Outbound Traffic followed by Allowed Event	73
2.149LP_Default Brute Force Attack Successful	73
2.150LP_Default Connection Attempts on Closed Port	74
2.151LP_Default CPU Usage Status	74
2.152LP_Default Device Stopped Sending Logs for Half an Hour	74
2.153LP_Default DNS Tunneling Detection - Query Size	75
2.154LP_Default Excessive Blocked Connections	75
2.155LP_Default File Association Changed	76
2.156LP_Default Guest Account Added to Administrative Group	76
2.157LP_Default Inbound Connection with Non-Whitelist Country	77
2.158LP_Default Inbound RDP Connection	77
2.159LP_Default Inbound SMB Connection	77
2.160LP_Default Inbound SMTP Connection	78
2.161LP_Default Inbound SSH Connection	78
2.162LP_Default IRC connection	79

2.163LP_Default Malware Detected	79
2.164LP_Default Malware not Cleaned	79
2.165LP_Default Malware Removed	80
2.166LP_Default Memory Usage Status	80
2.167LP_Default Network Configuration Change on Network Device	81
2.168LP_Default Outbound Connection with Non-Whitelist Country	81
2.169LP_Default Outbound Traffic from Unusual Source	82
2.170LP_Default Port Scan Detected	82
2.171LP_Default Possible Cross Site Scripting Attack Detected	82
2.172LP_Default Possible Network Performance Degradation Detected	83
2.173LP_Default Possible Non-PCI Compliant Inbound Network Traffic Detected	83
2.174LP_Default Possible Spamming Zombie	84
2.175LP_Default Possible SQL Injection Attack	84
2.176LP_Default Possible System Instability State Detected	85
2.177LP_Default PowerSploit and Empire Schtasks Persistence	85
2.178LP_Default Successful Login outside Normal Hour	86
2.179LP_Default Successful Login Using a Default Account	86
2.180LP_Default System Time Change	87
2.181LP_Default TCP Probable SynFlood Attack	87
2.182LP_Default Unapproved Port Activity Detected	87
2.183LP_Default Unusual Number of Failed Vendor User Login	88
2.184LP_HandleKatz Duplicating LSASS Handle	88
2.185LP_PowerShell Execution Policy Modification Detected	89
2.186LP_Devtoolslauncher Executes Specified Binary	89
2.187LP_DHCP Callout DLL Installation Detected	90
2.188LP_DHCP Server Error Failed Loading the CallOut DLL	90
2.189LP_DHCP Server Loaded the CallOut DLL	91
2.190LP_Direct Autorun Keys Modification Detected	91
2.191LP_Disable of ETW Trace Detected	92
2.192LP_MiniNt Registry Key Addition	92
2.193LP_Discovery via Discovery via PowerSploit Recon Module Detected	93
2.194LP_DLL Load via LSASS Detected	93
2.195LP_DNS Server Error Failed Loading the ServerLevelPluginDLL	94
2.196LP_DNS ServerLevelPluginDll Install	94
2.197LP_Domain Trust Discovery Detected	94
2.198LP_dotNET DLL Loaded Via Office Applications	95
2.199LP_DPAPI Domain Backup Key Extraction Detected	95
2.200LP_DPAPI Domain Master Key Backup Attempt	96
2.201LP_Dridex Process Pattern Detected	96
2.202LP_Droppers Exploiting CVE-2017-11882 Detected	97
2.203LP_Drupal Arbitrary Code Execution Detected	97
2.204LP_Elevated Command Prompt Activity by Non-Admin User Detected	97
2.205LP EMC Possible Ransomware Detection	98
2.206LP_Empire PowerShell Launch Parameters	98
2.207LP_Empire PowerShell UAC Bypass Detected	98

2.208LP_Enabled User Right in AD to Control User Objects	99
2.209LP_PowerShell Encoded FromBase64String Detected	99
2.210LP_Encoded IEX Detected	100
2.211LP_Encoded PowerShell Command Detected	100
2.212LP_Eventlog Cleared Detected	101
2.213LP_Executables Stored in OneDrive	101
2.214LP_Execution in Non-Executable Folder Detected	102
2.215LP_Execution in Outlook Temp Folder Detected	102
2.216LP_Execution in Webserver Root Folder Detected	102
2.217LP_Execution of Renamed PaExec Detected	103
2.218LP_Execution via Control Panel Items	103
2.219LP_Execution via HTA using IE JavaScript Engine Detected	104
2.220LP_Execution via Squiblydoo Technique Detected	104
2.221LP_Execution via Windows Scripting Host Component Detected	105
2.222LP_Exim MTA Remote Code Execution Vulnerability Detected	105
2.223LP_Exim Remote Command Execution Detected	106
2.224LP_Existing Service Modification Detected	106
2.225LP_External Disk Drive or USB Storage Device Detected	106
2.226LP_Fail2ban IP Banned	107
2.227LP_File Creation by PowerShell Detected	107
2.228LP_File Deletion Detected	108
2.229LP_File or Folder Permissions Modifications	108
2.230LP_File System Permissions Weakness	109
2.231LP_Firewall Configuration Modification Detected	109
2.232LP_Firewall Disabled via Netsh Detected	109
2.233LP_First Time Seen Remote Named Pipe	110
2.234LP_FirstClass Failed Login Attempt	110
2.235LP_FirstClass Failed Password Change Attempt	111
2.236LP_Formbook Process Creation Detected	111
2.237LP_FortiGate Admin Login Disable	111
2.238LP_FortiGate Anomaly	112
2.239LP_FortiGate Antivirus Botnet Warning	112
2.240LP_FortiGate Antivirus Scan Engine Load Failed	112
2.241LP_FortiGate Attack	113
2.242LP_FortiGate Critical Events	113
2.243LP_FortiGate Data Leak Protection	113
2.244LP_FortiGate IPS Events	114
2.245LP_FortiGate Malicious URL Attack	114
2.246LP_FortiGate Virus	114
2.247LP_FortiGate VPN SSL User Login Failed	115
2.248LP_FromBase64String Command Line Detected	115
2.249LP_FSecure File Infection	116
2.250LP_FSecure Virus Detection	116
2.251LP_Fsutil Suspicious Invocation Detected	116
2.252LP_GAC DLL Loaded Via Office Applications Detected	117

2.253LP_Generic Password Dumper Activity on LSASS Detected	117
2.254LP_Grabbing Sensitive Hives via Reg Utility	117
2.255LP_Hacktool Ruler Detected	118
2.256LP_HH Execution Detected	118
2.257LP_Hidden Files and Directories Detected	119
2.258LP_Hiding Files with Attrib Detected	119
2.259LP_IIS Native-Code Module Command Line Installation	120
2.260LP_In-memory PowerShell Detected	120
2.261LP_Indicator Blocking - Driver Unloaded	121
2.262LP_Indicator Blocking - Sysmon Registry Edited	121
2.263LP_Install Root Certificate	122
2.264LP_Suspicious InstallUtil Execution	122
2.265LP_Invocation of Active Directory Diagnostic Tool Detected	123
2.266LP_Java Running with Remote Debugging	123
2.267LP_Judgement Panda Exfil Activity	123
2.268LP_JunOS Attack	124
2.269LP_JunOS Authentication Failed	124
2.270LP_JunOS Policy Violation	125
2.271LP_JunOS Security Log Clear	125
2.272LP_Kaspersky Antivirus - Outbreak Detection	125
2.273LP_Kaspersky Antivirus - Update Fail	126
2.274LP_Kaspersky Antivirus Extremely Out of Date Event	126
2.275LP_Kaspersky Antivirus Outbreak Detection by Source	127
2.276LP_Kaspersky Antivirus Outbreak Detection by Virus	127
2.277LP_Kaspersky Antivirus Threat Affecting Multiple Host	128
2.278LP_Kerberoasting via PowerShell Detected	128
2.279LP_Kernel Firewall Connection Denied	128
2.280LP_Koadic Execution Detected	129
2.281LP_Large ICMP Traffic	129
2.282LP_Local Account Creation on Workstation Detected	130
2.283LP_LockCrypt Ransomware	130
2.284LP_Log Files Creation of Dot-Net-to-JS Detected	131
2.285LP_LSASS Access from Non System Account Detected	131
2.286LP_LSASS Memory Dump Detected	131
2.287LP_LSASS Memory Dump File Creation	132
2.288LP_LSSAS Memory Dump with MiniDumpWriteDump API Detected	132
2.289LP_LSASS Memory Dumping Detected	133
2.290LP_Macro file Creation Detected	133
2.291LP_Malicious Base64 Encoded PowerShell Keywords in Command Lines Detected	134
2.292LP_Malicious File Execution Detected	135
2.293LP_Malicious Service Installations Detected	135
2.294LP_Malware Shellcode in Verclsid Target Process	136
2.295LP_Malware Threat Connection from Malicious Source	136
2.296LP_Malware Threat Connection to Malicious Destination	137

2.297LP_Malware Threat Connection to Malicious URLs	137
2.298LP_Malware Threat Emails Sent to Attacker	137
2.299LP_Meltdown and Spectre Vulnerabilities	138
2.300LP_Meterpreter or Cobalt Strike Getsystem Service Start Detected . . .	138
2.301LP_Microsoft ActiveX Control Code Execution Vulnerability Detected . .	139
2.302LP_Microsoft DotNET Framework Remote Code Execution Detected . .	139
2.303LP_Microsoft Office Memory Corruption Vulnerability CVE-2015-1641 Detected	139
2.304LP_Microsoft Office Memory Corruption Vulnerability CVE-2017-0199 Detected	140
2.305LP_Microsoft Office Memory Corruption Vulnerability CVE-2017-11882 Detected	140
2.306LP_Mimikatz Command Line Detected	141
2.307LP_Mitre Discovery Using Query Registry Detected	141
2.308LP_Mitre Discovery Using System Network Configuration Discovery Detected	142
2.309LP_Mitre Persistence via Winlogon Helper DLL Detected	142
2.310LP_MMC Spawning Windows Shell Detected	143
2.311LP_Most Exploitable Vulnerabilities Detected	143
2.312LP_Mshta JavaScript Execution Detected	144
2.313LP_MSHTA Spawning Windows Shell Detected	144
2.314LP_MSHTA Suspicious Execution Detected	144
2.315LP_MsiExec Web Install Detected	145
2.316LP_MSTSC Shadowing Detected	145
2.317LP_Multiple Failed Login Followed by Successful Login Followed by Logoff	146
2.318LP_Named Pipe added to Null Session Detected	146
2.319LP_Narrators Feedback-Hub Persistence Detected	147
2.320LP_Net exe Execution Detected	147
2.321LP_NetNTLM Downgrade Attack Detected	148
2.322LP_Netsh Port Forwarding Detected	148
2.323LP_Netsh RDP Port Forwarding Detected	149
2.324LP_Network Share Connection Removed	149
2.325LP_Network Share Discovery	149
2.326LP_Network Sniffing Detected	150
2.327LP_New Firewall Port Opening Detected	150
2.328LP_New RUN Key Pointing to Suspicious Folder Detected	151
2.329LP_New Service Creation	151
2.330LP_Non Interactive PowerShell Execution	152
2.331LP_NoPowerShell Tool Activity Detected	152
2.332LP_NotPetya Ransomware Activity Detected	153
2.333LP_Office365 Multiple Failed Login from Different Host by Single User .	153
2.334LP_Office365 Multiple Failed Login from Same Host	154
2.335LP_Office365 Multiple Successful Login from Different Country by Single User	154
2.336LP_Office365 Multiple Successful Login From Different Host by Single User	155

2.337LP_Office365 Password Resets	155
2.338LP_OpenWith Execution of Specified Binary Detected	155
2.339LP_Password Change on DSRM Account Detected	156
2.340LP_Password Dumper Remote Thread in LSASS	156
2.341LP_Password Spraying Attack Detected	157
2.342LP_Persistence and Execution at Scale via GPO Scheduled Task	157
2.343LP_Possible Access to ADMIN Share	158
2.344LP_Possible Account Misuse-Privilege Escalation	158
2.345LP_Possible Applocker Bypass Detected	158
2.346LP_Possible Bitsadmin Download Detected	159
2.347LP_Possible Botnet Connection-DNS Server Modified	159
2.348LP_Possible Botnet Connection-IRC Port	160
2.349LP_Possible Botnet Connection-Outbound DDOS	160
2.350LP_Possible Botnet Connection-Outbound Spam	161
2.351LP_Possible CLR DLL Loaded Via Office Applications	161
2.352LP_Possible Credential Dump-Tools Named Pipes Detected	162
2.353LP_Possible Data Breach	162
2.354LP_Possible Data Breach-Off Hour Transfer	163
2.355LP_Possible DDOS Attack	163
2.356LP_Possible Detection of SafetyKatz	164
2.357LP_Possible DNS Rebinding Detected	164
2.358LP_Possible Empire Monkey Detected	165
2.359LP_Possible Executable Used by PlugX in Uncommon Location	165
2.360LP_Possible Impacket Lateralization Detected	166
2.361LP_Possible Impacket SecretDump Remote Activity	166
2.362LP_Possible Inbound Spamming Detected	167
2.363LP_Possible Insider Threat	167
2.364LP_Malicious Payload Download via Office Binaries	168
2.365LP_Possible Malware Detected	168
2.366LP_Possible Modification of Boot Configuration	168
2.367LP_Possible Outbound Spamming Detected	169
2.368LP_Possible Pass the Hash Activity Detected	169
2.369LP_Possible Privilege Escalation via Weak Service Permissions	170
2.370LP_Possible Process Hollowing Image Loading	170
2.371LP_Possible SPN Enumeration Detected	171
2.372LP_Possible SquiblyTwo Detected	171
2.373LP_Possible Taskmgr run as LOCAL_SYSTEM Detected	172
2.374LP_Powershell AMSI Bypass via dotNET Reflection	172
2.375LP_PowerShell Base64 Encoded Shellcode Detected	172
2.376LP_PowerShell Network Connections Detected	173
2.377LP_PowerShell Profile Modification	173
2.378LP_PowerShell Rundll32 Remote Thread Creation Detected	174
2.379LP_PowerShell Script Run in AppData Detected	174
2.380LP_PowerShell Version Downgrade Detected	175
2.381LP_Process Dump via Comsvcs DLL Detected	175

2.382LP_Process Dump via Rundll32 and Comsvcs Detected	175
2.383LP_Process Hollowing Detected	176
2.384LP_Process Injection Detected	176
2.385LP_Protected Storage Service Access Detected	177
2.386LP_PsExec Tool Execution Detected	177
2.387LP_Psr Capture Screenshots Detected	178
2.388LP_Pulse Secure Arbitrary File Reading Detected	178
2.389LP_Query Registry Network	178
2.390LP_Rare Scheduled Task Creations Detected	179
2.391LP_RDP Login from Localhost Detected	179
2.392LP_RDP Over Reverse SSH Tunnel Detected	180
2.393LP_RDP Registry Modification	180
2.394LP_RDP Sensitive Settings Changed	180
2.395LP_Reconnaissance Activity with Net Command	181
2.396LP_RedSocks Backdoor Connection	181
2.397LP_RedSocks Bad Neighborhood Detection	182
2.398LP_RedSocks Blacklist URL Detection	182
2.399LP_RedSocks FileSharing	183
2.400LP_RedSocks Ransomware Connection	183
2.401LP_RedSocks Sinkhole Detection	183
2.402LP_RedSocks Tor Connection	184
2.403LP_RedSocks Trojan Connection	184
2.404LP_Register new Logon Process by Rubeus	185
2.405LP_Registry Persistence Mechanisms Detected	185
2.406LP_Regsvcs-Regasm Detected	186
2.407LP_Remote PowerShell Session	186
2.408LP_Remote System Discovery	186
2.409LP_Renamed Binary Detected	187
2.410LP_Renamed ProcDump Detected	187
2.411LP_Renamed PsExec Detected	188
2.412LP_Rogue Access Point Detected	188
2.413LP_RSA SecurID Account Lockout	189
2.414LP_RSA SecurID Account Lockout	189
2.415LP_Rubeus Hack Tool Detected	189
2.416LP_Run PowerShell Script from ADS Detected	190
2.417LP_Rundll32 Internet Connection Detected	190
2.418LP_SAM Registry Hive Dump via Reg Utility	191
2.419LP_Scheduled Task Creation Detected	191
2.420LP_SCM Database Handle Failure Detected	192
2.421LP_SCM Database Privileged Operation Detected	192
2.422LP_Screensaver Activities Detected	192
2.423LP_Secure Deletion with SDelete	193
2.424LP_SecurityXploded Tool Detected	193
2.425LP_Signed Binary Proxy Execution - Network Detected	194
2.426LP_Signed Binary Proxy Execution - Process Detected	194

2.427LP_smbexec Service Installation Detected	195
2.428LP_SolarisLDAP Group Remove from LDAP Detected	195
2.429LP_SolarisLDAP Password Spraying Attack Detected	196
2.430LP_SolarisLDAP Possible Bruteforce Attack Detected	196
2.431LP_SolarisLDAP Successful Bruteforce Attack Detected	197
2.432LP_SolarisLDAP User Account Lockout Detected	197
2.433LP_Sophos XG Firewall - Inbound Attack Detected by IDP	198
2.434LP_Sophos XG Firewall - Outbound Attack Detected by IDP	198
2.435LP_SophosUTM Policy Violation	198
2.436LP_SSHD Connection Denied	199
2.437LP_Stealthy Scheduled Task Creation via VBA Macro Detected	200
2.438LP_Sticky Key Like Backdoor Usage Detected	200
2.439LP_Stop Windows Service Detected	201
2.440LP_Successful Lateral Movement to Administrator via Pass the Hash using Mimikatz Detected	201
2.441LP_Successful Overpass the Hash Attempt	202
2.442LP_Suspect Svchost Activity Detected	202
2.443LP_Suspect Svchost Memory Access	202
2.444LP_Suspicious Access to Sensitive File Extensions	203
2.445LP_Suspicious Calculator Usage Detected	203
2.446LP_Suspicious Call by Ordinal Detected	204
2.447LP_Suspicious Certutil Command Detected	204
2.448LP_Suspicious Code Page Switch Detected	205
2.449LP_Suspicious Commandline Escape Detected	205
2.450LP_Suspicious Compression Tool Parameters	205
2.451LP_Suspicious Control Panel DLL Load Detected	206
2.452LP_Suspicious Csc Source File Folder Detected	206
2.453LP_Suspicious Debugger Registration Detected	207
2.454LP_Suspicious Double Extension Detected	207
2.455LP_Suspicious Driver Load from Temp	208
2.456LP_Suspicious Eventlog Clear or Configuration Using Wevtutil Detected .	208
2.457LP_Suspicious Execution from Outlook	209
2.458LP_Suspicious GUP Usage Detected	209
2.459LP_Suspicious HWP Sub Processes Detected	210
2.460LP_Suspicious In-Memory Module Execution Detected	210
2.461LP_Suspicious Kerberos RC4 Ticket Encryption	211
2.462LP_Suspicious MsiExec Directory Detected	211
2.463LP_Suspicious Named Pipes Detected	211
2.464LP_Suspicious Outbound Kerberos Connection	212
2.465LP_Suspicious Outbound RDP Connections Detected	212
2.466LP_Suspicious Parent of Csc Detected	213
2.467LP_Suspicious PowerShell Invocation Based on Parent Process	213
2.468LP_Suspicious PowerShell Parameter Substring Detected	214
2.469LP_Suspicious Process Start Locations Detected	214
2.470LP_Suspicious Program Location with Network Connections	215

2.471LP_Suspicious PsExec Execution Detected	215
2.472LP_Suspicious RDP Redirect Using TSCON Detected	216
2.473LP_Suspicious Remote Thread Created	216
2.474LP_Suspicious RUN Key from Download Detected	217
2.475LP_Suspicious Rundll32 Activity Detected	217
2.476LP_Suspicious Scripting in a WMI Consumer	218
2.477LP_Suspicious Service Path Modification Detected	219
2.478LP_Suspicious Svchost Process Detected	219
2.479LP_Suspicious TSCON Start	220
2.480LP_Suspicious Typical Malware Back Connect Ports Detected	220
2.481LP_Suspicious CSharp or FSharp Interactive Console Execution	221
2.482LP_Suspicious Userinit Child Process	221
2.483LP_Suspicious Windows ANONYMOUS LOGON Local Account Creation	222
2.484LP_Suspicious WMI Execution Detected	222
2.485LP_Svchost DLL Search Order Hijack Detected	223
2.486LP_SysKey Registry Keys Access	223
2.487LP_Sysmon Configuration Modification Detected	224
2.488LP_Sysmon Driver Unload Detected	224
2.489LP_Sysmon Error Event Detected	224
2.490LP_System File Execution Location Anomaly Detected	225
2.491LP_System Service Discovery	225
2.492LP_Tap Driver Installation Detected	226
2.493LP_Tasks Folder Evasion Detected	226
2.494LP_Terminal Service Process Spawn Detected	227
2.495LP_Threat Intel Allowed Connections from Suspicious Sources	227
2.496LP_Threat Intel Connections with Suspicious Domains	228
2.497LP_Time-Stomping of Users Directory Files Detected	228
2.498LP_Transferring Files with Credential Data via Network Shares	229
2.499LP_TrendMicroDeepSecurity Virus Quarantined	229
2.500LP_UAC Bypass via Event Viewer Detected	229
2.501LP_Unix Possible Bruteforce Attack	230
2.502LP_Unix User Deleted	230
2.503LP_Unsigned Driver Loading Detected	231
2.504LP_Possible Ursnif Registry Activity	231
2.505LP_VBA DLL Loaded by Office	231
2.506LP_VM - High Risk Vulnerability on High Impact Assets	232
2.507LP_VM - High Risk Vulnerability on Low Impact Assets	232
2.508LP_VM - High Risk Vulnerability on Medium Impact Assets	233
2.509LP_VM - Medium Risk Vulnerability on High Impact Assets	233
2.510LP_VM - Medium Risk Vulnerability on Low Impact Assets	234
2.511LP_VM - Medium Risk Vulnerability on Medium Impact Assets	234
2.512LP_WannaCry MS17-010 Vulnerable Sources	234
2.513LP_WannaCry Sources in Connections to Sinkhole Domain	235
2.514LP_WCE wceaux dll Access Detected	235
2.515LP_Wdigest Registry Modification	236

2.516LP_Weak Encryption Enabled for User	236
2.517LP_Potential Webshell Activity Detected	236
2.518LP_Windows Audit Logs Cleared	237
2.519LP_Windows Credential Editor Detected	237
2.520LP_Windows Data Copied to Removable Device	238
2.521LP_Windows Defender Antivirus Disable via Registry Modification	238
2.522LP_Shadow Copy Deletion Using OS Utilities Detected	239
2.523LP_Windows Defender Exclusion Set Detected	239
2.524LP_Windows Excessive Amount of Files Copied to Removable Device	240
2.525LP_Windows Failed Login Attempt Using Service Account	241
2.526LP_Windows Failed Login Followed by Lockout Event	241
2.527LP_Windows Local User Management	242
2.528LP_WMI DLL Loaded by Office	242
2.529LP_Windows Processes Suspicious Parent Directory Detected	243
2.530LP_Windows Registry Persistence COM Key Linking Detected	243
2.531LP_Windows Shell Spawning Suspicious Program	244
2.532LP_Windows Suspicious Creation of User Accounts	244
2.533LP_Windows User Account Created via Command Line	245
2.534LP_Windows User Account Change to End with Dollar Sign	245
2.535LP_Windows Webshell Creation Detected	246
2.536LP_Winlogon Helper DLL	246
2.537LP_WMI Backdoor Exchange Transport Agent	247
2.538LP_WMI Modules Loaded by Suspicious Process	247
2.539LP_WMI Persistence - Script Event Consumer Detected	248
2.540LP_WMI Persistence - Script Event Consumer File Write	248
2.541LP_WMI Spawning Windows Shell	249
2.542LP_WMIExec VBS Script Detected	249
2.543LP_Wmiprvse Spawning Process	249
2.544LP_WScript or CScript Dropper Detected	250
2.545LP_Wsreset UAC Bypass Detected	250
2.546LP_XSL Script Processing Detected	251
2.547LP_ZOHO Dctask64 Process Injection Detected	251
2.548LP_APT 34 Initial Access Using Spearphishing Link Detected	252
2.549LP_Credential Dumping using procdump Detected	252
2.550LP_Suspicious File Deletion Detected	253
2.551LP_Security Software Discovery Process Detected	253
2.552LP_System Network Configuration Discovery	254
2.553LP_System Network Connections Discovery	254
2.554LP_Exfiltration over Cloud Application Detected	255
2.555LP_Remote File Copy Detected	255
2.556LP_Privilege Escalation - Bypassing User Account Control Detected	255
2.557LP_Process Execution from Suspicious Location	256
2.558LP_Active Directory Enumeration via ADFind	256
2.559LP_Possible Command Prompt Process Hollowing	257
2.560LP_Suspicious Taskkill Activity	257

2.561LP_Suspicious File or Directory Permission Modification	258
2.562LP_Ryuk Wake-On-LAN Activity	258
2.563LP_EXE or DLL Dropped in Perflogs Folder	259
2.564LP_Credential Access via LaZagne	259
2.565LP_RDP Connection Initiated from Domain Controller	259
2.566LP_Active Directory Module Load in PowerShell	260
2.567LP_Possible Active Directory Enumeration via AD Module	260
2.568LP_Microsoft Defender Disabling Attempt via PowerShell	261
2.569LP_Possible Kerberoasting via Rubeus	261
2.570LP_Suspicious Scheduled Task Creation	262
2.571LP_RDP Connection Initiated from Suspicious Country	262
2.572LP_Scheduled Task Deletion	263
2.573LP_Possible GootKit WScript Execution	263
2.574LP_Exchange Remote Code Execution CVE-2020-0688 Attempt	263
2.575LP_BlueKeep Vulnerability CVE-2019-0708 Exploitation	264
2.576LP_ZoHo ManageEngine Pre-Auth File Upload CVE-2019-8394 Exploitation Attempt	264
2.577LP_ZoHo ManageEngine Desktop Central CVE-2020-10189 Exploitation Attempt	265
2.578LP_Fortinet Pre-Auth File Read CVE-2018-13379 Exploitation Attempt	265
2.579LP_Adobe ColdFusion Remote Code Execution CVE-2018-15961 Attempt	266
2.580LP_Default Hard disk Usage Status	266
2.581LP_Default License Grace State	266
2.582LP_Default License Invalid	267
2.583LP_Microsoft Build Engine Loading Credential Libraries	267
2.584LP_Microsoft Build Engine started by Office	268
2.585LP_Potential Phishing Attack Detected	268
2.586LP_Safe DLL Search Mode Disabled	268
2.587LP_Potential Intrusion Detected	269
2.588LP_Windows Crash Dump Disabled	269
2.589LP_Suspicious Shells Spawn by SQL Server	270
2.590LP_Suspicious Microsoft SQL Server PowerShell Module Use Detected	270
2.591LP_HermeticWiper Driver Load	271
2.592LP_UltraVNC Execution via Command Line	271
2.593LP_Office Security Settings Changed	271
2.594LP_HermeticWiper IoC Hashes Detected	272
2.595LP_IsaacWiper IoC Hashes Detected	272
2.596LP_WhisperGate IoC Hashes Detected	273
2.597LP_GhostWriter IoC Detected	273
2.598LP_Actinium IoC Domains Detected	274
2.599LP_Suspicious VMTToolsd Child Process	274
2.600LP_Credential Access via Pypykatz	274
2.601LP_Impacket PsExec Execution	275
2.602LP_Oracle WebLogic CVE-2021-2109 Exploitation	275
2.603LP_Possible JSP Webshell Detected	276

2.604LP_PowerShell ADRecon Execution	276
2.605LP_PowerView PowerShell Commandlets	276
2.606LP_PowerView PowerShell Commandlets	278
2.607LP_Stealthy VSTO Persistence	279
2.608LP_Suspicious DLL or VBS Files being created in ProgramData	279
2.609LP_Suspicious VMToolsd Child Process	280
2.610LP_Suspicious WMPRVSE Child Process	280
2.611LP_TerraMaster TOS CVE-2020-28188 Exploitation	281
2.612LP_VMware VSphere CVE-2021-21972 Exploitation	281
2.613LP_VMware View Planner CVE-2021-21978 Exploitation	281
2.614LP_Zoho ManageEngine ADSelfService Plus CVE-2021-40539 Exploitation	282
2.615LP_Possible Access to ADMIN Share	282
2.616LP_PsExec Tool Execution Detected	283
2.617LP_Screensaver Activities Detected	283
2.618LP_Suspect Svchost Activity Detected	284
2.619LP_Time-Stomping of Users Directory Files Detected	284
2.620LP_Windows Defender Exclusion Set Detected	285
2.621LP_Suspicious Netsh DLL Persistence Detected	285
2.622LP_Usage of Procdump Detected	285
2.623LP_Conhost Spawning Suspicious Processes	286
2.624LP_Proxy Execution via Explorer	286
2.625LP_Wlrmldr Lolbin Use as Launcher	287
2.626LP_Suspicious Process Execution via Pester Detected	287
2.627LP_Root Certificate Installation Detected	287
2.628LP_Suspicious process spawned by FTP	288
2.629LP_Chromeloader Cross-Process Injection to Load Extention	288
2.630LP_Proxy Execution via Explorer	289
2.631LP_Suspicious Root Certificate installation Detected	289
2.632LP_Windows Logon Reminder Usage as Launcher	290
2.633LP_Suspicious File Transfer Using Replace	290
2.634LP_Proxy Execution via Program Compatibility Wizard	291
2.635LP_Suspicious Driver Installation via PnPUtil	291
2.636LP_Application Whitelisting Bypass via PresentationHost	292
2.637LP_Suspicious File Extraction via Expand Detected	292
2.638LP_Suspicious Use of Extrac32 Detected	293
2.639LP_Shell spawn via HTML Help Detected	293
2.640LP_DLL Injection with Tracker Detected	293
2.641LP_Powershell Code Execution via SyncAppvPublishingServer	294
2.642LP_Malicious PE Execution by Microsoft Visual Studio Debugger	294
2.643LP_Suspicious Atbroker Registry Change Detected	295
2.644LP_DLL loaded Via Certoc Binary Detected	295
2.645LP_Suspicious Remote Binary Usage Detected	296
2.646LP_Suspicious ASP NET Compiler Execution Detected	296
2.647LP_Suspicious LoadAssembly PowerShell Diagnostic Script Execution . .	297
2.648LP_Suspicious Invocation PowerShell Diagnostic Script Execution	297

2.649LP_Registry Configured RunOnce Task Execution	298
2.650LP_RunOnce Registry Key Configuration Change	298
2.651LP_Suspicious WSL Bash Execution	299
2.652LP_WSL Execution Detected	299
2.653LP_Suspicious Usage of Csharp or Roslyn Csharp Interactive Console	299
2.654LP_Possible Commandline Obfuscation Detected	300
2.655LP_Possible Emotet Activity Detected	300
2.656LP_Suspicious Use of Control Panel Items	301
2.657LP_Suspicious Use of CSharp Interactive Console Detected	301
2.658LP_Suspicious Use of Colorcpl Detected	302
2.659LP_Suspicious File Download via Certreq	302
2.660LP_Process Dump via Rundll32 and Comsvcs	303
2.661LP_Registry Key Import Detected	303
2.662LP_Suspicious MachineGUID Query Detected	304
2.663LP_Process Injection Via Mavinject Detected	304
2.664Possible File Transfer Using Finger Detected	305
2.665LP_Suspicious Use of Findstr Detected	305
2.666LP_Suspicious File Overwrite Using extrac32 Detected	305
2.667LP_Suspicious Sysmon Driver Unload Detected	306
2.668LP_Suspicious Execution via IE per User Utility	306
2.669LP_Proxy Execution via xWizard	307
2.670LP_Suspicious MSHTA Process Pattern	307
2.671LP_COM Object Execution via Shell Extension CLSID Verification Host	308
2.672LP_Suspicious Setup Information File Invoked via DefaultInstall	308
2.673LP_Creation of Alternate Data Stream	309
2.674LP_Alternate Data Stream Created using Findstr	309
2.675LP_Suspicious Download Using Diantz	310
2.676LP_Ngrok RDP Tunnel Detected	310
2.677LP_Ngrok Execution	311
2.678LP_Windows Defender Uninstall via PowerShell	311
2.679LP_Hijacked Binary Execution via Settings Synchronizer	312
2.680LP_Suspicious Execution of Dump64	312
2.681LP_Code Compilation via Visual Basic Command Line Compiler	313
2.682LP_File Downloaded from Suspicious URL Using GfxDownloadWrapper	313
2.683LP_Suspicious CLR Logs File Creation	314
2.684LP_CLR DLL Loaded via Scripting Application	314
2.685LP_Obfuscation Script Usage via MSHTA to Execute Vbscript	315
2.686LP_Microsoft Defender Logging Disabled	315
2.687LP_UAC Bypass via CMLUA or CMSTPLUA	316
2.688LP_High Number of Service Stop or Task Kill in Short Span	316
2.689LP_LSA Protected Process Light Disabled	317
2.690LP_Suspicious Invocation of Microsoft Workflow Compiler	317
2.691LP_Process Dump via Sqldumper Detected	318
2.692LP_Suspicious Usage of SQLToolsPS Detected	318
2.693LP_Proxy Execution of Malicious Payload via Pubprn	319

2.694LP_File Download via IMEWDBLD	319
2.695LP_Memory Dump via Adplus	319
2.696LP_Remote Thread Created via Ttdinject	320
2.697LP_Proxy Download via OneDriveStandaloneUpdater	320
2.698LP_Suspicious WMIC ActiveScriptEventConsumer Created	321
2.699LP_Remote Connection Established via Msbuild	321
2.700LP_Executables Started in Suspicious Folder	322
2.701LP_Windows RDP Port Modified	322
2.702LP_Curl Silent Mode Execution Detected	323
2.703LP_High Volume of File Modification or Deletion in Short Span	323
2.704LP_Non-Existent User Login Attempt Detected	324
2.705LP_Execution of Temporary Files Via Office Application	324
2.706LP_Execution of Temporary Files Via Office Application	324
2.707LP_Malicious Image Loaded Via Excel	325
2.708LP_Malicious Chrome Extension Detected	325
2.709LP_Chrome Extension Installed Outside of the Webstore	326
2.710LP_Chrome Extension Installed with DevTools Permission	326
2.711LP_Suspicious WMIC Process Creation	327
2.712LP_Browser Credential Files Accessed	327
2.713LP_Windows Defender Antivirus Definitions Removal Detected	328
2.714LP_Exchange ProxyShell Pattern Detected	328
2.715LP_Successful Exchange ProxyShell Attack	329
2.716LP_Malicious Base64 Encoded PowerShell Keywords in Command Lines Detected	329
2.717LP_DLL Loaded Via AllocConsole and RunDLL32	330
2.718LP_Active Directory Database Dump Attempt	331
2.719LP_Suspicious Child Process Creation via OneNote	331
2.720LP_Usage of Web Request Command	332
2.721LP_Reconnaissance Activity with Nltest	333
2.722LP_Regsvr32 Network Activity Detected	333
2.723LP_Possible Reconnaissance Activity	334
2.724LP_Privilege Escalation via Kerberos KrbRelayUp	334
2.725LP_Suspicious Execution of LNK File	335
2.726LP_Insecure Policy Set via Set-ExecutionPolicy	335
2.727LP_Network Connection to Suspicious Server	336
3 NON-MITRE ATT&CK Analytics	337
3.1 LP_Windows Login Attempt on Disabled Account	337
3.2 LP_VMware Link Up	337
3.3 LP_VMware Link Down	338
3.4 LP_LogPoint License Expiry Status	338
3.5 LP_Mitre Initial Access Using Spearphishing link Detected	338
3.6 LP_Mitre Command and Control Using Standard Application Layer Protocol Detected	339
3.7 LP_Endpoint Protect Threat Content Detected	339

3.8	LP_Endpoint Protect Device Disconnect	340
3.9	LP_Endpoint Protect File Delete	340
3.10	LP_Endpoint Protect File Copied To USB Device	340
3.11	LP_System Owner or User Discovery Process Detected	341
3.12	LP_System Services Discovery Detected	341
3.13	LP_SolarisLDAP Password Spraying Attack Detected	342
3.14	LP_Microsoft Defender AMSI Trigger	342
3.15	LP_Petitpotam - Anonymous RPC and File Share	343
3.16	LP_RDP Sensitive Settings Changed	343
3.17	LP_Secure Deletion with SDelete	343
3.18	LP_Suspicious Keyboard Layout Load Detected	344
3.19	LP_Remote Code Execution using WMI Win32_Process Class over WinRM	344
3.20	LP_Remote Code Execution using WMI Win32_Service Class over WinRM	345
3.21	LP_Suspicious Microsoft SQL Server PowerShell Module Use Detected .	345
3.22	LP_Shadow Copy Deletion Using OS Utilities Detected	346
3.23	LP_Child Process Spawned via Diskshadow Detected	346
3.24	LP_Code Execution Via Diskshadow Detected	347
3.25	LP_Process Pattern Match For CVE-2021-40444 Exploitation	347
3.26	LP_Suspicious Extexport Execution Detected	348
3.27	LP_Proxy Execution via Workfolders	348
3.28	LP_Proxy Execution via Windows Update Client	349
3.29	LP_Suspicious DLL Execution Using Windows Address Book	349
3.30	LP_Suspicious Use of Dotnet Detected	350
3.31	LP_Execution of Arbitrary Executable Using Storddiag	350
3.32	LP_Process Creation via Time Travel Tracer	351
3.33	LP_Time Travel Debugging Utility DLL Loaded	351
3.34	LP_File Execution via Msdeploy	351
3.35	LP_CVE-2022-40684 Exploitation Detected	352
3.36	LP_Possible Proxy Execution of Malicious Code	352
3.37	LP_Suspicious Usage of BitLocker Management Script	353
3.38	LP_Proxy Execution of Payloads via Microsoft Signed Script	353
3.39	LP_Execution of Windows Defender Offline Shell from Suspicious Folder	354
3.40	LP_DLL Loaded Via AccCheckConsole	354
3.41	LP_Proxy Execution via Appvlp	355
3.42	LP_Proxy DLL Execution via UtilityFunctions	355
3.43	LP_Suspicious Usage of Squirrel Binary	355
3.44	LP_Suspicious File Share Permission	356
3.45	LP_Legitimate Application Dropping Script File	356
4	Alert Rules Dashboards	358
4.1	LP_Mitre Attack Analytics Overview	358
4.2	Adding the Alert Rules Dashboard	358
5	KB-Lists	362

s.. Logpoint Documentation documentation master file, created by
sphinx-quickstart on Wed Aug 3 14:33:36 2011.

ALERT RULES

Alert Rules consists of alert packages, the *LP_Mitre Attack Analytics Overview* dashboard package and *Knowledge Base (KB) Lists* for analytics integrated into Logpoint. It provides a compliance and triage dashboard, enabling you to analyze trends and behaviors of entities and users within the organization and perform defensive gap assessment with MITRE ATT&CK. The alerts triggered by Logpoint are categorized based on the [MITRE ATT&CK](#) framework and are the starting point to build various detection techniques. When Logpoint identifies threats within your environment, it triggers security alerts based on predetermined rules, allowing you to detect the malicious activity, advanced malware and their Techniques, Tactics and Procedures (TTPs) early, so you can take corrective actions against them. You can customize dashboards and alerts to suit your needs and perform in-depth analysis with customized data and searches.

Logpoint's [ATT&CK navigator](#) shows the coverage of the ATT&CK framework in Logpoint. You can use the navigator to match Logpoint alerts with the relevant ATT&CK techniques and tactics. Read more about MITRE ATT&CK techniques and tactics in addition to their integration in Logpoint on the [Logpoint website](#).

Alert Rules Component

1. Alert Packages

- [MITRE ATT&CK Analytics](#)
- [NON-MITRE ATT&CK Analytics](#).

Required Log Source

MITRE ATT&CK Analytics

- Windows Security Audit
- Windows Sysmon

Default Alert Rules

- All applicable log sources

MITRE ATT&CK ANALYTICS

The MITRE ATT&CK alerts available in Alert Rules are:

2.1 LP_High Severity EPP Alert

- **Trigger Condition:** High or critical severity alert is generated by any endpoint protection platform like CrowdStrike and Microsoft Defender for Endpoint.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** CrowdStrikeEPO, Microsoft Defender ATP
- **Query:**

```
norm_id=* device_category=EPP log_level IN [ "High", "Critical"]
```

2.2 LP_Host Generating Multiple Medium Severity EPP Alert

- **Trigger Condition:** Multiple medium severity alerts are generated by endpoint protection platforms like CrowdStrike and Microsoft Defender for Endpoint.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** CrowdStrikeEPO, Microsoft Defender ATP

- **Query:**

```
norm_id=* device_category=EPP log_level="Medium" | chart distinct_count(detection_
↪ id) as DC by host_id | search DC > 1
```

2.3 LP_Host Generating Multiple High Severity EPP Alert

- **Trigger Condition:** Multiple high or critical severity alerts are generated by endpoint protection platforms like CrowdStrike and Microsoft Defender for Endpoint.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** CrowdStrikeEPO, Microsoft Defender ATP
- **Query:**

```
norm_id=* device_category=EPP log_level IN ["high", "critical"] | chart distinct_
↪ count(detection_id) as DC by host_id | search DC > 1
```

2.4 LP_Medium Severity EPP Alert

- **Trigger Condition:** Medium severity alert is generated by any endpoint protection platform like CrowdStrike and Microsoft Defender for Endpoint.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** CrowdStrikeEPO, Microsoft Defender ATP
- **Query:**

```
norm_id=* device_category=EPP log_level="Medium"
```

2.5 LP_Windows Service Stop or Delete

- **Trigger Condition:** Windows service or process being stopped, deleted or disabled via system binaries is detected. `sc.exe`, `net.exe` and `net1.exe` are Microsoft Windows system internal binaries that adversaries can use to stop or delete services and processes to render those services unavailable to legitimate users or to avoid hindrances in their attack chain.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Service Stop
- **ATT&CK ID:** T1489
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create ("process" IN ["*\sc.exe", ".*\net.exe", ".*\net1.exe"]
↪ command="*stop*") OR ("process"="*\sc.exe" command IN ["*delete*", ".*disabled*
↪"]) -user IN EXCLUDED_USERS
```

2.6 LP_Suspicious Hack Tools Execution

- **Trigger Condition:** Execution of different Windows-based hack tools via their import hash (imphash) is detected, even if the files have been renamed. The `MALICIOUS_TOOLS_IMPHASH` list must be imported before activating this alert.
- **ATT&CK Category:** Credential Access, Resource Development
- **ATT&CK Tag:** OS Credential Dumping, Tool
- **ATT&CK ID:** T1003, T1588.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 hash_import IN MALICIOUS_TOOLS_IMPHASH
```

2.7 LP_Suspicious Execution of XORDump Utility for LSASS Memory Dump

- **Trigger Condition:** Suspicious execution of XORDump Utility, commonly used for LSASS Memory Dump, is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** LSASS Memory
- **ATT&CK ID:** T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\xordump.exe" OR command IN ["* -process ↪
↪ lsass.exe *", "* -m comsvcs *", "* -m dbghelp *", "* -m dbgcore *"]
```

2.8 LP_Suspicious Execution of Createdump Utility for Memory Dump

- **Trigger Condition:** Usage of the *createdump.exe* LOLOBIN utility to dump process memory is detected. Adversaries often seek to dump the *lsass.exe* process memory because it contains sensitive information, such as user credentials and authentication tokens.
- **ATT&CK Category:** Credential Access, Defense Evasion
- **ATT&CK Tag:** LSASS Memory, Masquerading
- **ATT&CK ID:** T1003.001, T1036
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\createdump.exe" OR file="FX_VER_
↪ INTERNALNAME_STR'" command IN ["* -u *", "* -full *", "* -f *", "* --name *", "*.dmp*
↪"]
```

2.9 LP_Suspicious DsInternals Get-ADReplAccount Activities

- **Trigger Condition:** Suspicious activities related to Get-ADReplAccount from the DsInternals PowerShell Module are detected. Adversaries may use this tool to maliciously access Domain Controllers' credentials. For event id 4104, Powershell Script Block logging is required.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** DCSync
- **ATT&CK ID:** T1003.006
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(label="process" label=create command="*Get-ADReplAccount*" command="*-All*"
↪ command="*Server*") OR (norm_id=WinServer event_id=4104 script_block="*Get-
↪ ADReplAccount*" script_block="*-All*" script_block="*Server*")
```

2.10 LP_Suspicious Activities Associated with NTDS Exfiltration

- **Trigger Condition:** Suspicious activities related to the Active Directory Domain Database (ntds.dit) are detected. Adversaries may attempt to access or create a copy of the Active Directory domain database to steal credential information and obtain information about domain members, such as devices, users and access rights.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** NTDS
- **ATT&CK ID:** T1003.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create ("process" IN ["*\\NTDSDump.exe", "*\\NTDSDumpEx.exe
↪"]) OR (command="*ntds.dit*" command="*system.hive*" OR (command=
↪ "*NTDSgrab.ps1*") OR (command="*ac i ntds*" command="*create full*") OR
↪ (command="*/c copy*" command="*\\windows\\ntds\\ntds.dit*") OR (command=
↪ "*activate instance ntds*" command="*create full*") OR (command="*powershell*"
↪ command="*ntds.dit*") OR (command="*ntds.dit*" (parent_process IN [
↪ "*tomcat*", "*\\AppData*", "*\\Temp\\*", "*\\Public\\*", "*\\PerfLogs\\*" ] OR "process" IN [
↪ "*\\Public\\*", "*\\PerfLogs\\*" ])))
```

(continues on next page)

(continued from previous page)

2.11 LP_Possible LSASS Memory Dump Via Windows Task Manager

- **Trigger Condition:** Creation of a *lsass.dmp* file by the taskmgr process is detected. Adversaries often seek to dump the *lsass.exe* process memory because it contains sensitive information, such as user credentials and authentication tokens.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** LSASS Memory
- **ATT&CK ID:** T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 "process"="*\taskmgr.exe" path=  
↪ "\Appdata\local\*" file="lsass*.dmp"
```

2.12 LP_Possible LSASS Dump Via SilentProcessExit Technique

- **Trigger Condition:** Dumping of a possible LSASS via the SilentProcessExit Technique is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** LSASS Memory
- **ATT&CK ID:** T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id IN [12,13,14] target_object="*Microsoft\Windows  
↪ NT\CurrentVersion\SilentProcessExit\lsass.exe"
```

2.13 LP_NTDS or SAM Database Copy Operation

- **Trigger Condition:** Copy operation of Active Directory Domain Database (ntds.dit) or Security Account Manager (SAM) files is detected. Adversaries may attempt to access or create a copy of the Active Directory domain database or SAM database to steal credential information and obtain other information about domain members, such as devices, users and access rights.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, Security Account Manager, NTDS
- **ATT&CK ID:** T1003, T1003.002, T1003.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create (command IN ["*copy*", "*xcopy*", "*Copy-Item*",
↪ "*move*", "*cp*", "*mv*"] OR "process"="*\esentutl.exe" command IN ["*/y*", "*/vss*",
↪ "*/d*"]) command IN ["*\NTDS.dit",
↪ ".*\GLOBALROOT\Device\HarddiskVolumeShadowCopy*", ".*\SYSTEM*",
↪ ".*\SECURITY*", ".*C:\tmp\log*", ".*\config\SAM", ".*system32/config/SAM*"]
```

2.14 LP_Microsoft IIS Service Account Password Dumped

- **Trigger Condition:** Execution of Information Services (IIS) command-line tool AppCmd to list passwords is detected. An attacker with IIS web server access via a web shell can decrypt and dump the IIS AppPool service account password using AppCmd.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ("process"="*\appcmd.exe" or file=appcmd.exe)↗
↪ command="*list *" (command IN ["*/config*", "*/xml*", ".*-config*", ".*-xml*"]) OR↗
↪ (command IN ["*/@t'", "*/text*", "*/show*", ".*-@t'", ".*-text*", ".*-show*",
↪ ".*password*", ".*:\*"])
```

2.15 LP_Dumpert Process Dumper Execution

- **Trigger Condition:** Dumping of a possible credential via a tool called NPPSpy is detected. NPPSpy is a Network Provider/Credential Manager DLL that extracts credentials and stores them in plain text. This alert monitors file creation, registry manipulation and process creation events that indicate a potential credential dump via NPPSpy.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** LSASS Memory
- **ATT&CK ID:** T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 hash_import=
↪ "09D278F9DE118EF09163C6140255C690" or command="*Dumpert.dll*
```

2.16 LP_Credential Dump Via NPPSpy

- **Trigger Condition:** Dumping of a possible credential via a tool called NPPSpy is detected. NPPSpy is a Network Provider/Credential Manager DLL that extracts credentials and stores them in plain text. This alert monitors file creation, registry manipulation and process creation events that indicate a potential credential dump via NPPSpy.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(label=Registry label=Set target_object IN ["*\System\CurrentControlSet\Services\*",
↪ "*CurrentControlSet\Control\*"] target_object="*\NetworkProvider*" -(target_object
↪ IN ["*\System\CurrentControlSet\Services\WebClient\NetworkProvider*",
↪ "*\System\CurrentControlSet\Services\LanmanWorkstation\NetworkProvider*",
↪ "*\System\CurrentControlSet\Services\RDPNP\NetworkProvider*"] OR "process"=
↪ "C:\Windows\System32\poqexec.exe")) OR (label=file label=create file IN ["NPPSpy.txt",
↪ "NPPSpy.dll"]) OR (label="process" label=create command=
↪ "*\System\CurrentControlSet\Services\*" command="*\NetworkProvider*")
```

2.17 LP_Malicious PowerShell Commandlets Detected

- **Trigger Condition:** Commandlet names from well-known Command and Scripting Interpreter, PowerShell exploitation frameworks are detected. The MALICIOUS_POWERSHELL_COMMANDLET_NAMES list must be imported for this alert to work correctly.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** PowerShell
- **ATT&CK ID:** T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
command IN MALICIOUS_POWERSHELL_COMMANDLET_NAMES -command="*Get-
↪ SystemDriveInfo*" OR script_block IN MALICIOUS_POWERSHELL_COMMANDLET_
↪ NAMES -script_block="*Get-SystemDriveInfo*"
```

2.18 LP_Code Execution Via Diskshadow Detected

- **Trigger Condition:** Usage of diskshadow binary to execute code from a file is detected. Adversaries can use diskshadow with -s or /s tag to execute a command from a file and bypass detection.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\diskshadow.exe" command IN ["*/s *", "*-s *
↪ "]
```

2.19 LP_Image Mount Indicator in Recent Files

- **Trigger Condition:** Recent element files pointing to .iso, .img, .vhd or .vhdx files are detected. These image files are used in phishing attacks to deliver malware and circumvent the Mark of the Web (MotW) in Windows to execute malicious commands. It is a false positive on server systems, but on workstations, users rarely mount .iso or .img files.
- **ATT&CK Category:** Initial Access, Defense Evasion
- **ATT&CK Tag:** Mark-of-the-Web Bypass, Spearphishing Attachment
- **ATT&CK ID:** T1553.005, T1566.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id="WindowsSysmon" event_id=11 path="*\Microsoft\Windows\Recent\*" file IN [
↳ "*.iso.lnk", "*.img.lnk", "*.vhd.lnk", "*.vhdx.lnk"]
```

2.20 LP_Disk Image File Created

- **Trigger Condition:** Image files with extensions like .iso, .vhd, and .vhdx are downloaded from the internet into a user's download or temporary folder. Adversaries often deliver their malware payloads through a .iso file format to bypass the Mark of the Web (MotW) in Windows and execute their payload successfully.
- **ATT&CK Category:** Initial Access, Defense Evasion
- **ATT&CK Tag:** Mark-of-the-Web Bypass, Spearphishing Attachment
- **ATT&CK ID:** T1553.005, T1566.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id="WindowsSysmon" event_id=11 (path="*Users*" path="*Downloads*") OR
↳ (path="*Appdata*") file IN ["*.iso", "*.vhd", "*.vhdx", "*.img"]
```

2.21 LP_PowerShell Execution via DLL Detected

- **Trigger Condition:** Execution of PowerShell via DLL instead of *powershell.exe* is detected. Powershell is a command-line shell used in Windows. Adversaries can execute PowerShell for malicious activities even if *powershell.exe* is blocked and no strict application whitelisting is implemented.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** PowerShell, Rundll32
- **ATT&CK ID:** T1059.001, T1218.011
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ("process" IN ["*\rundll32.exe", "*\regsvcs.exe",
↳ "*\InstallUtil.exe", "\regasm.exe"] OR file in ["RUNDLL32.EXE", "RegSvcs.exe", "InstallUtil.
↳ exe", "RegAsm.exe"]) command IN ["*Default.GetString*", "*FromBase64String*",
↳ "*Invoke-Expression*", "*IEX *", "*Invoke-Command*", "*ICM *", "*DownloadString*"]
```

2.22 LP_Suspicious Windows Defender Registry keys Modification

- **Trigger Condition:** Changes in the Windows Defender registry settings to disable Windows Defender functionalities. Adversaries try to alter Windows Defender-associated registries to disable protection and detection features.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Disable or Modify Tools
- **ATT&CK ID:** T1562.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=registry label=set target_object IN ["*\SOFTWARE\Microsoft\Windows Defender*",
↳ "*\SOFTWARE\Policies\Microsoft\Windows Defender*"] ( detail="DWORD(
↳ 0x00000001)" target_object IN ["*\DisableAntiSpyware", "*\DisableAntiVirus",
↳ "*\DisableBehaviorMonitoring", "*\DisableIntrusionPreventionSystem",
↳ "*\DisableIOAVProtection", "*\DisableOnAccessProtection",
↳ "*\DisableRealtimeMonitoring", "*\DisableScanOnRealtimeEnable",
↳ "*\DisableScriptScanning", "*\DisableEnhancedNotifications",
↳ "*\DisableBlockAtFirstSeen"] ) OR ( detail="DWORD(0x00000000)" target_object IN [
↳ "*\App and Browser protection\DisallowExploitProtectionOverride",
↳ "*\Features\TamperProtection", "*\MpEngine\MpEnablePus", "*\PUAProtection",
↳ "*\SignatureUpdate\ForceUpdateFromMU", "*\SpyNet\SpynetReporting",
↳ "*\SpyNet\SubmitSamplesConsent", "*\Windows Defender Exploit Guard\Controlled
↳ Folder Access\EnableControlledFolderAccess"] )
```

(continued from previous page)

2.23 LP_Executable Files Created and Executed by Office Applications

- **Trigger Condition:** When the executable file dropped or modified via office applications and executed within a specific time range is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing, Spearphishing Attachment
- **ATT&CK ID:** T1566, T1566.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
[norm_id=WindowsSysmon event_id=11 "process" IN ["*\WINWORD.EXE", "*\EXCEL.EXE",
↪ "\POWERPNT.EXE", "*\MSACCESS.EXE"] file IN ["*.exe", "*.com", "*.bat", "*.cmd"]]]2
↪ as s1 followed by [norm_id=WindowsSysmon event_id=1] as s2 within 2 minute on s1.
↪ path=s2.path and s1.file=s2.file | rename s1.host as host, s1.user as user, s1.domain as2
↪ domain, s1.process as "process", s1.file as file, s1.path as path
```

2.24 LP_WMI Backdoor in Exchange Transport Agent

- **Trigger Condition:** A WMI backdoor in Exchange Transport Agents (ETA) via WMI event filters is detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Event Triggered Execution, Windows Management Instrumentation Event Subscription
- **ATT&CK ID:** T1546, T1546.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (parent_process="*\EdgeTransport.exe" -("process"=
↪ "C:\Windows\System32\conhost.exe" OR ("process"="C:\Program2
↪ Files\Microsoft\Exchange Server\*" "process"="*\Bin\OleConverter.exe")) -user IN2
↪ EXCLUDED_USERS
```

2.25 LP_Suspicious Msiexec Usage Detected

- **Trigger Condition:** A .msi file executed from publicly writable folder and a command prompt or powershell spawned by msiexec.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Msiexec
- **ATT&CK ID:** T1218.007
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ("process"="*\msiexec.exe" command IN
["*\ProgramData*", " *\AppData\Local*", " *\AppData\Roaming*", " *\Users\Public*"]
command IN [ "*.msi *", "*.msi" ]) OR
(parent_process="*\msiexec.exe" "process" IN
["*\cmd.exe", " *\powershell.exe", " *\pwsh.exe" ])
```

2.26 LP_Suspicious Usage of Advanced IP Scanner

- **Trigger Condition:** Suspicious usage of Advanced IP Scanner is detected.
- **ATT&CK Category:** Reconnaissance, Discovery
- **ATT&CK Tag:** Network Service Discovery, Network Share Discovery, Gather Victim Network Information
- **ATT&CK ID:** T1046, T1135, T1590
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create ("process"="*\advanced_ip_scanner*" OR file="*\advanced_
↪ ip_scanner*") OR (description="*Advanced IP Scanner*") OR (command="*/portable*"
↪ command="*/lng*")
```

2.27 LP_Persistence through Port Monitor Registry modification

- **Trigger Condition:** A new entry in the printer monitor registry is detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Boot or Logon Autostart Execution, Port Monitors
- **ATT&CK ID:** T1547, T1547.010
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 target_object=
↪ "HKLM\SYSTEM\CurrentControlSet\Control\Print\Monitors\*" detail="*.dll" -(("process
↪ "= "C:\Windows\System32\spoolsv.exe" target_object=
↪ "*\System\CurrentControlSet\Control\Print\Monitors\CutePDF Writer Monitor v4.
↪ 0\Driver*" detail="cpwmon64_v40.dll" user IN ["*AUTHOR*", "*AUTOR*"]) OR (target_
↪ object= "*Control\Print\Monitors\MONVNC\Driver*" ) OR (target_object=
↪ "*Control\Print\Environments\*" target_object= "*\Drivers\*" target_object= "*\VNC
↪ Printer*"))
```

2.28 LP_File Dropped in Suspicious Location

- **Trigger Condition:** Dropping a file in a suspicious system location is detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Ingress Tool Transfer
- **ATT&CK ID:** T1105
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 path IN ["C:\ProgramData*", "*\AppData\Local*",
↪ "*\AppData\Roaming*", "C:\Users\Public*"] -"process" IN ["*\Microsoft Visual
↪ Studio\Installer\*\BackgroundDownload.exe", "C:\Windows\system32\cleanmgr.exe",
↪ "*\Microsoft\Windows Defender\*\MsMpEng.exe",
↪ "C:\Windows\SysWOW64\OneDriveSetup.exe", "*\AppData\Local\Microsoft\OneDrive*
↪ ", "*\Microsoft\Windows Defender\platform\*\MpCmdRun.exe",
↪ "*\AppData\Local\Temp\mpam-*.exe"] -file IN ["vs_setup_bootstrapper.exe",
↪ "DismHost.exe", "*_PSScriptPolicyTest*.ps1"]
```

2.29 LP_Alternate PowerShell Hosts via Powershell Module

- **Trigger Condition:** Alternate Command and Scripting Interpreter and PowerShell hosts are detected. Adversaries might use this technique to bypass detections looking for *powershell.exe*. PowerShell commands/scripts can also be executed without directly invoking the *powershell.exe* binary. Powershell module logging is needed for log source.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4103 host_application IN ["*= powershell*", "*=?
↪ C:\Windows\System32\WindowsPowerShell\v1.0\powershell*", "*=?
↪ C:\Windows\SysWOW64\WindowsPowerShell\v1.0\powershell*", "*= C:/Windows/
↪ System32/WindowsPowerShell/v1.0/powershell*", "*= C:/Windows/SysWOW64/
↪ WindowsPowerShell/v1.0/powershell*"] -(host_application IN ["*=?
↪ C:\WINDOWS\System32\sdiagnhost.exe -Embedding*", "*ConfigSyncRun.exe*",
↪ "*C:\Windows\system32\dsac.exe*", "*C:\Windows\system32\wsmprovhost.exe -
↪ Embedding*"] OR payload IN ["*Update-Help*", "*Failed to update Help for the?
↪ module*"])
```

2.30 LP_Suspicious Usage of Where Binary

- **Trigger Condition:** An enumeration attempt on browser bookmarks to learn more about compromised hosts is detected.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Browser Bookmark Discovery
- **ATT&CK ID:** T1217
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Process" label=Create "process"="*\where.exe" command in ["*places.sqlite*",
↳ "*cookies.sqlite*", "*formhistory.sqlite*", "*logins.json*", "*key4.db*", "*key3.db*",
↳ "*sessionstore.jsonlz4*", "*History*", "*Bookmarks*", "*Cookies*", "*Login Data*"]
```

2.31 LP_MSHTA - Activity Detected

- **Trigger Condition:** Network connection events initiated by *mshta.exe* are detected. Adversaries abuse *mshta.exe* for proxy execution of malicious .hta files, and Javascript or VBScript through a trusted Windows utility.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** Signed Binary Proxy Execution, Mshta
- **ATT&CK ID:** T1218, T1218.005
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=3 (command="*mshta.exe" or parent_command=
↳ "*mshta.exe") -user IN EXCLUDED_USERS
```

2.32 LP_Alternate PowerShell Hosts via Named Pipe

- **Trigger Condition:** Alternate Command and Scripting Interpreter and PowerShell hosts are detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=17 pipe="PSHost*" source_image=* -source_image
↳ IN ["*\powershell.exe", "*\powershell_ise.exe", "*\WINDOWS\System32\sdiagnhost.exe",
↳ "*\WINDOWS\System32\wsmprovhost.exe", "*\Windows\system32\dsac.exe",
↳ "*\Windows\system32\wbem\wmiprvse.exe", "*\ForefrontActiveDirectoryConnector.exe",
↳ "*c:\windows\system32\inetsrv\w3wp.exe", "C:\Program Files\Citrix\*", "C:\Program
↳ Files\Microsoft\Exchange Server\*", "C:\Windows\system32\ServerManager.exe",
↳ "C:\Program Files\PowerShell\7\pwsh.exe", ".*\Program Files\Microsoft SQL
↳ Server\*\Tools\Binn\SQLPS.exe"]
```

(continues on next page)

(continued from previous page)

2.33 LP_Suspicious File Execution Using Wcript or Cscript

- **Trigger Condition:** Process create events for the *fltmc.exe* utility and the specific command line used to unload minifilter drivers is detected. An adversary may attempt to block indicators or events captured by sensors from being gathered and analyzed.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Indicator Blocking
- **ATT&CK ID:** T1562, T1562.006
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Process" label=Create ("process"="*\fltmc.exe" OR command="*\fltmc*unload*") -
↪ user IN EXCLUDED_USERS
```

2.34 LP_Suspicious Child Process Spawned by Microsoft Office Product

- **Trigger Condition:** Suspicious child process spawned by Microsoft Office Products such as Excel, Powerpoint, Onenote or Visio are detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell, Windows Command Shell, Malicious File
- **ATT&CK ID:** T1059, T1059.001, T1059.003, T1204.002
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Process" label=Create parent_process IN ["*\WINWORD.EXE", " *\EXCEL.EXE",
↪ " *\POWERPNT.exe", " *\MSPUB.exe", " *\VISIO.exe", " *\OUTLOOK.EXE",
↪ " *\MSACCESS.EXE", " *\EQNEDT32.EXE", " *\Onenote.exe", " *\wordview.exe",
↪ " *\outlook.exe"] ("process" IN ["\AppVLP.exe", " *\bash.exe", " *\bitsadmin.exe",
↪ " *\certoc.exe", " *\certutil.exe", " *\cmd.exe", " *\cmstp.exe", " *\control.exe", " *\cscript.exe",
↪ " *\curl.exe", " *\forfiles.exe", " *\hh.exe", " *\ieexec.exe", " *\installutil.exe", " *\javaw.exe",
↪ " *\mftrace.exe", " *\Microsoft.Workflow.Compiler.exe", " *\msbuild.exe", " *\msdt.exe",
↪ " *\mshta.exe", " *\msidb.exe", " *\msiexec.exe", " *\msxsl.exe", " *\odbcconf.exe",
↪ " *\localua.exe", " *\powershell.exe", " *\pwsh.exe", " *\regasm.exe", " *\regsvcs.exe",
↪ " *\regsvr32.exe", " *\rundll32.exe", " *\schtasks.exe", " *\scrcons.exe", " *\scriptrunner.exe",
↪ " *\sh.exe", " *\svchost.exe", " *\verclsid.exe", " *\wmic.exe", " *\workfolders.exe", " *\wscript.exe",
↪ " *\AppData*\*\*\Local\Public\*\*\ProgramData\*\*\Windows\Task\*"]
```

(continued from previous page)

2.35 LP_Windows Login Attempt on Disabled Account

- **Trigger Condition:** Login attempt on disabled account is detected.
- **ATT&CK Category:** Initial Access, Persistence, Privilege Escalation, Defense Evasion
- **ATT&CK Tag:** Valid Accounts
- **ATT&CK ID:** T1078
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer* label=User label>Login label=Fail sub_status_code="0xC0000072" -
↪target_user=*$ -user=*$ -user IN EXCLUDED_USERS | rename user as target_user,
↪domain as target_domain, reason as failure_reason
```

2.36 LP_RClone Utility Execution

- **Trigger Condition:** Execution of the RClone tool or command line option used in the tool is detected.
- **ATT&CK Category:** Exfiltration
- **ATT&CK Tag:** Exfiltration Over Web Service, Exfiltration to Cloud Storage
- **ATT&CK ID:** T1567, T1567.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (command="*--config *" command="*--no-check-
↪certificate *" command="* copy *") OR (("process"="*\rclone.exe" OR description=
↪"Rsync for cloud storage") command IN ["*pass*", "*user*", "*copy*", "*sync*", "*config*",
↪", "*lsd*", "*remote*", "*ls*", "*mega*", "*pcloud*", "*ftp*", "*ignore-existing*", "*auto-
↪confirm*", "*transfers*", "*multi-thread-streams*", "*no-check-certificate *"])
```

2.37 LP_UAC Bypass via SDCLT

- **Trigger Condition:** User Account Control (UAC) bypass attempt via *SDCLT.exe* is detected or it detects modification to registry keys *HKCU:\Software\Classes\exefile\shell\runas\command\isolatedCommand* and *HKCU:\Software\Classes\Folder\shell\open\command* which can indicate UAC bypass using registry key manipulation of *sdclt.exe*.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** Abuse Elevation Control Mechanism, Bypass User Account Control
- **ATT&CK ID:** T1548, T1548.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
(norm_id=WindowsSysmon event_id=1 parent_process="*\sdclt.exe" parent_command=
↪ "*/kickoffelev*" integrity_level=High -"process" IN ["C:\Windows\SysWOW64\sdclt.exe"
↪ ", "C:\Windows\System32\sdclt.exe", "C:\Windows\SysWOW64\control.exe",
↪ "C:\Windows\System32\control.exe", "C:\Windows\System32\WerFault.exe",
↪ "C:\Windows\SysWOW64\WerFault.exe", "C:\Windows\System32\wermgr.exe",
↪ "C:\Windows\SysWOW64\wermgr.exe"]) OR (norm_id=WindowsSysmon event_id="13"
↪ target_object IN ["*\Classes\exefile\shell\runas\command\isolatedCommand*",
↪ "*/Classes\Folder\shell\open\command*"])
```

2.38 LP_Credential Dumping - Registry

- **Trigger Condition:** Attempts of adversaries to dump credentials to obtain account login and credential material exploiting registries, generally in the form of a hash or a clear text password, from the operating system and software are detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```

event_id IN ["12", "13", "14"]
-"process" IN ["*C:\WINDOWS\system32\lsass.exe", "*C:\WINDOWS\system32\services.
↪exe"]
-target_object = "*\Lsa\RestrictRemoteSamEventThrottlingWindow"
target_object IN [
↪ "*\SOFTWARE\Microsoft\Windows\CurrentVersion\Authentication\Credential Provider\*"
↪ ", "*\SYSTEM\CurrentControlSet\Control\Lsa\*",
↪ "*\SYSTEM\CurrentControlSet\Control\SecurityProviders\SecurityProviders\*",
↪ "*\Control\SecurityProviders\WDigest\*"]
-user IN EXCLUDED_USERS

```

2.39 LP_Suspicious Binary Execution in User Directory

- **Trigger condition:** An executable in the users directory started from Microsoft Word, Excel, Powerpoint, Publisher or Visio is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Malicious File
- **ATT&CK ID:** T1204.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```

label="Process" label=Create parent_process IN ["*\WINWORD.EXE", "*\EXCEL.EXE",
↪ "*\POWERPNT.exe", "*\MSPUB.exe", "*\VISIO.exe", "*\MSACCESS.exe",
↪ "*\EQNEDT32.exe"] "process"="C:\users\*.exe" -"process"="*\Teams.exe"

```

2.40 LP_Suspicious WMIC Child Process

- **Trigger condition:** Suspicious child process of WMIC is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Windows Management Instrumentation
- **ATT&CK ID:** T1047
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process="*\wmic.exe" - "process" IN [
↪ "C:\Windows\System32\conhost.exe", "C:\Windows\system32\wbem\WMIC.exe",
↪ "C:\Windows\syswow64\wbem\WMIC.exe", "C:\Windows\system32\WerFault.exe",
↪ "C:\Windows\SysWOW64\WerFault.exe"]
```

2.41 LP_Suspicious File Execution Using Wscript or Cscript

- **Trigger condition:** File with extensions of .jse, .vbe, .js and .vba is executed using wscript or cscript is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Visual Basic, JavaScript
- **ATT&CK ID:** T1059.005, T1059.007
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" "process" IN ["*\wscript.exe", "cscript.exe"] -
↪ command="*.json*" command IN ["*.jse*", "vbe*", "js*", "vba*"]
```

2.42 LP_BCDEdit Safe Mode Command Execution

- **Trigger condition:** Spawning of Boot Configuration Data Edit (BCDEdit) from suspicious processes, to configure a reboot into safe mode, is detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Inhibit System Recovery
- **ATT&CK ID:** T1490
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\bcdedit.exe" command IN ["*minimal*",
↪ "*network*", "*safebootalternateshell*"] parent_process IN ["*\WINWORD.EXE",
↪ "EXCEL.EXE", "POWERPNT.EXE", "MSACCESS.EXE", "MSPUB.EXE",
↪ "OUTLOOK.EXE", "fltldr.exe", "cscript.exe", "powershell.exe", "pwsh.exe",
↪ "wscript.exe", "cmd.exe", "rundll32.exe", "regsvr32.exe", "mshta.exe",
↪ "msbuild.exe"]
```

2.43 LP_Suspicious Encoded PowerShell Command Line

- **Trigger condition:** A suspicious PowerShell base64 encoded command is detected. Adversaries can use this technique to evade defense mechanisms by encoding and decoding payload.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command IN ["*-e JAB*", "*-e JAB*", "*-e JAB*", "*-e JAB*", "*-e JAB*", "*-e JAB*", "*-en JAB*", "*-enc JAB*", "*-enc* JAB*", "*-w*", "*-hidden -e* JAB*", "* BA^J e-", "*-e SUVY|*", "*-e aWV4|*", "*-e SQBFAFgA*", "*-e aQBIAHgA*", "*-enc SUVY|*", "*-enc aWV4|*", "*-enc SQBFAFgA*", "*-enc aQBIAHgA*"] -command="* -ExecutionPolicy remotesigned *" -user IN EXCLUDED_USERS
```

2.44 LP_Persistence Attack through Accessibility Process Feature

- **Trigger condition:** Accessibility features used to execute a command prompt or other backdoors are detected.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Event Triggered Execution, Accessibility Features
- **ATT&CK ID:** T1546, T1546.008
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 user="SYSTEM" parent_process IN ["*\\Utilman.exe",
→ "*\\winlogon.exe"] "process" IN ["*\\osk.exe", "*\\Magnify.exe", "*\\Narrator.exe",
→ "*\\sethc.exe", "*\\utilman.exe", "*\\ATBroker.exe", "*\\DisplaySwitch.exe"] -file IN ["osk.
→ exe", "sethc.exe", "utilman2.exe", "DisplaySwitch.exe", "ATBroker.exe", "ScreenMagnifier.
→ exe", "SR.exe", "Narrator.exe", "magnify.exe"]
```

2.45 LP_Suspicious DLL Added to Applnit DLL Registry

- **Trigger condition:** A suspicious Applnit_DLL functionality seen in an environment that could relate to a possible persistence attack is detected.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Event Triggered Execution, Applnit DLLs
- **ATT&CK ID:** T1546, T1546.010
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=Registry (target_object IN [
  ↳ "*\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Windows\Applnit_Dlls",
  ↳ "*\SOFTWARE\Wow6432Node\Microsoft\Windows
  ↳ NT\CurrentVersion\Windows\Applnit_Dlls"] OR new_value IN [
  ↳ "*\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Windows\Applnit_Dlls",
  ↳ "*\SOFTWARE\Wow6432Node\Microsoft\Windows
  ↳ NT\CurrentVersion\Windows\Applnit_Dlls"]) -detail= "(Empty)"
```

2.46 LP_Firewall Rule Addition via Netsh Detected

- **Trigger condition:** A connection allowed by a port or application on the Windows firewall is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Disable or Modify System Firewall
- **ATT&CK ID:** T1562, T1562.004
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label= "Process" label=Create command IN [ "*netsh* firewall add*" ] -user IN EXCLUDED_
  ↳ USERS
```

2.47 LP_MSHTA Spawned by SVCHOST Detected

- **Trigger condition:** Microsoft HTML Application Host (MSHTA) binary spawned by the Svchost process is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Mshta
- **ATT&CK ID:** T1218.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process="*\svchost.exe" "process"="*\mshta.exe" -
↪ user IN EXCLUDED_USERS
```

2.48 LP_Exploitation of CVE-2019-1388 Detected

- **Trigger condition:** An exploitation attempt of CVE-2019-1388 in which the UAC consent dialogue used to invoke a Windows process running as LOCAL_SYSTEM is detected. CVE-2019-1388 is an elevation of privilege vulnerability in the Windows Certificate Dialog.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** Exploitation for Privilege Escalation
- **ATT&CK ID:** T1068
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process="*\consent.exe" "process"="*\iexplore.exe"
↪ "command"="* http*" (integrity_level="System" OR user IN ["SYSTEM", "*AUTHORI*",
↪ "*AUTORI*", "*AUKTORI*"])
```

2.49 LP_Sophos EPP Registry Modification

- **Trigger condition:** Modifying Sophos EPP Tamper Protection registry keys to turn off services is detected. Sophos EPP Tamper Protection is the service offered by the EPP that constantly checks if a malware or adversary or rogue employee turns off the AV services to avoid detection.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Modify Registry
- **ATT&CK ID:** T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Registry label=Set label=value target_object IN [
↪ "*\CurrentControlSet\Services\Sophos Endpoint*\SEDEnabled",
↪ "*\CurrentControlSet\Services\Sophos Endpoint*\SAVEEnabled "] detail= "DWORD"
↪ (0x00000000) "
```

2.50 LP_Office365 Inbox Rule with Special Characters Created

- **Trigger condition:** A new inbox rule created on Office365 with a suspicious name made of only special characters is detected.
- **ATT&CK Category:** Collection
- **ATT&CK Tag:** Email Forwarding Rule
- **ATT&CK ID:** T1114.003
- **Minimum Log Source Requirement:** Office365
- **Query:**

```
norm_id=Office365 action="New-InboxRule" name=* | process regex("(?P<match>^[^a-
↪ zA-Z0-9]*$)", "name") | search match=*
```

2.51 LP_Suspicious WerFault Process Creation

- **Trigger condition:** A services.exe spawns werfault.exe process from non-default paths is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036

- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process" = "*\WerFault.exe" ("process" =
↪ "C:\Windows\WinSxS\*" OR -"process" IN ["C:\Windows\System32\*",
↪ "C:\Windows\SysWOW64\*"])
```

2.52 LP_Suspicious WerFault File Creation

- **Trigger condition:** A non-system process drops the *WerFault.exe* binary inside the *C:\Windows\WinSxS* folder is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=File label=Create path="C:\Windows\WinSxS\*" file="WerFault.exe" - "process" [?]
↪ IN ["C:\Windows\System32\*", "C:\Windows\SysWOW64\*", "*C:\Windows\WinSxS\*"]
```

2.53 LP_Snake Malware Covert Store Registry Key Detected

- **Trigger condition:** A registry operation for the key *SECURITYPolicySecretsn* is detected. Snake Malware utilizes the registry key to store the encryption key.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Modify Registry
- **ATT&CK ID:** T1112
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(norm_id=WindowsSysmon event_id IN [12,13,14] target_object=
↪ "*SECURITY\Policy\Secrets\n") OR (norm_id=Winserver event_id=4657 path=
↪ "*SECURITY\Policy\Secrets\n")
```

2.54 LP_Suspicious WerFault Service Creation

- **Trigger condition:** A new service installed using the *WerFault.exe* file is detected. *WerFault.exe* is a system component that plays a crucial role in Windows operating systems. It manages system error reporting.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
norm_id=WinServer event_id IN [4697,7045] (file="WerFault.exe" OR path="*WerFault.
↪ exe") (path="C:\Windows\WinSxS\*" OR -path IN ["C:\Windows\System32*",
↪ "C:\Windows\SysWOW64*"])
```

2.55 LP_Suspicious Named Pipe Connection to Azure AD Connect Database

- **Trigger condition:** Named pipe connection to Azure AD Connect database from suspicious processes coming from command shells like PowerShell, which may indicate attackers attempting to dump plaintext credentials of AD and Azure AD connector account using tools such as AADInternals is detected.
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=Pipe label=Connect pipe="*\\tsql\\query" -image IN [
↪ "*\\Program Files\\Microsoft Azure AD Sync\\Bin\\miiserver.exe", "*\\Tools\\Binn\\SqlCmd.exe
↪ "]
```

2.56 LP_Suspicious Driver Loaded

- **Trigger condition:** Misuse of known drivers by adversaries for malicious purposes is detected. The driver itself are not malicious but are misused by threat actors. For this alert to trigger SUSPICIOUS_DRIVER list is required.
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Image label=Load image IN SUSPICIOUS_DRIVER
```

2.57 LP_AADInternals PowerShell Cmdlet Execution

- **Trigger condition:** The execution of *AADInternals* commandlets is detected. AADInternals (S0677) toolkit is a PowerShell module containing tools for administering and hacking Azure AD and Office 365. Adversaries use *AADInternals* to extract the credentials from the system where the AAD Connect server was installed and compromise the AAD environment.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows, PowerShell
- **Query:**

```
norm_id=WinServer event_source="Microsoft-Windows-PowerShell" event_id=4104  
↪script_block IN AADINTERNALS_CMDLETS
```

2.58 LP_Suspicious Scheduled Task Creation via Masqueraded XML File

- **Trigger condition:** The creation of a suspicious scheduled task using an XML file with a masqueraded extension is detected.

- **ATT&CK Category:** Persistence, Defense Evasion
- **ATT&CK Tag:** Masquerading, Match Legitimate Name or Location, Scheduled Task/Job and Scheduled Task
- **ATT&CK ID:** T1036, T1036.005, T1053 and T1053.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

```
label=create label="process" "process"="*\schtasks.exe" command IN ["*/create*", "*-
↪ create*"] command IN ["*/xml*", "*-xml*"] (-integrity_level=system OR -integrity_
↪ label=*system*) -command = *.xml* ((-parent_process IN [
↪ ".*:\ProgramData\OEM\UpgradeTool\CareCenter_*\BUnzip\Setup_msi.exe",
↪ ".*:\Program Files\Axis Communications\AXIS Camera Station\SetupActions.exe",
↪ ".*:\Program Files\Axis Communications\AXIS Device Manager\AdmSetupActions.exe",
↪ ".*:\Program Files (x86)\Zemana\AntiMalware\AntiMalware.exe", ".*:\Program
↪ Files\Dell\SupportAssist\pcdrui.exe" ]) OR (-parent_process = ".*\rundll32.exe"
↪ command = ".*\WINDOWS\Installer\MSI*.tmp,
↪ zzzzInvokeManagedCustomActionOutOfProc" ))
```

2.59 LP_Suspicious Microsoft Equation Editor Child Process

- **Trigger condition:** A suspicious child process of Microsoft's equation editor is detected as a sign of possible exploitation of CVE-2017-11882. CVE-2017-11882 is a vulnerability in Microsoft Office's Equation Editor component.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Exploitation for Client Execution
- **ATT&CK ID:** T1203
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

```
label="Process" label=Create parent_process=".*\EQNEDT32.exe" - "process" IN [
↪ "C:\Windows\System32\WerFault.exe", "C:\Windows\SysWOW64\WerFault.exe"]
```

2.60 LP_Windows Error Process Masquerading

- **Trigger condition:** Suspicious Windows error reporting process behavior, where network connections are made after execution is detected.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon

```
[norm_id=WindowsSysmon event_id=1 "process" IN ["*\WerMgr.exe", "*\WerFault.exe"]][?]
↪ as s1 followed by [norm_id=WindowsSysmon event_id=3 "process" IN ["*\WerMgr.exe",
↪ "*\WerFault.exe"]] as s2 within 1 minute on s1.process_guid=s2.process_guid | rename[?]
↪ s1.host as host, s1.user as user, s1.domain as domain, s1.image as image, s2.destination_
↪ address as destination_address, s2.destination_port as destination_port
```

2.61 LP_Bypass UAC via CMSTP Detected

- **Trigger condition:** Child processes of automatically elevated instances of Microsoft Connection Manager Profile Installer (*cmstp.exe*) are detected.
- **ATT&CK Category:** Privilege Escalation, Defense Evasion
- **ATT&CK Tag:** CMSTP, Abuse Elevation Control Mechanism, Bypass User Account Control
- **ATT&CK ID:** T1218.003, T1548, T1548.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\cmstp.exe" command IN ["/s*", "/au*", "/
↪ ni*", "*-s*", "*-au*", "*-ni*"] -user IN EXCLUDED_USERS
```

2.62 LP_Application Whitelisting Bypass via Dxcap Detected

- **Trigger condition:** Adversaries bypass process and/or signature-based defenses by execution of *Dxcap.exe* is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Trusted Developer Utilities Proxy Execution
- **ATT&CK ID:** T1127
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

- **Query:**

```
label="Process" label=Create "process"="*\dxcap.exe" command="*-c*" command="*.
↪exe*" -user IN EXCLUDED_USERS
```

2.63 LP_Suspicious WMIC XSL Script Execution

- **Trigger condition:** Loading of a Windows Script module through wmic by Microsoft Core XML Services (MSXML) process is detected to bypass application whitelisting.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** XSL Script Processing
- **ATT&CK ID:** T1220
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
[norm_id=WindowsSysmon event_id=1 file="wmic.exe" command IN ["* format*:*", "*/
↪format*:*", "*-format*:*"] -command IN ["*format:list*", "*format:table*",
↪"*format:htable", "*format:tablesys*", "*format:table*", "*format:textvaluelist*
↪", "*format:TEXTVALUELIST*", "*format:csv*", "*format:value*"]] as s1 followed by
↪[norm_id=WindowsSysmon event_id=7 image IN ["*jscript.dll", "*vbscript.dll"]] as s2
↪within 2 minute on s1.process_guid=s2.process_guid | rename s1.process as "process",
↪s1.host as host, s1.domain as domain, s1.command as command, s2.image as loaded_
↪image
```

2.64 LP_Suspicious File Execution via MSHTA

- **Trigger condition:** Execution of javascript or VBScript files and other abnormal extension files executed via mshta binary is detected.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** JavaScript, Deobfuscate/Decode Files or Information, Mshta
- **ATT&CK ID:** T1059.007, T1140, T1218.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" "process"="*\mshta.exe" command IN ["*javascript*",
↳ "*vbscript*", "*.jpg*", "*.png*", "*.lnk*", "*.xls*", "*.doc*", "*.zip*"] -user IN [
↳ EXCLUDED_USERS
```

2.65 LP_Regsvr32 Anomalous Activity Detected

- **Trigger condition:** Various anomalies concerning *regsvr32.exe* are detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Signed Binary Proxy Execution, Regsvr32
- **ATT&CK ID:** T1218, T1218.010
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 ((image="*\regsvr32.exe" command="*\Temp\*")
↳ OR (image="*\regsvr32.exe" parent_image="*\powershell.exe") OR (image=
↳ "*\regsvr32.exe" parent_image="*\cmd.exe") OR (image="*\regsvr32.exe" command
↳ IN ["*/i:http* scrobj.dll", "*/i:ftp* scrobj.dll"]) OR (image="*\wscript.exe" parent_image=
↳ "*\regsvr32.exe") OR (image="*\EXCEL.EXE" command="*..\..\
↳ \Windows\System32\regsvr32.exe *")) -user IN EXCLUDED_USERS
```

2.66 LP_Remote File Execution via MSIEXEC

- **Trigger condition:** Suspicious use of *msiexec.exe* to install remote Microsoft Software Installer (MSI) files is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Msiexec
- **ATT&CK ID:** T1218.007
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" "process"="*/msiexec.exe" command="*http*" command
↳ IN ["*/i*", "*/-i*"] ((command IN ["*/q*", "*/quiet*", "*/qn*", "*/-q*", "*/-quiet*", "*/-qn*
↳ ") OR (command IN ["*/-Q-", "*/-I-Q*", "*/q-i*", "*/-q/i*", "*/q/i*"] )) -(parent_image=
↳ "*setup*") -integrity_level=SYSTEM
```

2.67 LP_Execution of Trojanized 3CX Application

- **Trigger Condition:** Execution of the trojanized version of the 3CX Desktop is detected. 3CX Desktop versions 18.12.407 and 18.12.416 are known to be trojanized by the Lazarus Group and are also signed using the 3CX signature.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masqueradings
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 file="3CXDesktopApp.exe" product IN ["*3CX Ltd*",
↪ ", "*3CX Desktop App*"] file_version IN ["*18.12.407*", "18.12.416*"]
```

2.68 LP_Msbuild Spawned by Unusual Parent Process

- **Trigger condition:** Suspicious use of *msbuild.exe* by an uncommon parent process is detected. *msbuild.exe* is a legitimate Microsoft tool used for building and deploying software applications.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Trusted Developer Utilities Proxy Execution, MSBuild
- **ATT&CK ID:** T1127, T1127.001
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label=Create label="Process" "process"="*\MSBuild.exe" -parent_process in ["*\devenv.
↪ exe", "*\cmd.exe", "*\msbuild.exe", "*\python.exe", "*\explorer.exe", "*\nuget.exe"]
```

2.69 LP_Suspicious Files Designated as System Files Detected

- **Trigger condition:** The execution of the **+s** option of the **attrib** command is detected to designate scripts or executable files in suspicious locations as system

files, hiding them from users and making them difficult to detect or remove. *attrib.exe* is a Windows command-line utility that allows users to adjust file or folder attributes such as read-only, hidden and system.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Hide Artifacts, Hidden Files and Directories
- **ATT&CK ID:** T1564, T1564.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Create label="Process" "process"="*\attrib.exe" command = "*" +s "*" command in [
↪ "*" %*", "*\Users\Public\*", "*\AppData\Local\*", "*\ProgramData\*",
↪ "*\Windows\Temp\*" ] command in [ "*.bat*", "*.dll*", "*.exe*", "*.hta*", "*.ps1*", "*.
↪ vbe*", "*.vbs*" ] -command="*\Windows\TEMP\*.exe"
```

2.70 LP_Bypass User Account Control using Registry

- **Trigger condition:** Bypass of User Account Control (UAC) is detected. Adversaries bypass UAC mechanisms to elevate process privileges on the system. The alert queries for **\mscfile\shell\open\command** or **\ms-settings\shell\open\command**.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Bypass User Account Control
- **ATT&CK ID:** T1548, T1548.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon (event_id=12 or event_id=13 or event_id=14) (target_object=
↪ "*\mscfile\shell\open\command\*" or target_object="*\ms-
↪ settings\shell\open\command\*") -user IN EXCLUDED_USERS
```

2.71 LP_LSASS Process Access by Mimikatz

- **Trigger condition:** Process access to LSASS is detected, which is typical for Mimikatz (0x1000 *PROCESS_QUERY_LIMITED_INFORMATION*, 0x0400 *PROCESS_QUERY_INFORMATION* "only old versions", 0x0010 *PROCESS_VM_READ*).

- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=10 image="C:\windows\system32\lsass.exe" access?
↪ IN ["0x1410", "0x1010"] -user IN EXCLUDED_USERS
```

2.72 LP_Unsigned Image Loaded Into LSASS Process

- **Trigger condition:** Loading of unsigned images like DLL or EXE into the LSASS process is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, LSASS Memory
- **ATT&CK ID:** T1003, T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 image="*\lsass.exe" signed="false" -user IN?
↪ EXCLUDED_USERS
```

2.73 LP_Usage of Sysinternals Tools Detected

- **Trigger condition:** The use of Sysinternals tools due to the addition of *accepteula* key to a registry is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(label=Registry label=Set target_object="*\EulaAccepted") or (label=Create label=
↪ "Process" command IN ["*-accepteula*", "*/accepteula*"])
```

2.74 LP_Microsoft SharePoint Remote Code Execution Detected

- **Trigger condition:** The execution of a remote code in Microsoft SharePoint (CVE-2019-19781).
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Exploit Public-Facing Application
- **ATT&CK ID:** T1190
- **Minimum Log Source Requirement:** Firewall, IDS/IPS, Web server
- **Query:**

```
request_method=POST (url='*_layouts/15/Picker.aspx*WebControls.ItemPickerDialog*'  
↪ OR resource='*_layouts/15/Picker.aspx*WebControls.ItemPickerDialog*')
```

2.75 LP_DenyAllWAF SQL Injection Attack

- **Trigger condition:** DenyAllWAF detects SQL injection attack.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Exploit Public-Facing Application
- **ATT&CK ID:** T1190
- **Minimum Log Source Requirement:** DenyAll WAF
- **Query:**

```
norm_id=DenyAllWAF label=SQL label=Injection
```

2.76 LP_Windows CryptoAPI Spoofing Vulnerability Detected

- **Trigger condition:** Vulnerability related to CVE-2020-0601 is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Subvert Trust Controls, Code Signing
- **ATT&CK ID:** T1553, T1553.002
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label=CVE label=Exploit label=Detect cve_id="CVE-2020-0601" -
↪ user IN EXCLUDED_USERS
```

2.77 LP_Malicious use of Scriptrunner Detected

- **Trigger condition:** The malicious use of *Scriptrunner.exe* is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Signed Binary Proxy Execution
- **ATT&CK ID:** T1218
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="create" label="process" ("process"="*\ScriptRunner.exe" OR file="ScriptRunner.
↪ exe") command="*-appvscript *"
```

2.78 LP_Suspicious process related to Rundll32 Detected

- **Trigger condition:** A suspicious process related to *RunDLL32.exe* is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Rundll32
- **ATT&CK ID:** T1218.011

- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="create" label="process" (command IN ["*javascript:*", "*.RegisterXLL*"] OR
↪(command="*url.dll*" command="*OpenURL*") OR (command="*url.dll*" command=
↪"*OpenURLA*") OR (command="*url.dll*" command="*FileProtocolHandler*") OR
↪(command="*zipfldr.dll*" command="*RouteTheCall*") OR (command="*shell32.dll*"
↪command="*Control_RunDLL*") OR (command="*shell32.dll*" command="*ShellExec_
↪RunDLL*") OR (command="*mshtml.dll*" command="*PrintHTML*") OR (command=
↪"*advpack.dll*" command="*LaunchINFSection*") OR (command="*advpack.dll*"
↪command="*RegisterOCX*") OR (command="*ieadvpack.dll*" command=
↪"*LaunchINFSection*") OR (command="*ieadvpack.dll*" command="*RegisterOCX*")
↪OR (command="*ieframe.dll*" command="*OpenURL*") OR (command="*shdocvw.dll*"
↪" command="*OpenURL*") OR (command="*syssetup.dll*" command=
↪"*SetupInfObjectInstallAction*"") OR (command="*setupapi.dll*" command=
↪"*InstallHinfSection*") OR (command="*pcwutl.dll*" command="*LaunchApplication*"
↪") OR (command="*dfshim.dll*" command="*ShOpenVerbApplication*"))
```

2.79 LP_Javascript conversion to executable Detected

- **Trigger condition:** A windows executable `jsc.exe` is used to convert javascript files to craft malicious executables.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Trusted Developer Utilities Proxy Execution
- **ATT&CK ID:** TT1127
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="create" label="process" "process"="*\\jsc.exe" command="*.js"
```

2.80 LP_Suspicious Execution of Gpscript Detected

- **Trigger condition:** A group policy script `gpscript.exe` is used to execute logon or startup scripts configured in Group Policy.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Signed Binary Proxy Execution

- **ATT&CK ID:** T1218
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="create" label="process" "process"="*\gpscript.exe" command IN ["*/logon*", "*/  
↪/startup*"]
```

2.81 LP_Proxy Execution via Desktop Setting Control Panel

- **Trigger condition:** A windows internal binary *rundll32* with *desk.cpl* is used to execute spoof binary with ".cpl" extension.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Rundll32
- **ATT&CK ID:** T1218.011
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" "process"="*\rundll32.exe" command="*desk.  
↪cpl*InstallScreenSaver*.scr*"
```

2.82 LP_Credentials Dumping Tools Accessing LSASS Memory

- **Trigger condition:** Arbitrary tools accessing LSASS memory are detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** LSASS Memory
- **ATT&CK ID:** T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```

norm_id=WindowsSysmon event_id=10 image="*\lsass.exe" access IN ["0x40*",
↪ "0x100000*", "0x1410*", "0x1438*", "0x143a*", "0x1418*", "0x1f0fff*", "0x1f1fff*",
↪ "0x1f2fff*", "0x1f3fff*"]
-(
"process" IN ["C:\WINDOWS\system32\taskmgr.exe", "C:\Windows\System32\perfmon.
↪ exe"]
OR
("process" IN ["C:\Program Files\*", "C:\Program Files (x86)\*"] access IN ["0x1410",
↪ "0x410"])
OR
("process" IN ["C:\ProgramData\Microsoft\Windows Defender\*", "C:\Program
↪ Files\Windows Defender\*", "C:\Program Files\Microsoft Security Client\*"] "process" =
↪ "*\MsMpEng.exe")
OR
("process" = "C:\Windows\System32\svchost.exe" call_trace=
↪ "*|C:\ProgramData\Microsoft\Windows Defender\Definition Updates\{* call_trace="*}
↪ \mpengine.dll+*" access="0x1418")
OR
(call_trace IN ["*|c:\program files\windows defender\mprtp.dll*", "*|c:\program
↪ files\windows defender\MpClient.dll*"])
OR
("process" = "C:\Program Files\WindowsApps\*" "process" = "*\GamingServices.exe"
↪ access IN ["0x1410", "0x410"])
OR
("process" IN ["*\PROCEXP64.EXE", "*\PROCEXP.EXE",
↪ "C:\WINDOWS\system32\taskhostw.exe", "*\MBAMInstallerService.exe"] access IN [
↪ "0x1410", "0x410", "0x40"])
OR
("process" IN ["C:\WINDOWS\system32\wbem\wmiprvse.exe",
↪ "C:\Windows\syswow64\MsiExec.exe", "C:\Windows\System32\msiexec.exe"] access
↪ IN ["0x1410", "0x410", "0x1f1fff", "0x1f3fff"])
OR
("process" IN ["C:\Windows\system32\wininit.exe", "C:\Windows\System32\lsass.exe"]
↪ access="0x1000000")
OR
("process" = "C:\ProgramData\VMware\VMware Tools\*" "process" = "*\vmtoolsd.exe")
OR
("process" = "C:\WINDOWS\system32\svchost.exe" access IN ["0x100000", "0x1410"])
OR
("process" IN ["*\thor.exe", "*\thor64.exe", "*\aurora-agent.exe", "*\aurora-agent-64.exe
↪ "] access IN ["0x40", "0x1010"])
OR
("process" = "*\explorer.exe" access="0x401")
OR
("process" = "C:\Windows\system32\MRT.exe" access IN ["0x1410", "0x1418"])
OR

```

(continues on next page)

(continued from previous page)

```

("process" IN ["*\handle.exe", " *\handle64.exe"] access="0x40")
OR
("process"="C:\Program Files (x86)\Microsoft\Edge\Application\*" "process"=
↪ " *\Installer\setup.exe")
OR
("process"=" *\AppData\Local\WebEx\WebexHost.exe" access="0x401")
OR
("process"="C:\PROGRAMDATA\MALWAREBYTES\MBAMSERVICE\ctlrupdate\mbupdatr.
↪ exe" access="0x1410")
OR
("process" IN ["*:\Windows\Temp\*", " *\AppData\Local\Temp\*"] "process"="*.
↪ tmp\DropboxUpdate.exe" access IN ["0x410", "0x1410"])
OR
"process"=" *\SteamLibrary\steamapps\*"

```

2.83 LP_Xwizard DLL Side Loading Detected

- **Trigger condition:** The use of xwizard binary from the non-default directory is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** DLL Side-Loading
- **ATT&CK ID:** T1574.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```

label="Process" label=Create "process"=" *\xwizard.exe" - "process"=
↪ "C:\Windows\System32\*"

```

2.84 LP_DLL Side Loading Via Microsoft Defender

- **Trigger condition:** An execution of mpcmdrun binary from non default path is detected.
- **ATT&CK Category:** Persistence, Defense Evasion
- **ATT&CK Tag:** DLL Side-Loading
- **ATT&CK ID:** T1574.002

- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Image label=Load "process" IN ["*\MpCmdRun.exe", " *\NisSrv.exe"] - "process" IN [
↪ "C:\Program Files\Windows Defender\*", "C:\ProgramData\Microsoft\Windows
↪ Defender\Platform\*"] image="*\mpclient.dll"
```

2.85 LP_ZIP File Creation or Extraction via Printer Migration CLI Tool

- **Trigger condition:** The creation or extraction of .zip file via *printbrm* utility is detected.
- **ATT&CK Category:** Defense Evasion, Command and Control
- **ATT&CK Tag:** Ingress Tool Transfer, NTFS File Attributes
- **ATT&CK ID:** T1105, T1564.004
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" "process"="*\printbrm.exe" command="*f*" command=
↪ " *.zip"
```

2.86 LP_Credentials Capture via Rpcping Detected

- **Trigger condition:** The creation of Remote Procedure Call (RPC) via Rcping binary is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" "process"="*\rpcping.exe" command="*s*" (
↪ (command="*u*" command="*NTLM*") OR (command="*t*" command="*ncacn_np*
↪ ))
```

2.87 LP_Suspicious ConfigSecurityPolicy Execution Detected

- **Trigger condition:** A local file upload via ConfigSecurityPolicy binary to attack the control server is detected.
- **ATT&CK Category:** Exfiltration
- **ATT&CK Tag:** Exfiltration Over Web Service
- **ATT&CK ID:** T1567
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" "process"="*\\ConfigSecurityPolicy.exe" command IN [
↪ "*https://*", "*http://*", "*ftp://*"]
```

2.88 LP_C-Sharp Code Compilation Using Ilasm Detected

- **Trigger condition:** C# code is either compiled into executables or into DLL using ilasm utility.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Trusted Developer Utilities Proxy Execution
- **ATT&CK ID:** T1127
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Process" label="Create" ("process"="*\\ilasm.exe" OR file="ilasm.exe")
```

2.89 LP_Process Dump via Resource Leak Diagnostic Tool

- **Trigger condition:** A process dump is detected using a Microsoft Windows native tool `rdrlleakdiag.exe`.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** LSASS Memory

- **ATT&CK ID:** T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create ("process"="*\RdrLeakDiag.exe" or file="RdrLeakDiag.exe"
↪) command="*fullmemdmp"
```

2.90 LP_Suspicious DLL execution via Register-Cimprovider

- **Trigger condition:** A dll file load/execution is detected using a Microsoft Windows native tool *Register-Cimprovider.exe*.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Hijack Execution Flow
- **ATT&CK ID:** TT1574
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" "process"="*\register-cimprovider.exe" command="*-
↪path*" command="*dll"
```

2.91 Accessibility features - Process

- **Trigger condition:** Adversaries establish persistence and/or elevate privileges by executing malicious content by process features.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Event Triggered Execution, Accessibility Features
- **ATT&CK ID:** T1546,T1546.008
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 parent_image="*winlogon.exe" (image="*sethc.
↪exe" or image="*utilman.exe" or image="*osk.exe" or image="*magnify.exe" or
↪image="*displayswitch.exe" or image="*narrator.exe" or image="*atbroker.exe") -
↪user IN EXCLUDED_USERS
```

2.92 LP_Accessibility Features-Registry

- **Trigger condition:** An adversary establish persistence and/or elevates privileges by executing malicious content, replacing accessibility feature binaries, pointers, or references to these binaries in the registry.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Event Triggered Execution, Accessibility Features
- **ATT&CK ID:** T1546,T1546.008
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon (event_id=12 or event_id=13 or event_id=14) target_object=
↳ "*HKLM\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution"
↳ Options\*" -user IN EXCLUDED_USERS
```

2.93 LP_Active Directory DLLs Loaded By Office Applications

- **Trigger condition:** Kerberos DLL or DSParse DLL loaded by the Office products like WinWord, Microsoft PowerPoint, Microsoft Excel or Microsoft Outlook is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Malicious File
- **ATT&CK ID:** T1204.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 "process" IN ["*\winword.exe*", "*\powerpnt.exe*",
↳ "*\excel.exe*", "*\outlook.exe*"] image IN ["*\kerberos.dll*", "*\c.dll*"] -user IN
↳ EXCLUDED_USERS
```

2.94 LP_DCSync detected

- **Trigger condition:** The abuse of Active Directory Replication Service (ADRS) detected from a non-machine account to request credentials or DC Sync by creating a new SPN.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, DCSync
- **ATT&CK ID:** T1003,T1003.006
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
((norm_id=WinServer event_id=4662 access_mask="0x100" properties IN ["*1131f6aa-9c07-11d1-f79f-00c04fc2dcd2*", "*1131f6ad-9c07-11d1-f79f-00c04fc2dcd2*", "*89e95b76-444d-4c62-991a-0facbeda640c*", "*Replicating Directory Changes All*"] - user="*$" -user="MSOL_*") or (norm_id=WinServer event_id=4742 service="*GC/*"))- user IN EXCLUDED_USERS
```

2.95 LP_Active Directory Replication User Backdoor

- **Trigger condition:** Modification of the security descriptor of a domain object for granting Active Directory replication permissions to a user.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** File and Directory Permissions Modification, Windows File and Directory Permissions Modification
- **ATT&CK ID:** T1222,T1222.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5136 ldap_display="ntsecuritydescriptor" attribute_value IN ["*1131f6aa-9c07-11d1-f79f-00c04fc2dcd2*", "*1131f6ad-9c07-11d1-f79f-00c04fc2dcd2*", "*89e95b76-444d-4c62-991a-0facbeda640c*"] -user IN EXCLUDED_USERS
```

2.96 LP_Activity Related to NTDS Domain Hash Retrieval

- **Trigger condition:** Copying of *ntds.dit* file is detected. *NTDS.dit* file is a database that stores the Active Directory data (including users, groups, security descriptors and password hashes).
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, NTDS
- **ATT&CK ID:** T1003, T1003.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create command IN [ "*vssadmin.exe Delete Shadows*",
↪ "*vssadmin create shadow /for=C:*", "*copy \\?
↪ \\GLOBALROOT\\Device\\*\\windows\\ntds\\ntds.dit*", "*copy \\?
↪ \\GLOBALROOT\\Device\\*\\config\\SAM*", "*vssadmin delete shadows /for=C:*", "*reg
↪ SAVE HKLM\\SYSTEM*", "*esentutl.exe /y /vss *\\ntds.dit*", "*esentutl.exe /y /vss *\\SAM*
↪ ", "*esentutl.exe /y /vss *\\SYSTEM*"]
```

2.97 LP_AD Object WriteDAC Access Detected

- **Trigger condition:** WRITE_DAC, which can modify the discretionary access-control list (DACL) in the object security descriptor, is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** File and Directory Permissions Modification
- **ATT&CK ID:** T1222
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4662 object_server="DS" access_mask=0x40000 object_
↪ type IN ["19195a5b-6da0-11d0-afd3-00c04fd930c9", "domainDNS"] -user IN
↪ EXCLUDED_USERS
```

2.98 LP_AD Privileged Users or Groups Reconnaissance Detected

- **Trigger condition:** *priv* users or groups recon based on 4661 event ID and privileged users or groups SIDs are detected. The object names must be; domain admin, KDC service account, admin account, enterprise admin, group policy creators and owners, backup operator, or remote desktop users.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Account Discovery, Local Account, Domain Account
- **ATT&CK ID:** T1087,T1087.001,T1087.002
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4661 object_type IN ["SAM_USER", "SAM_GROUP"]
↪ object_name IN ["*-512", "*-502", "*-500", "*-505", "*-519", "*-520", "*-544", "*-551",
↪ "*-555", "*admin*"] -user IN EXCLUDED_USERS
```

2.99 LP_Addition of SID History to Active Directory Object

- **Trigger condition:** Addition of SID History to Active Directory Object is detected. An attacker can use the SID history attribute to gain additional privileges.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Access Token Manipulation, SID-History Injection
- **ATT&CK ID:** T1134,T1134.005
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer (event_id IN ["4765", "4766"] OR (norm_id=WinServer event_id=4738
↪ -SidHistory IN ["-", "%%1793"])) -user IN EXCLUDED_USERS
```

2.100 LP_Admin User Remote Logon Detected

- **Trigger condition:** Successful remote login by the administrator depending on the internal pattern is detected.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts
- **ATT&CK ID:** T1078
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4624 logon_type="10" (authentication_package=
↪ "Negotiate" OR package="Negotiate") user="Admin-*" -user IN EXCLUDED_USERS |?
↪ rename package as authentication_package
```

2.101 LP_Adwind RAT JRAT Detected

- **Trigger condition:** The applications like *javaw.exe*, *cscript* in the AppData folder, or set values of Windows Run* register used by Adwind or JRAT are detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, Visual Basic, JavaScript/JScript, Windows Command Shell, PowerShell
- **ATT&CK ID:** T1059, T1059.001, T1059.003, T1059.005, T1059.007
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
(event_id=1 command IN ["*\AppData\Roaming\Oracle*\java*.exe ", "*cscript.exe?
↪ *Retrive*.vbs *"]) OR (event_id=11 file IN ["*\AppData\Roaming\Oracle\bin\java*.exe",
↪ "*\Retrive*.vbs"]) OR (event_id=13 target_object=
↪ "HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Run*" detail="%AppData
↪ %\Roaming\Oracle\bin\*")
```

2.102 LP_Apache Struts 2 Remote Code Execution Detected

- **Trigger condition:** A remote code execution vulnerability (CVE-2017-5638) in Apache Struts 2 is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Exploit Public-Facing Application
- **ATT&CK ID:** T1190
- **Minimum Log Source Requirement:** ApacheTomcat
- **Query:**

```
norm_id=ApacheTomcatServer label=Content label=Invalid label=Type | norm on content_
↪ type #cmd=<command:quoted>
```

2.103 LP_AppCert DLLs Detected

- **Trigger condition:** Adversaries establish persistence and/or elevate privileges by executing malicious content triggered by AppCert DLLs loaded into processes.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Event Triggered Execution, AppCert DLLs
- **ATT&CK ID:** T1546, T1546.009
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon (event_id=12 or event_id=13 or event_id=14) target_object=
↪ "*"System\CurrentControlSet\Control\Session Manager\AppCertDlls\*" -user IN
↪ EXCLUDED_USERS
```

2.104 LP_Application Shimming - File Access Detected

- **Trigger condition:** Adversaries establish persistence or elevate privileges by executing malicious content initiated by application shims is detected.
- **ATT&CK Category:** Persistence, Privilege Escalation

- **ATT&CK Tag:** Event Triggered Execution, Application Shimming
- **ATT&CK ID:** T1546, T1546.011
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon ((event_id=11 file="*C:\Windows\AppPatch\Custom\*" or
↪ (event_id=1 "process"="*\sdbinst.exe") or (event_id IN [12,13,14] target_object=
↪ "*\SOFTWARE\Microsoft\Windows NT\CurrentVersion\AppCompatFlags\InstalledSDB\*"
↪ )) -user IN EXCLUDED_USERS
```

2.105 LP_Application Whitelisting Bypass via Bginfo Detected

- **Trigger condition:** Application whitelisting bypass via Bginfo is detected.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** Signed Binary Proxy Execution, Visual Basic, Indirect Command Execution
- **ATT&CK ID:** T1218, T1059.005, T1202
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\bginfo.exe" command="*/popup*"
↪ command="*/nolicprompt*" -user IN EXCLUDED_USERS
```

2.106 LP_Application Whitelisting Bypass via Dnx Detected

- **Trigger condition:** Execution of Dnx binary with ConsoleApp commandline argument is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Compile After Delivery, Signed Binary Proxy Execution
- **ATT&CK ID:** T1027.004, T1218

- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\dnx.exe" command="*ConsoleApp*" -user
↪ IN EXCLUDED_USERS
```

2.107 LP_Audio Capture Detected

- **Trigger condition:** The use of Powershell, sound recorder application, or command to get the audio device is detected. Adversaries attempt to leverage peripheral devices or applications to obtain audio recordings for sensitive conversations.
- **ATT&CK Category:** Collection
- **ATT&CK Tag:** Audio Capture
- **ATT&CK ID:** T1123
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 ((image="*SoundRecorder.exe" and command="*/
↪ FILE*") or command="*Get-AudioDevice*" or command="*WindowsAudioDevice-
↪ Powershell-Cmdlet*") -user IN EXCLUDED_USERS
```

2.108 LP_Authentication Package Detected

- **Trigger Condition:** The LSA process loaded by services other than Issac, svchos, msixexec and services is detected. Windows authentication package DLLs are loaded by the Local Security Authority (LSA) process at the system start. Adversaries may abuse authentication packages to execute DLLs when the system boots.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Authentication Package, Security Support Provider
- **ATT&CK ID:** T1547.002, T1547.005
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id IN [12,13,14] -event_type=INFO (target_object=
↳ "*\\SYSTEM\\CurrentControlSet\\Control\\Lsa\\*" - "process" in [
↳ "*C:\\WINDOWS\\system32\\lsass.exe", "*C:\\Windows\\system32\\svchost.exe",
↳ "*C:\\Windows\\system32\\services.exe", "C:\\Windows\\system32\\msiexec.exe"]
```

2.109 LP_Autorun Keys Modification Detected

- **Trigger Condition:** Modification of autostart extensibility point (ASEP) in the registry is detected. ASEP allows a particular program to run automatically when a user logs into the system. Adversaries may achieve persistence by adding a program to a startup folder or referencing it with a Registry run key.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Boot or Logon Autostart Execution, Registry Run Keys / Startup Folder
- **ATT&CK ID:** T1547, T1547.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Registry label=Set label=Value -event_type=info target_object IN [
↳ "\\software\\Microsoft\\Windows\\CurrentVersion\\Run*", "\\software\\Microsoft\\Windows
↳ NT\\CurrentVersion\\Winlogon\\Userinit*", "\\software\\Microsoft\\Windows
↳ NT\\CurrentVersion\\Winlogon\\Shell*",
↳ "\\*\\Microsoft\\Windows\\CurrentVersion\\Policies\\Explorer\\Run",
↳ "\\*\\software\\Microsoft\\Windows NT\\CurrentVersion\\Windows*",
↳ "\\*\\software\\Microsoft\\Windows\\CurrentVersion\\Explorer\\User Shell Folders*" detail
↳ IN ["*C:\\Windows\\Temp\\*", "*C:\\$Recycle.bin\\*", "*C:\\Temp\\*", "*C:\\Users\\Public\\*",
↳ "*C:\\Users\\Default\\*", "*C:\\Users\\Desktop\\*", "*\\AppData\\Local\\*", "*Public\\*",
↳ "*\\wscript*", "*\\cscript*", "*\\powershell.exe*"] -detail=
↳ "*\\AppData\\Local\\Microsoft\\Teams\\Update.exe *"
```

2.110 LP_Bloodhound and Sharphound Hack Tool Detected

- **Trigger Condition:** Command-line parameters used by Bloodhound and Sharphound hack tools are detected.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Account Discovery

- **ATT&CK ID:** T1087
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 (image IN ["*\Bloodhound.exe*", "*\SharpHound.
↪exe*"] OR command IN ["*-CollectionMethod All *", "*.exe -c All -d *", "*Invoke-
↪Bloodhound*", "*Get-BloodHoundData*"] OR (command="* -JsonFolder *" command=
↪"* -ZipFileName *" OR (command="* DCOOnly *" command="* --NoSaveCache *")) -
↪user IN EXCLUDED_USERS
```

2.111 LP_BlueMashroom DLL Load Detected

- **Trigger Condition:** Suspicious dynamic-link libraries (DLLs) loading from the AppData Local path are detected. Adversaries can inject DLLs from AppData into processes to evade process-based defenses and elevate privileges.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Regsvr32, DLL Side-Loading
- **ATT&CK ID:** T1218.010, T1574.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
norm_id=WindowsSysmon event_id=1 command IN ["*\regsvr32*\AppData\Local\*",
↪"*\AppData\Local\*, DllEntry*"] -user IN EXCLUDED_USERS
```

2.112 LP_Remote Thread Creation via Cactustorch

- **Trigger Condition:** Creation of a remote thread from CACTUSTORCH is detected.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** Process Hollowing, Visual Basic, JavaScript, Mshta
- **ATT&CK ID:** T1055.012, T1059.005, T1059.007, T1218.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Remote" label="Thread" label="Create" "process" IN ["*\System32\cscript.exe",
↪ " *\System32\wscript.exe", " *\System32\mshta.exe", " *\winword.exe", " *\excel.exe"]
↪ image=" *\SysWOW64\*" -start_module=* -user IN EXCLUDED_USERS
```

2.113 LP_Call to a Privileged Service Failed

- **Trigger Condition:** The privileged service call using *LsaRegisterLogonProcess* fails.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** Valid Account
- **ATT&CK ID:** T1078
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4673 service="LsaRegisterLogonProcess()" event_type=
↪ " *Failure*" -user IN EXCLUDED_USERS
```

2.114 LP_Capture a Network Trace with netsh

- **Trigger Condition:** Network trace capture via *netsh.exe* trace functionality is detected. *netsh.exe* is a command-line utility in Windows for configuring and displaying the network configuration on the system. Adversaries may abuse its functionality to sniff network traffic to capture information about an environment, including the authentication with credentials information.
- **ATT&CK Category:** Discovery, Credential Access
- **ATT&CK Tag:** Network Sniffing
- **ATT&CK ID:** T1040
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"=" *\netsh.exe" command=" *trace*" command=
↪ " *start*"
```

2.115 LP_CEO Fraud - Possible Fraudulent Email Behavior

- **Trigger Condition:** An email received from a threat source in the internal network exhibits fraudulent behavior. For this alert to work, you must update the following:
 - HOME_DOMAIN, which is the list of selected domain names. For example, logpoint.com
 - MANAGERS, which is the list of selected managers and executives. For example, Alice
 - SERVER_ADDRESS, which is the list of trusted clients or servers from where the emails are received.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing
- **ATT&CK ID:** T1566, T1566.001
- **Minimum Log Source Requirement:** Exchange MT
- **Query:**

```
norm_id=ExchangeMT event_id=receive sender=* receiver IN HOME_DOMAIN original_
↪ client_address=* -original_client_address IN SERVER_ADDRESS | norm on sender
↪ <target_manager:all>@<domain:string> |
norm on message_id @<original_domain:'.*'><:'\>'> | search target_manager IN
↪ MANAGERS
```

2.116 LP_Certutil Encode Detected

- **Trigger Condition:** The *certutil* command, sometimes used for data exfiltration, is used to encode files.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Obfuscated Files or Information
- **ATT&CK ID:** T1027
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 command IN ["certutil -f -encode *", "certutil.exe -
↪ f -encode *", "certutil -encode -f *", "certutil.exe -encode -f *"] -user IN EXCLUDED_
↪ USERS
```

2.117 LP_Change of Default File Association Detected

- **Trigger Condition:** A registry value is set to change the file association. Adversaries establish persistence by executing malicious content triggered by a file type association.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Event Triggered Execution, Change Default File Association
- **ATT&CK ID:** T1546, T1546.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=Registry label=Set label=Value target_object="*HKEY_
↳ CLASSES_ROOT\mscfile*" detail in ["*powershell*", "*.exe*", "*.dat*"] -user IN
↳ EXCLUDED_USERS
```

2.118 LP_Citrix ADC VPN Directory Traversal Detected

- **Trigger Condition:** The exploitation of directory traversal vulnerability (CVE-2019-19781) in Citrix ADC is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** External Remote Services
- **ATT&CK ID:** T1133
- **Minimum Log Source Requirement:** Webserver, Firewall
- **Query:**

```
norm_id=* (url="*/../vpns/*" OR resource="*/../vpns/*")
```

2.119 LP_Clear Command History

- **Trigger Condition:** Command line arguments to delete console history are detected. Adversaries can use this technique to remove the traces of their executed commands.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** Clear Command History
- **ATT&CK ID:** T1070.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command IN ["*rm (Get-PSReadlineOption).
↪HistorySavePath*", "*del (Get-PSReadlineOption).HistorySavePath*", "*Set-
↪PSReadlineOption -HistorySaveStyle SaveNothing*", "*Remove-Item (Get-
↪PSReadlineOption).HistorySavePath*"]
```

2.120 LP_Clearing of PowerShell Logs Detected

- **Trigger Condition:** A console history logs clear is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Indicator Removal
- **ATT&CK ID:** T1070
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
(norm_id=WinServer event_id=4103 command="Remove-Item" payload=
↪"*consolehost*history*") OR (label=File label=Delete (object="ConsoleHost_history.txt
↪" OR file="ConsoleHost_history.txt"))
```

2.121 LP_Clipboard Data Access Detected

- **Trigger Condition:** Adversaries collect data stored on a clipboard from users copying information within or between applications is detected.
- **ATT&CK Category:** Collection
- **ATT&CK Tag:** Clipboard Data
- **ATT&CK ID:** T1115
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 (image="*clip.exe" or command="*Get-Clipboard*
↪") -user IN EXCLUDED_USERS
```

2.122 LP_Cmdkey Cached Credentials Recon Detected

- **Trigger Condition:** The usage of *cmdkey* to detect cached credentials.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 image="*\cmdkey.exe" command="*/list*" -user
↪ IN EXCLUDED_USERS
```

2.123 LP_CMSTP Detected

- **Trigger Condition:** Adversaries abuse CMSTP for proxy execution of malicious code. *CMSTP.exe* accepts an installation information file (INF) as a parameter and installs a service profile leveraged for remote access connections. Also, the adversary supplies *CMSTP.exe* with INF files infected with malicious commands.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** Signed Binary Proxy Execution, CMSTP
- **ATT&CK ID:** T1218, T1218.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 image="*CMSTP.exe" -user IN EXCLUDED_USERS
```

2.124 LP_CMSTP Execution Detected

- **Trigger Condition:** Loading and execution of local or remote payloads using CMSTP. Adversaries abuse CMSTP.exe to load and execute DLLs and/or COM scriptlets (SCT) from remote servers. The execution bypasses AppLocker and other safe listing defenses since CMSTP.exe is a legitimate and signed Microsoft application.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** CMSTP, Component Object Model
- **ATT&CK ID:** T1218.003, T1559.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(norm_id="WindowsSysmon" ((event_id IN [12, 13] target_object="*\cmmgr32.exe*") OR
↪ (event_id=10 call_trace="*cmlua.dll*") OR (event_id=3 "process"="*\cmstp.exe" is_
↪ initiated="true"))) OR (label="Process" label=Create parent_process="*\cmstp.exe")
```

2.125 LP_CMSTP UAC Bypass via COM Object Access

- **Trigger Condition:** Loading and execution of local or remote payloads using CMSTP is detected. Adversaries abuse CMSTP.exe to bypass User Account Control and execute arbitrary commands from a malicious INF through an auto-elevated COM interface.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Bypass User Access Control, CMSTP
- **ATT&CK ID:** T1548.002, T1218.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 parent_process="*\DllHost.exe" parent_
↪ command IN ["*/Processid:{3E5FC7F9-9A51-4367-9063-A120244FBEC7}*","*/Processid:
↪ {3E000D72-A845-4CD9-BD83-80C07C3B881F}*","*/Processid:{BD54C901-076B-434E-
↪ B6C7-17C531F4AB41}*","*/Processid:{D2E7041B-2927-42FB-8E9F-7CE93B6DC937}*","
↪ "*/Processid:{E9495B87-D950-4AB5-87A5-FF6D70BF3E90}*"] integrity_level IN ["High",
↪ "System"]
```

2.126 LP_CobaltStrike Process Injection Detected

- **Trigger Condition:** Creation of remote threat with specific characteristics that are typical for Cobalt Strike beacons.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=8 start_address IN ["*0B80", "*0C7C", "*0C88"] -  
↪ user IN EXCLUDED_USERS
```

2.127 LP_Windows Command Line Execution with Suspicious URL and AppData Strings

- **Trigger Condition:** Execution of Windows command line with command line parameters URL and AppData string used by droppers.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=8 start_address IN ["*0B80", "*0C7C", "*0C88"] -  
↪ user IN EXCLUDED_USERS
```

2.128 LP_Compiled HTML File Detected

- **Trigger Condition:** Adversaries abuse Compiled HTML files (.chm) to conceal malicious code.
- **ATT&CK Category:** Defense Evasion, Execution

- **ATT&CK Tag:** Signed Binary Proxy Execution, Compiled HTML File
- **ATT&CK ID:** T1218, T1218.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 image="*hh.exe" -user IN EXCLUDED_USERS
```

2.129 LP_Console History Discovery Detected

- **Trigger Condition:** Adversaries attempt to get detailed information about the console history discovery is detected.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** System Information Discovery
- **ATT&CK ID:** T1082
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command IN ["*Get-History*", "*PSReadline\ConsoleHost_
↪ history.txt*", "(Get-PSReadlineOption).HistorySavePath*"]
```

2.130 LP_Control Panel Items - Registry Detected

- **Trigger Condition:** Adversaries abuse *control.exe* for proxy execution of malicious payloads.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Signed Binary Proxy Execution, Control Panel Items
- **ATT&CK ID:** T1218, T1218.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon (event_id=12 or event_id=13 or event_id=14) (target_object=
↪ "*\SOFTWARE\Microsoft\Windows\CurrentVersion\Explorer\ControlPanel\NameSpace*
↪ " or target_object="*\Software\Microsoft\Windows\CurrentVersion\Controls
↪ Folder\*\ShellEx\PropertySheetHandlers\*" or target_object=
↪ "*\Software\Microsoft\Windows\CurrentVersion\Control Panel\*" ) (contin
↪ EXCLUDED_USERS
```

(continued from previous page)

2.131 LP_Copy from Admin Share Detected

- **Trigger Condition:** Copying of file from a remote C\$ or ADMIN\$ share via copy command is detected.
- **ATT&CK Category:** Lateral Movement, Command, Exfiltration
- **ATT&CK Tag:** Remote Services, SMB/Windows Admin Shares, Ingress Tool Transfer, Data from Network Shared Drive
- **ATT&CK ID:** T1021,T1021.002, T1105, T1039
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (command="*\\\\*" command="*$*") OR (command=
↳ "*\\Sysvol\\*") ("process" IN
↳ ["*\\robocopy.exe", "*\\xcopy.exe"]) OR ("process"="*\\cmd.exe" command="*copy*")
↳ OR ("process" IN
↳ ["*\\powershell.exe", "*\\pwsh.exe"] command IN
↳ ["*copy-item*", "*copy*", "*cpi*", "*cp *", "*move *", "*move-item*", "*mi *", "*mv *"]
↳ ))
```

2.132 LP_Copying Sensitive Files with Credential Data

- **Trigger Condition:** Copying of sensitive files with credential data is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Create label="Process" (("process"="*\\esentutl.exe" OR file="esentutl.exe"
↳ command IN ["*vss*", "* /m *", "* /y *"]) OR command IN ["*\\windows\\ntds\\ntds.dit*",
↳ "*\\config\\sam*", "*\\config\\security*", "*\\config\\system *", "*\\repair\\sam*",
↳ "*\\repair\\system*", "*\\repair\\security*", "*\\config\\RegBack\\sam*",
↳ "*\\config\\RegBack\\system*", "*\\config\\RegBack\\security*"])
```

2.133 LP_Copyright Violation Email

- **Trigger Condition:** An email with copyright or infringement contents as message subject is received. For this alert to work, the list KNOWN_SERVER_HOST must be updated known mail servers.
- **ATT&CK Category:** Collection
- **ATT&CK Tag:** Email Collection
- **ATT&CK ID:** T1114
- **Minimum Log Source Requirement:** ExchangeMT
- **Query:**

```
device_category=Email* sender=* receiver=* -source_host IN KNOWN_SERVER_HOST
↪ subject IN ["*copyright*", "*infringement*"] | norm on receiver <user:all>@
↪ <domain:string>
```

2.134 LP_CreateMiniDump Hacktool Detected

- **Trigger Condition:** The use of the *CreateMiniDump* hack tool to dump the LSASS process memory for credential extraction on the attacker's machine is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping, LSASS Memory
- **ATT&CK ID:** T1003, T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
(event_id=1 (image="*\CreateMiniDump.exe*" OR hash=
↪ "4a07f944a83e8a7c2525efa35dd30e2f")) OR (event_id=11 file="*\lsass.dmp*")
```

2.135 LP_CreateRemoteThread API and LoadLibrary

- **Trigger Condition:** The use of CreateRemoteThread API and LoadLibrary function to inject DLL into a process is detected.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=8 start_module="*\kernel32.dll" start_function=
↪ "LoadLibraryA" -user IN EXCLUDED_USERS
```

2.136 LP_Command Obfuscation via Character Insertion

- **Trigger Condition:** Command obfuscation of command prompt by character insertion is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, Windows Command Shell
- **ATT&CK ID:** T1059, T1059.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Process" label=Create parent_process='*\cmd.exe' parent_command="cmd*/c*" [?]
↪ norm on parent_command <command_match:'[^\w](s\^+e\^*t|s\^*e\^+t)[^\w]'\> [?]
↪ search command_match=*
```

2.137 LP_Command Obfuscation via Environment Variable Concatenation Reassembly

- **Trigger Condition:** Command obfuscation in command prompt by environment variable concatenation reassembly is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, Windows Command Shell
- **ATT&CK ID:** T1059, T1059.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Process" label=Create "parent_process"='*cmd.exe' command='cmd*/c*' | norm
→ on command <command_match:'%[^%]+%{4}'> | rename command as changed_
→ command, command_match as command | search command=*
```

2.138 LP_Credential Access via Input Prompt Detected

- **Trigger Condition:** A command executed to capture user input to obtain the credentials is detected.
- **ATT&CK Category:** Credential Access, Collection
- **ATT&CK Tag:** Input Capture, GUI Input Capture
- **ATT&CK ID:** T1056, T1056.002
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
((label="Process" label=Create command="*UI.promptforcredential*" command=
→ "*getnetworkcredential*") OR (norm_id=WinServer event_id=4104 script_block="*UI.
→ promptforcredential*" script_block="*getnetworkcredential*")) | rename script_block as
→ command
```

2.139 LP_Credential Dump Tools Dropped Files Detected

- **Trigger Condition:** Creation of files with a well-known filename, or parts of credential dump software or files produced by them is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 file IN ["*\\pwdump*", "*\\kirbi*", "*\\pwhashes*",
→ "*\\wce_ccache*", "*\\wce_krbtkts*", "*\\fgdump-log*", "*\\test.pwd", "*\\lsremora64.dll",
→ "*\\lsremora.dll", "*\\fgexec.exe", "*\\wceaux.dll", "*\\SAM.out", "*\\SECURITY.out",
→ "*\\SYSTEM.out", "*\\NTDS.out", "*\\DumpExt.dll", "*\\DumpSvc.exe", "*\\cachedump64.
→ exe", "*\\cachedump.exe", "*\\pstgdump.exe", "*\\servpw.exe", "*\\servpw64.exe",
→ "*\\pwdump.exe", "*\\procdump64.exe"] -user IN EXCLUDED_USERS
```

2.140 LP_Credential Dumping - Process Creation

- **Trigger Condition:** Attempts by adversaries to dump credentials for obtaining account login and credential material using different commands like *ntdsutil*, *procdump*, *wce* or *gsecdump*, in the form of a hash or a clear text password from operating systems and software are detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command IN ["*Invoke-Mimikatz -DumpCreds*",
↪ "*gsecdump -a*", "*wce -o*", "*procdump*-ma*lsass.exe", "*ntdsutil*ac [?]",
↪ "ntds*ifm*create full*"]
```

2.141 LP_Credential Dumping - Process Access

- **Trigger Condition:** Attempts by adversaries to dump credentials for obtaining account login and credential material using different commands like *ntdsutil*, *procdump*, *wce*, or *gsecdump*, in the form of a hash or a clear text password from operating systems and software.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=10 target_image="*C:\Windows\system32\lsass.exe"
↪ " (access="*0x1010*" or access="*0x1410*" or access="*0x147a*" or access="*0x143a*"
↪ ") call_trace="*C:\Windows\SYSTEM32\ntdll.dll" or call_trace=
↪ "*C:\Windows\system32\KERNELBASE.dll" or call_trace="*|UNKNOWN(*)" -user IN [?]
↪ EXCLUDED_USERS
```

2.142 LP_Credential Dumping - Registry Save

- **Trigger Condition:** Credential dumping activities are detected. Adversaries attempt to dump credentials for obtaining account login and credential material exploiting registries, generally in the form of a hash or a clear text password from operating systems and software using different commands like *ntdsutil*, *procdump*, *wce* or *gsecdump*.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" "process"="*\reg.exe" command IN ["* save *", "*?
↪ export *"] command IN ["*HKLM\sam*", "*HKLM\system*", "*HKEY_LOCAL_
↪ MACHINE\SAM*", "*HKEY_LOCAL_MACHINE\SECURITY*"]
```

2.143 LP_Credential Dumping with ImageLoad Detected

- **Trigger Condition:** Attempts by adversaries to dump credentials using DLL images are detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Image" label="Load" image IN ["*C:\Windows\System32\samlib.dll*",
↪ "*C:\Windows\System32\WinSCard.dll*", "*C:\Windows\System32\cryptdll.dll*",
↪ "*C:\Windows\System32\hid.dll*", "*C:\Windows\System32\vaultcli.dll*"] - "process" IN [
↪ "*\Sysmon.exe", "*\svchost.exe", "*\logonui.exe"] -user IN EXCLUDED_USERS
```

2.144 LP_Credentials Access in Files Detected

- **Trigger Condition:** Command line arguments containing pattern to search pass in files are detected. Adversaries can use this technique to search for local file systems and remote file shares to discover files containing insecurely stored credentials.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Unsecured Credentials, Credentials in Files
- **ATT&CK ID:** T1552, T1552.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command IN ["**findstr* /si pass*", "**select-string -Pattern*  
↪ pass*", "**list vdir*/text:password*"]
```

2.145 LP_Registry Enumeration for credentials Detected

- **Trigger Condition:** Search of the compromised system's registry to find and obtain insecurely stored credentials is detected. Adversaries can inspect the Windows Registry on compromised systems for insecurely stored credentials and passwords, as the registry contains configuration data used by the system and software.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Unsecured Credentials, Credentials in Registry
- **ATT&CK ID:** T1552, T1552.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="**\reg.exe" command="**query*" command="**/  
↪ t*" command="**REG_SZ*" command="**/s*" (command=  
↪ "**HKCU\Software\SimonTatham\PuTTY\Sessions*" OR (command="**/f *" command IN [  
↪ "**HKLM*", "**HKCU*"))
```

2.146 LP_Default Account privilege elevation followed by restoration of previous account state

- **Trigger Condition:** A user is added to a group or assigned privilege followed by restoration or removal from those rights.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Account Manipulation, Exploitation for Privilege Escalation
- **ATT&CK ID:** T1098, T1068
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
[label=User label=Group label=Management label=Add | rename target_user as
↪account]as s1 followed by [ label=User label=Group (label=Remove or label=Delete) -
↪target_user=*$ | rename target_user as account] as s2 on s1.account=s2.account |
↪rename s1.log_ts as ElevationTime_ts, s2.log_ts as RestorationTime_ts, s1.user as
↪UserElevation, s2.user as UserRestoration, s1.account as Account, s1.message as
↪PrivilegeElevation, s2.message as PrivilegeRestoration
```

2.147 LP_Default Blocked Inbound Traffic followed by Allowed Event

- **Trigger Condition:** Blocked inbound traffic followed by allowed traffic is detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
[norm_id=*firewall or norm_id=*IDS label=Block or label=Deny label=Connection -source_
↪address IN HOMENET destination_address IN HOMENET] as s1 followed by [norm_
↪id=*firewall label=Allow label=Connection -source_address IN HOMENET destination_
↪address IN HOMENET] as s2 on s1.source_address=s2.source_address | rename s1.
↪source_address as source
```

2.148 LP_Default Blocked Outbound Traffic followed by Allowed Event

- **Trigger Condition:** Blocked outbound traffic followed by allowed traffic is detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
[norm_id=*firewall or norm_id=*IDS label=Block or label=Deny label=Connection source_
↪address IN HOMENET -destination_address IN HOMENET] as s1 followed by [norm_
↪id=*firewall label=Allow label=Connection source_address IN HOMENET -destination_
↪address IN HOMENET]
as s2 on s1.source_address=s2.source_address | rename s1.source_address as source
```

2.149 LP_Default Brute Force Attack Successful

- **Trigger Condition:** Five failed users login attempts followed by a successful login from the same user within five minutes is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Brute Force
- **ATT&CK ID:** T1110
- **Minimum Log Source Requirement:** Windows, AWS, Firewall, WAF, Unix
- **Query:**

```
[label=User label=Login label=Fail -user=*$ | chart count() as cnt by user | search cnt > 5]
↪as s1 followed by [label=User label=Login label=Successful] as s2 on s1.user = s2.user
↪rename s2.user as user
```

2.150 LP_Default Connection Attempts on Closed Port

- **Trigger Condition:** A connection is established on closed ports. For the alert to work, you must update the list ALERT_OPEN_PORTS, which includes a list of open ports.
- **ATT&CK Category:** Command And Control, Persistence, Privilege Escalation
- **ATT&CK Tag:** Traffic Signaling, Port Knocking
- **ATT&CK ID:** T1205, T1205.001
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Connection -destination_port IN ALERT_OPEN_PORTS source_address=*?  
↪ destination_port=*
```

2.151 LP_Default CPU Usage Status

- **Trigger Condition:** The use of CPU exceeds 90%.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Logpoint
- **Query:**

```
label=Metrics label=CPU label=Usage use>90
```

2.152 LP_Default Device Stopped Sending Logs for Half an Hour

- **Trigger Condition:** A device that has not sent logs for half an hour or more is detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Service Stop

- **ATT&CK ID:** T1489
- **Minimum Log Source Requirement:** Firewall, IDS, IPS, Proxy Server, Windows, Unix
- **Query:**

```
| chart max(col_ts) as max_time_ts by device_ip | process current_time(a) as time | chart
↪ max(time-max_time_ts) as elapsed_time by max_time_ts, device_ip | search elapsed_
↪ time>1800
```

2.153 LP_Default DNS Tunneling Detection - Query Size

- **Trigger Condition:** Traffic with more than 64 characters in Application Layer Protocol and DNS is detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Application Layer Protocol, DNS, Dynamic Resolution, Domain Generation Algorithms
- **ATT&CK ID:** T1071,T1071.004,T1568,T1568.002
- **Minimum Log Source Requirement:** Firewall, IDS/IPS, Webserver, DNS Server
- **Query:**

```
norm_id=* "DNS" qname=* | process count_char(qname) as charCount | search
↪ charCount>64
```

2.154 LP_Default Excessive Blocked Connections

- **Trigger Condition:** 50 blocked or denied connections are observed from the same source within a minute.
- **ATT&CK Category:** Impact, Command and Control
- **ATT&CK Tag:** Network Denial of Service, Endpoint Denial of Service, Proxy
- **ATT&CK ID:** T1498, T1499, T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
[50 label=Connection (label=Deny OR label=Block) source_address=* having same source_
↪ address within 1 minute]
```

2.155 LP_Default File Association Changed

- **Trigger Condition:** Adversaries establish persistence and/or elevate privileges by executing malicious content triggered by a file type association.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Event Triggered Execution, Change Default File Association
- **ATT&CK ID:** T1546, T1546.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon (event_id=12 or event_id=13 or event_id=14) (target_object=
↪ "*"SOFTWARE\Classes\*" or target_object=
↪ "*"SOFTWARE\Microsoft\Windows\CurrentVersion\Explorer\GlobalAssocChangedCounter*"
↪ "-user IN EXCLUDED_USERS
```

2.156 LP_Default Guest Account Added to Administrative Group

- **Trigger Condition:** A guest account is added to security group management.
- **ATT&CK Category:** Credential Access, Persistence, Privilege Escalation, Defense Evasion, Initial Access
- **ATT&CK Tag:** Account Manipulation, Abuse Elevation Control Mechanism, Bypass User Access Control, Valid Accounts
- **ATT&CK ID:** T1098, T1548, T1548.002, T1078
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
label=Security label=Group label=Management label=Add (member_sid="S-1-5-21-*-501
↪ " OR target_id="S-1-5-21-*-501") | rename target_user as member, group as group_
↪ name
```

2.157 LP_Default Inbound Connection with Non-Whitelist Country

- **Trigger Condition:** An inbound connection established with a non-whitelisted country is detected. For this alert to work, you must update the list `WHITELIST_COUNTRY`.
- **ATT&CK Category:** Command And Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
-source_address IN HOMENET destination_address IN HOMENET | process geoip(source_↪address) as country | search -country IN WHITELIST_COUNTRY
```

2.158 LP_Default Inbound RDP Connection

- **Trigger Condition:** Inbound RDP traffic events on destination port 3389 is detected.
- **ATT&CK Category:** Lateral Movement, Command And Control
- **ATT&CK Tag:** Remote Services, Application Layer Protocol
- **ATT&CK ID:** T1021, T1071
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Connection -source_address IN HOMENET destination_address in HOMENET↪↪destination_port=3389
```

2.159 LP_Default Inbound SMB Connection

- **Trigger Condition:** Inbound SMB traffic events on destination port 445 is detected.
- **ATT&CK Category:** Lateral Movement, Command And Control

- **ATT&CK Tag:** Application Layer Protocol
- **ATT&CK ID:** T1071
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Connection -source_address IN HOMENET destination_address in HOMENET  
↔ destination_port=445
```

2.160 LP_Default Inbound SMTP Connection

- **Trigger Condition:** Inbound SMTP traffic event on destination ports 25, 456, 587, 2525, and 2526 is detected.
- **ATT&CK Category:** Command And Control
- **ATT&CK Tag:** Application Layer Protocol
- **ATT&CK ID:** T1071
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Connection -source_address IN HOMENET destination_address in HOMENET  
↔ destination_port in [25,465,587,2525,2526]
```

2.161 LP_Default Inbound SSH Connection

- **Trigger Condition:** Inbound Remote Services SSH traffic event on destination port 22 is detected.
- **ATT&CK Category:** Lateral Movement, Command and Control
- **ATT&CK Tag:** Remote Services, Application Layer Protocol
- **ATT&CK ID:** T1021, T1071
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Connection -source_address IN HOMENET destination_address in HOMENET
↪ destination_port=22
```

2.162 LP_Default IRC connection

- **Trigger Condition:** The IRC connection is detected. For this alert to work, you must update ALERT_IRC_PORT list with possible IRC ports.
- **ATT&CK Category:** Command and Control, Discovery
- **ATT&CK Tag:** Proxy, Network Service Scanning
- **ATT&CK ID:** T1090, T1046
- **Minimum Log Source Requirement:** Firewall, IDS/IPS, Webserver
- **Query:**

```
(destination_port IN ALERT_IRC_PORT OR destination_port=6667)
```

2.163 LP_Default Malware Detected

- **Trigger Condition:** A malware or a virus is detected in the system.
- **ATT&CK Category:** Resource Development
- **ATT&CK Tag:** Develop Capabilities, Malware
- **ATT&CK ID:** T1587, T1587.001
- **Minimum Log Source Requirement:** Antivirus
- **Query:**

```
(label=Virus OR label=Malware ) (label=Detect OR label=Find) (virus=* OR malware=* OR
↪ file=* OR path=*) | rename malware as virus
```

2.164 LP_Default Malware not Cleaned

- **Trigger Condition:** A malware clean events including deletion, removal, and quarantine, is followed by detecting the same malware in the same host.
- **ATT&CK Category:** Discovery, Defense Evasion

- **ATT&CK Tag:** Network Service Scanning,Exploitation for Defense Evasion,Software Discovery, Security Software Discovery
- **ATT&CK ID:** T1046, T1211, T1518, T1518.001
- **Minimum Log Source Requirement:** Antivirus
- **Query:**

```
norm_id=* malware=* action IN ["*delete*", "*remove*", "*quarantine*"] as s1 followed
↳ by [norm_id=* malware=* source_address=*] as s2 on s1.malware=s2.malware | process
↳ compare(s1.source_address, s2.source_address) as match | search match=true | rename
↳ s1.source_address as source_address, s1.malware as malware
```

2.165 LP_Default Malware Removed

- **Trigger Condition:** Removal of malware or a virus from the system is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Indicator Removal on Host, Obfuscated Files or Information, Indicator Removal from Tools
- **ATT&CK ID:** T1070, T1027, T1027.005
- **Minimum Log Source Requirement:** Antivirus
- **Query:**

```
(label=Virus OR label=Malware ) (label=Remove OR label=Clean OR label=Delete) -label=
↳ "Not" -label=Error | rename malware as virus | search virus=*
```

2.166 LP_Default Memory Usage Status

- **Trigger Condition:** Physical memory usage exceeds 90% of the total memory available is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Logpoint
- **Query:**

```
label=Metrics label=Memory label=Usage object="Physical Memory" use>90
```

2.167 LP_Default Network Configuration Change on Network Device

- **Trigger Condition:** A change in the core network event source, such as a router or switch, is detected.
- **ATT&CK Category:** Persistence, Credential Access, Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Modify Existing Service, Account Manipulation, Abuse Elevation Control Mechanism, Bypass User Access Control, Impair Defenses, Indicator Blocking, Modify Registry, Exploitation for Privilege Escalation
- **ATT&CK ID:** T1098, T1548, T1562, T1562.006, T1112, T1068
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Network label=Configuration (label=Change OR label=Modify OR label=Reset OR
↪label=Enable OR label=Disable OR label=Add or label=Delete or label=Undelete)
```

2.168 LP_Default Outbound Connection with Non-Whitelist Country

- **Trigger Condition:** Outbound connections with non-whitelisted countries are detected. For this alert to work, you must update the list WHITELIST_COUNTRY.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
source_address IN HOMENET -destination_address IN HOMENET | process
↪geoip(destination_address) as country | search -country IN WHITELIST_COUNTRY
```

2.169 LP_Default Outbound Traffic from Unusual Source

- **Trigger Condition:** Outbound traffic is detected from an unusual source. For this alert to work, you must update the list ALERT_UNUSUAL_SOURCE with source addresses from which outbound connections are not established.
- **ATT&CK Category:** Command and Control, Exfiltration
- **ATT&CK Tag:** Proxy, Automated Exfiltration, Exfiltration Over C2 Channel
- **ATT&CK ID:** T1090, T1020, T1041
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
source_address IN ALERT_UNUSUAL_SOURCE source_address IN HOMENET
↪ (label=Traffic OR label=Connection) -destination_address IN HOMENET
```

2.170 LP_Default Port Scan Detected

- **Trigger Condition:** Connection from multiple ports of a public IP address to a destination address is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Firewall, IDS, IPS, Webserver
- **Query:**

```
-source_address IN HOMENET destination_port=* | chart distinct_count(destination_
↪ port) as CNT by source_address, destination_address | search CNT>50
```

2.171 LP_Default Possible Cross Site Scripting Attack Detected

- **Trigger Condition:** The script tag indicating the XSS attack is detected in the URL.
- **ATT&CK Category:** Initial Access

- **ATT&CK Tag:** Exploiting Public-Facing Application
- **ATT&CK ID:** T1190
- **Minimum Log Source Requirement:** Firewall, IDS/IPS, Webserver
- **Query:**

```
norm_id=* url IN ["*<script>*", "%3c%73%63%72%69%70%74%3e*", "%3cscript%3e*"]  
↪ or resource IN ["*<script>*", "%3c%73%63%72%69%70%74%3e*", "%3cscript%3e*"]  
↪ | rename resource as url
```

2.172 LP_Default Possible Network Performance Degradation Detected

- **Trigger Condition:** 100 or more network-related errors are detected in security devices within five minutes.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Network Denial of Service
- **ATT&CK ID:** T1498
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
norm_id=((label=Connection (label=Error or label=Fail or label=Deny or label=Drop)) or  
↪ (label="Limit" label=Exceed) or (label=Packet label=Drop) or (label=Protocol  
↪ label=Deny)) | chart count() as Event by device_ip, norm_id | search Event>1000
```

2.173 LP_Default Possible Non-PCI Compliant Inbound Network Traffic Detected

- **Trigger Condition:** An inbound connection is detected in secure devices over non-compliant ports as specified by PCI compliance practices. For this alert to work, you must update the list NON_PCI_COMPLIANT_PORT.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090

- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Inbound label=Connection destination_port IN NON_PCI_COMPLIANT_PORT -
↪ source_address IN HOMENET
```

2.174 LP_Default Possible Spamming Zombie

- **Trigger Condition:** Systems other than mail servers attempt to establish an outbound SMTP connection is detected. For this alert to work, you must update the list MAIL_SERVERS with possible mail servers to remove false positives. For example, *exchange*, *postfix*, and so on.
- **ATT&CK Category:** Command and Control, Impact
- **ATT&CK Tag:** Proxy, Application Layer Protocol, Network Denial of Service
- **ATT&CK ID:** T1090, T1071, T1498
- **Minimum Log Source Requirement:** All except Mail Server
- **Query:**

```
-norm_id IN MAIL_SERVERS destination_port IN ["25", "587"]
```

2.175 LP_Default Possible SQL Injection Attack

- **Trigger Condition:** SQL character injection in the input field of a web application is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Exploit Public-Facing Application
- **ATT&CK ID:** T1190
- **Minimum Log Source Requirement:** Firewall, IDS/IPS, Webserver
- **Query:**

```
norm_id=* url IN SQL_INJECTION_CHARACTER or resource IN SQL_INJECTION_
↪ CHARACTER | rename resource as url
```

2.176 LP_Default Possible System Instability State Detected

- **Trigger Condition:** The instability of a system is detected. For example, a system shut down or restarts more than five times within ten minutes. A correlation rule is designed to detect if a system has become unstable.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** System Shutdown/Reboot
- **ATT&CK ID:** T1529
- **Minimum Log Source Requirement:** OS
- **Query:**

```
[5 (-label=Require -label=Request -label=Reply) (label=Restart OR label=Shutdown OR
↪ label=Boot) having same device_ip within 10 minutes]
```

2.177 LP_Default PowerSploit and Empire Schtasks Persistence

- **Trigger Condition:** Creation of a `schtask` via PowerSploit or Empire Default Configuration is detected.
- **ATT&CK Category:** Execution, Persistence, Privilege Escalation
- **ATT&CK Tag:** Scheduled Task/Job, Scheduled Task, Command and Scripting Interpreter, PowerShell + **ATT&CK ID:** T1053, T1053.005, T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process="*\powershell.exe" "process"="*\schtasks.
↪ exe" command = "*/Create*" command = "*/SC*" (command in ["*ONLOGON*",
↪ "*DAILY*", "*ONIDLE*", "*Updater*"] command = "*/TN*" command = "*Updater*"
↪ command = "*/TR*" command = "*powershell*")
```

2.178 LP_Default Successful Login outside Normal Hour

- **Trigger Condition:** Successful user login beyond regular office hour is detected. You can adjust the regular work hour according to your company.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts
- **ATT&CK ID:** T1078
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
label=Login label=Successful target_user=* ((day_of_week(log_ts)=2 OR day_of_week(log_
↪ts)=3 OR day_of_week(log_ts)=4 OR day_of_week(log_ts)=5 OR day_of_week(log_ts)=6) |
↪(hour(log_ts)>0 hour(log_ts)<9) OR hour(log_ts)>17) OR (day_of_week(log_ts) IN [1, 7]) |
↪rename target_user as user
```

2.179 LP_Default Successful Login Using a Default Account

- **Trigger Condition:** Successful login attempts using a vendor default account is detected. The alert is essential for those organizations employing Payment Card Industry (PCI) Compliance.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts, Default Accounts
- **ATT&CK ID:** T1078, T1078.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
label=User label=Login label=Successful (target_user=* OR user=*) (target_user IN
↪DEFAULT_USERS OR user IN DEFAULT_USERS) | rename target_user as user
```

2.180 LP_Default System Time Change

- **Trigger Condition:** The system time is changed or when Logpoint command `/opt/immune/installed/system/root_actions/*_ntp.sh` is executed.
- **ATT&CK Category:** Persistence, Impact
- **ATT&CK Tag:** Modify Existing Service, Data Destruction
- **ATT&CK ID:** T1485
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
(label=System label=Time label=Change) OR (label=Execute label=Command command=  
↪ "/opt/immune/installed/system/root_actions/*_ntp.sh")
```

2.181 LP_Default TCP Probable SynFlood Attack

- **Trigger Condition:** Security devices detect ten TCP Syn flood events within a minute.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Endpoint Denial of Service
- **ATT&CK ID:** T1499
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
[10 TCP SYN having same source_address within 1 minute]
```

2.182 LP_Default Unapproved Port Activity Detected

- **Trigger Condition:** A user uses unapproved ports.
- **ATT&CK Category:** Defense Evasion, Persistence, Command And Control
- **ATT&CK Tag:** Boot or Logon Autostart Execution, Port Monitors, Traffic Signaling, Port Knocking
- **ATT&CK ID:** T1547, T1547.01, T1205, T1205.001

- **Minimum Log Source Requirement:** Firewall, IDS/IPS, Webserver
- **Query:**

```
norm_id=* source_port IN UNAPPROVED_PORT or destination_port IN UNAPPROVED_
↪PORT or port IN UNAPPROVED_PORT | rename source_port as port, destination_port
↪as port
```

2.183 LP_Default Unusual Number of Failed Vendor User Login

- **Trigger Condition:** Failed user logins using default credentials for more than 10 times are detected. For this alert to work, you must update the list DEFAULT_USERS with default vendor user names.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts, Default Accounts
- **ATT&CK ID:** T1078, T1078.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
label=User label>Login label=Fail (target_user=* OR user=*) (target_user IN DEFAULT_
↪USERS OR user IN DEFAULT_USERS) | rename target_user as user | chart count() as
↪Event by user, source_address | search Event>10
```

2.184 LP_HandleKatz Duplicating LSASS Handle

- **Trigger Condition:** The HandleKatz tool directly opening LSASS process to duplicate its handle is detected.
- **ATT&CK Category:** Execution, Credential Access
- **ATT&CK Tag:** LSASS Memory, Native API
- **ATT&CK ID:** T1003.001, T1106
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=10 access="0x1440" "image"="*\sass.exe" call_
↪ trace="C:\Windows\System32\ntdll.dll+*" call_trace="*|UNKNOWN(*" call_trace="*)"
```

2.185 LP_PowerShell Execution Policy Modification Detected

- **Trigger Condition:** The registry value for the PowerShell execution policy is changed.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** PowerShell, Modify Registry
- **ATT&CK ID:** T1059.001, T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
::S
```

```
norm_id=WindowsSysmon      event_id=13      event_type=setvalue
target_object IN ["ShellIdsMicrosoft.PowerShellExecutionPolicy","PoliciesMicrosoftWindow
detail IN ["Bypass","RemoteSigned","Unrestricted"] -image IN
["C:WindowsSystem32*","C:WindowsSysWOW64*"]
```

2.186 LP_Devtoolslauncher Executes Specified Binary

- **Trigger Condition:** The use of *devtoolslauncher* to execute other binaries is detected. Devtoolslauncher is a Microsoft Windows executable, a part of VS/VSCode installation, that enables the use of developer tools by other applications. Adversaries attempt to bypass process or signature-based defenses by proxying the execution of malicious content with signed binaries using *devtoolslauncher* and *LaunchForDeploy* commands.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** System Binary Proxy Execution
- **ATT&CK ID:** T1218
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\devtoolslauncher.exe" command=
↳ "*LaunchForDeploy*" -user IN EXCLUDED_USERS
```

2.187 LP_DHCP Callout DLL Installation Detected

- **Trigger Condition:** Installation of a *Callout DLL* via *CalloutDlls* and *CalloutEnabled* parameters in the registry, used to execute code in the context of the DHCP server is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Hijack Execution Flow, DLL Side-Loading, Modify Registry
- **ATT&CK ID:** T1574, T1574.002, T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 target_object IN [
↳ "*\Services\DHCPServer\Parameters\CalloutDlls",
↳ "*\Services\DHCPServer\Parameters\CalloutEnabled"] -user IN EXCLUDED_USERS
```

2.188 LP_DHCP Server Error Failed Loading the CallOut DLL

- **Trigger Condition:** DHCP server error in which a specified Callout DLL in registry cannot be loaded.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Hijack Execution Flow, DLL Side-Loading
- **ATT&CK ID:** T1574, T1574.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WinServer event_id IN ["1031", "1032", "1034"] event_source="Microsoft-
↳ Windows-DHCP-Server" -user IN EXCLUDED_USERS
```

- ```
norm_id=WinServer event_id=1033 -user IN EXCLUDED_USERS
```

## 2.190 LP\_Direct Autorun Keys Modification Detected

- ```
label="Process" label=Create "process"="*reg.exe" command="*add*"
↪ command IN ["*\\software\\Microsoft\\Windows\\CurrentVersion\\Run*",
↪ "*\\software\\Microsoft\\Windows\\CurrentVersion\\RunOnce*",
↪ "*\\software\\Microsoft\\Windows\\CurrentVersion\\RunOnceEx*",
↪ "*\\software\\Microsoft\\Windows\\CurrentVersion\\RunServices*",
↪ "*\\software\\Microsoft\\Windows\\CurrentVersion\\RunServicesOnce*",
↪ "*\\software\\Microsoft\\Windows NT\\CurrentVersion\\Winlogon\\Userinit*",
↪ "*\\software\\Microsoft\\Windows NT\\CurrentVersion\\Winlogon\\Shell*",
↪ "*\\software\\Microsoft\\Windows NT\\CurrentVersion\\Windows*",
↪ "*\\software\\Microsoft\\Windows\\CurrentVersion\\Explorer\\User Shell Folders*",
```

(continued from previous page)

2.191 LP_Disable of ETW Trace Detected

- **Trigger Condition:** A command that clears or disables the ETW trace log, indicating a logging evasion attempt by adversaries. Adversaries can cease the flow of logging temporarily or permanently without generating any additional event clear log entries from this method.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Indicator Blocking
- **ATT&CK ID:** T1562, T1562.006
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Create label="process" ((command="* cl */Trace*") OR (command="* clear-log */
↳ Trace*") OR (command="* sl*/e:false*") OR (command="* set-log*/e:false*") OR
↳ (command="*Remove-EtwTraceProvider*" command="*EventLog-Microsoft-Windows-
↳ WMI-Activity-Trace*" command="*{1418ef04-b0b4-4623-bf7e-d74ab47bbdaa}*") OR
↳ (command="*Set-EtwTraceProvider*" command="*{1418ef04-b0b4-4623-bf7e-
↳ d74ab47bbdaa}*") command="*EventLog-Microsoft-Windows-WMI-Activity-Trace*"
↳ command="*0x11*") OR (command="*logman update trace*" command="* --p *")
↳ command="* -ets *")) -user IN EXCLUDED_USERS
```

2.192 LP_MiniNt Registry Key Addition

- **Trigger Condition:** The addition of a key *MiniNt* to the registry is detected. Windows Event Log service will stop the write events after reboot.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Disable or Modify Tools
- **ATT&CK ID:** T1562, T1562.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=Registry label=Set label=Value target_object=
↪ "HKLM\SYSTEM\CurrentControlSet\Control\MiniNt" -user IN EXCLUDED_USERS
```

2.193 LP_Discovery via Discovery via PowerSploit Recon Module Detected

- **Trigger Condition:** Adversaries abuse Command and Script Interpreters to execute scripts via the PowerSploitReconnaissance module. For this alert to work, you must update the list POWERSPLOIT_RECON_MODULES.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4104 (scriptblocktext in POWERSPLOIT_RECON_
↪ MODULES OR script_block in POWERSPLOIT_RECON_MODULES) -user IN EXCLUDED_
↪ USERS | rename scriptblocktext as script_block
```

2.194 LP_DLL Load via LSASS Detected

- **Trigger Condition:** A method to load DLL via the LSASS process using an undocumented registry key is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Boot or Logon Autostart Execution, LSASS Driver
- **ATT&CK ID:** T1547, T1547.008
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id IN ["12", "13"] target_object IN [
↪ "*\CurrentControlSet\Services\NTDS\DirectoryServiceExtPt*",
↪ "*\CurrentControlSet\Services\NTDS\LsaDbExtPt*"]
```

2.195 LP_DNS Server Error Failed Loading the ServerLevelPluginDLL

- **Trigger Condition:** Application Layer Protocol and DNS server error where a specified plugin DLL in the registry cannot be loaded.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Hijack Execution Flow, DLL Side-Loading
- **ATT&CK ID:** T1574, T1574.002
- **Minimum Log Source Requirement:** DNS Server
- **Query:**

```
event_source="DNS Server" event_id IN ["150", "770"]
```

2.196 LP_DNS ServerLevelPluginDll Install

- **Trigger Condition:** Installation of a plugin DLL via the ServerLevelPluginDll parameter in the registry used to execute code in Application Layer Protocol and DNS server.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Hijack Execution Flow, DLL Side-Loading
- **ATT&CK ID:** T1574, T1574.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon (event_id=13 target_object=
↪ "*"\\services\\DNS\\Parameters\\ServerLevelPluginDll") OR (event_id=1 command=
↪ "dnscmd.exe /config /serverlevelpluginDll *" ) -user IN EXCLUDED_USERS
```

2.197 LP_Domain Trust Discovery Detected

- **Trigger Condition:** Adversaries attempt to gather information on domain trust relationships is detected. Domain trust is a relationship between two domains that allows users in one domain to be authenticated in the other domain. It enables

users to access resources in a trusted domain as if they were local. Adversaries may attempt to establish domain trusts to access additional resources or move laterally within an organization's network. They may also use domain trusts to hide their activities or to evade detection.

- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Domain Trust Discovery
- **ATT&CK ID:** T1482
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (("process"="*\dsquery.exe" command="*-filter*"
↪command="*trustedDomain*") OR ("process"="*\nltest.exe" command="*domain_
↪trusts*")) -user IN EXCLUDED_USERS
```

2.198 LP_dotNET DLL Loaded Via Office Applications

- **Trigger Condition:** Assembly of DLL loaded by the Office Product is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing, Spearphishing Attachment
- **ATT&CK ID:** T1566, T1566.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 "process" IN ["*\winword.exe*", "\powerpnt.exe*
↪", "\excel.exe*", "\outlook.exe*"] image="*C:\Windows\assembly\*" -user IN
↪EXCLUDED_USERS
```

2.199 LP_DPAPI Domain Backup Key Extraction Detected

- **Trigger Condition:** Tools extracting the LSA secret DPAPI domain backup key from Domain Controllers are detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping

- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
(norm_id=WinServer event_id=4662 object_type="SecretObject" access_mask="0x2"
↪ object_name="*BCKUPKEY") -user IN EXCLUDED_USERS
```

2.200 LP_DPAPI Domain Master Key Backup Attempt

- **Trigger Condition:** An attempt to backup DPAPI master key is detected. The event is generated on the source and not on the Domain Controller.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4692 -user IN EXCLUDED_USERS
```

2.201 LP_Dridex Process Pattern Detected

- **Trigger Condition:** A typical dridex process patterns are detected.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (("process"="*svchost.exe" command="*C:\Users\*"
↪ command="*\Desktop\*" -parent_process="C:\Windows\System32\*" ) OR (parent_
↪ process="*\excel.exe" "process"="*\regsvr32.exe" command IN ["*-s *",
↪ ".*\AppData\Local\Temp\*" ] -command="*.dll*" ) OR (parent_process="*svchost.exe" ((
↪ "process"="*\whoami.exe" command="*/all*") OR ("process" IN ["*\net.exe", ".*\net1.
↪ exe"] command="*view*")))) -user IN EXCLUDED_USERS
```

2.202 LP_Droppers Exploiting CVE-2017-11882 Detected

- **Trigger Condition:** The exploitation using CVE-2017-11882 to start EQNEDT32.EXE and other sub-processes like mshta.exe are detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Exploitation for Defense Evasion
- **ATT&CK ID:** T1211
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 parent_image="*\EQNEDT32.EXE" -user IN EXCLUDED_USERS
```

2.203 LP_Drupal Arbitrary Code Execution Detected

- **Trigger Condition:** The exploitation of arbitrary code execution vulnerability (CVE-2018-7600) in Drupal, is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Exploit Public-Facing Application
- **ATT&CK ID:** T1190
- **Minimum Log Source Requirement:** Firewall, IDS/IPS, Webserver
- **Query:**

```
norm_id=* label=Access request_method=POST resource='ajax_form*drupal*ajax'
```

2.204 LP_Elevated Command Prompt Activity by Non-Admin User Detected

- **Trigger Condition:** The execution of an elevated command prompt by a non-admin user.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command-Line Interface
- **ATT&CK ID:** T1059
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4688 -user IN ADMINS "process"="cmd.exe" token_elevation_type="*(2)" -user IN EXCLUDED_USERS
```

2.205 LP_EMC Possible Ransomware Detection

- **Trigger Condition:** Suspicious data activity affecting more than 200 files or in-house baseline is detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Data Encrypted for Impact, Data Destruction, Proxy
- **ATT&CK ID:** T1486, T1485, T1090
- **Minimum Log Source Requirement:** EMC
- **Query:**

```
label=EMC -"bytesWritten"="0" -"bytesWritten"="0x0" event="0x80"
flag=0x2 userSid=*| chart count() as handle by userSid, clientIP | search
handle>200
```

2.206 LP_Empire PowerShell Launch Parameters

- **Trigger Condition:** Suspicious PowerShell command line parameters used in Empire are detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command IN ["*-NoP -sta -NonI -W Hidden -Enc *", "* -
↪noP -sta -w 1 -enc *", "* -NoP -NonI -W Hidden -enc *", "* -enc SQB*", "* -nop -exec
↪bypass -EncodedCommand*"] -user IN EXCLUDED_USERS
```

2.207 LP_Empire PowerShell UAC Bypass Detected

- **Trigger Condition:** Empire Command and Scripting Interpreter and PowerShell UAC bypass methods are detected.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Abuse Elevation Control Mechanism, Bypass User Access Control
- **ATT&CK ID:** T1548

- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 command IN ["*-NoP -NonI -w Hidden -c x=((gp
↪ HKCU:Software\Microsoft\Windows Update).Update)*", "-* -NoP -NonI -c x=((gp
↪ HKCU:Software\Microsoft\Windows Update).Update)*"] -user IN EXCLUDED_USERS
```

2.208 LP_Enabled User Right in AD to Control User Objects

- **Trigger Condition:** Logpoint detects a scenario where if a user is assigned the *SeEnableDelegation Privilege* right in Active Directory, they will be allowed to control other Active Directory user's objects.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** Valid Accounts
- **ATT&CK ID:** T1078
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4704 message="*SeEnableDelegationPrivilege*" -user IN
↪ EXCLUDED_USERS
```

2.209 LP_PowerShell Encoded FromBase64String Detected

- **Trigger Condition:** The .NET method *FromBase64String* decodes a Base64-encoded string is detected. Base64 is a widely used encoding scheme representing binary data in an ASCII string format.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell, Deobfuscate/Decode Files or Information
- **ATT&CK ID:** T1059, T1059.001, T1140
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

- **Query:**

```
label="process" label=create command IN [
  ↳ "*OgA6AEYAcgBvAG0AQgBhAHMAZQA2ADQAUwB0AHIAaQBuAGcA*",
  ↳ "*oAOgBGAHIAbwBtAEIAYQBzAGUANgA0AFMAAdABYAGkAbgBnA*",
  ↳ "*6ADoARgByAG8AbQBCAGEAcwBIADYANABTAHQAcgBpAG4AZw*" ]
```

2.210 LP_Encoded IEX Detected

- **Trigger Condition:** The use of the "IEX" (Invoke-Expression) cmdlet to execute encoded PowerShell commands is detected. "IEX" is a built-in cmdlet in PowerShell that allows users to run scripts or commands stored in a string. Adversaries may use encoding to conceal the contents of their scripts or commands, making it more difficult for defenders to detect and analyze their activities. Adversaries may use the "IEX" cmdlet to execute encoded PowerShell commands as part of their attack. They may also use encoding to hide their activities' true nature or evade detection. False Positive: Some legitimate processes might use encoded commands.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell, Deobfuscate/Decode Files or Information
- **ATT&CK ID:** T1059, T1059.001, T1140
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="process" label=create command IN ["*SUVYIChb*", "*|FWCAoW*", "*JRVggKF*",
  ↳ "*aWV4IChb*", "*|leCAoW*", "*pZXggKF*", "*aWV4IChOZX*", "*|leCAoTmV3*",
  ↳ "*pZXggKE5ld*", "*SUVYIChOZX*", "*|FWCAoTmV3*", "*JRVggKE5ld*"] -user IN [
  ↳ EXCLUDED_USERS
```

2.211 LP_Encoded PowerShell Command Detected

- **Trigger Condition:** Execution of encoded Command and Scripting Interpreter and PowerShell commands are detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** PowerShell
- **ATT&CK ID:** T1059.001

- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\powershell.exe" command IN ["*-e *", "*-
↪enc *", "*-ec *", "*-en *", "*-enco *"] -command="* -Encoding *" -("parent_process
↪="C:\Packages\Plugins\Microsoft.GuestConfiguration.ConfigurationforWindows\*"
↪parent_process="*\gc_worker.exe")
```

2.212 LP_Eventlog Cleared Detected

- **Trigger Condition:** One of the Windows Event logs been cleared is detected. Adversaries can use this technique to remove the traces of intrusion.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Clear Windows Event Logs
- **ATT&CK ID:** T1070.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=104 event_source="Microsoft-Windows-Eventlog" -user IN
↪EXCLUDED_USERS
```

2.213 LP_Executables Stored in OneDrive

- **Trigger Condition:** A user stores files that are executable in OneDrive.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Office365
- **Query:**

```
event_source=OneDrive source_file_extension IN EXECUTABLES | chart
count() by user_id, source_address, source_file, source_file_extension,
source_relative_url
```

2.214 LP_Execution in Non-Executable Folder Detected

- **Trigger Condition:** Process creation from an uncommon directory is detected. Adversaries may drop and execute payloads from such Windows locations to evade detection and gain persistence.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process" IN SUSPICIOUS_FOLDER_EXE_EXECUTION - "process"
↪ "*" \servicing\TrustedInstaller.exe "
```

2.215 LP_Execution in Outlook Temp Folder Detected

- **Trigger Condition:** Execution of a suspicious program in the Outlook's temp folder is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing, Spearphishing Attachment
- **ATT&CK ID:** T1566, T1566.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process" = "*" \Temporary Internet Files\Content.Outlook\*" -
↪ user IN EXCLUDED_USERS
```

2.216 LP_Execution in Webserver Root Folder Detected

- **Trigger Condition:** A suspicious program execution in a web service root folder (filter out false positives) is detected. Attackers use this common tactic to achieve persistence in web servers by placing their malicious files in the web service root directory. False positives could be various applications and tools, including ping or nslookup command invocations.

- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Server Software Component, Web Shell
- **ATT&CK ID:** T1505, T1505.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process" IN ["*\\wwwroot\\*", "*\\wmpub\\*", "*\\htdocs\\*"] -
↪ "process" IN ["*\\bin\\*", "*\\Tools\\*", "*\\SMSComponent\\*"] parent_process="*\\services.
↪ exe" -user IN EXCLUDED_USERS
```

2.217 LP_Execution of Renamed PaExec Detected

- **Trigger Condition:** Execution of renamed paexec via imphash and executable product string is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 product IN ["*PAExec*"] hash_imphash IN [
↪ "11D40A7B7876288F919AB819CC2D9802", "6444f8a34e99b8f7d9647de66aabe516",
↪ "dfd6aa3f7b2b1035b76b718f1ddc689f", "1a6cca4d5460b1710a12dea39e4a592c"] -
↪ image="*paexec*" -user IN EXCLUDED_USERS
```

2.218 LP_Execution via Control Panel Items

- **Trigger Condition:** Execution of binary via Signed Binary Proxy Execution, Control Panel items are detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Control Panel Items
- **ATT&CK ID:** T1218.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

- **Query:**

```
label="Process" label=Create "process"="*\control.exe" command="*control*"
↪ command="*cpl*" -user IN EXCLUDED_USERS
```

2.219 LP_Execution via HTA using IE JavaScript Engine Detected

- **Trigger Condition:** The execution of an HTA (HTML Application) file using the Internet Explorer JavaScript engine. HTAs are standalone applications written in HTML and can execute scripts, such as JavaScript or VBScript, on a system. Adversaries may use HTAs as a delivery mechanism for their payloads or execute arbitrary code on a system. Adversaries may use HTAs as a way to bypass security controls or to evade detection. They may also use them to execute arbitrary code on a system, potentially allowing them to access sensitive information or compromise the system.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Mshta
- **ATT&CK ID:** T1218.005
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 "process"="*mshta.exe" image="*jscript9.dll" -
↪ user IN EXCLUDED_USERS
```

2.220 LP_Execution via Squiblydoo Technique Detected

- **Trigger Condition:** Execution of the Squiblydoo technique is detected. Squiblydoo runs payloads or scripts by leveraging the Windows Script Host (WSH) and its default file associations. Adversaries may use Squiblydoo to bypass security controls or to evade detection. Adversaries may use the Squiblydoo technique to execute arbitrary code on a system, potentially allowing them to access sensitive information or compromise the system. They may also use it to hide their activities' true nature or evade detection.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** Signed Binary Proxy Execution, Regsvr32

- **ATT&CK ID:** T1218, T1218.01
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 image="*scrobj.dll" -user IN EXCLUDED_USERS
```

2.221 LP_Execution via Windows Scripting Host Component Detected

- **Trigger Condition:** This alert detects the execution of a script using the Windows Scripting Host (WSH) component on a system. WSH is a Microsoft technology that allows users to run scripts and automate tasks on Windows systems. Adversaries may use the WSH component to execute arbitrary code on a system, potentially allowing them to access sensitive information or compromise the system. They may also use it to hide their activities' true nature or evade detection.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter
- **ATT&CK ID:** T1059
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 image in ["*wshom.ocs", "*sccrun.dll", "*vbscript.dll"] -user IN EXCLUDED_USERS
```

2.222 LP_Exim MTA Remote Code Execution Vulnerability Detected

- **Trigger Condition:** Remote code execution vulnerability in Exim MTA is detected. The U.S. National Security Agency (NSA) reported that Russian military cyber actors, also known as Sandworm Team, have been actively exploiting a critical vulnerability in Exim MTA since August 2019.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning, Software Discovery, Security Software Discovery
- **ATT&CK ID:** T1046, T1518, T1518.001
- **Minimum Log Source Requirement:** Vulnerability Management
- **Query:**

```
norm_id=VulnerabilityManagement cve_id="CVE-2019-10149"
```

2.223 LP_Exim Remote Command Execution Detected

- **Trigger Condition:** Remote command execution in Exim is detected (CVE-2019-10149 is detected).
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Exploitation for Client Execution
- **ATT&CK ID:** T1203
- **Minimum Log Source Requirement:** Mail Server
- **Query:**

```
norm_id=* receiver="{run"
```

2.224 LP_Existing Service Modification Detected

- **Trigger Condition:** A modification of an existing service via the sc.exe system utility is detected. Adversaries abuses the Windows Service Control Manager to execute malicious commands or payloads without creating new services.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Create or Modify System Process, Windows Service
- **ATT&CK ID:** T1543, T1543.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" "process" IN ["*sc.exe", "*powershell.exe", "*cmd.exe"]  
↪ command="*sc*" command="*config*" command="*binpath*" -user IN EXCLUDED_  
↪ USERS
```

2.225 LP_External Disk Drive or USB Storage Device Detected

- **Trigger Condition:** External disk drives or plugged in USB devices are detected.
- **ATT&CK Category:** Lateral Movement, Initial Access
- **ATT&CK Tag:** Replication Through Removable Media, Hardware Additions
- **ATT&CK ID:** T1091, T1200

- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer ((event_id IN ["6416"] class="DiskDrive") OR
message="USB Mass Storage Device") -user IN EXCLUDED_USERS
```

2.226 LP_Fail2ban IP Banned

- **Trigger Condition:** A client's IP address is banned after exceeding the limit for failed authentications.
- **ATT&CK Category:** Credential Access, Persistence
- **ATT&CK Tag:** Brute Force, Valid Accounts, Account Manipulation
- **ATT&CK ID:** T1110, T1078, T1098
- **Minimum Log Source Requirement:** Fail2ban
- **Query:**

```
norm_id=Fail2ban label=IP label=Block | process geoip(source_address) as
country
```

2.227 LP_File Creation by PowerShell Detected

- **Trigger Condition:** The creation of a new file using PowerShell on a system. PowerShell is a powerful scripting language that is built into Windows and can be used to automate a wide variety of tasks. Adversaries may use PowerShell to create new files, drop and execute malicious payloads or store data for later retrieval. False positive Notice: Administrative tasks and genuine processes might cause the alert to trigger as well. Proper analysis and whitelisting are recommended.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** PowerShell
- **ATT&CK ID:** T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 file=* "process"="*powershell.exe" -file IN [ "
↪ PSScriptPolicyTest_*. ", "PowerShell_transcript.*", "powershell.exe.log",
↪ "StartupProfileData*", "ModuleAnalysisCache" ] -user IN EXCLUDED_USERS -file IN [ " *.
↪ mui" ]
```

2.228 LP_File Deletion Detected

- **Trigger Condition:** Adversaries delete files to erase the traces of the intrusion.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Indicator Removal on Host, File Deletion
- **ATT&CK ID:** T1070, T1070.004
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon      event_id=1      (command="remove-item"
or      command="vssadmin*Delete      Shadows      /All      /Q"      or
command="wmic*shadowcopy delete" or command="wbddadmin delete
catalog -q*" or command="bcdedit*bootstatuspolicy ignoreallfailures" or
command="bcdedit*recoveryenabled no") -user IN EXCLUDED_USERS
```

2.229 LP_File or Folder Permissions Modifications

- **Trigger Condition:** Modifications to file or folder permissions are detected. Permissions control access to files and directories and determine which users and processes can read, write, or execute them. Adversaries may attempt to modify these permissions to gain unauthorized access to sensitive files or to execute arbitrary code on a system. They can also use these modifications to escalate system privileges or move laterally within an organization's network.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Windows File and Directory Permissions Modification
- **ATT&CK ID:** T1222.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process"      label=Create      (("process"      IN      ["cacls.exe",
"icacls.exe",      "net.exe",      "net1.exe"]      command      IN      ["/grant",
"/setowner",      "/inheritance:r"])      OR      ("process"      =      "attrib.exe"
command="-r*")      OR      "process"="takeown.exe")      -(command="*ICACLS
C:ProgramDatadynatracegatewayconfigconnectivity.history /reset"      OR
(command="*ICACLS C:ProgramDatadynatracegatewayconfigconfig.properties
/grant :r *" command="*S-1-5-19:F") OR (command="AppDataLocalProgramsMicrosoft
VS Code"      OR      parent_process="*Microsoft VS CodeCode.exe")) -user IN
EXCLUDED_USERS
```

2.230 LP_File System Permissions Weakness

- **Trigger Condition:** A weakness in the file system permissions on a system is detected. File system permissions control access to files and directories and determine which users and processes can read, write, or execute them. Adversaries may exploit weaknesses in file system permissions to gain unauthorized access to sensitive files or execute arbitrary code on a system.
- **ATT&CK Category:** Persistence, Privilege Escalation, Defense Evasion
- **ATT&CK Tag:** Hijack Execution Flow, Services File Permissions Weakness
- **ATT&CK ID:** T1574,T1574.010
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon      event_id=7      (image="Temp*"      or
image="*C:Users*" or status!="*Valid") -user IN EXCLUDED_USERS
```

2.231 LP_Firewall Configuration Modification Detected

- **Trigger Condition:** When there is a change or modification to the Windows firewall configuration on a system. This could indicate malicious activity, as an adversary may be attempting to disable or bypass the firewall to gain unauthorized access to the system or network. False Positive Notice: Legitimate system maintenance or system administration tasks may involve the modification of firewall configurations, and these could potentially trigger the alert. It is essential to carefully review and investigate any instances of this alert before taking action to ensure that the activity detected is genuinely malicious.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Non-Standard Port
- **ATT&CK ID:** T1571
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4946 rule=* -user IN EXCLUDED_USERS
```

2.232 LP_Firewall Disabled via Netsh Detected

- **Trigger Condition:** *netsh* command turns off the Windows firewall is detected.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Disable or Modify System Firewall
- **ATT&CK ID:** T1562.004
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=Create "process"="*\netsh.exe" command="*set*" command=
↪ "*firewall*"(( command="*opmode*" command="*disable*") OR (command="*state*"
↪ command="*off*"))
```

2.233 LP_First Time Seen Remote Named Pipe

- **Trigger Condition:** The alert rule excludes the named pipes accessible remotely and notifies on new cases. Also, it helps to detect lateral movement and remote execution using named pipes.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote Services
- **ATT&CK ID:** T1021
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5145 share_name="IPC$" -relative_target
IN ["atsvc", "samr", "lsarpc", "winreg", "netlogon", "srvsvc",
"protected_storage", "wkssvc", "browser", "netdfs", "svcctl", "spoolss",
"ntsvcs", "LSM_API_service", "HydraLsPipe", "TermSrv_API_service",
"MsFteWds"] -user IN EXCLUDED_USERS
```

2.234 LP_FirstClass Failed Login Attempt

- **Trigger Condition:** A user or a gateway attempts to log in with an incorrect password.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Exploitation for Credential Access, Exploitation for Privilege Escalation, Brute Force
- **ATT&CK ID:** T1212, T1068, T1110
- **Minimum Log Source Requirement:** Firstclass

- **Query:**

norm_id=FirstClass label=Login label=Fail

2.235 LP_FirstClass Failed Password Change Attempt

- **Trigger Condition:** A user fails to change their password.
- **ATT&CK Category:** Credential Access, Persistence
- **ATT&CK Tag:** Account Manipulation, Exploitation for Credential Access, Exploitation for Privilege Escalation
- **ATT&CK ID:** T1098, T1212, T1068
- **Minimum Log Source Requirement:** Firstclass
- **Query:**

norm_id=FirstClass label=Password label=Change label=Fail

2.236 LP_Formbook Process Creation Detected

- **Trigger Condition:** Formbook like process executions injecting code into a set of files in the System32 folder, which executes a unique command line to delete the dropper from the AppData Temp folder is detected.
- **ATT&CK Category:** Resource Development
- **ATT&CK Tag:** Malware
- **ATT&CK ID:** T1587.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process IN ["*:\Windows\System32\*.exe",
↪ "*:\Windows\SysWOW64\*.exe"] (command="*c*" command="*\Users\*" ((command=
↪ "*del*" command in ["*\AppData\Local\Temp\*", "*\Desktop\*"]) OR (command=
↪ "*type nul >*" command="*\Desktop\*")))) command="*.exe"
```

2.237 LP_FortiGate Admin Login Disable

- **Trigger Condition:** The administrator login is disabled in the system.
- **ATT&CK Category:** Impact, Credential Access, Persistence

- **ATT&CK Tag:** Account Access Removal, Account Manipulation
- **ATT&CK ID:** T1531, T1098
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti*      event_category=event      sub_category=system
message_id=32021 user=*
```

2.238 LP_FortiGate Anomaly

- **Trigger Condition:** An anomaly in the system is detected.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning
- **ATT&CK ID:** T1046
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti*      event_category=anomaly      sub_category=anomaly
log_level=alert attack=* | process geoip(source_address) as source_country |
process geoip(destination_address) as destination_country
```

2.239 LP_FortiGate Antivirus Botnet Warning

- **Trigger Condition:** A botnet warning from antivirus is detected.
- **ATT&CK Category:** Command and Control, Impact
- **ATT&CK Tag:** Proxy, Network Denial of Service
- **ATT&CK ID:** T1090, T1498
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti*      (event_category=av      OR      event_category=antivirus)
sub_category=botnet message_id=9248 | process geoip(source_address) as
source_country | process geoip(destination_address) as destination_country
```

2.240 LP_FortiGate Antivirus Scan Engine Load Failed

- **Trigger Condition:** *Antivirus Scan Engine Load Failure* is detected.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** Impair Defenses, Impair Defenses, Disable or Modify Tools
- **ATT&CK ID:** T1562, T1562.001
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti*          event_category=av          sub_category=scanerror
message_id=8974 | process geoip(source_address) as source_location |
process geoip(destination_address) as destination_location
```

2.241 LP_FortiGate Attack

- **Trigger Condition:** An attack in the system is detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Network Denial of Service
- **ATT&CK ID:** T1498
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti* attack=* | process geoip(source_address) as source_country |
process geoip(destination_address) as destination_country
```

2.242 LP_FortiGate Critical Events

- **Trigger Condition:** Critical events in the system are detected.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning
- **ATT&CK ID:** T1046
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti*          event_category=event          sub_category=system
log_level=critical
```

2.243 LP_FortiGate Data Leak Protection

- **Trigger Condition:** An attempt to data leak is detected.
- **ATT&CK Category:** Exfiltration
- **ATT&CK Tag:** Automated Exfiltration

- **ATT&CK ID:** T1020
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti* event_category=utm sub_category=dlp file=* | process
geoip(source_address) as source_country | process geoip(destination_address)
as destination_country
```

2.244 LP_FortiGate IPS Events

- **Trigger Condition:** An intrusion attempt is detected in the system.
- **ATT&CK Category:** Discovery, Defense Evasion
- **ATT&CK Tag:** Network Service Scanning, Exploitation for Defense Evasion
- **ATT&CK ID:** T1046, T1211
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti* event_category=utm sub_category=ips user=* | process
geoip(source_address) as source_country | process geoip(destination_address)
as destination_country
```

2.245 LP_FortiGate Malicious URL Attack

- **Trigger Condition:** A malicious attack in a system is detected. This alert rule is valid only for FortiOS V6.0.4.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing, Spearphishing Link
- **ATT&CK ID:** T1566, T1566.002
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti* event_category=ips sub_category="malicious-url"
message_id=16399 | process geoip(source_address) as source_country |
process geoip(destination_address) as destination_country
```

2.246 LP_FortiGate Virus

- **Trigger Condition:** A virus attack is detected.
- **ATT&CK Category:** Discovery, Defense Evasion

- **ATT&CK Tag:** Network Service Scanning, Exploitation for Defense Evasion
- **ATT&CK ID:** T1046, T1211
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti* event_category=utm sub_category=virus | process
geoip(source_address) as source_country | process geoip(destination_address)
as destination_country
```

2.247 LP_FortiGate VPN SSL User Login Failed

- **Trigger Condition:** A VPN SSL login failure is detected.
- **ATT&CK Category:** Initial Access, Credential Access
- **ATT&CK Tag:** Valid Accounts, Brute Force
- **ATT&CK ID:** T1078, T1110
- **Minimum Log Source Requirement:** Fortigate
- **Query:**

```
norm_id=Forti* event_category=event sub_category=vpn
message_id=39426 user=*
```

2.248 LP_FromBase64String Command Line Detected

- **Trigger Condition:** When the *FromBase64String* command used in a command line interface on a system is detected. This command decodes a string that was encoded using base64 encoding.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** PowerShell, Obfuscated Files or Information, Deobfuscate/Decode Files or Information
- **ATT&CK ID:** T1059.001, T1027, T1140
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create command="*FromBase64String*" -user IN EXCLUDED_
↳ USERS
```

2.249 LP_FSecure File Infection

- **Trigger Condition:** An infected file is detected.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning, File and Directory Discovery
- **ATT&CK ID:** T1046, T1083
- **Minimum Log Source Requirement:** Fsecure Gatekeeper
- **Query:**

norm_id=FSecureGatekeeper label=Infection label=File label=Attack

2.250 LP_FSecure Virus Detection

- **Trigger Condition:** Virus alert is detected while scanning.
- **ATT&CK Category:** Discovery, Defense Evasion
- **ATT&CK Tag:** Network Service Scanning, Exploitation for Defense Evasion
- **ATT&CK ID:** T1046, T1211
- **Minimum Log Source Requirement:** Fsecure
- **Query:**

norm_id=FSecure* label=Detect label=Malware malware=*

2.251 LP_Fsutil Suspicious Invocation Detected

- **Trigger Condition:** Execution of Fsutil with *Createjournal* or *Deletejournal* command line argument is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Indicator Removal
- **ATT&CK ID:** T1070
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ("process"="*\fsutil.exe" OR file="fsutil.exe") command IN [
↪ "*deletejournal*", "*createjournal*"] -user IN EXCLUDED_USERS
```

2.252 LP_GAC DLL Loaded Via Office Applications Detected

- **Trigger Condition:** GAC DLL loaded by an Office Product is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing, Spearphishing Attachment
- **ATT&CK ID:** T1566, T1566.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 "process" IN ["*\winword.exe*", ".*\powerpnt.exe*
↪", ".*\excel.exe*", ".*\outlook.exe*"] image IN ["*C:\Windows\Microsoft.
↪NET\assembly\GAC_MSIL*"] -user IN EXCLUDED_USERS
```

2.253 LP_Generic Password Dumper Activity on LSASS Detected

- **Trigger Condition:** Process handle on LSASS process with access mask is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer (event_id=4656 OR event_id="4663")
object_name="lsass.exe" access_mask IN ["*0x40", "0x1400", "0x1000",
"0x100000", "0x1410", "0x1010", "0x1438", "0x143a", "0x1418", "0x1f0fff",
"0x1f1fff", "0x1f2fff", "0x1f3fff"] -user IN EXCLUDED_USERS
```

2.254 LP_Grabbing Sensitive Hives via Reg Utility

- **Trigger Condition:** Grabbing of Sensitive Hives via Reg Utility is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** LSA Secrets, Cached Domain Credentials, Credentials in Registry

- **ATT&CK ID:** T1003.004, T1003.005, T1552.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\reg.exe" command IN ["*save*", "*export*"]
↪ command IN ["*hklm*", "*hkey_local_machine*"] command IN ["*\system", "*\sam",
↪ "*\security"] -user IN EXCLUDED_USERS
```

2.255 LP_Hacktool Ruler Detected

- **Trigger Condition:** Sensepost uses a Hacktool ruler.
- **ATT&CK Category:** Discovery, Execution
- **ATT&CK Tag:** Account Discovery, Use Alternate Authentication Material, Pass the Hash, Email Collection, Command-Line Interface + **ATT&CK ID:** T1087, T1550, T1550.002, T1114, T1059
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id IN ["4776", "4624", "4625"]
workstation="RULER" -user IN EXCLUDED_USERS
```

2.256 LP_HH Execution Detected

- **Trigger Condition:** The *hh.exe* process running on a system is detected. *HH.exe* is a legitimate process associated with the Windows HTML Help feature and is used to display compiled help files (.chm) on a system. While the execution of *hh.exe* in itself is not necessarily malicious, an adversary may use this process as part of a more significant attack. For example, they may embed malicious code in a compiled help file and use *hh.exe* to execute it on a target system. False Positive Note: Legitimate applications or system processes may use *hh.exe* to display help files, which could trigger the alert. It is essential to carefully review and investigate any instances of this alert before taking action to ensure that the detected activity is genuinely malicious.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Compiled HTML File
- **ATT&CK ID:** T1218.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

- **Query:**

```
label="Process" label=Create ("process"="hh.exe" OR file="hh.exe")
command IN [".chm*", "http", ".application", "AppDataLocal*",
"Content.Outlook*", "Downloads*", "UsersPublic*", "*Temp*"] -user IN
EXCLUDED_USERS
```

2.257 LP_Hidden Files and Directories Detected

- **Trigger Condition:** When the presence of hidden files and directories on a system is detected. Adversaries may use hidden files and directories to conceal malicious files or activities from the victim. They may also use these files to store command and control information or to persist on a system after an initial compromise. By hiding their files and directories, adversaries can make it more difficult for defenders to detect and respond to their activities.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Hide Artifacts, Hidden Files and Directories
- **ATT&CK ID:** T1564, T1564.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*attrib.exe" command IN ["*+h*", "*+s*"] -
↪ user IN EXCLUDED_USERS
```

2.258 LP_Hiding Files with Attrib Detected

- **Trigger Condition:** The use of *attrib.exe* to hide files from users is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Hide Artifacts, Hidden Files and Directories
- **ATT&CK ID:** T1564, T1564.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Create label="Process" "process"="*\attrib.exe" command = "*+h*" - (command
↪ = "*\desktop.ini*" OR (parent_process = "*\cmd.exe" command = "*+R +H +S +A \*.
↪ cui*" parent_command = "*C:\WINDOWS\system32\*.bat*"))
```

2.259 LP_IIS Native-Code Module Command Line Installation

- **Trigger Condition:** Logpoint detects suspicious IIS native-code module installations via the command line.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Server Software Component, Web Shell
- **ATT&CK ID:** T1505, T1505.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 command IN ["*\APPCMD.EXE install module /
↪name:*"] -user IN EXCLUDED_USERS
```

2.260 LP_In-memory PowerShell Detected

- **Trigger Condition:** Loading of *System.Management.Automation.dll* by other processes than PowerShell is detected. Adversaries can use this technique to evade defenses by loading the DLL and executing Powershell commands without the need of executing *powershell.exe* binary.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Image label=load image IN ["*\System.Management.Automation.Dll", "*\System.
↪Management.Automation.ni.Dll"] -"process" IN [ "*\Altaro.SubAgent.exe", "*\AppV_
↪Manage.exe", "azureadconnect.exe", "*\CcmExec.exe", "*\configsyncrun.exe",
↪"*\choco.exe", "*\ctxappvservice.exe", "*\DVLS.Console.exe", "*\edgetransport.exe",
↪"*\exsetup.exe", "*\forefrontactivedirectoryconnector.exe", "*\InstallUtil.exe",
↪"*\JenkinsOnDesktop.exe", "*\Microsoft.EnterpriseManagement.ServiceManager.UI.
↪Console.exe", "*\mmc.exe", "*\mscorsvw.exe", "*\msexchangedelivery.exe",
↪"*\msexchangefrontendtransport.exe", "*\msexchangehmworker.exe",
↪"*\msexchangesubmission.exe", "*\msiexec.exe", "*\MsiExec.exe", "*\noderunner.exe",
↪"*\NServiceBus.Host.exe", "*\NServiceBus.Host32.exe", "*\NServiceBus.Hosting.Azure.
↪HostProcess.exe", "*\OuiGui.WPF.exe", "*\powershell.exe", "*\powershell_ise.exe",
↪"*\pwsh.exe", "*\SCCMcliCtrWPF.exe", "*\ScriptEditor.exe", "*\ScriptRunner.exe",
↪"*\sdiaghost.exe", "*\servermanager.exe", "*\setup100.exe", "*\ServiceHub.
↪VSDetectedHost.exe", "*\SPCAFRClient.exe", "*\SPCAF.SettingsEditor.exe", "*\SQLPS.
↪exe", "*\telemetryservice.exe", "*\UMWorkerProcess.exe", "*\w3wp.exe",
↪"*\wsmprovhost.exe", "*\dsac.exe", "*\RemoteFXvGPUDisablement.exe",
↪"*\runscripthelper.exe", "*\SyncAppvPublishingServer.exe", "*\winrmshost.exe"
```

(continues on next page)

(continued from previous page)

2.261 LP_Indicator Blocking - Driver Unloaded

- **Trigger Condition:** Adversaries blocks indicators or events captured by sensors from being gathered and analyzed.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Indicator Blocking
- **ATT&CK ID:** T1562, T1562.006
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 (image="*fltmc.exe" or command="*fltmc*unload*  
↪") -user IN EXCLUDED_USERS
```

2.262 LP_Indicator Blocking - Sysmon Registry Edited

- **Trigger Condition:** An indicator blocking via registry editing is detected. Adversaries might block indicators or events typically captured by sensors from being gathered and analyzed to evade detection.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Indicator Blocking
- **ATT&CK ID:** T1562, T1562.006
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id IN [12,13,14] target_object in [  
↪ "*HKLM\System\CurrentControlSet\Services\SysmonDrv*",  
↪ "*HKLM\System\CurrentControlSet\Services\Sysmon*",  
↪ "*HKLM\System\CurrentControlSet\Services\Sysmon64*" ] - "process" IN ["*\Sysmon64.  
↪ exe", "*\Sysmon.exe"] -event_type=INFO -user IN EXCLUDED_USERS
```

2.263 LP_Install Root Certificate

- **Trigger Condition:** Undermine security controls by adversaries that warn users of untrusted activity or prevent the execution of untrusted programs detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Subvert Trust Controls, Install Root Certificate
- **ATT&CK ID:** T1553, T1553.004
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id IN ["12", "13", "14"] "process"!="*svchost.exe"
↪target_object IN ["*\SOFTWARE\Microsoft\EnterpriseCertificates\Root\Certificates\*",
↪"*\Microsoft\SystemCertificates\Root\Certificates\*"] -user IN EXCLUDED_USERS
```

2.264 LP_Suspicious InstallUtil Execution

- **Trigger Condition:** Use of *InstallUtil* for proxy execution of code through a trusted Windows utility is detected. *InstallUtil* is a command-line utility that allows installation and uninstallation of resources by executing specific installer components specified in .NET binaries. Typically, adversaries utilize the most commonly found way to invoke via the InstallUtil Uninstall method.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Signed Binary Proxy Execution, InstallUtil
- **ATT&CK ID:** T1218, T1218.004
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create ( "process"="*Microsoft.NET\Framework*" "process"=
↪"*\InstallUtil.exe" command="* /logfile="* command="*/LogToConsole=false*")
```

2.265 LP_Invocation of Active Directory Diagnostic Tool Detected

- **Trigger Condition:** Execution of *ntdsutil.exe* used for various attacks against the OS Credential Dumping, NTDS database (OS Credential Dumping, NTDS.DIT) is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, NTDS
- **ATT&CK ID:** T1003, T1003.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
'label="Process" label=Create "process"="*\ntdsutil.exe" -user IN EXCLUDED_USERS'
```

2.266 LP_Java Running with Remote Debugging

- **Trigger Condition:** A JAVA process running with remote debugging allowing more than just localhost to connect, is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Exploitation for Client Execution
- **ATT&CK ID:** T1203
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=create label="process" command="*transport=dt_socket,address=*" command IN [
↪ "*jre1.*", "*jdk1.*"] -command IN ["*address=127.0.0.*", "*address=localhost*"]
```

2.267 LP_Judgement Panda Exfil Activity

- **Trigger Condition:** Russian group activity as described in Global Threat Report 2019 by CrowdStrike is detected.
- **ATT&CK Category:** Credential Access

- **ATT&CK Tag:** OS Credential Dumping, Unsecured Credentials, Credentials In Files
- **ATT&CK ID:** T1552, T1552.001, T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 ((image="*\xcopy.exe" command="* /S /E /C /Q /
↪ H *") OR (image="*\adexplorer.exe" command="* -snapshot * c:\users\*")) -user IN
↪ EXCLUDED_USERS
```

2.268 LP_JunOS Attack

- **Trigger Condition:** Logpoint detects an attack pattern.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Network Denial of Service, Endpoint Denial of Service
- **ATT&CK ID:** T1498, T1499
- **Minimum Log Source Requirement:** JunOS
- **Query:**

```
norm_id=JunOS (label=Application OR label=appddos OR threat=*dos*) label=Attack
↪ (label=Warning OR label=Successful)
```

2.269 LP_JunOS Authentication Failed

- **Trigger Condition:** Failure of an authentication.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts, Brute Force
- **ATT&CK ID:** T1078, T1110
- **Minimum Log Source Requirement:** JunOS
- **Query:**

```
norm_id=JunOS label=User (label=Authentication OR Login) label=Fail
```

2.270 LP_JunOS Policy Violation

- **Trigger Condition:** A policy violation is detected.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation, Credential Access
- **ATT&CK Tag:** Bypass User Access Control, Exploitation for Credential Access, Exploitation for Privilege Escalation
- **ATT&CK ID:** T1548, T1212, T1068
- **Minimum Log Source Requirement:** JunOS
- **Query:**

```
norm_id=JunOS label=Policy (label=Violation OR label=Error)
```

2.271 LP_JunOS Security Log Clear

- **Trigger Condition:** An administrator has cleared one or more audit logs.
- **ATT&CK Category:** Defense Evasion, Impact
- **ATT&CK Tag:** Indicator Removal on Host, Data Destruction, Indicator Removal on Host, File Deletion
- **ATT&CK ID:** T1070, T1485, T1070, T1070.004
- **Minimum Log Source Requirement:** JunOS
- **Query:**

```
norm_id=JunOS label=Log label=Clear
```

2.272 LP_Kaspersky Antivirus - Outbreak Detection

- **Trigger Condition:** This alert rule is triggered whenever a threat is detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Software Discovery, Security Software Discovery

- **ATT&CK ID:** T1518, T1518.001
- **Minimum Log Source Requirement:** Kaspersky
- **Query:**

```
norm_id=KasperskyAntivirus event_type="*threat*detected" | rename wstrPar5 as virus |  
↪ chart distinct_count(win_name) as CNT by virus, event_type
```

2.273 LP_Kaspersky Antivirus - Update Fail

- **Trigger Condition:** Automatic updates are disabled, not all the components are updated, or there is a network error.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Impair Defenses, Disable or Modify Tools
- **ATT&CK ID:** T1562, T1562.001
- **Minimum Log Source Requirement:** Kaspersky
- **Query:**

```
norm_id=KasperskyAntivirus (event_type="Automatic updates are disabled" OR event_  
↪ type="Not all components were updated" OR event_type="Network update error" OR  
↪ event_type="Error updating component"  
OR description="Error downloading update files" OR description="Update files are  
↪ corrupted") | rename event_type as reason, description as reason
```

2.274 LP_Kaspersky Antivirus Extremely Out of Date Event

- **Trigger Condition:** Outdated events are detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Indicator Blocking
- **ATT&CK ID:** T1562, T1562.006
- **Minimum Log Source Requirement:** Kaspersky
- **Query:**

```
norm_id=KasperskyAntivirus event_type="*extremely out of date*"
```

2.275 LP_Kaspersky Antivirus Outbreak Detection by Source

- **Trigger Condition:** More than one source is affected by the same virus.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Software Discovery, Security Software Discovery
- **ATT&CK ID:** T1518, T1518.001
- **Minimum Log Source Requirement:** Kaspersky
- **Query:**

```
norm_id=KasperskyAntivirus "event_type"="Threats have been detected" | chart distinct_  
↪count(win_name) as DC | search DC>1
```

2.276 LP_Kaspersky Antivirus Outbreak Detection by Virus

- **Trigger Condition:** More than ten viruses are detected in the system.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Software Discovery, Security Software Discovery
- **ATT&CK ID:** T1518, T1518.001
- **Minimum Log Source Requirement:** Kaspersky
- **Query:**

```
norm_id=KasperskyAntivirus "event_type"="Threats have been detected" | chart distinct_  
↪count(wstrPar5) as DC | search DC>10
```

2.277 LP_Kaspersky Antivirus Threat Affecting Multiple Host

- **Trigger Condition:** The same threat is detected in multiple hosts.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Indicator Blocking
- **ATT&CK ID:** T1562, T1562.006
- **Minimum Log Source Requirement:** Kaspersky
- **Query:**

```
norm_id=KasperskyAntivirus event_type="*threat*detected" | chart distinct_count(win_
↪ name) as HostCount by event_type | process quantile(HostCount) | chart count() by
↪ event_type, quantile, HostCount
```

2.278 LP_Kerberoasting via PowerShell Detected

- **Trigger Condition:** Steal or forge Kerberos tickets, Kerberoasting via Command and Scripting Interpreter, and PowerShell is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Steal or Forge Kerberos Tickets, Kerberoasting
- **ATT&CK ID:** T1558, T1558.003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4103 (command_name="Invoke-Kerberoast" OR command=
↪ "Invoke-Kerberoast") -user IN EXCLUDED_USERS | rename command_name as
↪ command
```

2.279 LP_Kernel Firewall Connection Denied

- **Trigger Condition:** Ten firewall connections are denied from the same source to the same destination in a minute.
- **ATT&CK Category:** Impact, Command and Control

- **ATT&CK Tag:** Network Denial of Service, Endpoint Denial of Service, Proxy
- **ATT&CK ID:** T1498, T1499, T1090
- **Minimum Log Source Requirement:** Kernel
- **Query:**

```
[10 norm_id=Kernel label=Firewall label=Connection label=Deny having same source_
↪address, destination_address within 1 minute]
```

2.280 LP_Koadic Execution Detected

- **Trigger Condition:** The use of command line parameters associated with the Koadic hack tool during process creation events in Windows systems is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** - Windows Command Shell, Visual Basic, JavaScript
- **ATT&CK ID:** T1059.003, T1059.005, T1059.007
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\cmd.exe" command="*/q*/c*chcp*" -user[?]
↪IN EXCLUDED_USERS
```

2.281 LP_Large ICMP Traffic

- **Trigger Condition:** ICMP datagrams with a size greater than 1024 bytes are received.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning
- **ATT&CK ID:** T1046
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
((label=Receive label=Packet) or label=Illegal label=Receive label=Packet) (packet_length>
↪ 1024 or fragment_length>1024)
```

2.282 LP_Local Account Creation on Workstation Detected

- **Trigger Condition:** Creation of a local account on a domain workstation that is not Windows Domain Controller (DC).
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Create Account
- **ATT&CK ID:** T1136
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label=User label=Account label=Create -target_user="*$" target_
↪ user=* -host in WINDOWS_DC -user IN EXCLUDED_USERS
```

2.283 LP_LockCrypt Ransomware

- **Trigger Condition:** LockCrypt ransomware encrypts a file.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Disk Wipe, Disk Content Wipe, Data Encrypted for Impact, Data Destruction
- **ATT&CK ID:** T1561, T1561.001, T1486, T1485
- **Minimum Log Source Requirement:** Integrity Scanner
- **Query:**

```
norm_id=IntegrityScanner label = File label="Rename" new_file=*.lock | norm on new_
↪ file <path:.*><:'\''><EncryptedFileName:.*> | norm on file_path <:.*><:'\''>
↪ <OriginalFileName:.*> | rename hostname as host | chart count() by log_ts, host, path,
↪ OriginalFileName, EncryptedFileName order by count() desc limit 10
```

2.284 LP_Log Files Creation of Dot-Net-to-JS Detected

- **Trigger Condition:** Creation of log files of Dot-Net-to-JavaScript.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter
- **ATT&CK ID:** T1059
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 path="*UsageLogs*" file in ["*cscript.exe.log",
↪ "*wscript.exe.log", "*wmic.exe.log", "*mshta.exe.log", "*svchost.exe.log", "*regsvr32.
↪ exe.log", "*rundll32.exe.log"] -user IN EXCLUDED_USERS
```

2.285 LP_LSASS Access from Non System Account Detected

- **Trigger Condition:** Potential mimikatz-like tools accessing LSASS from non system account is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id IN ["4663", "4656"] object_type="Process" object_name=
↪ "*\\lsass.exe" -user="*$" -user IN EXCLUDED_USERS
```

2.286 LP_LSASS Memory Dump Detected

- **Trigger Condition:** Process access to lsass.exe with access rights 0x1ffff is detected.
- **ATT&CK Category:** Credential Access

- **ATT&CK Tag:** LSASS Memory
- **ATT&CK ID:** T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=10 "image"="C:\windows\system32\lsass.exe"
↪ access="0x1ffff" call_trace IN ["*dbghelp.dll*", "*dbgcore.dll*"] -user IN EXCLUDED_
↪ USERS
```

2.287 LP_LSASS Memory Dump File Creation

- **Trigger Condition:** LSASS memory dump creation using operating systems utilities is detected. *Procdump* uses process name in the output file if no name is specified.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 file="*lsass*dmp" -user IN EXCLUDED_USERS
```

2.288 LP_LSSAS Memory Dump with MiniDumpWriteDump API Detected

- **Trigger Condition:** The use of *MiniDumpWrite Dump* API for dumping *lsass.exe* memory in a stealth way is detected. Tools like *ProcessHacker* and some attacker *tradecraft* use this API found in *dbghelp.dll* or *dbgcore.dll*. For example, *SilentTrynity C2 Framework* has a module that leverages this API to dump the contents of *Lsass.exe* and transfer it over the network back to the attacker's machine.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003

- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
(norm_id=WindowsSysmon event_id=7 image IN ["*\dbgghelp.dll", "*\dbgcore.dll"]
↪ "process" IN ["*\msbuild.exe", "*\cmd.exe", "*\svchost.exe", "*\rundll32.exe",
↪ "*\powershell.exe", "*\word.exe", "*\excel.exe", "*\powerpnt.exe", "*\outlook.exe",
↪ "*\monitoringhost.exe", "*\wmic.exe", "*\msiexec.exe", "*\bash.exe", "*\wscript.exe",
↪ "*\cscript.exe", "*\mshta.exe", "*\regsvr32.exe", "*\schtasks.exe", "*\dnx.exe",
↪ "*\regsvcs.exe", "*\sc.exe", "*\scriptrunner.exe"] -"process"="*Visual Studio*") OR
↪ (event_id=7 image IN ["*\dbgghelp.dll", "*\dbgcore.dll"] Signed="FALSE" -"process"=
↪ "*Visual Studio*") -user IN EXCLUDED_USERS
```

2.289 LP_LSASS Memory Dumping Detected

- **Trigger Condition:** Creation of dump files containing the memory space of *lsass.exe*, containing sensitive credentials is detected. It identifies the use of Sysinternals *procdump.exe* to export the memory space of *lsass.exe* containing sensitive credentials.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ((command="*lsass*" command="*.dmp*" -"process"=
↪ "*\werfault.exe") OR ("process"="*\procdump*" command="*lsass*")) -user IN
↪ EXCLUDED_USERS
```

2.290 LP_Macro file Creation Detected

- **Trigger Condition:** Creation of a macro file is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, Visual Basic
- **ATT&CK ID:** T1059, T1059.005
- **Minimum Log Source Requirement:** Windows Sysmon

- **Query:**

```
norm_id=WindowsSysmon event_id=11 file in ["*.docm", "*.pptm", "*.xism", "*.xlm", "*.dotm", "*.xltm", "*.potm", "*.ppsm", "*.sldm", "*.xlam", "*.xla"]
```

2.291 LP_Malicious Base64 Encoded PowerShell Keywords in Command Lines Detected

- **Trigger Condition:** When base64 encoded strings are used in hidden malicious Command and Scripting Interpreter, PowerShell command lines. Adversaries hides their activities by encoding commands to bypass detection with this technique.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
norm_id=WindowsSysmon event_id=1 image="*\powershell.exe" command IN ["*  
↳ hidden ", "*AGkAdABzAGEAZABtAGkAbgAgAC8AdABYAGEAbgBzAGYAZQByA*",  
↳ "*aXRzYWRtaW4gL3RyYW5zZmVy*",  
↳ "*IAaQB0AHMAYQBkAG0AaQBuACAALwB0AHIAyQB0AHMAZgBIAHIA*",  
↳ "*JpdHNhZG1pbjAvdHJhbnNmZX*",  
↳ "*YgBpAHQAcbBhAGQAbQBpAG4AIAAvAHQAcbBhAG4AcwBmAGUAcg*",  
↳ "*Yml0c2FkbWlucC90cmFuc2Zlc*",  
↳ "*AGMAaAB1AG4AawBfAHMAaQB6AGUA*", "*JABjAGgAdQB0AGsAXwBzAGkAegBIA*",  
↳ ", "*JGNodW5rX3Npem*", "*QAYwBoAHUAbgBrAF8AcwBpAHoAZQ*",  
↳ "*RjaHVua19zaXpl*", "*Y2h1bmtfc2l6Z*",  
↳ "*AE8ALgBDAG8AbQBwAHIAZQBzAHMAaQBvAG4A*",  
↳ "*kATwAuAEMAbwBtAHAACgBIAHMAcwbBpAG8Abg*", "*IPLkNvbXByZXNzaW9u*",  
↳ "*SQBPAC4AQwBvAG0AcABYAGUAcwBzAGkAbwBuA*", "*SU8uQ29tcHJlc3Npb2*",  
↳ "*Ty5Db21wcmVzc2lvb*", "*AE8ALgBNAGUAbQBvAHIAeQBTAHQAcbBIAgeAbQ*",  
↳ "*kATwAuAE0AZQBtAG8AcgB5AFMAcABYAGUAYQBtA*",  
↳ "*IPLk1lbW9yeVN0cmVhb*", "*SQBPAC4ATQBIAg0AbwByAHkAUwB0AHIAZQBhAG0A*",  
↳ "*SU8uTWVtb3J5U3RyZWZt*", "*Ty5NZW1vcnltDHIY*",  
↳ "*4ARwBIAHQAQwBoAHUAbgBrA*", "*5HZXRDaHVua*",  
↳ "*AEcAZQB0AEMAaAB1AG4Aaw*",  
↳ "*LgBHAGUAdABDAGgAdQB0AGsA*", "*LkdldENodW5r*", "*R2V0Q2h1bm*",  
↳ "*AEgAUgBFAEEARABfAEkATgBGAE8ANgA0A*",  
↳ "*QASABSAEUAAQBEAF8ASQBOAEYATwA2ADQA*", "*RIUkVBRf9JTkZPNj*",  
↳ "*SFJFQURfSU5GTzY0*", "*VABIAFIARQBBAEQAXwBJAE4ARgBPADYANA*",  
↳ "*VEhSRUFEX0lORK82N*"]
```

(continues on next page)

(continued from previous page)

```

"*AHIAZQBhAHQAZQBSAGUAbQBvAHQAZQBUAGgAcgBIAGEAZA*",
↪ "*cmVhdGVSZW1vdGVUaHJlYW*\"",
↪ "*MAcgBIAGEAdABIAFIAZQBtAG8AdABIAFQAaABYAGUAYQBkA*",
↪ "*NyZWF0ZVJlbW90ZVRocmVhZ*", "*Q3JlYXRlUmVtb3RlVGhyZWFK*",
"*QwByAGUAYQB0AGUAUgBIAG0AbwB0AGUAVABoAHIAZQBhAGQA*",
↪ "*0AZQBtAG0AbwB2AGUA*", "*1lbW1vdm*", "*AGUAbQBtAG8AdgBIA*",
↪ "*bQBIAG0AbQBvAHYAZQ*", "*bWVtbW92Z*", "*ZW1tb3Zl*"] -user IN EXCLUDED_
↪ USERS

```

2.292 LP_Malicious File Execution Detected

- **Trigger Condition:** Execution of a suspicious file by *wscript* and *cscript*.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter
- **ATT&CK ID:** T1059
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```

norm_id=WindowsSysmon event_id=1 image IN ["*\\wscript.exe", "*\\cscript.exe"]?
↪ command IN ["*.jse", "*.vbe", "*.js", "*.vba"] -user IN EXCLUDED_USERS

```

2.293 LP_Malicious Service Installations Detected

- **Trigger Condition:** Malicious service installs appearing in lateral movement, credential dumping, and other suspicious activity are detected.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Credential Dumping, System Services, Service Execution, New Service
- **ATT&CK ID:** T1003, T1569, T1569.002, T1543
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=7045 service in ["*\\PAExec*", "mssecsvc2.0", "*net user*",
↪ "WCESERVICE", "WCE SERVICE", "winexesvc.exe*", "*\\DumpSvc.exe", "pwdump*",
↪ "gsecdump*", "cachedump*"] -user IN EXCLUDED_USERS
```

2.294 LP_Malware Shellcode in Verclsid Target Process

- **Trigger Condition:** A process accessing `verclsid.exe` that injects shellcode from a Microsoft Office application or VBA macro is detected.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Process Injection, Verclsid
- **ATT&CK ID:** T1055, T1218.012
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=10 image="*\\verclsid.exe" access="0x1FFFFFF" (call_
↪ trace="*|UNKNOWN(*VBE7.DLL*" OR ("process"="*\\Microsoft Office\\*" call_trace=
↪ "*|UNKNOWN*")) -user IN EXCLUDED_USERS
```

2.295 LP_Malware Threat Connection from Malicious Source

- **Trigger Condition:** Inbound connection from malicious sources is detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
(source_address=* OR destination_address=*) source_address in MALWARE_IP?
↪ destination_address IN HOMENET | process geoip(source_address) as country
```

2.296 LP_Malware Threat Connection to Malicious Destination

- **Trigger Condition:** Hosts make an outbound connection to malicious sources.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
(source_address=* OR destination_address=*) destination_address in MALWARE_IP
↪ source_address IN HOMENET | process geoip(destination_address) as country
```

2.297 LP_Malware Threat Connection to Malicious URLs

- **Trigger Condition:** A connection to a malicious URL is detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
url=* source_address=* | process domain(url) as domain | search domain in MALWARE_URL
```

2.298 LP_Malware Threat Emails Sent to Attacker

- **Trigger Condition:** Email is sent to malware listed emails.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy, Exfiltration Over C2 Channel, Automated Exfiltration, Email Collection
- **ATT&CK ID:** T1090, T1041, T1020, T1114

- **Minimum Log Source Requirement:** Mail Server
- **Query:**

```
(receiver in MALWARE_EMAILS OR sender in MALWARE_EMAILS) sender=* receiver=?
↪ (host=* OR source_host=*) | rename source_host as host
```

2.299 LP_Meltdown and Spectre Vulnerabilities

- **Trigger Condition:** Meltdown and Spectre vulnerabilities are detected in the system.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Software Discovery, Security Software Discovery
- **ATT&CK ID:** T1518, T1518.001
- **Minimum Log Source Requirement:** Vulnerability Management
- **Query:**

```
title=*spectre* or title=*meltdown* source_address=* | rename host as source_address ?
↪ chart count() by source_address, severity, cve_id, solution order by count() desc
```

2.300 LP_Meterpreter or Cobalt Strike Getsystem Service Start Detected

- **Trigger Condition:** The use of getsystem Meterpreter or Cobalt Strike command to obtain SYSTEM privileges by detecting a specific service starting.
- **ATT&CK Category:** Privilege Escalation, Defense Evasion
- **ATT&CK Tag:** Access Token Manipulation
- **ATT&CK ID:** T1134
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process="*\services.exe" command IN ['*cmd* /c *?
↪ echo *\pipe\*', '%COMPSEC%' /c * echo *\pipe\*', '*rundll32*.dll,a*/p:*'] -command=
↪ "*MpCmdRun*" -user IN EXCLUDED_USERS
```

2.301 LP_Microsoft ActiveX Control Code Execution Vulnerability Detected

- **Trigger Condition:** Remote code execution in Microsoft ActiveX Control (CVE-2012-0158) is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Exploitation for Client Execution
- **ATT&CK ID:** T1203
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=Key label="Map" label=Registry target_object=
↳ '*Software\Microsoft\Office*Resiliency' -user IN EXCLUDED_USERS
```

2.302 LP_Microsoft DotNET Framework Remote Code Execution Detected

- **Trigger Condition:** Remote code execution vulnerability (CVE-2017-8759) in Microsoft .NET Framework is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** User Execution, Malicious File
- **ATT&CK ID:** T1204, T1204.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 parent_process='*WINWORD.exe' parent_
↳ command='*.rtf*' "process"='*\csc.exe' -user IN EXCLUDED_USERS
```

2.303 LP_Microsoft Office Memory Corruption Vulnerability CVE-2015-1641 Detected

- **Trigger Condition:** The exploitation of memory corruption vulnerability (CVE-2015-1641) in Microsoft Office is detected.

- **ATT&CK Category:** Execution
- **ATT&CK Tag:** User Execution
- **ATT&CK ID:** T1204
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=Image label=Load "process" IN ['*WINWORD.exe',
↪ '*EXCEL.exe'] image='*MSVCR71.DLL' -user IN EXCLUDED_USERS
```

2.304 LP_Microsoft Office Memory Corruption Vulnerability CVE-2017-0199 Detected

- **Trigger Condition:** The exploitation of memory corruption vulnerability (CVE-2017-0199) in Microsoft Office is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** User Execution
- **ATT&CK ID:** T1204
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=Network label=Connection image='*WINWORD.exe'
↪ destination_address IN MOST_EXPLOITABLE_IPS -user IN EXCLUDED_USERS
```

2.305 LP_Microsoft Office Memory Corruption Vulnerability CVE-2017-11882 Detected

- **Trigger Condition:** The exploitation of memory corruption vulnerability (CVE-2017-11882) in Microsoft Office is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** User Execution
- **ATT&CK ID:** T1204
- **Minimum Log Source Requirement:** Windows Sysmon

- **Query:**

```
norm_id=WindowsSysmon label="Process" label=Create parent_image='*EQNEDT32.EXE'
↪ 'parent_command='*EQNEDT32.EXE*-Embedding' image='*.exe'-user IN EXCLUDED_
↪ USERS
```

2.306 LP_Mimikatz Command Line Detected

- **Trigger Condition:** *mimikatz* command line arguments are detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, LSASS Memory, Security Account Manager, LSA Secrets, Cached Domain Credentials, DCSync
- **ATT&CK ID:** T1003, T1003.001, T1003.002, T1003.003, T1003.004, T1003.005, T1003.006
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command IN ["*DumpCreds*", "*mimikatz*", "*::aadcookie*",
↪ ", "*::detours*", "*::memssp*", "*::mflt*", "*::ncroutemon*", "*::ngcsign*",
↪ "*::printrnightmare*", "*::skeleton*", "*::preshutdown*", "*::mstsc*", "*::multirdp*",
↪ "*rpc::*", "*token::*", "*crypto::*", "*dpapi::*", "*sekurlsa::*", "*kerberos::*",
↪ "*lsadump::*", "*privilege::*", "*process::*", "*vault::*", "*crypto::*", "*misc::*", "*event::*",
↪ ", "*IIS::AppHost*", "*net::*", "*sid::*", "*standard::*", "*vault::*"]
```

2.307 LP_Mitre Discovery Using Query Registry Detected

- **Trigger Condition:** Discovery uses the attack technique Query Registry.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Query Registry
- **ATT&CK ID:** T1012
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label="Process" label=Create commandline="*reg query*" -user IN EXCLUDED_USERS | process eval("attack_class='Discovery'") | process eval("technique='Query Registry'") | rename commandline as command | chart count() by user, host, domain, log_ts, command, attack_class, technique order by count() desc limit 10
```

2.308 LP_Mitre Discovery Using System Network Configuration Discovery Detected

- **Trigger Condition:** Discovery uses the attack technique System Network Configuration Discovery.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** System Network Configuration Discovery
- **ATT&CK ID:** T1016
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label="Process" label=Create (commandline="*ipconfig.exe*" OR commandline="*route.exe*" OR commandline="*netsh advfirewall*" OR commandline="*arp.exe*" OR commandline="*nbtstat.exe*" OR commandline="*netsh.exe*interface show" OR commandline="*net*config") -user IN EXCLUDED_USERS | process eval("attack_class='Discovery'") | process eval("technique='System Network Configuration Discovery'") | rename commandline as command | chart count() by user, host, domain, log_ts, command, attack_class, technique order by count() desc limit 10
```

2.309 LP_Mitre Persistence via Winlogon Helper DLL Detected

- **Trigger Condition:** Modifications in Winlogon registry keys are detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Boot or Logon Autostart Execution, Winlogon Helper DLL
- **ATT&CK ID:** T1547, T1547.004
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4657 object=Winlogon event_category=Registry path=
↳ "*Windows NT\CurrentVersion*" new_value=* -user IN EXCLUDED_USERS
```

2.310 LP_MMC Spawning Windows Shell Detected

- **Trigger Condition:** Windows command line executable starting from MMC is detected.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Distributed Component Object Model
- **ATT&CK ID:** T1021.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label= "Process" label=Create parent_process="*\mmc.exe" ("process" IN ["*\cmd.exe",
↳ "*\powershell.exe", "*\pwsh.exe", "*\wscript.exe", "*\cscript.exe", "*\sh.exe", "*\bash.
↳ exe", "*\reg.exe", "*\regsvr32.exe"] OR "process"="*\BITSADMIN*") -user IN
↳ EXCLUDED_USERS
```

2.311 LP_Most Exploitable Vulnerabilities Detected

- **Trigger Condition:** The most exploitable vulnerabilities from 2015 are detected in a network. For this alert to work, MOST_EXPLOITABLE_CVE must be updated with the list of exploitable vulnerabilities.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning, Software Discovery, Security Software Discovery
- **ATT&CK ID:** T1046, T1518, T1518.001
- **Minimum Log Source Requirement:** Vulnerability Management
- **Query:**

```
norm_id=VulnerabilityManagement cve_id IN MOST_EXPLOITABLE_CVE
```

2.312 LP_Mshta JavaScript Execution Detected

- **Trigger Condition:** The *mshta.exe* command is detected.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** Signed Binary Proxy Execution, Mshta
- **ATT&CK ID:** T1218, T1218.005
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 image="*\mshta.exe" command="*javascript*" -
↪ user IN EXCLUDED_USERS
```

2.313 LP_MSHTA Spawning Windows Shell Detected

- **Trigger Condition:** Windows command line executable started from MSHTA is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Mshta
- **ATT&CK ID:** T1218.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create parent_process="*\mshta.exe" "process" IN ["*\cmd.exe",
↪ "*\powershell.exe", "*\wscript.exe", "*\cscript.exe", "*\sh.exe", "*\bash.exe", "*\reg.
↪ exe", "*\regsvr32.exe", "*\bitsadmin.exe"]
```

2.314 LP_MSHTA Suspicious Execution Detected

- **Trigger Condition:** *mshta.exe* suspicious execution patterns sometimes involving file polyglotism is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Deobfuscate/Decode Files or Information

- **ATT&CK ID:** T1140
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
event_id=1 image="*\mshta.exe" command IN ["*vbscript*", "*.jpg*", "*.png*", "*.lnk*",
↪ "*.xls*", "*.doc*", "*.zip*"] -user IN EXCLUDED_USERS
```

2.315 LP_MsiExec Web Install Detected

- **Trigger Condition:** When the *msiexec* process starts with the web address as a parameter is detected.
- **ATT&CK Category:** Defense Evasion, Command and Control
- **ATT&CK Tag:** Ingress Tool Transfer, Msiexec
- **ATT&CK ID:** T1105, T1218.007
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=create label="process" command="*msiexec*" command="*://*"
```

2.316 LP_MSTSC Shadowing Detected

- **Trigger Condition:** Hijacking of Remote Desktop Protocol (RDP) session using Microsoft Terminal Services Client (MSTSC) shadowing is detected.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote Service Session Hijacking, RDP Hijacking
- **ATT&CK ID:** T1563, T1563.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Create label="Process" command="*noconsentprompt*" command="*shadow:*" -
↪ user IN EXCLUDED_USERS
```

2.317 LP_Multiple Failed Login Followed by Successful Login Followed by Logoff

- **Trigger Condition:** Multiple failed login attempts are followed by successful login, and then by log off from the same user are detected.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access, Credential Access
- **ATT&CK Tag:** Valid Accounts, Brute Force
- **ATT&CK ID:** T1078, T1110
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
[incident_name="Multiple Failed User Login Followed by Successful Login" incident_
↪ user=*] as FirstAlert followed by [norm_id=WinServer* label=User label=Logoff user=* -
↪ user IN EXCLUDED_USERS] as Logoff on FirstAlert.incident_user=Logoff.user | rename
↪ Logoff.user as User, FirstAlert.incident_address as SourceAddress
```

2.318 LP_Named Pipe added to Null Session Detected

- **Trigger Condition:** A new value set for the NullSessionPipe registry key is detected.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote Services
- **ATT&CK ID:** T1021
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 "process"="*\reg.exe" target_object=
↪ "\lanmanserver*NullSessionPipes" -user IN EXCLUDED_USERS
```

2.319 LP_Narrators Feedback-Hub Persistence Detected

- **Trigger Condition:** Abusing Windows 10 Narrator's Feedback-Hub is detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Boot or Logon Autostart Execution, Registry Run Keys/Startup Folder
- **ATT&CK ID:** T1547, T1547.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
(event_id=12 event_type="DeleteValue" target_object=
↪ "*\AppXypsaf9f1qserqevf0sws76dx4k9a5206\Shell\open\command\DelegateExecute")?
↪ OR (event_id=13 target_object=
↪ "*\AppXypsaf9f1qserqevf0sws76dx4k9a5206\Shell\open\command\(\Default)")
```

2.320 LP_Net exe Execution Detected

- **Trigger Condition:** The execution of Net.exe, which can be suspicious or benign, is detected.
- **ATT&CK Category:** Lateral Movement, Discovery, Defense Evasion
- **ATT&CK Tag:** Obfuscated Files or Information, System Network Connections Discovery, Remote Services, Network Share Discovery
- **ATT&CK ID:** T1027, T1049, T1021, T1135
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 image IN ["*\net.exe", "*\net1.exe"] command IN [
↪ "* group*", "* localgroup*", "* user*", "* view*", "* share", "* accounts*", "* use*", "*?
↪ stop *"] -user IN EXCLUDED_USERS
```

2.321 LP_NetNTLM Downgrade Attack Detected

- **Trigger Condition:** When post-exploitation using NetNTLM downgrade attacks are detected. NetNTLM is a proprietary authentication protocol used by Microsoft Windows. Adversaries may use a downgrade attack to force the use of a weaker version of the protocol, allowing them to intercept and crack the password hashes used for authentication. This can allow the adversary to gain unauthorized access to the system.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Disable or Modify Tools, Modify Registry
- **ATT&CK ID:** T1562, T1562.001, T1112
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
(event_id=13 target_object IN ["*SYSTEM*ControlSet*\Control\Lsa\lmcompatibilitylevel",
↪ "*SYSTEM*ControlSet*\Control\Lsa\NtLmMinClientSec",
↪ "*SYSTEM*ControlSet*\Control\Lsa\RestrictSendingNTLMTraffic"]) OR (norm_
↪ id=WinServer event_id=4657 object_name=
↪ "\REGISTRY\MACHINE\SYSTEM*ControlSet*\Control\Lsa" object_value IN [
↪ "LmCompatibilityLevel", "NtLmMinClientSec", "RestrictSendingNTLMTraffic"]) -user IN EXCLUDED_USERS
```

2.322 LP_Netsh Port Forwarding Detected

- **Trigger Condition:** The *netsh* command used in the configuration of port forwarding is detected. Port forwarding is a pivoting technique that redirects traffic from one port to another.
- **ATT&CK Category:** Lateral Movement, Command and Control
- **ATT&CK Tag:** Proxy, Exploitation of Remote Services
- **ATT&CK ID:** T1090, T1210
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="create" label="process" "process"="*\netsh.exe" command in ["*interface
↪ portproxy add v4tov4 *", "*i p a v*"] -user IN EXCLUDED_USERS
```

2.323 LP_Netsh RDP Port Forwarding Detected

- **Trigger Condition:** The *netsh* command used in the configuration of port forwarding of port 3389 for RDP is detected.
- **ATT&CK Category:** Lateral Movement, Command and Control
- **ATT&CK Tag:** Remote Services, Proxy
- **ATT&CK ID:** T1021, T1090
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command IN ["netsh i* p*=3389 c*"] -user IN EXCLUDED_
↳ USERS
```

2.324 LP_Network Share Connection Removed

- **Trigger Condition:** The removal of a share connection is detected. Adversaries removes share connections that are no longer useful to clean traces of their operation.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Network Share Connection Removal
- **ATT&CK ID:** T1070.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="create" label="process" "process" in ["*\\net.exe", "*\\net1.exe"] command =
↳ "*share*" command="*delete*"
```

2.325 LP_Network Share Discovery

- **Trigger Condition:** The net utility used to query a system for available shared drives using net view or net share command is detected. Adversaries look for folders and drive shared on remote systems to identify sources of information to gather as a precursor for collecting and identifying potential systems of interest for Lateral Movement.

- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Share Discovery
- **ATT&CK ID:** T1135
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=create label="process" ("process" in ["*net.exe", "*net1.exe"] command IN ["*view*  
↪", "*share*"]) OR (command="*get-smbshare -Name*")
```

2.326 LP_Network Sniffing Detected

- **Trigger Condition:** When the execution of network sniffing tools is detected. Adversaries may use network sniffing to intercept sensitive information, such as passwords or confidential data, as it is transmitted over the network. They may also use sniffing to gain visibility into network traffic and identify vulnerabilities or weaknesses.
- **ATT&CK Category:** Credential Access, Discovery
- **ATT&CK Tag:** Network Sniffing
- **ATT&CK ID:** T1040
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
'label="Process" label=create "process" IN ["*tshark.exe", "*windump.exe", "*logman.exe  
↪", "*tcpdump.exe", "*wprui.exe", "*wpr.exe"] -user IN EXCLUDED_USERS'
```

2.327 LP_New Firewall Port Opening Detected

- **Trigger Condition:** An opening of a new port in a firewall is detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Non-Standard Port
- **ATT&CK ID:** T1571
- **Minimum Log Source Requirement:** Windows

- **Query:**

```
norm_id=WinServer event_id=4657 object=FirewallRules event_category=Registry object_
↪ name="*ControlSet*FirewallPolicy\FirewallRules" new_value=* -user IN EXCLUDED_
↪ USERS | norm on new_value <:all>Action=<action:word><:all>Active=<active:word>
↪ <:all>Dir=<direction:word><:all>Protocol=<proto:int><:all>Port=<port:int><:all>
↪ Name=<rule:string><:'\"> | process eval("protocol = if(proto == 6) {return 'TCP'} else
↪ {return 'UDP'}")
```

2.328 LP_New RUN Key Pointing to Suspicious Folder Detected

- **Trigger Condition:** A new suspicious RUN key element pointing to an executable in a folder is detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Boot or Logon Autostart Execution, Registry Run Keys/Startup Folder
- **ATT&CK ID:** T1547, T1547.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
event_id=13 target_object IN ["*\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\Run\\*",
↪ "*\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\RunOnce\\*"] detail IN [
↪ "*C:\\Windows\\Temp\\*", "*\\AppData\\*", "%AppData%\\*", "*C:\\$Recycle.bin\\*",
↪ "*C:\\Temp\\*", "*C:\\Users\\Public\\*", "%Public%\\*", "*C:\\Users\\Default\\*",
↪ "*C:\\Users\\Desktop\\*", "wscript*", "cscript*"] -detail IN [
↪ "*\\AppData\\Local\\Microsoft\\OneDrive\\*"] -user IN EXCLUDED_USERS
```

2.329 LP_New Service Creation

- **Trigger Condition:** The creation of a new service is detected. Windows Services can allow the creation and management of long-running processes. It can start automatically and keep running for a long time after the user logs off. Adversaries might leverage this functionality to maintain persistence and escalate their privilege.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Create or Modify System Process, Windows Service

- **ATT&CK ID:** T1543, T1543.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" "process" IN ["*sc.exe", "*powershell.exe", "*cmd.exe"]
↪ command IN [ "*Get-WmiObject*Win32_Service*create*", "*create*binPath=*", "*New-Service*-BinaryPathName*", "*powershell*", "*mshta*", "*wscript*", "*cscript*",
↪ "*svchost*", "*dllhost*", "*cmd *", "*cmd.exe /c*", "*cmd.exe /k*", "*cmd.exe /r*",
↪ "*rundll32*", "*C:\Users\Public*", "*\Downloads\*", "*\Desktop\*",
↪ "*\Microsoft\Windows\Start Menu\Programs\Startup\*", "*C:\Windows\TEMP\*",
↪ "*\AppData\Local\Temp*" ] -user IN EXCLUDED_USERS
```

2.330 LP_Non Interactive PowerShell Execution

- **Trigger Condition:** Non-interactive Command and Scripting Interpreter and PowerShell activity by looking at *powershell.exe* with no *explorer.exe* as a parent is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
'label="Create" label="Process" ("Process" IN ["*\powershell.exe", "*\pwsh.exe"] OR
↪ (file IN ["PowerShell.EXE", "pwsh.dll"])) -(parent_process IN ["*C:\Windows\explorer.exe",
↪ "*C:\Windows\System32\CompatTelRunner.exe", "*C:\Windows\SysWOW64\explorer.exe",
↪ "C:\$WINDOWS.~BT\Sources\SetupHost.exe"]) -(parent_process="C:\Users\*
↪ "parent_process="*\AppData\Local\Programs\Microsoft VS Code\Code.exe" parent_
↪ command="* --ms-enable-electron-run-as-node *") -user IN EXCLUDED_USERS'
```

2.331 LP_NoPowerShell Tool Activity Detected

- **Trigger Condition:** Execution of NoCommand and Scripting Interpreter and PowerShell tool.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Shared Modules

- **ATT&CK ID:** T1129
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 -file in ["*cscript.exe.log", "*wscript.exe.log",
↪ "*wmic.exe.log", "*mshta.exe.log", "*svchost.exe.log", "*regsvr32.exe.log", "*rundll32.
↪ exe.log"] file="*.exe.log" -user IN EXCLUDED_USERS
```

2.332 LP_NotPetya Ransomware Activity Detected

- **Trigger Condition:** NotPetya ransomware activity in which the extracted passwords are passed back to the main module via named pipe is detected. The file system journal of drive C is deleted, and window event logs are cleared using wevtutil.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Signed Binary Proxy Execution, Rundll32, Indicator Removal on Host
- **ATT&CK ID:** T1218, T1218.011, T1070
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 (command="*\AppData\Local\Temp\*\.pipe\*"
↪ OR (image="*\rundll32.exe" command="*.dat, #1")) -user IN EXCLUDED_USERS
```

2.333 LP_Office365 Multiple Failed Login from Different Host by Single User

- **Trigger Condition:** A user attempts multiple failed logins from distinct hosts with a count greater than one.
- **ATT&CK Category:** Credential Access, Persistence, Defense Evasion, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Brute Force, Valid Accounts
- **ATT&CK ID:** T1110, T1078
- **Minimum Log Source Requirement:** Office365

- **Query:**

```
norm_id="Office365" source_address=* label=User label=Login label=Fail | chart distinct_
↪count(source_address) as DC by user | search DC>1
```

2.334 LP_Office365 Multiple Failed Login from Same Host

- **Trigger Condition:** Multiple failed logins from the same host with a count greater than five.
- **ATT&CK Category:** Credential Access, Persistence, Defense Evasion, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Brute Force, Valid Accounts
- **ATT&CK ID:** T1110, T1078
- **Minimum Log Source Requirement:** Office365
- **Query:**

```
norm_id="Office365" source_address=* label=User label=Login label=Fail | chart count(?)
↪as "Cnt" by user, source_address | search Cnt > 5
```

2.335 LP_Office365 Multiple Successful Login from Different Country by Single User

- **Trigger Condition:** A user attempts multiple failed logins from different countries with a count greater than one.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts
- **ATT&CK ID:** T1078
- **Minimum Log Source Requirement:** Office365
- **Query:**

```
norm_id="Office365" label=User label=login label=Successful source_address=* (?)
↪process geoup(source_address) as country | chart distinct_count(country) as DC by user (?)
↪search DC >1
```

2.336 LP_Office365 Multiple Successful Login From Different Host by Single User

- **Trigger Condition:** A user attempts multiple successful logins from a distinct host with a count greater than one.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts
- **ATT&CK ID:** T1078
- **Minimum Log Source Requirement:** Office365
- **Query:**

```
norm_id="Office365" label=User label=login label=Successful source_address=* | chart?
↪ distinct_count(source_address) as DC by user | search DC > 1
```

2.337 LP_Office365 Password Resets

- **Trigger Condition:** A user's password is reset.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Account Manipulation
- **ATT&CK ID:** T1098
- **Minimum Log Source Requirement:** Office365
- **Query:**

```
norm_id="Office365" label=Password label=Reset user=*
```

2.338 LP_OpenWith Execution of Specified Binary Detected

- **Trigger Condition:** The execution of `OpenWith.exe` with command line argument `"-c"` or `"/c"` is detected.
- **ATT&CK Category:** -

- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Process" label=Create "process"="*\OpenWith.exe" command IN ["*/c*", "*-c*"] -
↪ user IN EXCLUDED_USERS
```

2.339 LP_Password Change on DSRM Account Detected

- **Trigger Condition:** Password change in Directory Service Restore Mode (DSRM) account is detected.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Account Manipulation
- **ATT&CK ID:** T1098
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4794 -user IN EXCLUDED_USERS
```

2.340 LP_Password Dumper Remote Thread in LSASS

- **Trigger Condition:** Password dumper activity by monitoring remote thread creation event ID 8 in combination with the lsass.exe process as *TargetImage* is detected. The process in the field *Process* is a malicious program and a single execution can lead to hundreds of events.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, LSASS Memory
- **ATT&CK ID:** T1003, T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
'label="Remote" label="Thread" label="Create" image="*\lsass.exe" start_module="" -
↪user IN EXCLUDED_USERS'
```

2.341 LP_Password Spraying Attack Detected

- **Trigger Condition:** Multiple login fail attempts on a host by various users are detected. Adversaries can use a list of commonly used passwords against different versions to attempt to obtain valid account credentials.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Password Spraying
- **ATT&CK ID:** T1110.003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4625 | chart distinct_count(user) as UserCount, distinct_
↪list(user) as Users by host | search UserCount > 5
```

2.342 LP_Persistence and Execution at Scale via GPO Scheduled Task

- **Trigger Condition:** Lateral movement using GPO scheduled task used to deploy ransomware at scale is detected.
- **ATT&CK Category:** Persistence, Lateral Movement, Execution, Privilege Escalation
- **ATT&CK Tag:** Scheduled Task/Job, Scheduled Task
- **ATT&CK ID:** T1053, T1053.005
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5145 share_name="\\*\\SYSVOL" relative_target=
↪"*ScheduledTasks.xml" access="*WriteData*" -user IN EXCLUDED_USERS
```

2.343 LP_Possible Access to ADMIN Share

- **Trigger Condition:** Access to \$ADMIN share is detected, which may help to detect lateral movement attempts. Since Windows Admin Share activity is so common, it provides adversaries with a powerful, discreet way to move laterally within an environment.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote Services
- **ATT&CK ID:** T1021
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5140 share_name="Admin$" -user="*$" -user IN EXCLUDED_USERS
```

2.344 LP_Possible Account Misuse-Privilege Escalation

- **Trigger Condition:** The non-admin users are assigned privileged access. The event maps to event ID of 4648 and 4672 in Windows.
- **ATT&CK Category:** Privilege Escalation, Persistence, Defense Evasion
- **ATT&CK Tag:** Account Manipulation, Abuse Elevation Control Mechanism, Bypass User Account Control
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
((label=Privilege label=Assign) or (label=Login label=Explicit label=Credential) user=* - user in ADMINS) OR (label=User label=Add label=Group user=* group=*admin*)
```

2.345 LP_Possible Applocker Bypass Detected

- **Trigger Condition:** The execution of executables like msdt, installutil, regsvcs, regasm or msbuild.ieexec is detected, which is used to bypass Applocker whitelisting is detected.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Signed Binary Proxy Execution, Mshta, InstallUtil, Regsvcs/Regasm, Trusted Developer Utilities, MSBuild
- **ATT&CK ID:** T1218, T1218.004, T1218.009, T1127, T1218.005, T1127.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" command IN ["*\msdt.exe*", "*\installutil.exe*",
↪ "*\regsvcs.exe*", "*\regasm.exe*", "*\msbuild.exe*", "*\ieexec.exe*"] -user IN
↪ EXCLUDED_USERS
```

2.346 LP_Possible Bitsadmin Download Detected

- **Trigger Condition:** The use of *bitsadmin* downloading a file is detected.
- **ATT&CK Category:** Defense Evasion, Persistence
- **ATT&CK Tag:** BITS Jobs
- **ATT&CK ID:** T1197
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
'label="Process" label=Create ("process"="*\bitsadmin.exe" (command IN ["*/create *", "*/
↪ addfile *"] command="*http*")OR (7104command="*/transfer *")) OR (command="*copy
↪ bitsadmin.exe*") -user IN EXCLUDED_USERS'
```

2.347 LP_Possible Botnet Connection-DNS Server Modified

- **Trigger Condition:** An unauthorized default Application Layer Protocol and DNS server modification are detected in Unix or Windows Server.
- **ATT&CK Category:** Impact, Command and Control, Defense Evasion
- **ATT&CK Tag:** Network Denial of Service, Proxy, Exploitation for Defense Evasion
- **ATT&CK ID:** T1498, T1090, T1211

- **Minimum Log Source Requirement:** Windows
- **Query:**

```
((norm_id=Unix action="RUN" (file="etc/resolv.conf" or file="*\etc\host")) or (norm_
↪ id=WinServer* (label=File (label=Write or label=Modify) path=
↪ "C:\Windows\System32\Drivers\etc" object="hosts") or (label=DNS label=Update
↪ (label=Successful or label=Request OR label=Fail)) (host=* or source_address=*)) -user
↪ IN EXCLUDED_USERS
```

2.348 LP_Possible Botnet Connection-IRC Port

- **Trigger Condition:** The connection through the IRC port is detected. For this alert to work, you must update the list IRC_PORTS, including commonly used ports 6660 to 6669 and 6700.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Firewall, IDS/IPS, Webserver
- **Query:**

```
source_address=* destination_address=* destination_port in IRC_PORTS
```

2.349 LP_Possible Botnet Connection-Outbound DDOS

- **Trigger Condition:** Multiple hosts connecting to the same destination address is detected.
- **ATT&CK Category:** Impact, Command and Control, Defense Evasion
- **ATT&CK Tag:** Network Denial of Service, Proxy, Exploitation for Defense Evasion
- **ATT&CK ID:** T1498, T1090, T1211
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Connection source_address in HOMENET destination_address=* | chart distinct_
↪ count(source_address) as source by destination_address | search source>100
```

2.350 LP_Possible Botnet Connection-Outbound Spam

- **Trigger Condition:** An unauthorized email sent through an open relay is detected.
- **ATT&CK Category:** Command and Control, Defense Evasion, Impact
- **ATT&CK Tag:** Proxy, Exploitation for Defense Evasion, Network Denial of Service
- **ATT&CK ID:** T1090, T1211, T1498
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
(source_address=* or host=* method="HELO" or method="EHLO") or
↪ (label=Connection destination_port="25" source_address=* or host=*) | search -source_
↪ address IN MAIL_SERVER_IP
```

2.351 LP_Possible CLR DLL Loaded Via Office Applications

- **Trigger Condition:** CLR DLL loaded by an Office Product like WinWord, PowerPoint Excel or Outlook is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing, Spearphishing Attachment
- **ATT&CK ID:** T1566, T1566.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 "process" IN ["*\winword.exe", "*\powerpnt.exe",
↪ "*\excel.exe", "*\outlook.exe"] image IN ["*\clr.dll*"] -user IN EXCLUDED_USERS
```

2.352 LP_Possible Credential Dump-Tools Named Pipes Detected

- **Trigger Condition:** A well-known credential dumping tool execution via specifically named pipes like lsadump, cachedump, or wceservicepipe is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=17 pipe IN ["*\lsadump*", "*\cachedump*",
↪ "*\wceservicepipe*"] -user IN EXCLUDED_USERS
```

2.353 LP_Possible Data Breach

- **Trigger Condition:** Unauthorized transfer of sensitive data is detected using mail applications, cloud applications, or other sources. For the alert to work, you must update the lists RESIGNED_EMPLOYEES, KNOWN_DOMAINS, and CLOUD_APPLICATIONS.
- **ATT&CK Category:** Exfiltration
- **ATT&CK Tag:** Exfiltration Over Web Service, Exfiltration to Cloud Storage
- **ATT&CK ID:** T1567, T1567.002
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
(label=Mail object="*attachment*" sender in RESIGNED_EMPLOYEES -receiver in
↪ KNOWN_DOMAINS) or (label=Object label=Access (label=Write or label=Modify)
↪ event_category="*Removable*" user in RESIGNED_EMPLOYEES) or (label=Access
↪ label=Object (label=Write or label=Modify) path IN CLOUD_APPLICATIONS user in
↪ RESIGNED_EMPLOYEES) or (label=Data label=Transfer label=Sensitive source_
↪ address=* destination_address=*)
```

2.354 LP_Possible Data Breach-Off Hour Transfer

- **Trigger Condition:** Unauthorized transfer of sensitive data during off-hours is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
(norm_id=*Firewall or norm_id=*IDS*) label=Connection source_address=* destination_
↪address=* destination_port=* sent_datasize=* ((day_of_week(log_ts) IN ["Monday",
↪"Tuesday", "Wednesday", "Thursday", "Friday"]) and (hour(log_ts)<9 or hour(log_ts)>
↪17)) or (day_of_week(log_ts) IN ["Saturday", "Sunday"])) | chart sum((sent_datasize)/1024/
↪1024) as TotalSentMB by user | search TotalSentMB>20
```

2.355 LP_Possible DDOS Attack

- **Trigger Condition:** A considerable number of inbound traffic within a short period is detected.
- **ATT&CK Category:** Initial Access, Impact
- **ATT&CK Tag:** Exploit Public-Facing Application, Network Denial of Service
- **ATT&CK ID:** T1190, T1498
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Deny ((protocol=icmp or application="icmp" or service=icmp) or (protocol=http or
↪protocol=https) or (protocol=udp) or 'dns reply' or 'SYN') source_address=* destination_
↪address=* | chart count(source_address) as ddos_source by destination_address | search
↪ddos_source>2000
```

2.356 LP_Possible Detection of SafetyKatz

- **Trigger Condition:** SafetyKatz behavior where a temp file *debug.bin* is created in temp folder to dump credentials using *lsass*.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, LSASS Memory
- **ATT&CK ID:** T1003, T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 path="*\Temp" file="debug.bin" -user IN EXCLUDED_USERS
```

2.357 LP_Possible DNS Rebinding Detected

- **Trigger Condition:** Different DNS answers by one domain with IPs from internal and external networks are detected. Typically, DNS-answer contains TTL greater than 100. Application Layer Protocol and DNS-record are saved in the host cache during TTL.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
event_id=22 query="*" status_code="0" query_result IN [ "(:ffff:)?10.*", "(:ffff:)?192.168.*",  
↪ "(:ffff:)?172.16.*", "(:ffff:)?172.17.*", "(:ffff:)?172.18.*", "(:ffff:)?172.19.*", "(:ffff:)?172.20.*  
↪ ", "(:ffff:)?172.21.*", "(:ffff:)?172.22.*", "(:ffff:)?172.23.*", "(:ffff:)?172.24.*", "(:ffff:)?172.25.  
↪ *", "(:ffff:)?172.26.*", "(:ffff:)?172.27.*", "(:ffff:)?172.28.*", "(:ffff:)?172.29.*", "(:ffff:)?172.  
↪ 30.*", "(:ffff:)?172.31.*", "(:ffff:)?127.*"] -user IN EXCLUDED_USERS | chart  
↪ count(QueryName) as val by host | search val > 3
```


(continued from previous page)

2.360 LP_Possible Impacket Lateralization Detected

- **Trigger Condition:** Instances of lateral movement using the Impacket framework, specifically when utilizing the wmiexec, dcomexec, atexec and smbexec tools are detected.
- **ATT&CK Category:** Lateral Movement, Execution
- **ATT&CK Tag:** Windows Management Instrumentation, Inter-Process Communication, Distributed Component Object Model, Remote Services, Component Object Model, Component Object Model
- **ATT&CK ID:** T1047, T1559, T1021.003, T1021, T1559.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create command="*cmd.exe*" command="*/c*" command="*&1
↪ "*" (parent_process IN ["*\wmiprvse.exe", ".*\mmc.exe", ".*\explorer.exe", ".*\services.
↪ exe"] command="*/Q*" command="*\\127.0.0.1\\*" ) OR (parent_command IN [
↪ ".*svchost.exe -k netsvcs*", ".*taskeng.exe*"] command="*Windows\Temp\*" ) host.exe -
↪ k netsvcs", "taskeng.exe*"] command IN ["cmd.exe /C *Windows\Temp\*&1"]) -user IN
↪ EXCLUDED_USERS'
```

2.361 LP_Possible Impacket SecretDump Remote Activity

- **Trigger Condition:** Logpoint detects *share_name*AD credential dumping using impacket secretdump HKTL.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5145 share_name="\\*\\ADMIN$" relative_target=
↪ "SYSTEM32\\*.tmp" -user IN EXCLUDED_USERS
```

2.362 LP_Possible Inbound Spamming Detected

- **Trigger Condition:** Logpoint detects possible inbound spam.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Mail Server
- **Query:**

```
(sender=* receiver=* -sender in KNOWN_DOMAINS) | chart distinct_count(receiver) as?
↪ spam_receiver by sender | search spam_receiver>100
```

2.363 LP_Possible Insider Threat

- **Trigger Condition:** Logpoint detects alerts like privilege escalation, unauthorized access, and data breach for the same user.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Logpoint
- **Query:**

```
event_type="Possible Insider Threat" incident_user=* -incident_user in EXCLUDED_
↪ USERS | rename incident_user as user | chart distinct_count(incident_name) as?
↪ AlertCount by user | search AlertCount>2
```

2.364 LP_Malicious Payload Download via Office Binaries

- **Trigger Condition:** An arbitrary file downloaded using Microsoft Office binaries is detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Ingress Tool Transfer
- **ATT&CK ID:** T1105
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ("process" IN ["*\powerpnt.exe", ".*\winword.exe", ".*\excel.
↪exe"]) OR file IN ["powerpnt.exe", "winword.exe", "excel.exe"]) command=".*http*" -
↪user IN EXCLUDED_USERS
```

2.365 LP_Possible Malware Detected

- **Trigger Condition:** A file or software is detected as worm, virus, trojan, or malware.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Antivirus
- **Query:**

```
(label=Malware or label=Threat or label=Virus or label=Quarantine or label=Risk)
↪(malware=* OR risk=* OR virus=*) (file=* or application=* or url=*)
```

2.366 LP_Possible Modification of Boot Configuration

- **Trigger Condition:** When the use of the bcdedit command to delete or modify Boot Configuration Data is detected. Boot Configuration Data (BCD) files provide a store that describes boot applications and application settings. Boot configuration data edit (bcdedit) allows manipulating BCD. This tactic is used by malware or attackers as a destructive technique to prevent system recovery. Legitimate usage can trigger this alert. We recommend including the legitimate user in the EXCLUDED_USERS list.

- **ATT&CK Category:** Impact, Defense Evasion, Persistence
- **ATT&CK Tag:** Inhibit System Recovery, Pre-OS Boot, Bootkit
- **ATT&CK ID:** T1490, T1542, T1542.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 ((image="*\bcdedit.exe" command IN ["*delete*",
↪ "*import*", "set"]) OR ((command="*bootstatuspolicy*" command="*ignoreallfailures*"
↪ ") OR (command="*recoveryenabled*" command="*no*"))) -user IN EXCLUDED_USERS
```

2.367 LP_Possible Outbound Spamming Detected

- **Trigger Condition:** Mail received or sent to domains not included in the KNOWN_DOMAINS list is detected. The KNOWN_DOMAINS lists need to be updated with the domains known to communicate to and from the organization.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Mail Server
- **Query:**

```
(sender=* receiver=* -receiver in KNOWN_DOMAINS sender in KNOWN_DOMAINS) [?]
↪ chart distinct_count(receiver) as spam_receiver by sender | search spam_receiver>100
```

2.368 LP_Possible Pass the Hash Activity Detected

- **Trigger Condition:** When the attack technique passes the hash, which is used to move laterally inside the network. Pass the hash is a method of authenticating to a system using a password hash rather than the actual password. Adversaries may use this technique to gain unauthorized access to a system, bypassing normal authentication controls. Pass the hash attacks can be challenging to detect and prevent, as they do not involve using a clear-text password.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Use Alternate Authentication Material, Pass the Hash

- **ATT&CK ID:** T1550, T1550.002
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4624 ((caller_id="S-1-0-0" logon_type="3" logon_process=
↪ "NtLmSsp" key_length="0") OR (logon_type="9" logon_process="seclogo")) -user=
↪ "ANONYMOUS LOGON" -user IN EXCLUDED_USERS
```

2.369 LP_Possible Privilege Escalation via Weak Service Permissions

- **Trigger Condition:** The sc.exe utility spawning by a user with medium integrity level to change the service ImagePath or FailureCommand is detected.
- **ATT&CK Category:** Privilege Escalation, Defense Evasion
- **ATT&CK Tag:** Access Token Manipulation
- **ATT&CK ID:** T1134
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Process" label=Create "process"="*\sc.exe" integrity_level="Medium" command
↪ IN ["*config*binPath*", "*failure*command*"] -user IN EXCLUDED_USERS
```

2.370 LP_Possible Process Hollowing Image Loading

- **Trigger Condition:** Loading of *samlib.dll* or *WinSCard.dll* from untypical process is detected. For example, through process hollowing by Mimikatz.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Hijack Execution Flow, DLL Side-Loading, Process Injection, Process Hollowing
- **ATT&CK ID:** T1574, T1574.002, T1055, T1055.012
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 "process" IN ["*\notepad.exe"] image IN [
↪ "\saml.dll", "\WinSCard.dll"] -user IN EXCLUDED_USERS
```

2.371 LP_Possible SPN Enumeration Detected

- **Trigger Condition:** *Service Principal Name Enumeration* used for Steal or Forge Kerberos Tickets and Kerberoasting is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Steal or Forge Kerberos Tickets, Kerberoasting
- **ATT&CK ID:** T1558, T1558.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 command="*-q*" (image="*\setspn.exe" OR
↪ message="*Query or reset the computer* SPN attribute*") -user IN EXCLUDED_USERS
```

2.372 LP_Possible SquiblyTwo Detected

- **Trigger Condition:** WMI SquiblyTwo Attack with possible renamed WMI seeking for imphash is detected.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** Windows Management Instrumentation, Visual Basic, JavaScript, XSL Script Processing
- **ATT&CK ID:** T1047, T1059.005, T1059.007, T1220
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 file="wmic.exe" hash_imphash IN [
↪ "1B1A3F43BF37B5BFE60751F2EE2F326E", "37777A96245A3C74EB217308F3546F4C",
↪ "9D87C9D67CE724033C0B40CC4CA1B206"] command="*format:*" command="*http*"
```

2.373 LP_Possible Taskmgr run as LOCAL_SYSTEM Detected

- **Trigger Condition:** Creation of a *taskmgr.exe* process in the context of LOCAL_SYSTEM is detected. *Taskmgr.exe* is the executable file for Windows Task Manager.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\taskmgr.exe" user in ["*AUTHORI*",
↪ "*AUTORI*"]
```

2.374 LP_Powershell AMSI Bypass via dotNET Reflection

- **Trigger Condition:** Request to *amsilnitFailed* used to disable AMSI Scanning is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
'label="Process" label=Create command IN ["*System.Management.Automation.AmsiUtils*"]
↪ command IN ["*amsilnitFailed*"] -user IN EXCLUDED_USERS'
```

2.375 LP_PowerShell Base64 Encoded Shellcode Detected

- **Trigger Condition:** Potential Base64 encoded shellcode for PowerShell memory injection is detected.

- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows, PowerShell
- **Query:**

```
norm_id=WinServer event_id=4104 script_block="*AAAAYInIM*" script_block IN [
↪ "*OiCAAAAYInIM*", "*OiJAAAYInIM*"]
```

2.376 LP_PowerShell Network Connections Detected

- **Trigger Condition:** Logpoint detects a Command and Scripting Interpreter and PowerShell process that opens network connections. We recommend you check suspicious target ports and systems, and adjust them according to your environment. For example, extend filters with the company's IP range.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=3 image="*\powershell.exe" initiated="true" -
↪ destination_address IN HOMENET -user="NT AUTHORITY\SYSTEM" -user IN ?
↪ EXCLUDED_USERS
```

2.377 LP_PowerShell Profile Modification

- **Trigger Condition:** Modification of Command and Scripting Interpreter and PowerShell profile is detected.
- **ATT&CK Category:** Persistence, Privilege Escalation, Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, Event Triggered Execution, PowerShell Profile, Powershell
- **ATT&CK ID:** T1546, T1546.013, T1059, T1059.001

- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4103 command in ["Write-Output", "Add-Content"]  
↪ payload= "*powershell_profile*" -user IN EXCLUDED_USERS
```

2.378 LP_PowerShell Rundll32 Remote Thread Creation Detected

- **Trigger Condition:** The creation of a remote thread from a Powershell process in a rundll32 process is detected.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** PowerShell, Rundll32
- **ATT&CK ID:** T1059.001, T1218.011
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Remote" label="Thread" label="Create" "process" IN ["*\powershell.exe", "pwsh.  
↪ exe"] image="*\rundll32.exe" -user IN EXCLUDED_USERS
```

2.379 LP_PowerShell Script Run in AppData Detected

- **Trigger Condition:** A suspicious command line execution that invokes Command and Scripting Interpreter and PowerShell concerning an AppData folder is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** PowerShell
- **ATT&CK ID:** T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" command IN ["*powershell.exe*", "*\powershell*",  
↪ "*\pwsh*", "*pwsh.exe*"] command= "* /c *" command= "*\AppData\*" command IN [  
↪ "*Local*", "*Roaming\*"]
```

2.380 LP_PowerShell Version Downgrade Detected

- **Trigger Condition:** The execution of legacy PowerShell version 2 is detected.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell, Downgrade Attack
- **ATT&CK ID:** T1059, T1059.001, T1562.010
- **Minimum Log Source Requirement:** Windows, PowerShell
- **Query:**

```
norm_id=WinServer event_source=PowerShell event_id=400 host_version="2.0"
```

2.381 LP_Process Dump via Comsvcs DLL Detected

- **Trigger Condition:** Process memory dump via *comsvcs.dll* and *rundll32* is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 (image= "*\rundll32.exe" OR file= "RUNDLL32.EXE  
→") command IN ["*comsvcs*MiniDump*full*", "*comsvcs*MiniDumpW*full*"] -user IN  
→EXCLUDED_USERS
```

2.382 LP_Process Dump via Rundll32 and Comsvcs Detected

- **Trigger Condition:** Process memory dump performed via ordinal function 24 in *comsvcs.dll* is detected.
- **ATT&CK Category:** Defense Evasion, Credential Access
- **ATT&CK Tag:** Masquerading, OS Credential Dumping, LSASS Memory
- **ATT&CK ID:** T1036, T1003, T1003.001

- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 command IN ["*comsvcs.dll, #24*", "*comsvcs.dll,
↪ MiniDump*"] -user IN EXCLUDED_USERS
```

2.383 LP_Process Hollowing Detected

- **Trigger Condition:** Adversaries attempts to inject malicious code into suspended and hollowed processes to evade process-based defenses.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Process Injection, Process Hollowing
- **ATT&CK ID:** T1055, T1055.012
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 (image="*smss.exe" parent_command!="*smss.
↪ exe") or (image="*csrss.exe" (parent_command!="*smss.exe" and parent_command!=
↪ "*svchost.exe")) or (image="*wininit.exe" parent_command!="*smss.exe") or (image=
↪ "*winlogon.exe" parent_command!="*smss.exe") or (image="*lsass.exe" parent_
↪ command!="*wininit.exe") or (image="*LogonUI.exe" (parent_command!="*winlogon.
↪ exe" and parent_command!="*wininit.exe")) or (image="*services.exe" parent_
↪ command!="*wininit.exe") or (image="*spoolsv.exe" parent_command!="*services.exe
↪ ") or (image="*taskhost.exe" (parent_command!="*services.exe" and parent_command!
↪ = "*svchost.exe")) or (image="*taskhostw.exe" (parent_command!="*services.exe" and
↪ parent_command!="*svchost.exe")) or (image="*userinit.exe" (parent_command!=
↪ "*dwm.exe" and parent_command!="*winlogon.exe")) -user IN EXCLUDED_USERS
```

2.384 LP_Process Injection Detected

- **Trigger Condition:** Adversaries injects code into processes to evade process-based defenses and possibly elevate privileges using commands like Invoke-DllInjection.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055

- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 (command="*Invoke-DllInjection*" or command=
↪ "*C:\windows\synative\*" ) -user IN EXCLUDED_USERS
```

2.385 LP_Protected Storage Service Access Detected

- **Trigger Condition:** An access to a *protected_storage* service over the network is detected. The potential abuse of DPAPI to extract domain backup keys from Domain Controllers.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote Services
- **ATT&CK ID:** T1021
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5145 share_name="*IPC*" relative_target="protected_
↪ storage" -user IN EXCLUDED_USERS
```

2.386 LP_PsExec Tool Execution Detected

- **Trigger Condition:** PsExec service installation and execution event (Service and Sysmon) is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** System Services, Service Execution
- **ATT&CK ID:** T1569, T1569.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
((norm_id=WinServer service="PSEXESVC" event_id IN [7045, 7036]) OR (norm_
↪ id=WindowsSysmon event_id=1 "process"="*\PSEXESVC.exe" user="*SYSTEM*")) -
↪ user IN EXCLUDED_USERS
```

2.387 LP_Psr Capture Screenshots Detected

- **Trigger Condition:** The psr utility adversaries use to take screen captures of the desktop to gather information throughout an operation is detected. The *psr.exe* utility is a legitimate Windows application that captures desktop screenshots.
- **ATT&CK Category:** Collection
- **ATT&CK Tag:** Screen Capture
- **ATT&CK ID:** T1113
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\Psr.exe" command="*/start*" -user IN EXCLUDED_USERS
```

2.388 LP_Pulse Secure Arbitrary File Reading Detected

- **Trigger Condition:** The exploitation of arbitrary file reading vulnerability (CVE-2019-11510) in Pulse Secure is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** External Remote Services
- **ATT&CK ID:** T1113
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
norm_id=* url IN ['*dana*guacamole*', '*lmdb*data.mdb*', '*data*mtmp/system*']
```

2.389 LP_Query Registry Network

- **Trigger Condition:** Adversaries uses *reg.exe* component for network connection and interact with the Windows Registry to gather information about the system, configuration, and installed software.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Query Registry

- **ATT&CK ID:** T1012
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=3 image="*reg.exe" command="*reg query*" -user
↪ IN EXCLUDED_USERS
```

2.390 LP_Rare Scheduled Task Creations Detected

- **Trigger Condition:** Rare scheduled task creations are detected. A software gets installed on multiple systems. The aggregation and count function selects tasks with rare names.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Scheduled Task/Job, Scheduled Task
- **ATT&CK ID:** T1053, T1053.005
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id="106" | chart count() as val by task | search val < 5
```

2.391 LP_RDP Login from Localhost Detected

- **Trigger Condition:** RDP login with a localhost source address that may be a tunneled login is detected.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote Services, Remote Desktop Protocol
- **ATT&CK ID:** T1021, T1021.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4624 logon_type="10" source_address IN ["::1", "127.0.0.1
↪ "] -user IN EXCLUDED_USERS
```

2.392 LP_RDP Over Reverse SSH Tunnel Detected

- **Trigger Condition:** *svchost* hosting RDP *termsvcs* communicating with the loopback address and on TCP port 3389 is detected.
- **ATT&CK Category:** Lateral Movement, Command and Control
- **ATT&CK Tag:** Remote Services, Remote Desktop Protocol, Protocol Tunneling
- **ATT&CK ID:** T1021, T1021.001, T1572
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=3 "process"="*\svchost.exe" is_initiated="true"
↪source_port="3389" destination_address IN ["127.*", "::1"] -user IN EXCLUDED_USERS
```

2.393 LP_RDP Registry Modification

- **Trigger Condition:** Potential malicious modification of the property value of fDenyTS Connections and UserAuthentication to enable remote desktop connections is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Modify Registry
- **ATT&CK ID:** T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 target_object IN [
↪"*\\CurrentControlSet\\Control\\Terminal Server\\WinStations\\RDP-Tcp\\UserAuthentication
↪", "\\CurrentControlSet\\Control\\Terminal Server\\fDenyTSConnections"] details=
↪"DWORD (0x00000000)" -user IN EXCLUDED_USERS
```

2.394 LP_RDP Sensitive Settings Changed

- **Trigger Condition:** Changes registry keys related to RDP terminal service are detected.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** Modify Registry
- **ATT&CK ID:** T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 target_object IN [
  ↳ "*\services\TermService\Parameters\ServiceDll*", "*\Control\Terminal
  ↳ Server\SingleSessionPerUser*", "*\Control\Terminal Server\DenyTSConnections*" ] -
  ↳ user IN EXCLUDED_USERS
```

2.395 LP_Reconnaissance Activity with Net Command

- **Trigger Condition:** A set of commands often used in recon stages by different attack groups to discover the victim's information, systems, or network are detected.
- **ATT&CK Category:** Discovery, Reconnaissance
- **ATT&CK Tag:** Account Discovery, System Information Discovery, Gather Victim Host Information, Gather Victim Identity Information
- **ATT&CK ID:** T1087, T1082, T1589, T1592
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 command IN ["tasklist", "net time", "systeminfo",
  ↳ "whoami", "nbtstat", "net start", "*\net1 start", "qprocess", "nslookup", "hostname.exe
  ↳ ", "*\net1 user /domain", "*\net1 group /domain", "*\net1 group *domain admins* /
  ↳ domain", "*\net1 group *Exchange Trusted Subsystem* /domain", "*\net1 accounts /
  ↳ domain", "*\net1 user net localgroup administrators", "netstat -an"]
  ↳ -user IN EXCLUDED_USERS | chart count() as val by command | search val > 4
```

2.396 LP_RedSocks Backdoor Connection

- **Trigger Condition:** A backdoor event is detected. Adversaries develops malware and malware components as backdoors, which are used during targeting.
- **ATT&CK Category:** Resource Development
- **ATT&CK Tag:** Develop Capabilities, Malware

- **ATT&CK ID:** T1587, T1587.001
- **Minimum Log Source Requirement:** Redsocks
- **Query:**

```
norm_id=RedSocks description="*backdoor*" | process geoip(destination_address) as?
↪ country
```

2.397 LP_RedSocks Bad Neighborhood Detection

- **Trigger Condition:** A bad neighborhood is detected where adversaries use a connection proxy to direct network traffic between systems or act as an intermediary for network communications to a Command and Control server to avoid direct connections to their infrastructure.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Redsocks
- **Query:**

```
norm_id=RedSocks category="bad hood" | process geoip(destination_address) as? country
```

2.398 LP_RedSocks Blacklist URL Detection

- **Trigger Condition:** Blacklist URLs are detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Redsocks
- **Query:**

```
norm_id=RedSocks category="URL blacklist" | process geoip(destination_address) as?
↪ country
```

2.399 LP_RedSocks FileSharing

- **Trigger Condition:** Filesharing using an alternate platform like 4Shared, FileHippo, Torrent, Picofile, or WeTransfer is detected.
- **ATT&CK Category:** Exfiltration
- **ATT&CK Tag:** Exfiltration over Alternative Protocol
- **ATT&CK ID:** T1048
- **Minimum Log Source Requirement:** Redsocks
- **Query:**

```
norm_id=RedSocks category="Filesharing" description in ["*4share*", "*torrent*",
↪ "*FileHippo*", "*picofile*", "*wetransfer*"] | process geoip(destination_address) as?
↪ country
```

2.400 LP_RedSocks Ransomware Connection

- **Trigger Condition:** A ransomware event is detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Disk Wipe, Disk Content Wipe, Data Encrypted for Impact, Data Destruction, Proxy
- **ATT&CK ID:** T1561, T1561.001, T1486, T1485, T1090
- **Minimum Log Source Requirement:** Redsocks
- **Query:**

```
norm_id=RedSocks description="*ransomware*" | process geoip(destination_address) as?
↪ country
```

2.401 LP_RedSocks Sinkhole Detection

- **Trigger Condition:** Sinkhole is detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** -

- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Redsocks
- **Query:**

```
norm_id=RedSocks category="Sinkhole" | process geoip(destination_address) as country
```

2.402 LP_RedSocks Tor Connection

- **Trigger Condition:** A Tor connection is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Redsocks
- **Query:**

```
norm_id=RedSocks category="tor" | process geoip(destination_address) as country
```

2.403 LP_RedSocks Trojan Connection

- **Trigger Condition:** A trojan event is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Redsocks
- **Query:**

```
norm_id=RedSocks description="*trojan*" | process geoip(destination_address) as country
```

2.404 LP_Register new Logon Process by Rubeus

- **Trigger Condition:** Potential use of Rubeus via registered new trusted logon process is detected. Adversaries abuses a valid Kerberos ticket-granting ticket (TGT) or sniff network traffic to obtain a ticket-granting service (TGS) ticket that may be vulnerable to Brute Force.
- **ATT&CK Category:** Lateral Movement, Privilege Escalation
- **ATT&CK Tag:** Steal or Forge Kerberos Tickets, Kerberoasting
- **ATT&CK ID:** T1558, T1558.003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4611 logon_process="User32LogonProcess" -user IN EXCLUDED_USERS
```

2.405 LP_Registry Persistence Mechanisms Detected

- **Trigger Condition:** Persistence registry keys at the current version folder for registry keys are detected. Adversaries establish persistence and/or elevate privileges by executing malicious content triggered by Image File Execution Options (IFEEO) debuggers.
- **ATT&CK Category:** Privilege Escalation, Persistence
- **ATT&CK Tag:** Event Triggered Execution, Image File Execution Options Injection
- **ATT&CK ID:** T1546, T1546.012
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
event_id=13 target_object IN ["*\\SOFTWARE\\Microsoft\\Windows NT\\CurrentVersion\\Image File Execution Options\\*\\GlobalFlag",
"*\\SOFTWARE\\Microsoft\\Windows NT\\CurrentVersion\\SilentProcessExit\\*\\ReportingMode",
"*\\SOFTWARE\\Microsoft\\Windows NT\\CurrentVersion\\SilentProcessExit\\*\\MonitorProcess"] event_type="SetValue" -user IN EXCLUDED_USERS
```

2.406 LP_Regsvcs-Regasm Detected

- **Trigger Condition:** Adversaries abuses trusted Windows command line utilities *regsvcs* and *regasm* for proxy execution of code.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Signed Binary Proxy Execution, Regsvcs/Regasm
- **ATT&CK ID:** T1218, T1218.009
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=3 (image="*regsvcs.exe" or image="*regasm.exe")
```

2.407 LP_Remote PowerShell Session

- **Trigger Condition:** Remote PowerShell sessions on endpoints are detected. Powershell allows functionality to execute code on a remote system without using RDP.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(norm_id=WinServer event_id IN ["4103", "400"] execution_host="ServerRemoteHost" host_
↪ application="*wsmprovhost.exe*")OR (label="Process" label=Create ("process"=
↪ "*wsmprovhost.exe" OR parent_process="*\wsmprovhost.exe"))
```

2.408 LP_Remote System Discovery

- **Trigger Condition:** The components like *net.exe* and *ping.exe* are used to list other systems by IP address, hostname, or other logical identifiers on a network used for Lateral Movement from the current system.
- **ATT&CK Category:** Discovery

- **ATT&CK Tag:** Remote System Discovery
- **ATT&CK ID:** T1018
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon (image="*net.exe" or image="*ping.exe") (command="*view*"
↪ " or command="*ping*") -user IN EXCLUDED_USERS
```

2.409 LP_Renamed Binary Detected

- **Trigger Condition:** The execution of a renamed binary is detected. Renamed binaries are executable files disguised in a different name or file extension to evade detection by security measures.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Rename System Utilities
- **ATT&CK ID:** T1036.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Process" label=Create (application = "Sysinternals PsExec" OR description IN
["Windows PowerShell*", "pwsh*", "Execute processes remotely"] OR file IN
["powershell.exe", "pwsh.dll", "powershell_ise.exe", "psexec.exe", "psexec.c", "psexesvc.
↪ exe", "cscript.exe", "wscript.exe",
"mshta.exe", "regsvr32.exe", "wmic.exe", "certutil.exe", "rundll32.exe", "cmstp.exe",
↪ "msiexec.exe", "reg.exe"])
- "process" IN ["*\powershell.exe", ".*\pwsh.exe", ".*\powershell_ise.exe", ".*\psexec.exe",
↪ ".*\psexec64.exe", ".*\PSEXESVC.exe", ".*\cscript.exe", ".*\wscript.exe", ".*\mshta.exe",
↪ ".*\regsvr32.exe", ".*\wmic.exe", ".*\certutil.exe", ".*\rundll32.exe", ".*\cmstp.exe",
↪ ".*\msiexec.exe", ".*\reg.exe"]) -user IN EXCLUDED_USERS
```

2.410 LP_Renamed ProcDump Detected

- **Trigger Condition:** Execution of a renamed *ProcDump* executable used by attackers or malware.
- **ATT&CK Category:** Execution

- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon file="procdump" -image IN ["*\procdump.exe",
↪ ".*\procdump64.exe"]
```

2.411 LP_Renamed PsExec Detected

- **Trigger Condition:** Execution of a renamed *PsExec* used by attackers or malware.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon message="Execute processes remotely" product=
↪ "Sysinternals PsExec" -image IN ["*\PsExec.exe", ".*\PsExec64.exe"]
```

2.412 LP_Rogue Access Point Detected

- **Trigger Condition:** Rouge access point is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Exploitation for Defense Evasion, Exploitation for Defense Evasion, Software Discovery, Security Software Discovery
- **ATT&CK ID:** T1211, T1211, T1518, T1518.001
- **Minimum Log Source Requirement:** Firewall, IDS/IPS (ArubaOS, Cisco Controller)
- **Query:**

```
label=Accesspoint label=Rogue -label=Clear access_point=*
```

2.413 LP_RSA SecurID Account Lockout

- **Trigger Condition:** User's account is locked after entering the wrong passcode multiple times in a row.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Brute Force
- **ATT&CK ID:** T1110
- **Minimum Log Source Requirement:** RSA Secure ID
- **Query:**

```
norm_id=RSA_SecurID type=Runtime action=AUTHN_LOCKOUT_EVENT
```

2.414 LP_RSA SecurID Account Lockout

- **Trigger Condition:** User's account is locked after entering the wrong passcode multiple times in a row.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Brute Force
- **ATT&CK ID:** T1110
- **Minimum Log Source Requirement:** RSA Secure ID
- **Query:**

```
norm_id=RSA_SecurID type=Runtime action=AUTHN_LOCKOUT_EVENT
```

2.415 LP_Rubeus Hack Tool Detected

- **Trigger Condition:** The Command line parameters like asreproast, dump, impersonate user, harvest and other commands used by the Rubeus hack tool are detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping
- **ATT&CK ID:** T1003

- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Process" label=Create command IN ["* asreproast *", "* dump /service:krbtgt *",
↪ "* kerberoast *", "* createnetenonly /program:*", "* ptt /ticket:*", "* /impersonateuser:*",
↪ "* renew /ticket:*", "* asktgt /user:*", "* harvest /interval:*"] -user IN EXCLUDED_USERS
```

2.416 LP_Run PowerShell Script from ADS Detected

- **Trigger Condition:** PowerShell script execution from Alternate Data Stream (ADS) is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Hide Artifacts, NTFS File Attributes
- **ATT&CK ID:** T1564, T1564.004
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process IN ["*\powershell.exe", "*\pwsh.exe"]
↪ "process" IN ["*\powershell.exe", "*\pwsh.exe"] command="*Get-Content*"
↪ command="*-Stream*" -user IN EXCLUDED_USERS
```

2.417 LP_Rundll32 Internet Connection Detected

- **Trigger Condition:** A rundll32 that communicates with public IP addresses is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Rundll32
- **ATT&CK ID:** T1218.011
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=3 "process"="*\rundll32.exe" is_initiated="true" -
↪ (((destination_address IN HOMENET) OR destination_address IN ["127.*", "20.*", "51.
↪ 103.*", "51.104.*", "51.105.*"] OR (command="*PcaSvc.dll,PcaPatchSdbTask*" OR
↪ source_host="*.internal.cloudapp.net")) OR (parent_process=
↪ "C:\Windows\System32\svchost.exe" destination_port="443")) -user IN EXCLUDED
↪ USERS (continues on next page)
```

(continued from previous page)

2.418 LP_SAM Registry Hive Dump via Reg Utility

- **Trigger Condition:** Handle to SAM registry hive via reg utility is detected.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Query Registry
- **ATT&CK ID:** T1012
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4656 object_type="Key" object_name="*\SAM" "process
↪"="*\reg.exe" -user IN EXCLUDED_USERS
```

2.419 LP_Scheduled Task Creation Detected

- **Trigger Condition:** The creation of scheduled task is detected. Schtasks is a windows internal binary that allows us to schedule tasks.
- **ATT&CK Category:** Execution, Persistence, Privilege Escalation
- **ATT&CK Tag:** Scheduled Task/Job, Scheduled Task
- **ATT&CK ID:** T1053, T1053.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(label="Process" label=Create "process"="*\schtasks.exe" command="* /create *" -user[?]
↪IN EXCLUDED_USERS) OR (label="Registry" label="Key" label="Map" "target_object
↪"="*\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Schedule\TaskCache\Tree\" -
↪target_object IN ["*\SOFTWARE\Microsoft\Windows[?]
↪NT\CurrentVersion\Schedule\TaskCache\Tree\Microsoft\Windows\UpdateOrchestrator*
↪"] event_type=CreateKey) OR (norm_id=WinServer event_id=4698 (-command IN [
↪"*MpCmdRun.exe", "*msfeedssync.exe", "*usoclient.exe"] OR (-task=
↪"\CreateExplorerShellUnelevatedTask" command="*explorer.exe")))
```

2.420 LP_SCM Database Handle Failure Detected

- **Trigger Condition:** Non-system user fails to get a handle of the SCM database.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Endpoint Denial of Service
- **ATT&CK ID:** T1499
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4656 object_type="SC_MANAGER OBJECT" object_name=
↪ "servicesactive" event_type="Audit Failure" logon_id="0x3e4" -user IN EXCLUDED_
↪ USERS
```

2.421 LP_SCM Database Privileged Operation Detected

- **Trigger Condition:** Non-system user performs privileged operation on the SCM database.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** Abuse Elevation Control Mechanism, Bypass User Account Control
- **ATT&CK ID:** T1548, T1548.002
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4674 object_type="SC_MANAGER OBJECT" object_name=
↪ "servicesactive" privilege="SeTakeOwnershipPrivilege" logon_id="0x3e4" -user IN
↪ EXCLUDED_USERS
```

2.422 LP_Screensaver Activities Detected

- **Trigger Condition:** Screensaver registry key modified via *rundll32.exe* is detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Screensaver

- **ATT&CK ID:** T1546.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
norm_id=WindowsSysmon (event_id=12 or event_id=13 or event_id=14) (target_object=
↪ "*\Control Panel\Desktop\SCRNSAVE.exe") (parent_command!="*explorer.exe" or
↪ image!="*rundll32.exe" or command!="*shell32.dll, Control_RunDLL desk.cpl,
↪ ScreenSaver, *") -user IN EXCLUDED_USERS
```

2.423 LP_Secure Deletion with SDelete

- **Trigger Condition:** Logpoint detects renaming of a file during deletion using SDelete tool.
- **ATT&CK Category:** Defense Evasion, Impact
- **ATT&CK Tag:** Indicator Removal on Host, File Deletion, Obfuscated Files or Information, Indicator Removal from Tools, Data Destruction, Subvert Trust Controls, Code Signing
- **ATT&CK ID:** T1070, T1070.004, T1027, T1027.005, T1485, T1553, T1553.002
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id IN ["4656", "4663", "4658"] object_name IN ["*.AAA", "*.ZZZ
↪ "] -user IN EXCLUDED_USERS
```

2.424 LP_SecurityXploded Tool Detected

- **Trigger Condition:** Execution of the SecurityXploded tools is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credentials from Password Stores
- **ATT&CK ID:** T1555
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (vendor="SecurityXploded" OR "process" =
↳ "*PasswordDump.exe" OR file="*PasswordDump.exe") -user IN EXCLUDED_USERS
```

2.425 LP_Signed Binary Proxy Execution - Network Detected

- **Trigger Condition:** When adversaries bypass process and/or signature-based defenses by proxying execution of malicious content with signed binaries using windows components and commands like certutil, replace. Signed binary proxy execution is a technique that involves the use of a trusted, signed binary to execute malicious code. Adversaries may use this technique to bypass security controls and execute malicious code on a system without being detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=3 "process" IN ["*certutil.exe", "*certutil*script:http*:/
↳ /*", "*\replace.exe"] -user IN EXCLUDED_USERS
```

2.426 LP_Signed Binary Proxy Execution - Process Detected

- **Trigger Condition:** Adversaries bypasses process and/or signature-based defenses by proxying execution of malicious content with signed binaries using Windows components and commands like certutil or replace is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create ("process"="*mavinject.exe" or command="*V
↪injectrunning*" or command="*mavinject32*Vinjectrunning*" or command=
↪"*certutil*script:http*://*" or command="*msiexec*http*://*") -user IN EXCLUDED_
↪USERS
```

2.427 LP_smbexec Service Installation Detected

- **Trigger Condition:** *smbexec.py* tool is detected by identifying a specific service installation.
- **ATT&CK Category:** Lateral Movement, Execution
- **ATT&CK Tag:** Remote Services, System Services, Service Execution
- **ATT&CK ID:** T1021, T1569, T1569.002
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=7045 service="BTOBTO" service="*\execute.bat" -user IN
↪EXCLUDED_USERS
```

2.428 LP_SolarisLDAP Group Remove from LDAP Detected

- **Trigger Condition:** The removal of a group from LDAP is detected.
- **ATT&CK Category:** Credential Access, Persistence, Impact, Defense Evasion
- **ATT&CK Tag:** Account Manipulation, Account Access Removal
- **ATT&CK ID:** T1098, T1531
- **Minimum Log Source Requirement:** Solaris LDAP
- **Query:**

```
norm_id=SolarisLDAP label=Remove label=Member label=Management label=Group
```

2.429 LP_SolarisLDAP Password Spraying Attack Detected

- **Trigger Condition:** Multiple login or authentication fail attempts on a SOLARISLDAP by various users are detected. Adversaries can use a list of commonly used passwords against different accounts to attempt to obtain valid account credentials.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Solaris LDAP
- **Query:**

```
norm_id=SolarisLDAP label=User (label=Login OR label=Authentication) label=Fail | chart
↪ distinct_count(user) as UserCount, distinct_list(user) as Users | search UserCount > 5
```

2.430 LP_SolarisLDAP Possible Bruteforce Attack Detected

- **Trigger Condition:** Five failed Solaris LDAP user login or authentication attempts from a user are detected. Adversaries can perform brute force attacks to find the valid credentials of a user. The fail count number needs to be adjusted to the environment.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Brute Force
- **ATT&CK ID:** T1110
- **Minimum Log Source Requirement:** Solaris LDAP
- **Query:**

```
norm_id=SolarisLDAP label=User (label=Login OR label=Authentication) label=Fail | chart
↪ count() as cnt by user | search cnt > 5
```

2.431 LP_SolarisLDAP Successful Bruteforce Attack Detected

- **Trigger Condition:** Successful login event after multiple failed login counts is detected as defined in the query. Adversaries perform brute-force attacks to discover and validate credentials and gain access to the system and network. The fail count needs to be adjusted according to the environment.
- **ATT&CK Category:** Initial Access, Persistence, Privilege Escalation, Defense Evasion, Credential Access
- **ATT&CK Tag:** Valid Accounts, Account Manipulation, Brute Force, Forced Authentication
- **ATT&CK ID:** T1078, T1098, T1110, T1187
- **Minimum Log Source Requirement:** Solaris LDAP
- **Query:**

```
[norm_id=SolarisLDAP label=User (label=Login OR label=Authentication) label=Fail |
↪ chart count() as cnt by user | search cnt > 10 ] as s1 followed by [norm_id=SolarisLDAP
↪ label=User (label=Login OR label=Authentication) label=Successful] as s2 on s1.user =
↪ s2.user
```

2.432 LP_SolarisLDAP User Account Lockout Detected

- **Trigger Condition:** A locked user account is detected.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts, Abuse Elevation Control Mechanism, Bypass User Access Control
- **ATT&CK ID:** T1078, T1548
- **Minimum Log Source Requirement:** Solaris LDAP
- **Query:**

```
norm_id=SolarisLDAP label=User label=Account label=Lock
```

2.433 LP_Sophos XG Firewall - Inbound Attack Detected by IDP

- **Trigger Condition:** An inbound attack defined in IDP policy is detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Network Denial of Service, Endpoint Denial of Service
- **ATT&CK ID:** T1498, T1499
- **Minimum Log Source Requirement:** Sophos XG Firewall
- **Query:**

```
norm_id=SophosXGFirewall label=Attack label=Detect label=IDP destination_address=* -
↪source_address in HOMENET | process geoip(source_address) as country
```

2.434 LP_Sophos XG Firewall - Outbound Attack Detected by IDP

- **Trigger Condition:** An outbound attack defined in IDP policy is detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Network Denial of Service, Endpoint Denial of Service
- **ATT&CK ID:** T1498, T1499
- **Minimum Log Source Requirement:** Sophos XG Firewall
- **Query:**

```
norm_id=SophosXGFirewall label=Attack label=Detect label=IDP destination_address=* -
↪destination_address in HOMENET | process geoip(destination_address) as country
```

2.435 LP_SophosUTM Policy Violation

- **Trigger Condition:** Different policy violation from a source is detected. For this alert to work, the following list must be updated;
 - EXTREMIST_CONTENT, for example, weapons.

- CONCERNED _CONTENT, for example, alcohol, tobacco, gambling, and so on.
- CRIMINAL _CONTENT, for example, hacking, drugs, and so on.
- VULNERABLE _CONTENT, for example, abuse, and so on.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation, Credential Access
- **ATT&CK Tag:** Abuse Elevation Control Mechanism, Bypass User Access Control, Group Policy Modification, Exploitation for Credential Access, Exploitation for Privilege Escalation
- **ATT&CK ID:** T1548, T1484, T1212, T1068
- **Minimum Log Source Requirement:** Sophos UTM
- **Query:**

```
norm_id=SophosUTM category_name=* source_address=* | chart count(category_name
↪ IN EXTREMIST_CONTENT) as Extremist, count(category_name IN CONCERNED_
↪ CONTENT) as Concerning, count(category_name IN CRIMINAL_CONTENT) as Criminal,
↪ count(category_name IN VULNERABLE_CONTENT) as Vulnerable by source_address,
↪ user | chart sum(Extremist+Concerning+Criminal+Vulnerable) as Violation by Extremist,
↪ Concerning, Criminal, Vulnerable, source_address,
user order by Violation | search Violation>1
```

2.436 LP_SSHD Connection Denied

- **Trigger Condition:** Ten denied connections are detected from the same source.
- **ATT&CK Category:** Lateral Movement, Command and Control, Impact
- **ATT&CK Tag:** Remote Services, Commonly Used Port, Network Denial of Service, Endpoint Denial of Service
- **ATT&CK ID:** T1021, T1498, T1499
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
[10 norm_id=Unix label=Connection label=Deny having same source_address within 10
↪ seconds]
```

2.437 LP_Stealthy Scheduled Task Creation via VBA Macro Detected

- **Trigger Condition:** Office products such as Word, Excel, PowerPoint and Outlook.exe load *taskschd.dll* is detected.
- **ATT&CK Category:** Execution, Persistence, Privilege Escalation
- **ATT&CK Tag:** Scheduled Task/Job, Scheduled Task
- **ATT&CK ID:** T1053, T1053.005
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 image="*\taskschd.dll" process IN ["*\winword.
↪exe", "*\excel.exe", "*\powerpnt.exe", "*\outlook.exe"] -user IN EXCLUDED_USERS
```

2.438 LP_Sticky Key Like Backdoor Usage Detected

- **Trigger Condition:** The use and installation of a backdoor that uses an option to register a malicious debugger for built-in tools that are accessible on the login screen. Sticky keys are a Windows accessibility feature that allows a user to press a modifier key (For example, Shift, Ctrl, Alt) and remain active until another key is pressed. Adversaries may use a sticky key-like backdoor to gain unauthorized access to a system by pressing a specific combination of keys. This can allow them to execute malicious code or bypass security controls.
- **ATT&CK Category:** Privilege Escalation, Persistence
- **ATT&CK Tag:** Event Triggered Execution, Accessibility Features
- **ATT&CK ID:** T1546, T1546.008
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(norm_id=WindowsSysmon event_id=13 target_object IN [
↪ "\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Image File Execution
↪ Options\*\Debugger"] event_type="SetValue") OR (label="Process" label=Create
↪ parent_process="*\winlogon.exe" command IN ["*cmd.exe sethc.exe *", "*cmd.exe
↪ utilman.exe *", "*cmd.exe osk.exe *", "*cmd.exe Magnify.exe *", "*cmd.exe Narrator.
↪ exe *", "*cmd.exe DisplaySwitch.exe *"])
```

2.439 LP_Stop Windows Service Detected

- **Trigger Condition:** Windows Service stops.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Service Stop
- **ATT&CK ID:** T1489
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 image IN ["*\\sc.exe", "*\\net.exe", "*\\net1.exe"]
↪ command= "*stop*" -user IN EXCLUDED_USERS
```

2.440 LP_Successful Lateral Movement to Administrator via Pass the Hash using Mimikatz Detected

- **Trigger Condition:** Lateral Movement is successful in compromising the admin account via Pass the Hash method.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Use Alternate Authentication Material, Pass the Hash
- **ATT&CK ID:** T1550, T1550.002
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
[norm_id=WinServer event_id=4624 logon_type=9 logon_process=seclogon
↪ package=Negotiate label=User label=Login label=Successful -user IN EXCLUDED_
↪ USERS] as s1
followed by [norm_id=WinServer event_id=4672 label=Privilege label=Assign] as s2 on s1.
↪ user=s2.user | rename s1.log_ts
as log_ts, s1.user as user, s1.domain as domain, s1.user_id as user_id, s1.host as host
```

2.441 LP_Successful Overpass the Hash Attempt

- **Trigger Condition:** Successful logon with logon type 9 (NewCredentials), which matches the Overpass the Hash behavior of Mimikatz's sekurlsa::pth module is detected.
- **ATT&CK Category:** Lateral Movement, Defense Evasion
- **ATT&CK Tag:** T1550 - Use Alternate Authentication Material (2), T1550.002 - Pass the Hash (2)
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4624 logon_type="9" logon_process="seclogo" package=
↪ "Negotiate" -user IN EXCLUDED_USERS
```

2.442 LP_Suspect Svchost Activity Detected

- **Trigger Condition:** A suspicious Scvhost activity is detected. It is abnormal for svchost.exe to spawn without any CLI arguments and is observed when a malicious process spawns the process and injects code into the process memory space.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 image="*\svchost.exe" parent_image=* -parent_
↪ image IN ["*\rpcnet.exe", "\rpcnetp.exe", "\svchost.exe", "\Mrt.exe", "\MsMpEng.
↪ exe"] command=* command="*\svchost.exe" -user IN EXCLUDED_USERS
```

2.443 LP_Suspect Svchost Memory Access

- **Trigger Condition:** When access to svchost process memory such as that used by Invoke-Phantom to kill the winRM windows event logging service is detected. The "svchost.exe" process is a legitimate system that hosts multiple Windows services. However, adversaries may use this process to execute malicious code or gain unauthorized system access.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Disable or Modify Tools
- **ATT&CK ID:** T1562, T1562.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=10 image="*\windows\system32\svchost.exe"
↪access="0x1f3fff" call_trace="*unknown*" -user IN EXCLUDED_USERS
```

2.444 LP_Suspicious Access to Sensitive File Extensions

- **Trigger Condition:** Sensitive file extensions are detected.
- **ATT&CK Category:** Collection
- **ATT&CK Tag:** Data Staged
- **ATT&CK ID:** T1074
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5145 relative_target IN ["*.pst", "*.ost", "*.msg", "*.nst", "*.
↪oab", "*.edb", "*.nsf",
"*.bak", "*.dmp", "*.kirbi", "*\groups.xml", "*.rdp"] -user IN EXCLUDED_USERS
```

2.445 LP_Suspicious Calculator Usage Detected

- **Trigger Condition:** The use of calc.exe with command line parameters or in a suspicious directory, which is likely caused by some PoC or detection evasion, is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 (command="*\calc.exe*" OR (event_id=1 image=
↪ " *\calc.exe" -image="*\Windows\Sys*")) -user IN EXCLUDED_USERS
```

2.446 LP_Suspicious Call by Ordinal Detected

- **Trigger Condition:** When suspicious calls of DLLs through RUNDLL32 via ordinal. This search looks for executing scripts with rundll32. Adversaries may abuse rundll32.exe to proxy the execution of malicious code. Using rundll32.exe, vice executing directly, may avoid triggering security tools that may not monitor the execution of the rundll32.exe process because of allowlists or false positives from normal operations.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** Signed Binary Proxy Execution, Rundll32
- **ATT&CK ID:** T1218, T1218.011
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WinServer event_id=4688 "process"="*\rundll32.exe" command IN ["*,#*", "*,
↪ #*", " *.dll #*", " *.ocx #*"] -command IN ["*EDGEHTML.DLL*", " *#141*"] -user IN
↪ EXCLUDED_USERS
```

2.447 LP_Suspicious Certutil Command Detected

- **Trigger Condition:** A suspicious Microsoft certutil execution with subcommands like decode used to decode malicious code with the built-in certutil utility is detected.
- **ATT&CK Category:** Defense Evasion, Command and Control
- **ATT&CK Tag:** Ingress Tool Transfer, Deobfuscate/Decode Files or Information
- **ATT&CK ID:** T1140, T1105
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create ("process"="*\certutil.exe" OR file="CertUtil.exe")
↪ command IN ["* -decode *", "*/decode *", " *-decodehex *", "*/decodehex *", " *-
↪ urlcache *", "*/urlcache *", " *-verifyctl *", "*/verifyctl *", " *-encode *", "*/encode *",
↪ " *certutil* -URL*", " *certutil* /URL*", " *certutil* -ping*", " *certutil* (continues on next page)
↪ exportPFX *", " *-exportPFX *"] -user IN EXCLUDED_USERS
```

(continued from previous page)

2.448 LP_Suspicious Code Page Switch Detected

- **Trigger Condition:** Code page switch in a command line or batch scripts to a rare language is detected.
- **ATT&CK Category:** Defense Evasion, Discovery
- **ATT&CK Tag:** Masquerading, System Language Discovery
- **ATT&CK ID:** T1036, T1614.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\chcp.com" command IN ["* 936", "* 1258"] -  
↪ user IN EXCLUDED_USERS
```

2.449 LP_Suspicious Commandline Escape Detected

- **Trigger Condition:** Suspicious processes that use escape characters are detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Deobfuscate/Decode Files or Information
- **ATT&CK ID:** T1140
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=create label="process" command IN ["*h^t^t^p*", "*h\t\t\p*"]
```

2.450 LP_Suspicious Compression Tool Parameters

- **Trigger Condition:** Suspicious command line arguments of common data compression tools, such as 7z and Rar are detected.
- **ATT&CK Category:** Collection, Exfiltration

- **ATT&CK Tag:** Automated Exfiltration, Archive Collected Data
- **ATT&CK ID:** T1020, T1560
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ((file IN ["7z*.exe", "*.rar.exe", "*Command*Line*RAR*"]
↪ OR "process" IN ["*\\7z*.exe", "*\\rar.exe"]) command IN ["*-p*", "*-ta*", "*-tb*", "*-
↪ sdel*", "*-dw*", "*-hp*"]) OR (((("process"="*/powershell.exe" OR file="powershell.exe
↪ ") command="*-Recurse Compress-Archive*") OR ((("process"="*/rar.exe" OR file IN [
↪ "*rar.exe", "*Command*Line*RAR*"]) command="*rar* a*") -parent_process=
↪ "C:\\Program*")
```

2.451 LP_Suspicious Control Panel DLL Load Detected

- **Trigger Condition:** Execution of a suspicious Signed Binary Proxy Execution or Rundll32 from *control.exe* used by Equation Group and Exploit Kits is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Rundll32
- **ATT&CK ID:** T1218.011
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process="*\\System32\\control.exe" command=
↪ "*\\rundll32.exe *" -command="*Shell32.dll*"
```

2.452 LP_Suspicious Csc Source File Folder Detected

- **Trigger Condition:** Execution of csc.exe that uses a source in a suspicious folder is detected. For example, AppData.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** Obfuscated Files or Information, Compile After Delivery, User Execution, Native API
- **ATT&CK ID:** T1027, T1027.004, T1204, T1106
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

- **Query:**

```
label="process" label=create "process"="*\csc.exe" command IN ["*\AppData\*",
↪ ".*\Windows\Temp\*"] -(parent_process="*:\Program Files*" OR parent_process in [
↪ ".*\sdiagnhost.exe", ".*\w3wp.exe", ".*\choco.exe"] OR parent_command=
↪ ".*\ProgramData\Microsoft\Windows Defender Advanced Threat Protection*") -user IN
↪ EXCLUDED_USERS
```

2.453 LP_Suspicious Debugger Registration Detected

- **Trigger Condition:** Registration of a debugger for a program available in the login screen (sticky key backdoor) is detected.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Event Triggered Execution, Accessibility Features
- **ATT&CK ID:** T1546, T1546.008
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create command IN ["*\CurrentVersion\Image File Execution
↪ Options\sethc.exe*", ".*\CurrentVersion\Image File Execution Options\utilman.exe*",
↪ ".*\CurrentVersion\Image File Execution Options\osk.exe*", ".*\CurrentVersion\Image
↪ File Execution Options\magnify.exe*", ".*\CurrentVersion\Image File Execution
↪ Options\narrator.exe*", ".*\CurrentVersion\Image File Execution Options\displayswitch.
↪ exe*", ".*\CurrentVersion\Image File Execution Options\atbroker.exe*"]
```

2.454 LP_Suspicious Double Extension Detected

- **Trigger Condition:** Double extension of a file is detected. Adversaries use double extensions to mask the real file extension and evade detection by security software or bypass whitelisting.
- **ATT&CK Category:** Initial Access, Defense Evasion
- **ATT&CK Tag:** Double File Extension, Spearphishing Attachment, Masquerading
- **ATT&CK ID:** T1036.007, T1566.001, T1036
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ("process" IN ["*.doc.exe", "*.docx.exe", "*.doc.lnk", "*.docx.lnk", "*.xls.lnk", "xls.lnk", "*.ppt.lnk", "*.pptx.lnk", "*.rtf.lnk", "*.pdf.lnk", "*.txt.lnk", "*.doc.js", "*.docx.js", "*.xls.js", "*.xlsx.js", "*.ppt.js", "*.pptx.js", "*.rtf.js", "*.pdf.js", "*.txt.js", "*.tmp.bat", "*.xls.exe", "*.bat.exe", "*.xlsx.exe", "*.ppt.exe", "*.pptx.exe", "*.rtf.exe", "*.pdf.exe", "*.bat.exe", "*.txt.exe", "*.exe", "*_.exe"] OR command IN ["*.doc.exe*", "*.docx.exe*", "*.doc.lnk*", "*.docx.lnk*", "*.xls.lnk*", "*.xlsx.lnk*", "*.ppt.lnk*", "*.pptx.lnk*", "*.rtf.lnk*", "*.pdf.lnk*", "*.txt.lnk*", "*.doc.js*", "*.docx.js*", "*.xls.js*", "*.xlsx.js*", "*.ppt.js*", "*.pptx.js*", "*.rtf.js*", "*.pdf.js*", "*.txt.js*", "*.tmp.bat*", "*.xls.exe*", "*.bat.exe*", "*.xlsx.exe*", "*.ppt.exe*", "*.pptx.exe*", "*.rtf.exe*", "*.pdf.exe*", "*.bat.exe*", "*.txt.exe*", "*.exe*", "*_.exe*"] )
```

2.455 LP_Suspicious Driver Load from Temp

- **Trigger Condition:** Driver load from a temporary directory is detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** New Service
- **ATT&CK ID:** T1543
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=6 image="*\\Temp\\*" -user IN EXCLUDED_USERS
```

2.456 LP_Suspicious Eventlog Clear or Configuration Using Wevtutil Detected

- **Trigger Condition:** Clearing or configuration of eventlogs using wevtutil, PowerShell and wmic is detected. It is used by ransomware during the attack as seen by NotPetya and others.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Indicator Removal on Host
- **ATT&CK ID:** T1070
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Process" label=Create (((("process" IN ["*\powershell.exe", "*\pwsh.exe"]
↪command IN ["*Clear-EventLog*", "*Remove-EventLog*", "*Limit-EventLog*", "*Clear-
↪WinEvent*"]) OR ("process"="*\wmic.exe" command="* ClearEventLog *")) OR (
↪"process"="*\wevtutil.exe" command IN ["*clear-log*", "*cl*", "*set-log*", "*sl *"]) -
↪user IN EXCLUDED_USERS
```

2.457 LP_Suspicious Execution from Outlook

- **Trigger Condition:** *EnableUnsafeClient MailRules* used for Script Execution from Outlook is detected.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** Command and Scripting Interpreter, Indirect Command Execution
- **ATT&CK ID:** T1059, T1202
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (command="*EnableUnsafeClientMailRules*" OR (parent_
↪process="*\outlook.exe" command="\\*\*.exe")) -user IN EXCLUDED_USERS
```

2.458 LP_Suspicious GUP Usage Detected

- **Trigger Condition:** Execution of the Notepad++ updater in a suspicious directory used in DLL side-loading attacks is detected.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation
- **ATT&CK Tag:** Hijack Execution Flow, DLL Side-Loading
- **ATT&CK ID:** T1574, T1574.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\GUP.exe" -(("process" IN ["*\Program
↪Files\Notepad++\updater\GUP.exe", "*\Program Files (x86)\Notepad++\updater\GUP.
↪exe"]) OR ("process"="*\Users\*" "process" IN [
↪"*\AppData\Local\Notepad++\updater\GUP.exe",
↪"*\AppData\Roaming\Notepad++\updater\GUP.exe"])))
```

2.459 LP_Suspicious HWP Sub Processes Detected

- **Trigger Condition:** Hangul Word Processor (Hanword) sub-processes that could indicate exploitation are detected.
- **ATT&CK Category:** Execution, Initial Access
- **ATT&CK Tag:** Windows Command Shell, Exploitation for Client Execution, Spearphishing Attachment
- **ATT&CK ID:** T1059.003, T1203, T1566.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process="*\Hwp.exe" "process"="*\gbb.exe" -
↪user IN EXCLUDED_USERS
```

2.460 LP_Suspicious In-Memory Module Execution Detected

- **Trigger Condition:** An access to processes by other suspicious processes that have reflectively loaded libraries in their memory space are detected.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=10 (call_trace IN ["C:\Windows\SYSTEM32\ntdll.dll+*"
↪", "C:\Windows\System32\KERNELBASE.dll+*", "*UNKNOWN(*)"] OR (call_trace=
↪"*UNKNOWN*" access IN ["0x1F0FFF", "0x1F1FFF", "0x143A", "0x1410", "0x1010",
↪"0x1F2FFF", "0x1F3FFF", "0x1FFFFF"])) -user IN EXCLUDED_USERS
```

2.461 LP_Suspicious Kerberos RC4 Ticket Encryption

- **Trigger Condition:** Service ticket requests using the RC4 encryption type are detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Steal or Forge Kerberos Tickets, Kerberoasting
- **ATT&CK ID:** T1558, T1558.003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4769 ticket_option="0x40810000" Encryption_type="0x17" -
↪ service="$*" -user IN EXCLUDED_USERS
```

2.462 LP_Suspicious MsiExec Directory Detected

- **Trigger Condition:** Suspicious *msiexec* process starting in an uncommon directory is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\msiexec.exe" -"process" IN [
↪ "C:\Windows\System32\*", "C:\Windows\SysWOW64\*", "C:\Windows\WinSxS\*"]
```

2.463 LP_Suspicious Named Pipes Detected

- **Trigger Condition:** Suspicious named pipes commonly used by threat actors are detected.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation, Lateral Movement
- **ATT&CK Tag:** Process Injection, Lateral Tool Transfer

- **ATT&CK ID:** T1055, T1570
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id IN ["17", "18"] pipe IN ["\isapi_http", "\isapi_dg",
↪ "\isapi_dg2", "\sdlrpc", "\ahexec", "\winsession", "\lsassw",
↪ "\46a676ab7f179e511e30dd2dc41bd388", "\9f81f59bc58452127884ce513865ed20",
↪ "\e710f28d59aa529d6792ca6ff0ca1b34", "\rpchlp_3", "\NamePipe_MoreWindows",
↪ "\pcheap_reuse", "\msagent_", "\gruntsvc", "\PSEXESVC*",
↪ "\PowerShellISEPipeName_", "\csexec", "\paexec", "\remcom", "\lsadump",
↪ "\cachedump", "\wcservicepipe", "\psexec", "\mojo.5688.8052.183894939787088877",
↪ "\mojo.5688.8052.35780273329370473", "\mypipe-f", "\mypipe-h", "\ntsvcs_",
↪ "\scerpc_", "\DserNamePipe", "\srsvsvc_", "\lstatus_", "\MSSE-", "\postex_", "\spoolss_
↪ ", "\winsock", "\win_svc", "\dce_86"]
```

2.464 LP_Suspicious Outbound Kerberos Connection

- **Trigger Condition:** Suspicious outbound network activity via kerberos is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Steal or Forge Kerberos Tickets, Kerberoasting
- **ATT&CK ID:** T1558, T1558.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
norm_id=Windows* (event_id=3 OR event_id=5156) destination_port="88" is_initiated=
↪ "true" - "process" IN ["C:\Windows\System32\lsass.exe", "C:\Program
↪ Files\Google\Chrome\Application\chrome.exe", "C:\Program Files\Mozilla
↪ Firefox\firefox.exe"] -user IN EXCLUDED_USERS
```

2.465 LP_Suspicious Outbound RDP Connections Detected

- **Trigger Condition:** Non-Standard tools connecting to TCP port 3389 indicating possible Lateral Movement are detected.
- **ATT&CK Category:** Lateral Movement

- **ATT&CK Tag:** Exploitation of Remote Services
- **ATT&CK ID:** T1210
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=3 destination_port="3389" initiated="true" -image
↪ IN ["*\mstsc.exe", ".*\RTSApp.exe", ".*\RTS2App.exe", ".*\RDCMan.exe", ".*\ws_
↪ TunnelService.exe", ".*\RSSensor.exe",
".*\RemoteDesktopManagerFree.exe", ".*\RemoteDesktopManager.exe",
↪ ".*\RemoteDesktopManager64.exe", ".*\mRemoteNG.exe", ".*\mRemote.exe",
↪ ".*\Terminals.exe", ".*\spiceworks-finder.exe", ".*\FSDiscovery.exe", ".*\FSAssessment.exe
↪ ", ".*\MobaRTE.exe", ".*\chrome.exe", ".*\thor.exe", ".*\thor64.exe"] -user IN
↪ EXCLUDED_USERS
```

2.466 LP_Suspicious Parent of Csc Detected

- **Trigger Condition:** Suspicious parent of csc.exe is detected. It is an executable file part of the Microsoft .NET framework.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** Compile After Delivery, Visual Basic, JavaScript, Mshta
- **ATT&CK ID:** T1027.004, T1059.005, T1059.007, T1218.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"=".*\csc.exe*" parent_process IN [".*\wscript.exe",
↪ ".*\cscript.exe", ".*\mshta.exe"] -user IN EXCLUDED_USERS
```

2.467 LP_Suspicious PowerShell Invocation Based on Parent Process

- **Trigger Condition:** Suspicious PowerShell invocations from interpreters or unusual programs like wscript or IIS worker process(w3wp.exe) are detected. Admins can add other suspicious parent processes to increase visibility.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell

- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create parent_process IN ["*\mshta.exe", ".*\wscript.exe",
↪ ".*\cscript.exe", ".*\rundll32.exe", ".*\regsvr32.exe", ".*\services.exe", ".*\winword.exe",
↪ ".*\wmiprvse.exe", ".*\powerpnt.exe", ".*\excel.exe", ".*\msaccess.exe", ".*\mspub.exe",
↪ ".*\visio.exe", ".*\outlook.exe", ".*\amigo.exe", ".*\chrome.exe", ".*\firefox.exe",
↪ ".*\iexplore.exe", ".*\microsoftedgecp.exe", ".*\microsoftedge.exe", ".*\browser.exe",
↪ ".*\vivaldi.exe", ".*\safari.exe", ".*\sqlagent.exe", ".*\sqlserver.exe", ".*\sqlservr.exe",
↪ ".*\w3wp.exe", ".*\httpd.exe", ".*\nginx.exe", ".*\php-cgi.exe", ".*\jbossvc.exe",
↪ ".*\MicrosoftEdgeSH.exe", ".*\tomcat*"] "process"=".*\powershell.exe" -path=".*\Health[?]
↪ Service State\*"
```

2.468 LP_Suspicious PowerShell Parameter Substring Detected

- **Trigger Condition:** PowerShell invocation with a suspicious parameter substring is detected. PowerShell offers a commandline shell and a scripting language for automating and managing tasks.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=create label="process" "process"=".*\powershell.exe" command IN [".*-en*", ".*-
↪ ec*", ".*-nonj*", ".*-nop*", ".*-exe* bypass*", ".*-ep bypass*", ".*-win* hid*", ".*-w hid*
↪ ", ".*-sta*", ".*FromBase64String*"]
```

2.469 LP_Suspicious Process Start Locations Detected

- **Trigger Condition:** Execution of suspicious processes from unusual locations like Recycle bin or Fonts folder is detected. Adversaries often run malicious scripts or applications from unusual locations like temporary folders or recycle bin folders.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process" IN ["*:\RECYCLER\*",
↪ "*:\SystemVolumeInformation\*", "C:\Windows\Tasks\*", "C:\Windows\debug\*",
↪ "C:\Windows\fonts\*", "C:\Windows\help\*", "C:\Windows\drivers\*",
↪ "C:\Windows\addins\*", "C:\Windows\cursors\*", "C:\Windows\system32\tasks\*",
↪ "*\Windows\IME\*", "C:\Perflogs\*"] -user IN EXCLUDED_USERS
```

2.470 LP_Suspicious Program Location with Network Connections

- **Trigger Condition:** Network connections run in suspicious file system locations.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=3 "process" IN ["*\\$Recycle.bin", "*\\Users\\All Users\\*",
↪ "*\\Users\\Default\\*", "*\\Users\\Public\\*", "*\\Users\\Contacts\\*", "*\\Users\\Searches\\*",
↪ "C:\\Perflogs\\*", "*\\config\\systemprofile\\*", "*\\Windows\\Fonts\\*", "*\\Windows\\IME\\*",
↪ "*\\Windows\\addins\\*"] -user IN EXCLUDED_USERS
```

2.471 LP_Suspicious PsExec Execution Detected

- **Trigger Condition:** Execution of *psexec* or *paexec* with the renamed service name. This rule helps filter out the noise if *psexec* is used for legitimate purposes or if an attacker uses a different *psexec* client other than *sysinternal* one.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote Services
- **ATT&CK ID:** T1021

- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5145 share_name="IPC$" relative_target IN ["*-stdin", "*-
↳stdout", "*-stderr"] -relative_target="PSEXESVC*" -user IN EXCLUDED_USERS
```

2.472 LP_Suspicious RDP Redirect Using TSCON Detected

- **Trigger Condition:** A suspicious Remote Desktop Protocol (RDP) session redirect using `tscon.exe` is detected.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote Services, Remote Desktop Protocol
- **ATT&CK ID:** T1021, T1021.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 command="*/dest:rdp-tcp:*" -user IN EXCLUDED_
↳USERS
```

2.473 LP_Suspicious Remote Thread Created

- **Trigger Condition:** The suspicious processes (like `word.exe` or `outlook.exe`) create remote threads on other processes. This technique is used by malware to inject code and hide in other processes. The event indicates the source and target process. It gives information on the code that will run in the new thread: `StartAddress`, `StartModule` and `StartFunction`.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=8 "process" IN ["*\\bash.exe", "*\\cvtres.exe",
↪ "*\\defrag.exe", "*\\dnx.exe", "*\\esentutl.exe", "*\\excel.exe", "*\\expand.exe",
↪ "*\\explorer.exe", "*\\find.exe", "*\\findstr.exe", "*\\forfiles.exe", "*\\git.exe", "*\\gpupdate.
↪ exe", "*\\hh.exe", "*\\iexplore.exe", "*\\installutil.exe", "*\\lync.exe", "*\\makecab.exe",
↪ "*\\mDNSResponder.exe", "*\\monitoringhost.exe", "*\\msbuild.exe", "*\\mshta.exe",
↪ "*\\msiexec.exe", "*\\mspaint.exe", "*\\outlook.exe", "*\\ping.exe", "*\\powerpnt.exe",
↪ "*\\powershell.exe", "*\\provtool.exe", "*\\python.exe", "*\\regsvr32.exe", "*\\robocopy.
↪ exe", "*\\runonce.exe", "*\\sapcimc.exe", "*\\schtasks.exe", "*\\smartscreen.exe",
↪ "*\\spoolsv.exe", "*\\tstheme.exe", "*\\userinit.exe", "*\\vssadmin.exe", "*\\vssvc.exe",
↪ "*\\w3wp.exe", "*\\winlogon.exe", "*\\winscp.exe", "*\\wmic.exe", "*\\word.exe",
↪ "*\\wscript.exe"] - "process" = "Visual Studio*" -user IN EXCLUDED_USERS
```

2.474 LP_Suspicious RUN Key from Download Detected

- **Trigger Condition:** A suspicious RUN keys created by software located in the Download or temporary Outlook/Internet Explorer directories.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Boot or Logon Autostart Execution, Registry Run Keys/Startup Folder
- **ATT&CK ID:** T1547, T1547.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 "process" IN ["*\\Downloads\\*", "*\\Temporary
↪ Internet Files\\Content.Outlook\\*", "*\\Local Settings\\Temporary Internet Files\\*"] target_
↪ object= "*\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\Run\\*" -user IN EXCLUDED_
↪ USERS
```

2.475 LP_Suspicious Rundll32 Activity Detected

- **Trigger Condition:** Suspicious processes related to the RunDLL32 binary based on its command-line arguments are detected. Adversaries may abuse RunDLL32 to proxy code executions and avoid triggering security tools that may not monitor the execution of the *rundll32.exe* process because of allowlists or false positives from normal operations. Whitelisting is required due to the inherent RunDLL32 noise.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** Rundll32
- **ATT&CK ID:** T1218.011
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create ("process"="*\rundll32.exe" OR file="rundll32.exe")
↪ ((command="*javascript:*" command="*.RegisterXLL*") OR (command="*url.dll*"
↪ (command="*OpenURL*" OR command="*FileProtocolHandler*")) OR (command=
↪ "*zipfldr.dll*" command="*RouteTheCall*") OR (command="*shell32.dll*" (command=
↪ "*Control_RunDLL*" OR command="*ShellExec_RunDLL*")) OR (command="*mshtml.
↪ dll*" command="*PrintHTML*") OR (command="*advpack.dll*" (command=
↪ "*LaunchINFSection*" OR command="*RegisterOCX*")) OR ((command="*ieframe.dll*"
↪ " OR command="*shdocvw.dll*" command="*OpenURL*" OR (command="*syssetup.
↪ dll*" command="*SetupInfObjectInstallAction*") OR (command="*setupapi.dll*"
↪ command="*InstallHinfSection*") OR (command="*pcwutl.dll*" command=
↪ "*LaunchApplication*") OR (command="*dfshim.dll*" (command=
↪ "*ShOpenVerbApplication*" OR command="*ShOpenVerbShortcut*")) OR ((command=
↪ "*scrobj.dll*" command="*GenerateTypeLib*") OR (command="*shimgvw.dll*"
↪ command="*ImageView_Fullscreen*") command="*http*") OR (command="*comsvcs.
↪ dll*" command="*MiniDump*") OR (command IN ["*C:\Perflogs*", "*C:\ProgramData\*
↪ ", "*AppData\Local\Temp*", "*C:\Users\Public*"])) -((command="*shell32.dll,Control_
↪ RunDLL desk.cpl,screensaver,@screensaver*") OR (parent_process=
↪ "C:\Windows\System32\control.exe" command="*.cpl*" (parent_command=* parent_
↪ command="*.cpl*" command="*Shell32.dll*" command="*Control_RunDLL*") OR
↪ (command="*rundll32*Shell32.dll,Control_RunDLL*C:\Windows\System32\*")) | chart
↪ count() by command
```

2.476 LP_Suspicious Scripting in a WMI Consumer

- **Trigger Condition:** Suspicious scripting in the WMI Event Consumers.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=20 destination IN ["*new-object .webclient).
↪ downloadstring(*", "*new-object .webclient).downloadfile(*", "*new-object net.
↪ webclient).downloadstring(*", "*new-object net.webclient).downloadfile(*", "*iex(*",
↪ "*WScript.shell*", "*-nop*", "*-nopprofile*", "*-decode*", "*-enc*"] -user IN
↪ EXCLUDED_USERS
```

(continues on next page)

(continued from previous page)

2.477 LP_Suspicious Service Path Modification Detected

- **Trigger Condition:** Modification of service path to *powershell/cmd* is detected.
- **ATT&CK Category:** Persistence, Privilege Escalation
- **ATT&CK Tag:** Windows Service
- **ATT&CK ID:** T1543.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\sc.exe" command="*config*" command=
↪ "*binpath*" command ln ["*powershell*", "*cmd*", "*mshta*", "*wscript*", "*cscript*",
↪ "*rundll32*", "*svchost*", "*dllhost*", "*cmd.exe /c*", "*cmd.exe /k*", "*cmd.exe /r*",
↪ "*cmd /c*", "*cmd /k*", "*cmd /r*", "*C:\Users\Public*", "*\Downloads\*",
↪ "*\Desktop\*", "*\Microsoft\Windows\Start Menu\Programs\Startup\*",
↪ "*C:\Windows\TEMP\*", "\AppData\Local\Temp"]
```

2.478 LP_Suspicious Svchost Process Detected

- **Trigger Condition:** Any suspicious svchost process creation is detected. Svchost is essential in implementing shared service processes, where a number of services can share a process to reduce resource consumption.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Masquerading, Match Legitimate Name or Location, Process Injection
- **ATT&CK ID:** T1036, T1036.005, T1055
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\svchost.exe" -parent_process IN [
↪ "*\MsMpEng.exe", "*\Mrt.exe", "*\rpcnet.exe", "C:\Windows\System32\svchost.exe"] (-
↪ parent_process="*\services.exe" -command="* -k *") parent_process=* -user IN[?]
↪ EXCLUDED_USERS
```

2.479 LP_Suspicious TSCON Start

- **Trigger Condition:** `tscon.exe` process execution as LOCAL SYSTEM is detected. If `tscon.exe` run as SYSTEM, users can gain access to the currently logged-in session without credential.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Remote Access Software
- **ATT&CK ID:** T1219
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create user IN ["SYSTEM", "*AUTHOR*", "*AUTOR*"] "process"=
↳ "*\\tscon.exe" -user IN EXCLUDED_USERS
```

2.480 LP_Suspicious Typical Malware Back Connect Ports Detected

- **Trigger Condition:** Programs connecting to a typical malware back connect ports based on statistical analysis from two different sandbox system databases are detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Non-Standard Port
- **ATT&CK ID:** T1571
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
destination_port IN ["4443", "2448", "8143", "1777", "1443", "243", "65535", "13506",
↳ "3360", "200", "198", "49180", "13507", "6625", "4444", "4438", "1904", "13505",
↳ "13504", "12102", "9631", "5445",
"2443", "777", "13394", "13145", "12103", "5552", "3939", "3675", "666", "473", "5649",
↳ "4455", "4433", "1817", "100", "65520", "1960", "1515", "743", "700", "14154", "14103",
↳ "14102", "12322", "10101", "7210", "4040", "9943"] -image="*\\Program Files*"
-destination_address IN HOMENET -user IN EXCLUDED_USERS
```

2.481 LP_Suspicious CSharp or FSharp Interactive Console Execution

- **Trigger Condition:** Execution of CSharp or FSharp interactive console by scripting utilities like WScript or PowerShell is detected. The alert warns you of the use of the .NET framework by attackers for offensive purposes.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Trusted Developer Utilities Proxy Execution
- **ATT&CK ID:** T1127
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process" IN ["*\csi.exe", "*\fsi.exe"] parent_process IN [
↪ ".*\cmd.exe", ".*\powershell.exe", ".*\wscript.exe", ".*\cscript.exe"] -user IN EXCLUDED_
↪ USERS
```

2.482 LP_Suspicious Userinit Child Process

- **Trigger Condition:** Suspicious process spawned by *Userinit* is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" (parent_process="*\userinit.exe" -(command=
↪ ".*\netlogon\*" OR ("process"=".*\explorer.exe" OR file="explorer.exe")) -user IN?
↪ EXCLUDED_USERS
```

2.483 LP_Suspicious Windows ANONYMOUS LOGON Local Account Creation

- **Trigger Condition:** Creation of suspicious accounts similar to ANONYMOUS LOGON like using additional spaces, is detected. It is created to catch the exclusion of Logon Type 3 from ANONYMOUS LOGON accounts.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Create Account
- **ATT&CK ID:** T1136
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4720 user="*ANONYMOUS*LOGON*" -user IN [
  ↳ EXCLUDED_USERS
```

2.484 LP_Suspicious WMI Execution Detected

- **Trigger Condition:** When WMI executing suspicious commands, including but not limited to AV product enumeration and remote process creation, are detected. WMIC.exe is a built-in Microsoft program that allows command-line access to the Windows Management Instrumentation. Adversaries can use this technique to create remote or local processes, get details about antivirus and firewalls, delete shadow copies and modify defender configurations.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Windows Management Instrumentation
- **ATT&CK ID:** T1047
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ("process"="*\wmic.exe" or file=wmic.exe) command IN [
  ↳ "*/node:*process call create *", "*/path AntiVirusProduct get *", "*/path FirewallProduct
  ↳ get *", "*/shadowcopy delete *", "*/csproduct get*UUID*",
  ↳ "*/NAMESPACE:\root\Microsoft\Windows\Defender*"]
```

2.485 LP_Svchost DLL Search Order Hijack Detected

- **Trigger Condition:** Svchost DLL Search Order Hijack is detected. By default, IKEEXT and SessionEnv service call LoadLibrary on files that does not exist within C:/Windows/System 32/. An attacker can place their malicious logic within the PROCESS_ATTACH block of their library and restart the services mentioned above `svchost.exe -k netsvcs` to gain code execution on a remote machine.
- **ATT&CK Category:** Persistence, Privilege Escalation, Defense Evasion
- **ATT&CK Tag:** Hijack Execution Flow, DLL Side-Loading, DLL Search Order Hijacking
- **ATT&CK ID:** T1574, T1574.002, T1574.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 "process" IN ["*\\svchost.exe"] image IN [
↪ "*\\tsmsisrv.dll", "*\\tsvipsrv.dll", "*\\wlbsctrl.dll"] -image IN ["C:\\Windows\\WinSxS\\*"] -
↪ user IN EXCLUDED_USERS
```

2.486 LP_SysKey Registry Keys Access

- **Trigger Condition:** Requests and access operations to specific registry keys to calculate the SysKey are detected. Adversaries uses a tool (like Mimikatz) or a script (like Invoke-PowerDump) to get the SysKey to decrypt Security Account Manager (SAM) database entries from registry or hive and get NTLM and LM hashes of local accounts passwords.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Query Registry
- **ATT&CK ID:** T1012
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id IN [4656, 4663] object_type="key" object_name IN ["*\\sa\\JD
↪ ", "*\\sa\\GBG", "*\\sa\\Skew1", "*\\sa\\Data"]
-user IN EXCLUDED_USERS
```

2.487 LP_Sysmon Configuration Modification Detected

- **Trigger Condition:** Modification in Sysmon configuration.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Indicator Blocking
- **ATT&CK ID:** T1562, T1562.006
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=Sysmon label=Config label=Change -user IN EXCLUDED_USERS
```

2.488 LP_Sysmon Driver Unload Detected

- **Trigger Condition:** Unloading of Sysmon driver is detected. After error events are logged, logs will not be collected and parsed by Sysmon.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Disable or Modify Tools
- **ATT&CK ID:** T1562, T1562.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=255 id="DriverCommunication" -user IN EXCLUDED_USERS
```

2.489 LP_Sysmon Error Event Detected

- **Trigger Condition:** Sysmon error event is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Disable or Modify Tools
- **ATT&CK ID:** T1562, T1562.001

- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=255 -user IN EXCLUDED_USERS
```

2.490 LP_System File Execution Location Anomaly Detected

- **Trigger Condition:** Starting a Windows program executable in a suspicious folder is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Masquerading
- **ATT&CK ID:** T1036
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create
"process" IN ["*\\svchost.exe", "*\\rundll32.exe", "*\\services.exe", "*\\powershell.exe",
↪ "*\\powershell_ise.exe", "*\\pwsh.exe", "*\\regsvr32.exe", "*\\spoolsv.exe", "*\\lsass.exe",
↪ "*\\smss.exe", "*\\csrss.exe", "*\\conhost.exe", "*\\wininit.exe", "*\\lsmd.exe", "*\\winlogon.
↪ exe", "*\\explorer.exe", "*\\taskhost.exe", "*\\Taskmgr.exe", "*\\sihost.exe",
↪ "*\\RuntimeBroker.exe", "*\\smartscreen.exe", "*\\dllhost.exe", "*\\audiodg.exe",
↪ "*\\wlanext.exe", "*\\dashost.exe", "*\\schtasks.exe", "*\\cscript.exe", "*\\wscript.exe",
↪ "*\\wsl.exe", "*\\bitsadmin.exe", "*\\atbroker.exe", "*\\bcdedit.exe", "*\\certutil.exe",
↪ "*\\certreq.exe", "*\\cmstp.exe", "*\\consent.exe", "*\\defrag.exe", "*\\dism.exe",
↪ "*\\dllhst3g.exe", "*\\eventvwr.exe", "*\\msiexec.exe", "*\\runonce.exe", "*\\winver.exe",
↪ "*\\logonui.exe", "*\\userinit.exe", "*\\dwm.exe", "*\\Lsalso.exe", "*\\ntoskrnl.exe",
↪ "*\\wsmprovhost.exe", "*\\dfrgui.exe"]
- ("process" IN ["C:\\Windows\\System32\\*", "C:\\Windows\\SysWOW64\\*",
↪ "C:\\Windows\\WinSxS\\*", "*\\SystemRoot\\System32\\*", "C:\\Windows\\explorer.exe",
↪ "C:\\Program Files\\PowerShell\\7\\pwsh.exe", "C:\\Program
↪ Files\\WindowsApps\\MicrosoftCorporationII.WindowsSubsystemForLinux*\\wsl.exe"])
```

2.491 LP_System Service Discovery

- **Trigger Condition:** When an adversary attempts to get information about registered services is detected.

- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** System Service Discovery
- **ATT&CK ID:** T1007
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process" IN ["*\net.exe", "*\tasklist.exe", "*\sc.exe",
↪ "*\wmic.exe"] command IN ["*\net.exe* start*", "*\tasklist.exe* /SVC", "*\sc.exe* query*",
↪ "*\wmic.exe* service where*"]
```

2.492 LP_Tap Driver Installation Detected

- **Trigger Condition:** Installation of TAP software. It indicates possible preparation for data exfiltration using tunneling techniques.
- **ATT&CK Category:** Exfiltration
- **ATT&CK Tag:** Exfiltration Over Alternative Protocol
- **ATT&CK ID:** T1048
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
((norm_id=WindowsSysmon event_id=6) OR (norm_id=WinServer (event_id=7045 OR↪
↪ event_id=4697))) (path="*\tap0901*" OR file="*\tap0901*") -user IN EXCLUDED_USERS
```

2.493 LP_Tasks Folder Evasion Detected

- **Trigger Condition:** Evasion of task folder is detected. Task folder in system32 and syswow64 are globally writable paths. Adversaries can load or influence script hosts, or any .NET application in task to load and execute a custom assembly into cscript, wscript, regsvr32, mshta, and eventvwr.
- **ATT&CK Category:** Persistence, Privilege Escalation, Defense Evasion
- **ATT&CK Tag:** Hijack Execution Flow, DLL Side-Loading
- **ATT&CK ID:** T1574, T1574.002
- **Minimum Log Source Requirement:** Windows Sysmon

- **Query:**

```
norm_id=WinServer event_id=4688 command IN ["*echo *", "*copy *", "*type *", "*file*",
↪ *createnew*"] command IN ["* C:\Windows\System32\Tasks\*", "* C:\Windows\SysWow64\Tasks\*"]
```

2.494 LP_Terminal Service Process Spawn Detected

- **Trigger Condition:** Process spawned by the terminal service server process is detected. It can be used as an indicator for the exploitation of CVE-2019-0708.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Exploitation of Remote Services
- **ATT&CK ID:** T1210
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_command="*\svchost.exe*termsvcs"- "process" IN [
↪ "*\rdpclip.exe", "*\Windows\System32\csrss.exe*", "*\Windows\System32\wininit.exe",
↪ "*\Windows\System32\winlogon.exe"]
```

2.495 LP_Threat Intel Allowed Connections from Suspicious Sources

- **Trigger Condition:** A connection from suspicious sources are detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
norm_id=* label=Allow label=Connection -source_address in HOMENET destination_
↪ address in HOMENET | process ti(source_address) | rename et_ip_address as
↪ SourceAddress, cs_ip_address as SourceAddress, et_category as Category,
cs_category as Category, rf_ip_address as SourceAddress, rf_category as Category, et_
↪ score as Score, cs_score as Score, rf_score as Score, destination_port as Port | fields
↪ Category, SourceAddress, Score, Port
```

2.496 LP_Threat Intel Connections with Suspicious Domains

- **Trigger Condition:** A connection is established with a suspicious domain.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Firewall, IDS/IPS
- **Query:**

```
label=Connection (url=* OR domain=*) | process domain(url) as domain | process
  ↳ ti(domain) | rename et_category as Category, cs_category as Category, rf_category as
  ↳ Category, et_score as Score, cs_score as Score, rf_score as Score, rf_domain as Domain,
  ↳ et_domain as Domain, cs_domain as Domain
```

2.497 LP_Time-Stomping of Users Directory Files Detected

- **Trigger Condition:** Time-stomping of user directory file is detected. Sysmon can only detect a change of CreationTime and not LastWriteTime and LastAccessTime. Therefore, we recommend that whitelist legitimate noisy processes like browsers, slack, or teams to reduce false positives.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Indicator Removal on Host, Timestomp
- **ATT&CK ID:** T1070, T1070.006
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=2 path="C:\Users*" -source_image IN ["*iexplore.exe
  ↳ ", "*cortana*", "*\StartMenuExperienceHost.exe", "C:\Windows\system32\cleanmgr.exe
  ↳ ", "C:\Windows\Explorer.EXE", "*\LocalBridge.exe", "*\svchost.exe",
  ↳ "*\RuntimeBroker.exe", "*\msedge.exe"]-path=
  ↳ "*\AppData\Roaming\Microsoft\Windows\Recent\CustomDestinations" -user IN
  ↳ EXCLUDED_USERS
```

2.498 LP_Transfering Files with Credential Data via Network Shares

- **Trigger Condition:** Transfer of sensitive files with credential data using a network share.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5145 relative_target IN ["*\mimidrv*", ".*\sass*",
↪ ".*\windows\minidump\*", ".*\hiberfil*", ".*\sqldmpr*", ".*\sam*", ".*\ntds.dit*",
↪ ".*\security*"] -user IN EXCLUDED_USERS
```

2.499 LP_TrendMicroDeepSecurity Virus Quarantined

- **Trigger Condition:** A virus-infected file is quarantined.
- **ATT&CK Category:** Defense Evasion, Discovery
- **ATT&CK Tag:** Obfuscated Files or Information, Indicator Removal from Tools, Network Service Scanning
- **ATT&CK ID:** T1027, T1027.005, T1046
- **Minimum Log Source Requirement:** Trend Micro Deep Security
- **Query:**

```
norm_id=TrendMicroDeepSecurity label=Virus OR label=Malware label=File
↪ label=Quarantine
```

2.500 LP_UAC Bypass via Event Viewer Detected

- **Trigger Condition:** UAC bypass method using the Windows Event Viewer is detected.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation

- **ATT&CK Tag:** Abuse Elevation Control Mechanism, Bypass User Access Control
- **ATT&CK ID:** T1548, T1548.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(label="Process" label=Create parent_process="*\eventvwr.exe" - "process"="*\mmc.exe
↪") OR (norm_id = WindowsSysmon event_id=13 target_object=
↪ "HKCU*\mscfile\shell\open\command*")
```

2.501 LP_Unix Possible Bruteforce Attack

- **Trigger Condition:** An account is not present but is used repeatedly to login. This may be a brute force attack by a bot, malware, or threat agent.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Brute Force
- **ATT&CK ID:** T1110
- **Minimum Log Source Requirement:** Unix
- **Query:**

```
norm_id=Unix ((label=Account label=Absent) OR (label=User label=Authentication
↪ label=Fail)) user=* | chart count() as cnt by user | search cnt>10
```

2.502 LP_Unix User Deleted

- **Trigger Condition:** Deletion of a user account.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Account Access Removal
- **ATT&CK ID:** T1531
- **Minimum Log Source Requirement:** Unix
- **Query:**

```
norm_id=Unix label=User label=Account label=Management label=Delete label=Remove?
↪ user=*
```

2.503 LP_Unsigned Driver Loading Detected

- **Trigger Condition:** Loading of an unsigned driver is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=6 is_sign=False image=* -user IN EXCLUDED_USERS
```

2.504 LP_Possible Ursnif Registry Activity

- **Trigger Condition:** A new registry key under *AppDataLowSoftwareMicrosoft* is detected, which was used by Ursnif malware.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Modify Registry
- **ATT&CK ID:** T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 target_object=
↪ "*"Software\AppDataLow\Software\Microsoft\*" -user IN EXCLUDED_USERS
```

2.505 LP_VBA DLL Loaded by Office

- **Trigger Condition:** Loading of DLL related to VBA macros by Office products id detected. To reduce false positives, we recommend you filter the use of the legitimate macro.

- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing, Spearphishing Attachment
- **ATT&CK ID:** T1566, T1566.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 source_image IN ["*\winword.exe*", "*\powerpnt.
↪exe*", "*\excel.exe*", "*\outlook.exe*"] image IN ["*\VBE7.DLL*", "*\VBEUI.DLL*",
↪"*\VBE7INTL.DLL*"] -user IN EXCLUDED_USERS
```

2.506 LP_VM - High Risk Vulnerability on High Impact Assets

- **Trigger Condition:** High-risk vulnerability is detected in high impact assets.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning
- **ATT&CK ID:** T1046
- **Minimum Log Source Requirement:** Qualys, Vulnerability Management
- **Query:**

```
(col_type=qualys* or col_type=Nessus or norm_id=VulnerabilityManagement) (severity=4[?]
↪or severity=5) source_address IN HIGH_IMPACT_ASSETS
```

2.507 LP_VM - High Risk Vulnerability on Low Impact Assets

- **Trigger Condition:** High-risk vulnerability is detected in low impact assets.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning
- **ATT&CK ID:** T1046
- **Minimum Log Source Requirement:** Qualys, Vulnerability Management

- **Query:**

```
(col_type=qualys* or col_type=Nessus or norm_id=VulnerabilityManagement) (severity=4❗  
↪ or severity=5) source_address IN LOW_IMPACT_ASSETS
```

2.508 LP_VM - High Risk Vulnerability on Medium Impact Assets

- **Trigger Condition:** High-risk vulnerability is detected in medium impact assets.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning
- **ATT&CK ID:** T1046
- **Minimum Log Source Requirement:** Qualys, Vulnerability Management
- **Query:**

```
(col_type=qualys* or col_type=Nessus or norm_id=VulnerabilityManagement) (severity=4❗  
↪ or severity=5) source_address IN MEDIUM_IMPACT_ASSETS
```

2.509 LP_VM - Medium Risk Vulnerability on High Impact Assets

- **Trigger Condition:** Medium-risk vulnerability is detected in high impact assets.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning
- **ATT&CK ID:** T1046
- **Minimum Log Source Requirement:** Qualys, Vulnerability Management
- **Query:**

```
(col_type=qualys* or col_type=Nessus or norm_id=VulnerabilityManagement) (severity=2❗  
↪ or severity=3) source_address IN HIGH_IMPACT_ASSETS
```

2.510 LP_VM - Medium Risk Vulnerability on Low Impact Assets

- **Trigger Condition:** Medium-risk vulnerability is detected in low impact assets.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning
- **ATT&CK ID:** T1046
- **Minimum Log Source Requirement:** Qualys, Vulnerability Management
- **Query:**

```
(col_type=qualys* or col_type=Nessus or norm_id=VulnerabilityManagement) (severity=2   
↪ or severity=3) source_address IN LOW_IMPACT_ASSETS
```

2.511 LP_VM - Medium Risk Vulnerability on Medium Impact Assets

- **Trigger Condition:** Medium-risk vulnerability is detected in medium impact assets.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Network Service Scanning
- **ATT&CK ID:** T1046
- **Minimum Log Source Requirement:** Qualys, Vulnerability Management
- **Query:**

```
(col_type=qualys* or col_type=Nessus or norm_id=VulnerabilityManagement) (severity=2   
↪ or severity=3) source_address IN MEDIUM_IMPACT_ASSETS
```

2.512 LP_WannaCry MS17-010 Vulnerable Sources

- **Trigger Condition:** MS17-010 vulnerability is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -

- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Qualys, Vulnerability Management
- **Query:**

```
col_type=qualys* qualys_id IN [91345, 91357, 91359, 91360, 70077, 91360, 91345]
```

2.513 LP_WannaCry Sources in Connections to Sinkhole Domain

- **Trigger Condition:** A source tries to connect to the WannaCry sinkhole domain.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Proxy
- **ATT&CK ID:** T1090
- **Minimum Log Source Requirement:** Firewall, IDS/IPS, Webserver
- **Query:**

```
norm_id=* url IN WANNACRY_DOMAIN or domain IN WANNACRY_DOMAIN
```

2.514 LP_WCE wceaux.dll Access Detected

- **Trigger Condition:** *wceaux.dll* access during Windows Credential Editor (WCE) pass-the-hash remote command execution on the source host is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id IN ["4656", "4658", "4660", "4663"] object_name=
↳ "*"wceaux.dll" -user IN EXCLUDED_USERS
```

2.515 LP_Wdigest Registry Modification

- **Trigger Condition:** Modification of the wdigest registry value is detected. Wdigest is an windows authentication protocol which stores credential in plain text. Adversaries can enable wdigest authentication and retrieve plain text credential of users.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Modify Registry
- **ATT&CK ID:** T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Registry label=Value label=Set target_object="*WDigest\UseLogonCredential"
```

2.516 LP_Weak Encryption Enabled for User

- **Trigger Condition:** Weak encryption is enabled for a user profile, which is later used for hash or password cracking.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Modify Registry
- **ATT&CK ID:** T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WinServer event_id=4738 user_account_control IN ["*DES*", "*Preauth*",  
↪ "*Encrypted*"] user_account_control="*Enabled*" -user IN EXCLUDED_USERS
```

2.517 LP_Potential Webshell Activity Detected

- **Trigger Condition:** Specific command line parameters, commonly associated with reconnaissance activities via web shells, are detected.
- **ATT&CK Category:** Discovery, Persistence

- **ATT&CK Tag:** Remote System Discovery, System Owner/User Discovery, Account Discovery, Web Shell
- **ATT&CK ID:** T1018, T1033, T1087, T1505.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" ((parent_process IN ["*\\w3wp.exe", "*\\php-cgi.exe",
↪ "*\\nginx.exe", "*\\httpd.exe", "*\\caddy.exe", "*\\ws_tomcat-service.exe"] OR (parent_
↪ process IN ["*\\java.exe", "*\\javaw.exe"] (parent_process IN ["*-tomcat-*", "*\\tomcat*"]
↪ OR command IN ["*catalina.jar*", "*CATALINA_HOME*"]))) (((file IN ["net.exe", "net1.
↪ exe"] command IN ["* user *", "* use *", "* group *"]) OR (file = "ping.exe" command
↪ = "* -n *") OR command IN ["*&cd&echo*", "*cd /d *"] OR (file = "wmic.exe"
↪ command = "* /node:*") OR ("process" IN ["*\\whoami.exe", "*\\systeminfo.exe",
↪ "*\\quser.exe", "*\\ipconfig.exe", "*\\pathping.exe", "*\\tracert.exe", "*\\netstat.exe",
↪ "*\\schtasks.exe", "*\\vssadmin.exe", "*\\wevtutil.exe", "*\\tasklist.exe"] OR file IN [
↪ "whoami.exe", "sysinfo.exe", "quser.exe", "ipconfig.exe", "pathping.exe", "tracert.exe",
↪ "netstat.exe", "schtasks.exe", "VSSADMIN.EXE", "wevtutil.exe", "tasklist.exe"]) OR
↪ command IN ["* Test-NetConnection *", "*dir \\*"]))) -user IN EXCLUDED_USERS
```

2.518 LP_Windows Audit Logs Cleared

- **Trigger Condition:** The Windows Security audit log is cleared.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Clear Windows Event Logs
- **ATT&CK ID:** T1070.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label=Audit label=Log label=Clear -user IN EXCLUDED_USERS
```

2.519 LP_Windows Credential Editor Detected

- **Trigger Condition:** The use of Windows Credential Editor (WCE) is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping

- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
((label="Process" label=Create (hash_import IN ["a53a02b997935fd8eedcb5f7abab9b9f",
↪ "e96a73c7bf33a464c510ede582318bf2"] OR command="*.exe -S" parent_process=
↪ "*\services.exe")) OR (norm_id=WindowsSysmon event_id=13 target_object=
↪ "*Services\WCESERVICE\Start*"))
```

2.520 LP_Windows Data Copied to Removable Device

- **Trigger Condition:** A file is copied to removable storage. For this alert to work, you must update the list CRITICAL_HOSTS, which includes hosts where admin monitors file copy across removable storage.
- **ATT&CK Category:** Exfiltration
- **ATT&CK Tag:** Exfiltration Over Physical Medium, Exfiltration over USB
- **ATT&CK ID:** T1052, T1052.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer* event_id=4663 event_category="Removable Storage" access=
↪ "WriteData*" or access="*AppendData*" host IN CRITICAL_HOSTS -user IN
↪ EXCLUDED_USERS
```

2.521 LP_Windows Defender Antivirus Disable via Registry Modification

- **Trigger Condition:** Windows Defender Antivirus registry values added or modified to set it to a disabled state are detected. Windows Defender Antivirus is a native anti-malware component of Microsoft Windows. Adversaries generally attempt to turn off anti-virus components of any system to inhibit detection.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Disable or Modify Tools
- **ATT&CK ID:** T1562.001

- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label="create" "process"="*\reg.exe" command=
↪ "*HKLM\Software\Policies\Microsoft\Windows Defender*" command="*add*1*"
↪ command IN ["*DisableAntiSpyware*", "*DisableAntiVirus*", "*MpEnablePus*",
↪ "*DisableBehaviorMonitoring*", "*DisableIOAVProtection*",
↪ "*DisableOnAccessProtection*", "*DisableRealtimeMonitoring*",
↪ "*DisableScanOnRealtimeEnable*", "*DisableEnhancedNotifications*",
↪ "*DisableBlockAtFirstSeen*"]
```

2.522 LP_Shadow Copy Deletion Using OS Utilities Detected

- **Trigger Condition:** Windows Defender Antivirus registry values added or modified to set it to a disabled state are detected. Windows Defender Antivirus is a native anti-malware component of Microsoft Windows. Adversaries generally attempt to turn off anti-virus components of any system to inhibit detection.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Inhibit System Recovery
- **ATT&CK ID:** T1490
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Process" label="Create" ("process" IN ["*\powershell.exe", "*\wmic.exe",
↪ "*\vssadmin.exe", "*\diskshadow.exe"] command="*shadow*" command="*delete*")
↪ OR ("process"="*\wbadmin.exe" command="*delete*")
↪ (command="*systemstatebackup*" OR (command="*catalog*" command="*quiet*"))
↪ OR ("process"="*\vssadmin.exe" command="*resize*" command="*shadowstorage*"
↪ command IN ["*unbounded*", "*MaxSize=*"]) OR (command IN ["*Get-WmiObject*",
↪ "*gwmi*", "*Get-CimInstance*", "*gcim*"] command="*Win32_Shadowcopy*"
↪ "command IN ["*.Delete()", "*Remove-WmiObject*", "*rwmi*", "*Remove-
↪ CimInstance*", "*rcim*"])
```

2.523 LP_Windows Defender Exclusion Set Detected

- **Trigger Condition:** When Windows Defender Antivirus exclusion is added. Windows Defender Antivirus is a built-in antivirus program for Windows 10.

It provides real-time protection against malware, viruses, spyware and other malicious software. Windows Defender allows users to exclude specific files, folders or processes from scanning to improve performance and reduce false positives. Adversaries can abuse the file exclusion feature in Windows Defender to evade detection of their malicious binaries by excluding the file type or file from being scanned.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Disable or Modify Tools
- **ATT&CK ID:** T1562, T1562.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
(norm_id=WinServer event_source="Microsoft-Windows-Windows Defender" event_
↪ id=5007 new_value="HKLM\SOFTWARE\Microsoft\Windows Defender\Exclusions\*")
↪ OR (norm_id=WindowsSysmon event_id=13 target_object=
↪ "*\SOFTWARE\Policies\Microsoft\Windows Defender\Exclusions\Extensions\*" event_
↪ type=setvalue)
```

2.524 LP_Windows Excessive Amount of Files Copied to Removable Device

- **Trigger Condition:** One hundred or more files the user copied to the removable storage device are detected. Threat actors generally attempt to exfiltrate as much data as possible through removable storage devices from the victim organizations. Setting the threshold value according to the organization's behavior or risk appetite is recommended. It is recommended to enable this alert only if the organizational policy explicitly disallows this behavior.
- **ATT&CK Category:** Exfiltration
- **ATT&CK Tag:** Exfiltration Over Physical Medium, Exfiltration over USB
- **ATT&CK ID:** T1052, T1052.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer* event_id=4663 event_category="Removable Storage" access=
↪ "WriteData*" or access="*AppendData*" -user IN EXCLUDED_USERS | chart distinct_
↪ count(object) as DataCopied by user | search DataCopied>100
```

2.525 LP_Windows Failed Login Attempt Using Service Account

- **Trigger Condition:** A user fails to log in using a service account. Generally, failed logon events with logon type 5 indicate the password change without updating the service; however, a possibility of malicious users at work exists. Conversely, the existence of malicious users is less likely to happen as creating a new service or editing an existing service by default requires membership in Administrators or Server Operators. Also, malicious users will already have the authority to perpetuate their desired goal.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts
- **ATT&CK ID:** T1078
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer* label=User label=Login label=Fail target_user=*ORuser=?logon_
↪ type = 5 -user IN EXCLUDED_USERS | rename target_user as user, target_domain as ?
↪ domain
```

2.526 LP_Windows Failed Login Followed by Lockout Event

- **Trigger Condition:** A failed login attempt followed by account lockout is detected.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts, Exploitation for Credential Access, Exploitation for Privilege Escalation, Exploitation for Defense Evasion, Brute Force
- **ATT&CK ID:** T1078, T1212, T1068, T1211 ,T1110
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
[norm_id=WinServer label=User label=Login label=Fail -user IN EXCLUDED_USERS] as s1
↳ followed by [norm_id=WinServer label=User label=Account label=Lock user=*] as s2 on
↳ s1.user=s2.user | rename s1.user as User, s1.source_address as SourceAddress, s2.
↳ workstation as ComputerName, s2.caller_domain as Domain, s1.log_ts as
↳ LastFailedLogin_ts, s2.log_ts as LockedOut_ts
```

2.527 LP_Windows Local User Management

- **Trigger Condition:** A user is created on a non-domain controller. For the alert to work, you must update the list DOMAIN with domain controllers.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Create Account, Local Account
- **ATT&CK ID:** T1136, T1136.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer* label=User label=Create -target_user=*-user= -target_domain IN
↳ DOMAIN -domain IN DOMAIN -user IN EXCLUDED_USERS
```

2.528 LP_WMI DLL Loaded by Office

- **Trigger Condition:** Loading of DLLs related to WMI by Office products signaling VBA macros executing WMI Commands.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** User Execution, Malicious File
- **ATT&CK ID:** T1204, T1204.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 source_image IN ["*\winword.exe", ".*\powerpnt.
↳ exe", ".*\excel.exe", ".*\outlook.exe"] image IN ["*\wmiutils.dll", ".*\wbemcomn.dll",
↳ ".*\wbemprox.dll", ".*\wbemdisp.dll", ".*\wbemsvc.dll"]
-user IN EXCLUDED_USERS
```

2.529 LP_Windows Processes Suspicious Parent Directory Detected

- **Trigger Condition:** Suspicious parent processes of Windows processes are detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Rename System Utilities, Match Legitimate Name or Location
- **ATT&CK ID:** T1036.003, T1036.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process" IN ["*\svchost.exe", "*\taskhost.exe", "*\sm.exe",
↪ "\sasm.exe", "*\services.exe", "*\saio.exe", "*\csrss.exe", "*\wininit.exe",
↪ "*\winlogon.exe"] -((parent_process IN ["*\SavService.exe", "*\ngen.exe"] parent_
↪ process IN ["*\System32\*", "*\SysWOW64\*"]) OR (parent_process IN ["*\Windows\
↪ Defender\*", "*\Microsoft Security Client\*"] parent_process="*\MsMpEng.exe*") OR
↪ (parent_process="-"))
```

2.530 LP_Windows Registry Persistence COM Key Linking Detected

- **Trigger Condition:** COM object hijacking via TreatAs subkey is detected. It is rare, but there are some cases where system utilities use linking keys for backward compatibility.
- **ATT&CK Category:** Privilege Escalation, Persistence
- **ATT&CK Tag:** Event Triggered Execution, Component Object Model Hijacking
- **ATT&CK ID:** T1546, T1546.015
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=12 target_object="HKU\*_Classes\CLSID\*\TreatAs" -
↪ user IN EXCLUDED_USERS
```

2.531 LP_Windows Shell Spawning Suspicious Program

- **Trigger Condition:** A suspicious child process of Windows Shell and scripting processes such as Wscript, Rundll32, Regsvr32, powershell and Mshta is detected.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** PowerShell, Visual Basic, System Binary Proxy Execution
- **ATT&CK ID:** T1059.001, T1059.005, T1218
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create
parent_process IN ["*\mshta.exe", "powershell.exe", "rundll32.exe", "cscript.exe",
↪ "wscript.exe", "wmiprvse.exe", "pwsh.exe", "regsvr32.exe"]
"process" IN ["\schtasks.exe", "nslookup.exe", "certutil.exe", "bitsadmin.exe",
↪ "mshta.exe"]
-(path="*\ccmcache\*" OR (parent_process="*\mshta.exe" "process"="*\mshta.exe"
↪ parent_command="*C:\MEM_Configmgr_*" parent_command="*\splash.hta*"
parent_command="*{1E460BD7-F1C3-4B2E-88BF-4E770A288AF5}*" command=
↪ "C:\MEM_Configmgr_*" command="*\SMSSETUP\BIN\*"
command="*\autorun.hta*" command="*{1E460BD7-F1C3-4B2E-88BF-4E770A288AF5}*"
↪ ") OR command="*\nessus_*" OR (parent_command="*\Program
↪ Files\Amazon\WorkSpacesConfig\Scripts\setup-scheduledtask.ps1*" parent_command=
↪ "*\Program Files\Amazon\WorkSpacesConfig\Scripts\set-selfhealing.ps1*" parent_
↪ command="*\Program Files\Amazon\WorkSpacesConfig\Scripts\check-
↪ workspacehealth.ps1*"))
```

2.532 LP_Windows Suspicious Creation of User Accounts

- **Trigger Condition:** Creation of an account, followed by its deletion in a day is detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Account Create
- **ATT&CK ID:** T1136
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
[norm_id=WinServer* label=User label=Create -target_user=*-calleruser=?-calleruser=? -
↪user=*$ -user IN EXCLUDED_USERS | rename target_user as Account, caller_user as ?
↪user] as s1 followed by [norm_id=WinServer* label=User (label=Delete or ?
↪label=Remove) | rename target_user as Account, caller_user as user]
as s2 on s1.Account=s2.Account | rename s1.col_ts as CreatedTime_ts, s2.col_ts as ?
↪DeletedTime_ts, s1.user as CreatedUser, s2.user as DeletedUser, s1.Account as Account
```

2.533 LP_Windows User Account Created via Command Line

- **Trigger Condition:** Creation of a user account via CLI like PowerShell or net utility is detected.
- **ATT&CK Category:** Execution, Persistence
- **ATT&CK Tag:** Create Account, PowerShell, Local Account
- **ATT&CK ID:** T1136, T1059.001, T1136.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" (command="*New-LocalUser*" or command="*net user?
↪add*")
```

2.534 LP_Windows User Account Change to End with Dollar Sign

- **Trigger Condition:** A user account is changed to end with the dollar sign (\$).
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Account Manipulation
- **ATT&CK ID:** T1098
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer* label=User label=Account label=Change label=Name new_user=*$ -
↪user IN EXCLUDED_USERS | rename caller_user as user, caller_domain as domain
```

2.535 LP_Windows Webshell Creation Detected

- **Trigger Condition:** Creation of WebShell file on a static web site. The alert has been directly translated from sigma rule.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Server Software Component, Web Shell
- **ATT&CK ID:** T1505, T1505.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 ((path="*\inetpub\wwwroot*" file IN [ "*.asp", "*.ashx", "*.ph" ]) OR (path IN [ ".*\www\*", ".*\htdocs\*", ".*\html\*" ] file="*.ph") OR (file="*.jsp" path="*\cgi-bin\*" path="*.pl*"))
-path IN [ ".*\AppData\Local\Temp*", ".*\Windows\Temp*"]
```

2.536 LP_Winlogon Helper DLL

- **Trigger Condition:** Modification of registry entries related to winlogon.exe to load and execute possible malicious DLLs and/or executables is detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Boot or Logon Autostart Execution, Winlogon Helper DLL
- **ATT&CK ID:** T1547, T1547.004
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon (event_id=12 or event_id=13 or event_id=14) (target_object="*\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon\user_nameinit*" or
target_object="*\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon\Shell\*" or target_object="*\SOFTWARE\Microsoft\Windows
NT\CurrentVersion\Winlogon\Notify\*")
-user IN EXCLUDED_USERS
```

2.537 LP_WMI Backdoor Exchange Transport Agent

- **Trigger Condition:** WMI backdoor in Exchange Server Software Component and Transport Agents via WMI event filters is detected.
- **ATT&CK Category:** Privilege Escalation, Persistence
- **ATT&CK Tag:** Event Triggered Execution, Windows Management Instrumentation Event Subscription
- **ATT&CK ID:** T1546, T1546.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 parent_image="*\EdgeTransport.exe" -user IN[?]
↪ EXCLUDED_USERS
```

2.538 LP_WMI Modules Loaded by Suspicious Process

- **Trigger Condition:** Loading of WMI modules by suspicious processes like a binary from ProgramData is detected. Legitimate system processes and third-party utilities extensively use WMI. We recommend you whitelist to reduce false-positive flooding. Also, do not monitor C:Windows* as extensive whitelisting is required, which may hamper query's performance.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Windows Management Instrumentation
- **ATT&CK ID:** T1047
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Image label=Load image IN ["*wmicnt.dll", "*WmiApRpl.dll", "*wmi prov.dll",
↪ "*wmiutils.dll", "*wbemcomn.dll", "*wbemprox.dll", "*WMINet_Utls.dll", "*wbemsvc.dll",
↪ "*fastprox.dll"] -"process" IN ["C:\Program Files\*", "C:\Program Files (x86)\*",
↪ "*\WmiPrvSE.exe", "*\WmiApSrv.exe", "*\svchost.exe", "*\DeviceCensus.exe",
↪ "*\CompatTelRunner.exe", "*\sdiagnhost.exe", "*\SIHClient.exe", "*\ngentask.exe",
↪ "*\windows\system32\taskhostw.exe", "*\windows\system32\MoUseCoreWorker.exe",
↪ "*\windows\system32\wbem\WMIADAP.exe", "C:\Windows\Sysmon64.exe",
↪ "C:\Windows\Sysmon.exe", "C:\Windows\System32\wbem\unsecapp.exe", "*\logman.
↪ exe", "*\systeminfo.exe", "*\nvcontainer.exe", "C:\Windows\System32\wbem\WMIC.
↪ exe", "*\explorer.exe", "*\opera_autoupdate.exe", "*\MsMpEng.exe", "*\thor64.exe",
↪ "*\thor.exe", "*\WaAppAgent.exe", "*\WindowsAzureGuestAgent",
↪ "*\Microsoft\Teams\Update.exe", "*\Microsoft\Teams\current\Teams.exe",
↪ "*\Windows\System32\ServerManager.exe", "*\Windows\System32\wds.exe",
↪ "*\Windows\System32\dsrs.exe", "*\Windows\System32\SecurityHealthService.exe",
↪ "*\Windows\System32\dxdiag.exe", "*\Windows\System32\dispdiag.exe",
↪ "*\Windows\System32\gpreresult.exe", "*\Windows\System32\tasklist.exe"]
```

(continued from previous page)

2.539 LP_WMI Persistence - Script Event Consumer Detected

- **Trigger Condition:** Windows Management Instrumentation (WMI) script event consumers are detected. Attackers leverage WMI ActiveScriptEventConsumers remotely to move laterally in the network.
- **ATT&CK Category:** Privilege Escalation, Persistence
- **ATT&CK Tag:** Event Triggered Execution, Windows Management Instrumentation Event Subscription
- **ATT&CK ID:** T1546, T1546.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*:\WINDOWS\system32\wbem\scrcons.exe" ?  
↪parent_process="*:\Windows\System32\svchost.exe" -user IN EXCLUDED_USERS
```

2.540 LP_WMI Persistence - Script Event Consumer File Write

- **Trigger Condition:** File writes of WMI script event consumer are detected.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** Event Triggered Execution, Windows Management Instrumentation Event Subscription
- **ATT&CK ID:** T1546, T1546.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 source_image=  
↪ "C:\WINDOWS\system32\wbem\scrcons.exe" -user IN EXCLUDED_USERS
```

2.541 LP_WMI Spawning Windows Shell

- **Trigger Condition:** WMI spawning Command and Scripting Interpreter and PowerShell are detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell, Windows Management Instrumentation
- **ATT&CK ID:** T1059, T1059.001, T1047
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 parent_image="*\wmiprvse.exe" image=
↳ "\powershell.exe" -user IN EXCLUDED_USERS
```

2.542 LP_WMIExec VBS Script Detected

- **Trigger Condition:** WSF/JSE/JS/VBA/VBE File Execution execution by cscript or wscript is detected. Adversaries can utilize wscript and cscript to run suspicious files on a victim's workstation, such as malicious scripts or programs.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, Visual Basic, JavaScript
- **ATT&CK ID:** T1059, T1059.005, T1059.007
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Create label="process" "process" IN ["*\cscript.exe", "\wscript.exe"] command in [
↳ "\.js*", "\.jse*", "\.vba*", "\.vbe*", "\.vbs*"]
```

2.543 LP_Wmiprvse Spawning Process

- **Trigger Condition:** wmiprvse spawning unusual processes are detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Windows Management Instrumentation

- **ATT&CK ID:** T1047
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4688 parent_process="*WmiPrvSe.exe" -target_logon_id=
↪ "0x3e7" -logon_id="0x3e7" -"process" IN ["*WmiPrvse.exe", "*Werfault.exe"] -user
↪ IN EXCLUDED_USERS
```

2.544 LP_WScript or CScript Dropper Detected

- **Trigger Condition:** Execution of *wscript* or *cscript* scripts in user directories is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, Visual Basic, JavaScript
- **ATT&CK ID:** T1059.007, T1059.005, T1059
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process" IN ["*wscript.exe", "*cscript.exe"] command IN [
↪ ".*\Users\*", ".*\ProgramData\*"] command IN ["*.jse", "*.vbe", "*.js", "*.vba", "*.vbs
↪ "] -parent_process = "*winzip*"
```

2.545 LP_Wsreset UAC Bypass Detected

- **Trigger Condition:** A method that uses the *Wsreset.exe* tool to reset the Windows Store bypassing UAC is detected.
- **ATT&CK Category:** Privilege Escalation, Defense Evasion
- **ATT&CK Tag:** Abuse Elevation Control Mechanism, Bypass User Access Control
- **ATT&CK ID:** T1548, T1548.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process="*\WSreset.exe"(-"process"="*\conhost.
↪exe" OR integrity_level IN [High,System])
```

2.546 LP_XSL Script Processing Detected

- **Trigger Condition:** Application control bypass attempt via execution of embedded scripts inside Extensible Stylesheet Language (XSL) files is detected. The alert detects another variation of this technique, dubbed *Squiblytwo*, that utilizes WMI to invoke JScript or VBScript within an XSL file. Legitimate invocations of *msxsl* employ the *-o* command-line argument should be whitelisted to reduce false positives.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** XSL Script Processing
- **ATT&CK ID:** T1220
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (((("process"="*\wmic.exe" command IN ["*format*:*", "*format*:*", "*-format*:*"] ) -command in ["*Format:List", "*Format:htable",
↪"*Format:hform", "*Format:table", "*Format:mof", "*Format:value", "*Format:rawxml",
↪"*Format:xml", "*Format:csv"] ) OR ("process"="*\msxsl.exe" -command="*-o *")) -
↪user IN EXCLUDED_USERS
```

2.547 LP_ZOHO Dctask64 Process Injection Detected

- **Trigger Condition:** Process injection using ZOHO's *dctask64.exe* is detected.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Process Injection
- **ATT&CK ID:** T1055
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\dctask64.exe" -command="*DesktopCentral_
↪Agent\agent*" -user IN EXCLUDED_USERS
```

2.548 LP_APT 34 Initial Access Using Spearphishing Link Detected

- **Trigger Condition:** Entry vectors try to gain their initial foothold within a network using Spearphishing link with IOCs' attacks related to APT34. For the alert to work, it uses lists; IRANIAN_SPEARPHISHING_DOMAINS and IRANIAN_SPEARPHISHING_IP.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Spearphishing Link
- **ATT&CK ID:** T1566
- **Minimum Log Source Requirement:** EmailServer
- **Query:**

```
norm_id=* label=Detect label=Malicious label=URL (source_address in IRANIAN_
↳SPEARPHISHING_IP OR domain in IRANIAN_SPEARPHISHING_DOMAINS) -user IN
↳EXCLUDED_USERS
```

2.549 LP_Credential Dumping using procdump Detected

- **Trigger Condition:** An adversary obtains account login and password information using procdump, generally in the form of a hash or a clear text password, from the operating system and software.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Credential Dumping
- **ATT&CK ID:** T1003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=File label=Create file=*.dmp source_image=
↳"*procdump.exe" -user IN EXCLUDED_USERS | rename source_image as image
```

2.550 LP_Suspicious File Deletion Detected

- **Trigger Condition:** Adversaries removes trail files for an intrusion to keep their footprint low or remove them at the end as part of the post-intrusion cleanup process. For the alert to work, you must configure ACLs on paths and extensions you want to monitor for deletion operations.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Indicator Removal on Host, File Deletion
- **ATT&CK ID:** T1070, T1070.004
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label=Object label=Access access="*delete*" (relative_target="*.exe
↪ " OR relative_target="*.bat" OR relative_target="*.ps1" OR relative_target="*.cmd") -
↪ user IN EXCLUDED_USERS | rename relative_target as file
```

2.551 LP_Security Software Discovery Process Detected

- **Trigger Condition:** Adversaries attempts to get a listing of security software, configurations, defensive tools, and sensors that are installed on the system.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** Security Software Discovery
- **ATT&CK ID:** T1518
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label="Process" label=Create (command="*findstr.exe*virus" OR
↪ command="*findstr.exe*cylance" OR command="*findstr.exe*defender" OR
↪ command="*findstr.exe*cb" ) -user IN EXCLUDED_USERS
```

2.552 LP_System Network Configuration Discovery

- **Trigger Condition:** Discovery of network configuration via system utilities like ipconfig, route, or netsh is detected.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** System Network Configuration Discovery
- **ATT&CK ID:** T1016
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label="Process" label=Create (command="*ipconfig.exe*" OR
↪ command="*route.exe*" OR command="*netsh advfirewall*" OR command="*arp.exe*"
↪ " OR command="*nbtstat.exe*" OR command="*netsh.exe*interface show" OR
↪ command="*net*config" ) -user IN EXCLUDED_USERS | rename commandline as
↪ command
```

2.553 LP_System Network Connections Discovery

- **Trigger Condition:** Discovery of network connections via system utilities like netstat or net is detected.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** System Network Connections Discovery
- **ATT&CK ID:** T1049
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ("process" IN ["*net.exe", "*netstat.exe"] command IN [
↪ "*net* use*", "*net* sessions*", "*net* file*", "*netstat*"]) OR command="*Get-
↪ NetTCPConnection*" -user IN EXCLUDED_USERS
```

2.554 LP_Exfiltration over Cloud Application Detected

- **Trigger Condition:** Adversaries performs data exfiltration with a different protocol from the main Command and Control protocol or channel.
- **ATT&CK Category:** Exfiltration
- **ATT&CK Tag:** Exfiltration Over Alternative Protocol
- **ATT&CK ID:** T1048
- **Minimum Log Source Requirement:** ProxyServer
- **Query:**

```
norm_id=*Proxy* source_address=* destination_address=* destination_address IN ?
↪ CLOUD_APPLICATION_IP -user IN EXCLUDED_USERS
```

2.555 LP_Remote File Copy Detected

- **Trigger Condition:** Files are copied from one system to another to stage adversary tools or other files throughout an operation.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote File Copy
- **ATT&CK ID:** T1105
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label=Object label=Access access=* (relative_target="*.exe" OR ?
↪ relative_target="*.bat") -user IN EXCLUDED_USERS | rename relative_target as file
```

2.556 LP_Privilege Escalation - Bypassing User Account Control Detected

- **Trigger Condition:** Adversaries uses techniques to elevate a user's privileges manipulating UAC to administer if the target process is unprotected.
- **ATT&CK Category:** Privilege Escalation

- **ATT&CK Tag:** Bypass User Account Control
- **ATT&CK ID:** T1548
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
(norm_id=WindowsSysmon OR ((command=* OR commandline=*) norm_id=WinServer))
↪ label="Process" label=Create (command="*eventvwr.exe*" OR commandline=
↪ "*eventvwr.exe*" OR command="*wscript.exe*" OR commandline="*wscript.exe*" OR
↪ token_elevation_type="TokenElevationTypeLimited*")
-user IN EXCLUDED_USERS | rename commandline as command
```

2.557 LP_Process Execution from Suspicious Location

- **Trigger Condition:** Execution of a process from suspicious location is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4688 "process" IN ["C:\ProgramData\*.exe",
↪ "*\AppData\Local\*.exe", "*\AppData\Roaming\*.exe", "C:\Users\Public\*"] -"process
↪ " IN ["*\Teams.exe", "*\Teams\Update.exe", "*\Temp\*\dismhost.exe",
↪ "*\Microsoft\OneDrive\*\FileCoAuth.exe", "C:\ProgramData\Microsoft\*\MpCmdRun.exe
↪ ", "*\Local\Temp\*\BackgroundDownload.exe", "*\Microsoft\Windows
↪ Defender\*\NisSrv.exe", "C:\ProgramData\Microsoft\*\MsMpEng.exe"]
```

2.558 LP_Active Directory Enumeration via ADFind

- **Trigger Condition:** When enumeration of Active Directory using the ADfind tool is detected. AdFind is a CLI-based utility that can be used for gathering information from Active Directory like organizational units, users, computers, and groups. Adversaries can use this utility to gather information related to the Active Directory.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1059 - Command and Scripting Interpreter, T1059.001 - PowerShell

- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Process" label=Create "process"="*.exe" command IN ["*-f *objectcategory=*",
↪ "-sc trustdmp*", "*lockoutduration*", "*lockoutthreshold",
↪ "*lockoutobservationwindow*", "*maxpwdage*", "*minpwdage*", "*minpwdlength*",
↪ "*pwdhistorylength*", "*pwdproperties*", "-sc admincountdmp*", "-sc?",
↪ exchaddresses*"]
```

2.559 LP_Possible Command Prompt Process Hollowing

- **Trigger Condition:** Possible process hollowing of the command prompt is detected using applications like net.exe, nltest.exe or ipfconfig. Adversaries injects malicious code into suspended and hollowed processes to evade process-based defenses.
- **ATT&CK Category:** Defense Evasion, Privilege Escalation
- **ATT&CK Tag:** Process Injection, Process Hollowing
- **ATT&CK ID:** T1055, T1055.012
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WindowsSysmon event_id=1 parent_image="*cmd.exe" image IN ["*\net.exe",
↪ "\net1.exe", "\nltest.exe", "\ipconfig.exe"] -parent_command IN ["*/c *", "*/k *"]
```

2.560 LP_Suspicious Taskkill Activity

- **Trigger Condition:** More than two processes terminated in a short time via task kill command that may signal malicious activity like ransomware are detected.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Service Stop
- **ATT&CK ID:** T1489
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4688 "process"="*\taskkill.exe" | chart count() as cnt by host,
↪ "process" | search cnt > 2
```

2.561 LP_Suspicious File or Directory Permission Modification

- **Trigger Condition:** Permission modification of suspicious file or directory is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** File and Directory Permissions Modification, Windows File and Directory Permissions Modification
- **ATT&CK ID:** T1222.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4688 "process"="*\icacls.exe" command="icacls*:*/grant
↪ everyone*"
```

2.562 LP_Ryuk Wake-On-LAN Activity

- **Trigger Condition:** Ryuks Wake-On-LAN activity is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4688 "process"="*.exe" command="* 8 LAN *"
```

2.563 LP_EXE or DLL Dropped in Perflogs Folder

- **Trigger Condition:** The EXE or DLL file is dropped in Windows's Perflog directory.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 file IN ["*.dll", "*.exe"] path="C:\Perflogs"
```

2.564 LP_Credential Access via LaZagne

- **Trigger Condition:** Credential access via the popular open-source LaZagne tool is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, LSASS Memory
- **ATT&CK ID:** T1003,T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=10 call_trace="*C:\Windows\SYSTEM32\ntdll.  
↪dll+*|C:\Windows\System32\KERNELBASE.dll+*_ctypes.pyd+*python27.dll+*"
```

2.565 LP_RDP Connection Initiated from Domain Controller

- **Trigger Condition:** Initiation of RDP connection from a domain controller is detected.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Remote Services, Remote Desktop Protocol

- **ATT&CK ID:** T1021, T1021.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_source="Microsoft-Windows-TerminalServices-
↳ RemoteConnectionManager" event_id=1149 |
rename eventxml.param3 as source_address | search source_address IN WINDOWS_DC
```

2.566 LP_Active Directory Module Load in PowerShell

- **Trigger Condition:** Active Directory module loading in PowerShell is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4103 command="Import-Module" payload=
↳ "*ActiveDirectory*"
```

2.567 LP_Possible Active Directory Enumeration via AD Module

- **Trigger Condition:** Command related to retrieving the last logon date of a computer in an Active Directory (AD) is detected.
- **ATT&CK Category:** Execution, Discovery
- **ATT&CK Tag:** Remote System Discovery, Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1018, T1059, T1059.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4103 command="Get-ADComputer" payload=
↪ "*DNSHostName*LastLogonDate*"
```

2.568 LP_Microsoft Defender Disabling Attempt via PowerShell

- **Trigger Condition:** An attempt to disable Microsoft Defender via PowerShell is detected.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** Impair Defenses, Disable or Modify Tools, Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1562, T1562.001, T1059, T1059.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4104 script_block="Set-MpPreference -
↪ DisableRealtimeMonitoring $true"
```

2.569 LP_Possible Kerberoasting via Rubeus

- **Trigger Condition:** Kerberoasting attack via popular open-source tool Rubeus is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** Steal or Forge Kerberos Tickets, Kerberoasting
- **ATT&CK ID:** T1558, T1558.003
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 -"process"="C:\Windows\System32\*" image IN [
↪ "*\clr.dll", "*\kerberos.dll", "*\cryptdll.dll", "*\dsparse.dll"] | chart distinct_
↪ count(image) as dc, distinct_list(image) as images | search dc=4
```

2.570 LP_Suspicious Scheduled Task Creation

- **Trigger Condition:** When a suspicious scheduled task creation is detected in a Windows endpoint. The suspicious task here refers to tasks running scripts or programs from temp directories or insecure locations (writable by any user). Adversaries may abuse the Windows Task Scheduler to perform task scheduling for the initial or recurring execution of malicious code to achieve persistence, lateral movement, execution, detection evasion, and privilege escalation. Also, it is prevalent among ransomware to use public directories for scheduled task creation.
- **ATT&CK Category:** Execution, Persistence, Privilege Escalation
- **ATT&CK Tag:** Scheduled Task/Job, Scheduled Task
- **ATT&CK ID:** T1053, T1053.005
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label=Schedule label=Task label=Create command IN ["*C:\Users\*",
↪ "*C:\Windows\Temp\*", "*C:\ProgramData\*"] -command=
↪ "C:\ProgramData\Microsoft\Windows Defender\Platform\*"
```

2.571 LP_RDP Connection Initiated from Suspicious Country

- **Trigger Condition:** Initiation of RDP connection from a domain controller is detected.
- **ATT&CK Category:** Defense Evasion, Persistence, Privilege Escalation, Initial Access
- **ATT&CK Tag:** Valid Accounts, Domain Accounts
- **ATT&CK ID:** T1078, T1078.002
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_source="Microsoft-Windows-TerminalServices-
↪ RemoteConnectionManager" event_id=1149 -eventxml.param3 IN HOMENET | rename?
↪ eventxml.param3 as source_address
| process geoip(source_address) as country | search country IN SUSPICIOUS_COUNTRY
```

2.572 LP_Scheduled Task Deletion

- **Trigger Condition:** Deletion of a scheduled task using *schtasks* utility with *delete* command is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Scheduled Task
- **ATT&CK ID:** T1053.005
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(label="process" label="create" "process"="*\schtasks.exe" command="*delete*") OR
↪(norm_id=WinServer event_id=4699 -task="*\Microsoft\Windows\RemovalTools\MRT_
↪ERROR_HB")
```

2.573 LP_Possible GootKit WScript Execution

- **Trigger Condition:** GootKit banking trojan's WScript execution activity is detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, Visual Basic
- **ATT&CK ID:** T1059, T1059.003
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4688 "process"="*\wscript.exe" command="*\APPDATA\*.
↪js"
```

2.574 LP_Exchange Remote Code Execution CVE-2020-0688 Attempt

- **Trigger Condition:** A remote code execution attempt via CVE-2020-0688 in Microsoft Exchange is detected.
- **ATT&CK Category:** Initial Access

- **ATT&CK Tag:** External Remote Services
- **ATT&CK ID:** T1133
- **Minimum Log Source Requirement:** Firewall, Proxy Server
- **Query:**

```
norm_id=* (url="*/ecp/default.aspx*__VIEWSTATEGENERATOR*VIEWSTATE=*" OR
↪resource="*__VIEWSTATEGENERATOR*VIEWSTATE=*" )
```

2.575 LP_BlueKeep Vulnerability CVE-2019-0708 Exploitation

- **Trigger Condition:** The exploitation of BlueKeep, a remote desktop services remote code execution vulnerability, also known as CVE-2019-0708 is detected.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** Exploitation of Remote Services
- **ATT&CK ID:** T1210
- **Minimum Log Source Requirement:** IDS/IPS
- **Query:**

```
(norm_id=Short OR norm_id=SuricataIDS) message="*Windows RDP MS_T120*"
```

2.576 LP_ZoHo ManageEngine Pre-Auth File Upload CVE-2019-8394 Exploitation Attempt

- **Trigger Condition:** A pre-auth file upload vulnerability CVE-2019-8394 in ZoHo ManageEngine ServiceDesk Plus is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Exploit Public-Facing Application
- **ATT&CK ID:** T1190
- **Minimum Log Source Requirement:** Firewall, Proxy Server
- **Query:**

```
norm_id=* request_method=POST (url='*/common/FileAttachment.jsp?
↳module=CustomLogin*' OR resource='*/common/FileAttachment.jsp?
↳module=CustomLogin*')
```

2.577 LP_ZoHo ManageEngine Desktop Central CVE-2020-10189 Exploitation Attempt

- **Trigger Condition:** A remote code execution attempt via CVE-2019-11580 in ZoHo ManageEngine Desktop Central is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Exploit Public-Facing Application
- **ATT&CK ID:** T1190
- **Minimum Log Source Requirement:** Firewall, Proxy Server
- **Query:**

```
norm_id=* request_method=POST (url='*/mdm/client/v1/mdmLogUploader*webapps*_
↳chart*' OR resource='*/mdm/client/v1/mdmLogUploader*webapps*_chart*')
```

2.578 LP_Fortinet Pre-Auth File Read CVE-2018-13379 Exploitation Attempt

- **Trigger Condition:** The exploitation of pre-auth file read vulnerability (2018-13379) in Fortinet FortiOS is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** External Remote Services
- **ATT&CK ID:** T1133
- **Minimum Log Source Requirement:** Firewall, Proxy Server
- **Query:**

```
norm_id=* (url='*|lang=../../dev/cmdb/sslvpn_websession*' OR resource='*|lang=../../dev/cmdb/sslvpn_websession*')
```

2.579 LP_Adobe ColdFusion Remote Code Execution CVE-2018-15961 Attempt

- **Trigger Condition:** The exploitation of arbitrary file upload vulnerability (CVE-2018-15961) to upload JSP webshell for remote code execution in Adobe ColdFusion is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Exploit Public-Facing Application
- **ATT&CK ID:** T1190
- **Minimum Log Source Requirement:** Firewall, Proxy Server
- **Query:**

```
norm_id=* request_method=POST (url='*/cf_scripts/*/upload.cfm*' OR resource='*/cf_scripts/*/upload.cfm*')
```

2.580 LP_Default Hard disk Usage Status

- **Trigger Condition:** The hard disk uses storage greater than or equal to 80%.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Logpoint
- **Query:**

```
label=Harddisk label=Usage label=Metrics use>=80
```

2.581 LP_Default License Grace State

- **Trigger Condition:** Logpoint's license has expired and is operating in grace state.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -

- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Logpoint
- **Query:**

```
norm_id=Logpoint label=Audit label=License label=Grace
```

2.582 LP_Default License Invalid

- **Trigger Condition:** 's license is no longer valid.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:**
- **Query:**

```
norm_id=LogPoint label=Audit label=License label=Invalid
```

2.583 LP_Microsoft Build Engine Loading Credential Libraries

- **Trigger Condition:** Loading of credential libraries such as *vaultcli.dll* and *SAMLib.dll* by MS Build engine is detected.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** OS Credential Dumping, Security Account Manager
- **ATT&CK ID:** T1003, T1003.002
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=7 "process"='*\msbuild.exe' image IN ['*\vaultcli.dll',  
↪ '\SAMLib.DLL']
```

2.584 LP_Microsoft Build Engine started by Office

- **Trigger Condition:** Execution of Microsoft Build engine by Office products is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** MSBuild
- **ATT&CK ID:** T1127.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"='*msbuild.exe' parent_process IN ['*\eqnedt32.
↪exe', '*\excel.exe', '*\ftldr.exe', '*\msaccess.exe', '*\winword.exe', '*\mspub.exe',
↪ '*\outlook.exe', '*\powerpnt.exe']
```

2.585 LP_Potential Phishing Attack Detected

- **Trigger Condition:** Phishing attack is detected
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing, Spearphishing Attachment
- **ATT&CK ID:** T1566, T1566.001
- **Minimum Log Source Requirement:** MailServer
- **Query:**

```
label=Detect label=Malicious label=File file=* sender=* receiver=* hash=*
```

2.586 LP_Safe DLL Search Mode Disabled

- **Trigger Condition:** Safe DLL search mode is disabled.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Impair Defenses, Indicator Blocking
- **ATT&CK ID:** T1562, T1562.001

- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WindowSysmon event_id=13 target_object=
  ↳ '*\CurrentControlSet\Control\Session Manager\SafeDllSearchMode' detail="DWORD"
  ↳ (0x00000000)"
```

2.587 LP_Potential Intrusion Detected

- **Trigger Condition:** An intrusion by IDS or IPS devices is detected.
- **ATT&CK Category:** Command and Control, Defense Evasion
- **ATT&CK Tag:** Proxy, Exploitation for Defense Evasion
- **ATT&CK ID:** T1090, T1211
- **Minimum Log Source Requirement:** -
- **Query:**

```
label=Intrusion label=Detect source_address=* destination_address=*
```

2.588 LP_Windows Crash Dump Disabled

- **Trigger Condition:** Windows's crash dump registry setting is disabled.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Modify Registry
- **ATT&CK ID:** T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 target_object=
  ↳ "HKLM\System\CurrentControlSet\Control\CrashControl\CrashDumpEnabled" detail=
  ↳ "DWORD (0x00000000)"
```

2.589 LP_Suspicious Shells Spawn by SQL Server

- **Trigger Condition:** A suspicious shell process is spawned by the SQL Server process which may indicate exploitation of a vulnerability.
- **ATT&CK Category:** Initial Access, Execution
- **ATT&CK Tag:** Exploit Public-Facing Application, PowerShell
- **ATT&CK ID:** T1190, T1059.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4688 parent_process="*\sqlservr.exe" "process" IN [
↪ "\cmd.exe", "\powershell.exe", "\bash.exe", "\sh.exe", "\bitsadmin.exe"] -(parent_
↪ process IN ["C:\Program Files\Microsoft SQL Server\*", "*DATEV_
↪ DBENGINE\MSSQL\Binn\sqlservr.exe"] "process"="C:\Windows\System32\cmd.exe"?)
↪ command="'C:\Windows\system32\cmd.exe" *)
```

2.590 LP_Suspicious Microsoft SQL Server PowerShell Module Use Detected

- **Trigger Condition:** A PowerShell code through the `sqlps.exe` utility, which is included in the standard set of utilities supplied with the MSSQL Server is detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **ATT&CK ID:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Create label="Process"("process"="*\sqlps.exe" OR parent_process="*\sqlps.exe
↪ " OR file="*\sqlps.exe" ) -(parent_process="*\sqlagent.exe")
```

2.591 LP_HermeticWiper Driver Load

- **Trigger Condition:** When loading of HermeticWiper's driver IoC hashes is detected.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=6 (hash IN HERMETIC_WIPER_DRIVER_HASHES OR
↳ hash_sha1 IN HERMETIC_WIPER_DRIVER_HASHES OR hash_sha256 IN HERMETIC_
↳ WIPER_DRIVER_HASHES) | rename hash as ioc, hash_sha1 as ioc, hash_sha256 as ioc
```

2.592 LP_UltraVNC Execution via Command Line

- **Trigger Condition:** When UltraVNC execution via the command line is detected. Gamaredon is known to use this technique for gaining remote access.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Remote Access Software
- **ATT&CK ID:** T1219
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
norm_id=WinServer event_id=4688 command="*-autoreconnect *" command="*-
↳ connect *" command="*-id:*
```

2.593 LP_Office Security Settings Changed

- **Trigger Condition:** When modification of Microsoft Office security settings in the registry is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Modify Registry

- **ATT&CK ID:** T1112
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 target_object In ["*\Security\Trusted\Documents\TrustRecords*", "*\Security\AccessVBOM*", "*\Security\VBWarnings*"]
```

2.594 LP_HermeticWiper IoC Hashes Detected

- **Trigger Condition:** When any Hermetic Wiper IoC hash match is found. IoC Reference: Hashes are latest up to March 2022.
- **ATT&CK Category:** Resource Development
- **ATT&CK Tag:** Malware
- **ATT&CK ID:** T1588.001
- **Minimum Log Source Requirement:** IDS, IPS, Firewall, Windows Sysmon
- **Query:**

```
(hash IN HERMETIC_WIPER_HASHES OR hash_sha1 IN HERMETIC_WIPER_HASHES OR hash_sha256 IN HERMETIC_WIPER_HASHES) | rename hash as ioc, hash_sha1 as ioc, hash_sha256 as ioc
```

2.595 LP_IsaacWiper IoC Hashes Detected

- **Trigger Condition:** When any Issac Wiper IoC hash match is found. IoC Reference: Hashes are latest up to March 2022.
- **ATT&CK Category:** Resource Development
- **ATT&CK Tag:** Malware
- **ATT&CK ID:** T1588.001
- **Minimum Log Source Requirement:** IDS, IPS, Firewall, Windows Sysmon
- **Query:**

```
(hash IN ISAAC_WIPER_HASHES OR hash_sha1 IN ISAAC_WIPER_HASHES OR hash_
↪sha256 IN ISAAC_WIPER_HASHES) | rename hash as ioc, hash_sha1 as ioc, hash_sha256
↪as ioc
```

2.596 LP_WhisperGate IoC Hashes Detected

- **Trigger Condition:** When any WhisperGate IoC hash match by DEV-0586 is found. IoC Reference: Hashes are latest up to Feb 2022.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** IDS, IPS, Firewall, Windows Sysmon
- **Query:**

```
(hash IN WHISPERGATE_HASHES OR hash_sha1 IN WHISPERGATE_HASHES OR hash_
↪sha256 IN WHISPERGATE_HASHES) | rename hash as ioc, hash_sha1 as ioc, hash_
↪sha256 as ioc
```

2.597 LP_GhostWriter IoC Detected

- **Trigger Condition:** When any Belarusian threat actor GhostWriter (UNC1151) IoC domains or IP Address match is found. IoC Reference: IoCs are latest up to Feb 2022.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** Phishing
- **ATT&CK ID:** T1566
- **Minimum Log Source Requirement:** IDS, IPS, Firewall, Windows Sysmon
- **Query:**

```
(domain IN GHOSTWRITER_DOMAINS OR source_address IN GHOSTWRITER_IPS OR
↪destination_address IN GHOSTWRITER_IPS)
```

2.598 LP_Actinium IoC Domains Detected

- **Trigger Condition:** When any Actinium IoC domain match is found. IoC Reference: Hashes are latest up to Feb 2022.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** IDS, IPS, Firewall
- **Query:**

```
domain IN ACTINIUM_DOMAINS
```

2.599 LP_Suspicious VMToolsd Child Process

- **Trigger Condition:** Creation of a suspicious child process of the VMware Tools process that may indicate persistence set up by attackers.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1059 - Command and Scripting Interpreter
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4688 parent_process="*\vmtoolsd.exe" image IN ["*\cmd.exe",
↪ "\powershell.exe", "\wscript.exe", "\cscript.exe", "\rundll32.exe", "\regsvr32.exe"]
↪ -command IN ["*\VMware\VMware Tools\poweron-vm-default.bat*",
↪ "\VMware\VMware Tools\poweroff-vm-default.bat*", "\VMware\VMware Tools\resume-vm-default.bat*",
↪ "\VMware\VMware Tools\suspend-vm-default.bat*"]
```

2.600 LP_Credential Access via Pypykatz

- **Trigger Condition:** Credential access via the popular open-source Pypykatz tool is detected. Pypykatz is a Mimikatz implementation in the Python version >= 3.6.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** T1003.001 - LSASS Memory

- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=10 "image"="*\lsass.exe" call_trace=
↳ "*C:\Windows\SYSTEM32\ntdll.dll+*" call_trace=
↳ "*C:\Windows\System32\KERNELBASE.dll+*" call_trace="*libffi-7.dll*" call_trace="*_
↳ ctypes.pyd+*" call_trace="*python3*.dll+*
```

2.601 LP_Impacket PsExec Execution

- **Trigger Condition:** Execution of Impacket's PsExec utility is detected. Impacket is a collection of Python classes for working with network protocols. Impacket focuses on providing low-level programmatic access to the packets and is commonly used in PoCs.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** T1570 - Lateral Tool Transfer
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5145 share_name="IPC$" relative_target IN ["*RemCom_
↳ stdint*", "*RemCom_stdoutr*", "*RemCom_stderr*"] -user IN EXCLUDED_USERS
```

2.602 LP_Oracle WebLogic CVE-2021-2109 Exploitation

- **Trigger Condition:** Possible exploitation of the Oracle WebLogic server vulnerability CVE-2021-2109 is detected. This vulnerability allows a high privileged attacker with network access via HTTP to compromise Oracle WebLogic Server.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** T1190 - Exploit Public-Facing Application
- **Minimum Log Source Requirement:** Firewall, Proxy Server
- **Query:**

```
norm_id=* request_method=GET url="*com.bea.console.handles.JndiBindingHandle*"
↳ url="*ldap://*" url="*AdminServer*"
```

2.603 LP_Possible JSP Webshell Detected

- **Trigger Condition:** JSP Webshell is detected in the URL. This may indicate springshell is being exploited. However, if .jsp and .class files are commonly used in the network, the result may be false positives.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** T1505.003 - Web Shell
- **Minimum Log Source Requirement:** -
- **Query:**

```
status_code=200 request_method IN ["POST", "GET"] url in ["*.jsp*", "*.class*"]
```

2.604 LP_PowerShell ADRecon Execution

- **Trigger Condition:** Execution of the ADRecon PowerShell script for AD reconnaissance is detected. The script is reported to be actively used by FIN7. For the alert to work, the Script block logging must be enabled.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** Command and Scripting Interpreter, PowerShell
- **ATT&CK ID:** T1059, T1059.001
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4104 script_block IN ["*Function Get-ADRExcelComOb*",  
↪ "*ADRecon-Report.xlsx*", "*Get-ADRGPO*", "*Get-ADRDdomainController*"]
```

2.605 LP_PowerView PowerShell Commandlets

- **Trigger Condition:** Execution of PowerShell commandlets of the popular PowerView module of the PowerSploit framework is detected. For the alert to work, the script block logging must be enabled.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1059 - Command and Scripting Interpreter, T1059.001 - PowerShell

- **Minimum Log Source Requirement:** Windows

- **Query:**

```
norm_id=WinServer event_id=4104 script_block IN ["Export-PowerViewCSV", "Get-
↪IPAddress", "Resolve-IPAddress", "Convert-NameToSid", "ConvertTo-SID", "Convert-
↪ADName", "ConvertFrom-UACValue", "Add-RemoteConnection", "Remove-
↪RemoteConnection", "Invoke-UserImpersonation", "Invoke-RevertToSelf", "Request-
↪SPNTicket", "Get-DomainSPNTicket", "Invoke-Kerberoast", "Get-PathAcl", "Get-
↪DNSZone", "Get-DomainDNSZone", "Get-DNSRecord", "Get-DomainDNSRecord",
↪"Get-NetDomain", "Get-Domain", "Get-NetDomainController", "Get-DomainController
↪", "Get-NetForest", "Get-Forest", "Get-NetForestDomain", "Get-ForestDomain", "Get-
↪NetForestCatalog", "Get-ForestGlobalCatalog", "Find-DomainObjectPropertyOutlier",
↪"Get-NetUser", "Get-DomainUser", "New-DomainUser", "Set-DomainUserPassword",
↪"Get-UserEvent", "Get-DomainUserEvent", "Get-NetComputer", "Get-
↪DomainComputer", "Get-ADObject", "Get-DomainObject", "Set-ADObject", "Set-
↪DomainObject", "Get-ObjectAcl", "Get-DomainObjectAcl", "Add-ObjectAcl", "Add-
↪DomainObjectAcl", "Invoke-ACLScanner", "Find-InterestingDomainAcl", "Get-NetOU",
↪"Get-DomainOU", "Get-NetSite", "Get-DomainSite", "Get-NetSubnet", "Get-
↪DomainSubnet", "Get-DomainSID", "Get-NetGroup", "Get-DomainGroup", "New-
↪DomainGroup", "Find-ManagedSecurityGroups", "Get-DomainManagedSecurityGroup
↪", "Get-NetGroupMember", "Get-DomainGroupMember", "Add-DomainGroupMember
↪", "Get-NetFileServer", "Get-DomainFileServer", "Get-DFSshare", "Get-
↪DomainDFSshare", "Get-NetGPO", "Get-DomainGPO", "Get-NetGPOGroup", "Get-
↪DomainGPOLocalGroup", "Find-GPOLocation", "Get-
↪DomainGPOUserLocalGroupMapping", "Find-GPOComputerAdmin", "Get-
↪DomainGPOComputerLocalGroupMapping", "Get-DomainPolicy", "Get-NetLocalGroup
↪", "Get-NetLocalGroupMember", "Get-NetShare", "Get-NetLoggedon", "Get-
↪NetSession", "Get-LoggedOnLocal", "Get-RegLoggedOn", "Get-NetRDPSession",
↪"Invoke-CheckLocalAdminAccess", "Test-AdminAccess", "Get-SiteName", "Get-
↪NetComputerSiteName", "Get-Proxy", "Get-WMIRegProxy", "Get-LastLoggedOn",
↪"Get-WMIRegLastLoggedOn", "Get-CachedRDPConnection", "Get-
↪WMIRegCachedRDPConnection", "Get-RegistryMountedDrive", "Get-
↪WMIRegMountedDrive", "Get-NetProcess", "Get-WMIProcess", "Find-InterestingFile",
↪"Invoke-UserHunter", "Find-DomainUserLocation", "Invoke-ProcessHunter", "Find-
↪DomainProcess", "Invoke-EventHunter", "Find-DomainUserEvent", "Invoke-ShareFinder
↪", "Find-DomainShare", "Invoke-FileFinder", "Find-InterestingDomainShareFile", "Find-
↪LocalAdminAccess", "Invoke-EnumerateLocalAdmin", "Find-DomainLocalGroupMember
↪", "Get-NetDomainTrust", "Get-DomainTrust", "Get-NetForestTrust", "Get-ForestTrust",
↪"Find-ForeignUser", "Get-DomainForeignUser", "Find-ForeignGroup", "Get-
↪DomainForeignGroupMember", "Invoke-MapDomainTrust", "Get-DomainTrustMapping
↪"] -user IN EXCLUDED_USERS
```

2.606 LP_PowerView PowerShell Commandlets

- **Trigger Condition:** Execution of PowerShell commandlets of the popular PowerView module of the PowerSploit framework is detected. For the alert to work, the script block logging must be enabled.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1059 - Command and Scripting Interpreter, T1059.001 - PowerShell
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=4104 script_block IN ["Export-PowerViewCSV", "Get-
↪IPAddress", "Resolve-IPAddress", "Convert-NameToSid", "ConvertTo-SID", "Convert-
↪ADName", "ConvertFrom-UACValue", "Add-RemoteConnection", "Remove-
↪RemoteConnection", "Invoke-UserImpersonation", "Invoke-RevertToSelf", "Request-
↪SPNTicket", "Get-DomainSPNTicket", "Invoke-Kerberoast", "Get-PathAcl", "Get-
↪DNSZone", "Get-DomainDNSZone", "Get-DNSRecord", "Get-DomainDNSRecord",
↪"Get-NetDomain", "Get-Domain", "Get-NetDomainController", "Get-DomainController",
↪"Get-NetForest", "Get-Forest", "Get-NetForestDomain", "Get-ForestDomain", "Get-
↪NetForestCatalog", "Get-ForestGlobalCatalog", "Find-DomainObjectPropertyOutlier",
↪"Get-NetUser", "Get-DomainUser", "New-DomainUser", "Set-DomainUserPassword",
↪"Get-UserEvent", "Get-DomainUserEvent", "Get-NetComputer", "Get-
↪DomainComputer", "Get-ADObject", "Get-DomainObject", "Set-ADObject", "Set-
↪DomainObject", "Get-ObjectAcl", "Get-DomainObjectAcl", "Add-ObjectAcl", "Add-
↪DomainObjectAcl", "Invoke-ACLScanner", "Find-InterestingDomainAcl", "Get-NetOU",
↪"Get-DomainOU", "Get-NetSite", "Get-DomainSite", "Get-NetSubnet", "Get-
↪DomainSubnet", "Get-DomainSID", "Get-NetGroup", "Get-DomainGroup", "New-
↪DomainGroup", "Find-ManagedSecurityGroups", "Get-DomainManagedSecurityGroup",
↪"Get-NetGroupMember", "Get-DomainGroupMember", "Add-DomainGroupMember",
↪"Get-NetFileServer", "Get-DomainFileServer", "Get-DFSshare", "Get-
↪DomainDFSshare", "Get-NetGPO", "Get-DomainGPO", "Get-NetGPOGroup", "Get-
↪DomainGPOLocalGroup", "Find-GPOLocation", "Get-
↪DomainGPOUserLocalGroupMapping", "Find-GPOComputerAdmin", "Get-
↪DomainGPOComputerLocalGroupMapping", "Get-DomainPolicy", "Get-NetLocalGroup",
↪"Get-NetLocalGroupMember", "Get-NetShare", "Get-NetLoggedon", "Get-
↪NetSession", "Get-LoggedOnLocal", "Get-RegLoggedOn", "Get-NetRDPSession",
↪"Invoke-CheckLocalAdminAccess", "Test-AdminAccess", "Get-SiteName", "Get-
↪NetComputerSiteName", "Get-Proxy", "Get-WMIRegProxy", "Get-LastLoggedOn",
↪"Get-WMIRegLastLoggedOn", "Get-CachedRDPConnection", "Get-
↪WMIRegCachedRDPConnection", "Get-RegistryMountedDrive", "Get-
↪WMIRegMountedDrive", "Get-NetProcess", "Get-WMIProcess", "Find-InterestingFile",
↪"Invoke-UserHunter", "Find-DomainUserLocation", "Invoke-ProcessHunter", "Find-
↪DomainProcess", "Invoke-EventHunter", "Find-DomainUserEvent", "Invoke-ShareFinder",
↪"Find-DomainShare", "Invoke-FileFinder", "Find-InterestingDomainShareFile", "Find-
↪LocalAdminAccess", "Invoke-EnumerateLocalAdmin", "Find-DomainLocalGroupMember",
↪"Get-NetDomainTrust", "Get-DomainTrust", "Get-NetForestTrust", "Get-ForestTrust",
↪"Find-ForeignUser", "Get-DomainForeignUser", "Find-ForeignGroup", "Get-
↪DomainForeignGroupMember", "Invoke-MapDomainTrust", "Get-DomainTrustMapping",
↪"] -user IN EXCLUDED_USERS
```

(continues on next page)

(continued from previous page)

2.607 LP_Stealthy VSTO Persistence

- **Trigger Condition:** Persistence via Visual Studio Tools for Office (VSTO) add-ins in Office application is detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** Add-ins, Office Application Startup
- **ATT&CK ID:** T1137.006, T1137
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Registry label=Set target_object IN ["*\\Software\\Microsoft\\Office\\Outlook\\Addins\\*",
↳ "*\\Software\\Microsoft\\Office\\Word\\Addins\\*",
↳ "*\\Software\\Microsoft\\Office\\Excel\\Addins\\*",
↳ "*\\Software\\Microsoft\\Office\\Powerpoint\\Addins\\*",
↳ "*\\Software\\Microsoft\\VSTO\\Security\\Inclusion\\*" ] - "process" IN ["*\\msiexec.exe",
↳ "*\\regsvr32.exe", "*\\winword.exe", "*\\integrator.exe", "*\\OfficeClickToRun.exe",
↳ "*\\teams.exe", "C:\\Program Files\\AVG\\Antivirus\\RegSvr.exe"]
```

2.608 LP_Suspicious DLL or VBS Files being created in ProgramData

- **Trigger Condition:** When a file is created with .dll or vbs extension to the ProgramData folder. A DLL is a library containing code and data that can be used by multiple programs simultaneously. VBScript is an interpreted script language from Microsoft that is a subset of its Visual Basic programming language designed for interpretation by Microsoft's Internet Explorer web browser. Attackers use these techniques for the execution of malicious payloads. This method is predominantly used in Bumblebee attacks.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1204.002 - Malicious File
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 file IN ["*.dll", "*.vbs"] path="C:\ProgramData"
```

2.609 LP_Suspicious VMToolsd Child Process

- **Trigger Condition:** Creation of suspicious child process VMware Tools process, which may indicate persistence set up by attackers.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1059 - Command and Scripting Interpreter
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WinServer event_id=4688 parent_process="*\vmtoolsd.exe" image IN ["*\cmd.exe",
↪ "\powershell.exe", "\wscript.exe", "\cscript.exe", "\rundll32.exe", "\regsvr32.exe"]
↪ -command IN ["*\VMware\VMware Tools\poweron-vm-default.bat",
↪ "\VMware\VMware Tools\poweroff-vm-default.bat", "\VMware\VMware Tools\resume-vm-default.bat",
↪ "\VMware\VMware Tools\suspend-vm-default.bat"]
```

2.610 LP_Suspicious WMPRVSE Child Process

- **Trigger Condition:** A suspicious child process of WMIC is detected.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** Windows Management Instrumentation, Malicious File, Regsvr32
- **ATT&CK ID:** T1047, T1204.002, T1218.010
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (parent_process="*\wmprvse.exe" ("process" IN [
↪ "\certutil.exe", "\cscript.exe", "\mshta.exe", "\msiexec.exe", "\regsvr32.exe",
↪ "\rundll32.exe", "\verclsid.exe", "\wscript.exe"]) OR ("process"="\cmd.exe"
↪ command IN ["*cscript*", "*mshta*", "*powershell*", "*pwsh*", "*regsvr32*", "*rundll32*",
↪ "*wscript*"])-"process" IN ["*\conhost.exe", "\WMIC.exe", "\WerFault.exe",
↪ "\wmprvse.exe"])
```

2.611 LP_TerraMaster TOS CVE-2020-28188 Exploitation

- **Trigger Condition:** The exploitation of the TerraMaster TOS vulnerability CVE-2020-28188 is detected. CVE-2020-28188 is a remote command execution (RCE) vulnerability in TerraMaster TOS <= v4.2.06 that allows remote unauthenticated attackers to inject OS commands.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** T1190 - Exploit Public-Facing Application
- **Minimum Log Source Requirement:** Firewall, Proxy Server
- **Query:**

```
norm_id=* request_method=GET url="*/include/makecvs.php*" url="**?Event=*" url IN [
  ↳ "*/curl*", "*/wget*", "*/.py*", "*/.sh*", "*/chmod*", "*/_GET*"]
```

2.612 LP_VMware VSphere CVE-2021-21972 Exploitation

- **Trigger Condition:** The exploitation of VSphere Remote Code Execution vulnerability CVE-2021-21972 is detected.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** T1190 - Exploit Public-Facing Application
- **Minimum Log Source Requirement:** Firewall, Proxy Server
- **Query:**

```
norm_id=* request_method=POST url="*/ui/vropspluginui/rest/services/uploadova*"
```

2.613 LP_VMware View Planner CVE-2021-21978 Exploitation

- **Trigger Condition:** The exploitation of the VMware View Planner vulnerability CVE-2021-21978 is detected. CVE-2021-21978 is a flaw due to proper input validation and lack of authorization leading to arbitrary file upload in Log Upload web applications.
- **ATT&CK Category:** Initial Access

- **ATT&CK Tag:** T1190 - Exploit Public-Facing Application
- **Minimum Log Source Requirement:** Firewall, Proxy Server
- **Query:**

```
norm_id=* request_method=POST url="*logupload*" url="*logMetaData*" url="*wsgi_
↳log_upload.py"
```

2.614 LP_Zoho ManageEngine ADSelfService Plus CVE-2021-40539 Exploitation

- **Trigger Condition:** The REST API authentication bypass vulnerability (CVE-2021-40539) in Zoho ManageEngine ADSelfService Plus (v6113 and prior) is detected. For the detection to work, Administrators must fetch logs from the `\ManageEngine\ADSelfService Plus\logs` path.
- **ATT&CK Category:** Initial Access, Persistence
- **ATT&CK Tag:** T1190 - Exploit Public-Facing Application, T1505.003 - Web Shell
- **Minimum Log Source Requirement:** Web Server
- **Query:**

```
url=* url IN ["*/help/admin-guide/Reports/ReportGenerate.jsp*", "*/RestAPI/
↳LogonCustomization*", "*/RestAPI/Connection*"]
```

2.615 LP_Possible Access to ADMIN Share

- **Trigger Condition:** Access to \$ADMIN share that may help detect lateral movement attempts is detected. Since Windows Admin Share activity is so common, it provides adversaries with a powerful, discreet way to move laterally within an environment. Self-propagating ransomware and cryptocurrency miners, both rapidly emerging threats, rely on Windows Admin Shares. Suppose an adversary can obtain legitimate Windows credentials. The hidden shares (C\$, ADMIN\$, and IPC\$) can be accessed remotely via server message block (SMB) or the Net utility to transfer files and execute code. Windows Admin Shares are often used in conjunction with behaviors relating to Remote File Copy (T1105)—because adversaries commonly use the technique to copy files remotely—and Network Share Discovery (T1135). It can also occur with New Service (T1050) and Service Execution (T1035) because tools like PsExec deploys their receiver executable to admin shares, scheduling a service to execute it. Legitimate administrative activities may generate false positives and will require whitelisting.

- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** T1021.002 - SMB/Windows Admin Shares
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=5140 share_name="Admin$" -user="*$" -user IN EXCLUDED_USERS
```

2.616 LP_PsExec Tool Execution Detected

- **Trigger Condition:** PsExec service installation and execution events (service and Sysmon) are detected.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** System Services, Service Execution
- **ATT&CK ID:** T1569, T1569.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(norm_id=WinServer service="PSEXESVC" (event_id=7045 event_source="Service Control Manager" file="PSEXESVC.exe")
OR (event_id=7036)) OR (label=file label=create file=PSEXESVC.exe) OR (event_id IN [17, 18] pipe="\PSEXESVC*")
```

2.617 LP_Screensaver Activities Detected

- **Trigger Condition:** Adversaries's modification of registry key containing the path to binary used as screensaver executable is detected to establish persistence.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** T1546 - Event Triggered Execution, T1546.002 - Screensaver
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon (event_id=12 or event_id=13 or event_id=14) (target_object=
↳ "*\\Control Panel\\Desktop\\SCRNSAVE.exe") (parent_command!="*explorer.exe" or
↳ image!="*rundll32.exe" or command!="*shell32.dll, Control_RunDLL desk.cpl,
↳ ScreenSaver, *") -user IN EXCLUDED_USERS
```

2.618 LP_Suspect Svchost Activity Detected

- **Trigger Condition:** Scvhost activity is detected. It is abnormal for svchost.exe to spawn without any CLI arguments and is normally observed when a malicious process spawns the process and injects code into the process memory space.
- **ATT&CK Category:** Privilege Escalation, Defense Evasion
- **ATT&CK Tag:** T1055 - Process Injection
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 image="*\\svchost.exe" parent_image=* -parent_
↳ image IN ["*\\rpcnet.exe", "*\\rpcnetp.exe", "*\\svchost.exe", "*\\Mrt.exe", "*\\MsMpEng.
↳ exe"] command=* command="*\\svchost.exe" -user IN EXCLUDED_USERS
```

2.619 LP_Time-Stomping of Users Directory Files Detected

- **Trigger Condition:** Time-stomping of user directory file is detected. Sysmon can only detect a change of CreationTime and not LastWriteTime and LastAccessTime. Whitelisting legitimate noisy processes like browsers, Slack, or Teams are required to reduce false positives.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1070 - Indicator Removal on Host, T1070.006 - Timestomp
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=2 path="C:\\Users*" -source_image IN ["*\\iexplore.exe
↳ ", "*\\cortana*", "*\\StartMenuExperienceHost.exe", "C:\\Windows\\system32\\cleanmgr.exe
↳ ", "C:\\Windows\\Explorer.EXE", "*\\LocalBridge.exe", "*\\svchost.exe", "*\\RuntimeBroker.
↳ exe", "*\\msedge.exe", "*\\SearchApp.exe", "C:\\Windows\\system32\\ServerManager.exe
↳ ", "*\\ServiceHub.RoslynCodeAnalysisService32.exe"] -path=
↳ "*\\AppData\\Roaming\\Microsoft\\Windows\\Recent\\CustomDestinations\\*.*" (continues on next page)
↳ EXCLUDED_USERS
```

(continued from previous page)

2.620 LP_Windows Defender Exclusion Set Detected

- **Trigger Condition:** Added Windows Defender exclusion in the registry where an entity bypasses antivirus scanning from Windows Defender.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1562 - Impair Defenses, T1562.001 - Disable or Modify Tools
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_source="Microsoft-Windows-Windows Defender" event_
↪ id=5007 new_value="HKLM\SOFTWARE\Microsoft\Windows Defender\Exclusions\*"
```

2.621 LP_Suspicious Netsh DLL Persistence Detected

- **Trigger Condition:** Detects persistence via Netsh Helper.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** Netsh Helper DLL
- **ATT&CK ID:** T1546.007
- **Minimum Log Source Requirement:** Window Sysmon, Windows
- **Query:**

```
(label=Registry label=Set label=Value target_object="*\SOFTWARE\Microsoft\Netsh\*")
↪ OR (label="process" label=create "process"="*\netsh.exe" command="*add*")
↪ command="*helper*")
```

2.622 LP_Usage of Procdump Detected

- **Trigger Condition:** Suspicious use of the SysInternals ProcDump utility tool is detected.
- **ATT&CK Category:** Credential Access

- **ATT&CK Tag:** OS Credential Dumping, LSASS Memory
- **ATT&CK ID:** T1003, T1003.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" "process" IN ["*\procdump.exe", ".*\procdump64.exe"]
↪ command IN ["* -ma*", "*/ma*"]
```

2.623 LP_Conhost Spawning Suspicious Processes

- **Trigger Condition:** *conhost.exe* spawns other processes.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1202 - Indirect Command Execution
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
label="Process" label="Create" "parent_process"="*\conhost.exe" "process"=*
```

2.624 LP_Proxy Execution via Explorer

- **Trigger Condition:** *explorer.exe* is used in *cmd.exe* to proxy execution.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1202 - Indirect Command Execution
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
label="process" label="Create" "parent_process"="*\cmd.exe" "process"="*\explorer.exe"
↪ "command"="*explorer*"
```

2.625 LP_Wlrmldr Lolbin Use as Launcher

- **Trigger Condition:** *wlrmldr.exe* is used to proxy launch other executables.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1202 - Indirect Command Execution
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
label="process" "process"="*\wlrmldr.exe" - "parent_process"="*\winlogon.exe"
↪ command IN ['*-s *', '*-f *', '*-t *', '*-m *', '*-a *', '*-u *']
```

2.626 LP_Suspicious Process Execution via Pester Detected

- **Trigger Condition:** Detects code execution via *Pester.bat* (Pester - Powershell Module for testing).
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** T1059.001 - PowerShell, T1216 - Signed Script Proxy Execution
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="create" label="process" event_source="Microsoft-Windows-Sysmon" (
↪ "process"="*\powershell.exe" command="*Pester*Get-Help*") OR ("process"=
↪ "C:\Windows\System32\cmd.exe" command="*pester*;" command IN ["*help*",
↪ "*?*"])
```

2.627 LP_Root Certificate Installation Detected

- **Trigger Condition:** Adversaries may install a root certificate on a compromised system to avoid warnings when connecting to adversary-controlled web servers. This alert can detect the installation of a root certificate.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** T1553.004 - Install Root Certificate
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="Create" label="Process" event_source="Microsoft-Windows-Sysmon"
↪ command="*root*" ("process"="C:\Windows\System32\certutil.exe" command=
↪ "*-addstore*") OR ("process"="*\CertMgr.exe" command="*/add*") | norm on
↪ command <certificate:'\S+.cer'>
```

2.628 LP_Suspicious process spawned by FTP

- **Trigger Condition:** *ftp.exe* is used to file transfer, but it can be abused by spawning a new process using *ftp.exe*. The alert detects; renamed *ftp.exe*, *ftp.exe* script execution, and child processes run by *ftp.exe*.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** T1059 - Command and Scripting Interpreter, T1202 - Indirect Command Execution
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="create" label="process" event_source="Microsoft-Windows-Sysmon"
↪ (command="*-s.*" ("process"="C:\Windows\System32\ftp.exe" OR file="*ftp.exe*
↪ ")) OR (file="*ftp.exe*" - "process"="C:\Windows\System32\ftp.exe") OR parent_
↪ process="C:\Windows\System32\ftp.exe"
```

2.629 LP_Chromeloader Cross-Process Injection to Load Extension

- **Trigger Condition:** Chromeloader uses process injection using PowerShell and loads the malicious extension in Chrome.
- **ATT&CK Category:** Execution, Persistence, Privilege Escalation
- **ATT&CK Tag:** T1055 - Process Injection, T1059.001 - PowerShell, T1176 - Browser Extensions

- **Minimum Log Source Requirement:** -
- **Query:**

```
label="Process" label=Create parent_process="*powershell" parent_command = "*-exe* byp*  

↪-win* hid* -e* JAB*" command IN ["*--load-extension=*", "*Appdata\\local\\chrome*"]  

↪"process" = "*chrome"
```

2.630 LP_Proxy Execution via Explorer

- **Trigger Condition:** When Explorer is used to proxy execution. Explorer is a Microsoft Windows GUI shell used for task-based file management systems. Adversaries uses Explorer to proxy the execution of other commands or processes, evading defense mechanisms.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1202 - Indirect Command Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label=Create "process"="*\explorer.exe" "command"="*explorer*"
```

2.631 LP_Suspicious Root Certificate installation Detected

- **Trigger Condition:** Installation of a root certificate is detected. Adversaries may install a root certificate on a compromised system to avoid warnings when connecting to adversary-controlled web servers. However, sometimes Help Desk or IT may need to add a corporate Root CA on occasion manually. So they need to test if the GPO push doesn't trigger a False Positive.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1553.004 - Install Root Certificate
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="create" label="process" (command="*root*" (("process"="*\certutil.exe" command=
↪ "*-addstore*") OR ("process"="*\CertMgr.exe" command="*/add*"))))
```

2.632 LP_Windows Logon Reminder Usage as Launcher

- **Trigger Condition:** When *Wlrmldr* is used to proxy launch other executables. *Wlrmldr* (Windows Logon Reminder) is a Microsoft Windows Binary used by Microsoft to display messages at login. Adversaries uses *Wlrmldr* to pass parameters to *ShellExecute*.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1202 - Indirect Command Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label=create "process"="*\wlrmldr.exe" -"parent_process"="*\winlogon.exe" ⓘ
↪ command IN ['*-s *', '*-f *', '*-t *', '*-m *', '*-a *', '*-u *']
```

2.633 LP_Suspicious File Transfer Using Replace

- **Trigger Condition:** *Replace* is used to transfer (copy or download files) files. *Replace.exe* is a Microsoft Windows executable that allows replacing existing or adding new files in a directory if used with the */a* option. Adversaries uses the *replace* process to silently download or copy files in the target system.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1105 - Ingress Tool Transfer
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label=create "process"="*\replace.exe" command IN ["*/a*", "*-a*"]
```

2.634 LP_Proxy Execution via Program Compatibility Wizard

- **Trigger Condition:** Pcwrn process is used to initiate a proxy execution. Pcwrn is a Microsoft Windows Operating System file used to invoke Program Compatibility Troubleshooter/Wizard. Adversaries uses pcwrn to proxy the execution of other commands, processes, or executables in order to evade defense mechanisms. However, the specific focus needs to be on outlier events, for example unique counts, instead of commonly seen artifacts to prevent false positives.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1218 - Signed Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label=create label="process" parent_process="*\pcwrn.exe"
```

2.635 LP_Suspicious Driver Installation via PnPUtl

- **Trigger Condition:** Pnputil process is used to install or add drivers. PnPUtl is a Microsoft Windows process that lets an administrator perform actions on driver packages. Adversaries uses pnputil to install or add malicious drivers. Anyone who uses pnputil.exe who is not a system administrator should be investigated, even when they have system change permissions.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** T1547 - Boot or Logon Autostart Execution, T1547.006 - Kernel Modules and Extensions
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label=create "process"="*\pnputil.exe" command IN ["*-i*", "*/install*", "*/a*", "*/add-driver*", "*/inf*"]
```

2.636 LP_Application Whitelisting Bypass via PresentationHost

- **Trigger Condition:** Presentationhost process is used to execute browser applications. Presesntationhost is a Microsoft Windows application that enables the hosting of WPF applications in compatible browsers (including Microsoft Internet Explorer 6 and later). Adversaries uses presentationhost.exe to evade application whitelisting and execute malicious XAML Browser Application (XBAP) files.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1218 - Signed Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label=create "process"="*\presentationhost.exe" command="*.xbap"
```

2.637 LP_Suspicious File Extraction via Expand Detected

- **Trigger Condition:** Expand process is used for file transfer (copy or download files). Expand is a Microsoft Windows binary file provided by Microsoft that can extract one or more compressed files and retrieve them from distribution disks. Adversaries uses expand to silently download or copy files into the target system or location.
- **ATT&CK Category:** Defense Evasion, Command and Control
- **ATT&CK Tag:** T1105 - Ingress Tool Transfer, T1218 - Signed Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label=create "process"="*\expand.exe" command IN ["*.cab*", "*/F:*", "*/F:*  
↪", "*/C:\ProgramData\*", "*/C:\Public\*", "*/AppData\Local\Temp\*",  
↪ "*/AppData\Roaming\Temp\*"]
```

2.638 LP_Suspicious Use of Extrac32 Detected

- **Trigger Condition:** Suspicious file overwrite using `extrac32.exe` is detected.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Ingress Tool Transfer
- **ATT&CK ID:** T1105
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Create" label="Process" "process"="*\extrac32.exe" command="*extrac32*"
↪ command IN ["*/C*", "*/Y*", "*/\\*"]
```

2.639 LP_Shell spawn via HTML Help Detected

- **Trigger Condition:** *Hh* (HTML Help) spawns shell processes. *Hh.exe* is a Microsoft Windows executable program that allows developers to compile .chm file(s) with expanding tables of contents, shortcuts, keyword search, and pop-up topics. Adversaries uses *Hh* as a target for overwriting and executing their malicious commands, spawning other processes.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** T1047 - Windows Management Instrumentation, T1218.001 - Compiled HTML File
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label=create parent_process="*\\hh.exe" "process" IN ["*\\cmd.exe",
↪ "*\\powershell.exe", "*\\wscript.exe", "*\\cscript.exe", "*\\regsvr32.exe", "*\\wmic.exe",
↪ "*\\rundll32.exe"]
```

2.640 LP_DLL Injection with Tracker Detected

- **Trigger Condition:** DLL injection with the tracker process is detected. *Tracker.exe* is a legitimate internal Windows binary file required to incrementally generate resources like building on a 64-bit OS using 32-bit MSBuild. Adversaries can use it

to bypass application whitelisting solutions by proxy execution of an arbitrary DLL into another process.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1055.001 - Dynamic-link Library Injection
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="create" label="process" (("process"="*\tracker.exe" OR description="Tracker")  
↪command="*/d*" command="*/c*")
```

2.641 LP_Powershell Code Execution via SyncAppvPublishingServer

- **Trigger Condition:** Arbitrary Powershell command is executed via SyncAppvPublishingServer. VBScript files, such as SyncAppvPublishingServer.vbs, are trusted scripts, often signed with certificates. Adversaries can use SyncAppvPublishingServer.vbs to proxy execute PowerShell code.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1216 - Signed Script Proxy Execution, T1218 - Signed Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label='create' label='process' command='*\SyncAppvPublishingServer.vbs*' command='*,*'
```

2.642 LP_Malicious PE Execution by Microsoft Visual Studio Debugger

- **Trigger Condition:** Arbitrary Powershell command is executed via SyncAppvPublishingServer. VBScript files, such as SyncAppvPublishingServer.vbs, are trusted scripts, often signed with certificates. Adversaries can use SyncAppvPublishingServer.vbs to proxy execute PowerShell code.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** T1218 - Signed Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Create" label="Process"(parent_process="*\vsjitdebugger.exe" -(("process"=
↪ ".*\vsimmersiveactivatehelper*.exe" OR "process"=".*\devenv.exe")))
```

2.643 LP_Suspicious Atbroker Registry Change Detected

- **Trigger Condition:** Creation or modification of Assistive Technology (AT) registry value is detected. Atbroker is a Windows internal helper binary that provides accessibility tools like screen readers, speech input and text readers, people with disabilities use to accomplish tasks. Adversaries can modify the assistive technology registry value and include their malicious application to maintain persistence.
- **ATT&CK Category:** Persistence, Defense Evasion
- **ATT&CK Tag:** T1218 - Signed Binary Proxy Execution, T1547 - Boot or Logon Autostart Execution
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon label=Registry label=Set target_object IN [
↪ ".*\Software\Microsoft\Windows NT\CurrentVersion\Accessibility\ATs*",
↪ ".*\Software\Microsoft\Windows NT\CurrentVersion\Accessibility\Configuration*"]
```

2.644 LP_DLL loaded Via Certoc Binary Detected

- **Trigger Condition:** DLL loading is detected using certoc binary. Certoc is Windows internal binary used to install certificates, but it also has a feature to load a DLL by LoadDll tag. Adversaries can use certoc binary to load their malicious DLL even when they don't have the relevant access rights.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1218 - Signed Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon

- **Query:**

```
label="Process" label=Create command="*certoc.exe*" command IN ["* -LoadDll *", "* /
↪LoadDll *"] command="*.dll*"
```

2.645 LP_Suspicious Remote Binary Usage Detected

- **Trigger Condition:** remote.exe binary is used to bypass application whitelisting and execute or run a local or remote file. Remote.exe is a Windows binary server/client tool that allows users to run command-line programs on remote computers. Adversaries can use the remote.exe binary to spawn a new Powershell session, AWL bypass, and execute other commands.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1127 - Trusted Developer Utilities Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Process" label="Create" "process"="*\remote.exe" command="*/s*"
```

2.646 LP_Suspicious ASP NET Compiler Execution Detected

- **Trigger Condition:** A file with the extension .jse, .vbe, .js, or .vba is executed using wscript or cscript. Wscript and cscript are Windows binaries that provide an environment in which users can execute scripts in various languages or start a script to run in a command-line environment. Adversaries can code malicious scripts in .jse, .vbe, .js, or .vba files and execute them using wscript or cscript and bypass detection.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1127 - Trusted Developer Utilities Proxy Execution
- **Minimum Log Source Requirement:** -
- **Query:**

```
label=Create label="Process" "process" = "C:\Windows\Microsoft.NET\Framework*" "process"
↳ ".*\aspnet_compiler.exe"
```

2.647 LP_Suspicious LoadAssembly PowerShell Diagnostic Script Execution

- **Trigger Condition:** Microsoft signed script is used to execute commands and bypass AppLocker. CL_LoadAssembly.ps1, a windows native diagnostic script, provides two functions (LoadAssemblyFromNS and LoadAssemblyFromPath) for loading .NET/C# assemblies (DLLs/EXEs). An attacker can bypass Constrained Language mode by invoking PowerShell version 2 (Note: this must be enabled) and bypass AppLocker by loading an assembly through CL_LoadAssembly.ps1.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1216 - Signed Script Proxy Execution
- **Minimum Log Source Requirement:** -
- **Query:**

```
command IN [".*\CL_LoadAssembly.ps1", ".*\LoadAssemblyFromPath*"] "Process" =
↳ ".*\powershell.exe"
```

2.648 LP_Suspicious Invocation PowerShell Diagnostic Script Execution

- **Trigger Condition:** The execution of malicious payloads via SyncInvoke in CL_Invocation.ps1 module is detected. CL_Invocation is a PowerShell Diagnostic script, but an attacker can import it and then call SyncInvoke to launch a malicious executable.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1216 - Signed Script Proxy Execution
- **Minimum Log Source Requirement:** -
- **Query:**

```
command IN ["*\CL_Invocation.ps1 ", "*SynclInvoke*"] "Process"="*\powershell.exe"
```

2.649 LP_Registry Configured RunOnce Task Execution

- **Trigger Condition:** The RunOnce task executes as configured in the registry. Runonce.exe is a Microsoft Windows Operating System component called the *Run Once Wrapper Utility* that allows the installation program to reboot after initial start up to enable the user to make further configurations. Adversaries uses the runonce executable to evade defense mechanisms while running their programs/code through registry entries in the host machine.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1112 - Modify Registry
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label=create "process"="*\runonce.exe" command="* /AlternateShellStartup*
↪ "
```

2.650 LP_RunOnce Registry Key Configuration Change

- **Trigger Condition:** When the configuration of Run Once registry key is changed. Runonce.exe is a Microsoft Windows Operating System component called the *Run Once Wrapper Utility* that allows the installation program to reboot after initial start up to enable the user to make further configurations. Adversaries uses/changes the runonce registry key values to evade defense mechanisms while running their programs/code in the host machine.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1112 - Modify Registry
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="process" label=create "process"="*\runonce.exe" command="* /AlternateShellStartup*
↪ "
```

2.651 LP_Suspicious WSL Bash Execution

- **Trigger Condition:** When bash is used to execute the Linux command. Bash is a Unix shell and command language. Adversaries can use bash to execute a specified file or commands in the Windows subsystem for Linux and can be used as a defensive evasion mechanism. Executing programs using bash can trigger this alert, so alerts must be further analyzed to determine legitimate or illegitimate use.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1202 - Indirect Command Execution
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" command="*bash* -c *
```

2.652 LP_WSL Execution Detected

- **Trigger Condition:** When Windows subsystem for Linux (WSL) binary is used to execute Linux commands. WSL is a compatibility layer that allows running Linux binaries in Windows. Adversaries can use the wsl binary to execute Windows and Linux binaries, execute arbitrary Linux commands as root without a password or download files.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1202 - Indirect Command Execution
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" "process"="*\wsl.exe" command in ["*-e *", "--exec *"]
```

2.653 LP_Suspicious Usage of Csharp or Roslyn Csharp Interactive Console

- **Trigger Condition:** When the use of csi and rcsi binary are detected. Csi.exe is a Microsoft signed binary that provides C# interactive capabilities. Rcsi.exe is a Microsoft signed binary that can execute C# code. Adversaries can use these binaries to execute their malicious C# code.

- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1072 - Software Deployment Tools
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" ("process" IN ["*\csi.exe", "*\rcsi.exe"]) OR (file in ["csi.exe",  
↪ "\rcsi.exe"])
```

2.654 LP Possible Commandline Obfuscation Detected

- **Trigger Condition:** Suspicious characters in the command indicating possible command obfuscation is detected. Adversaries leverage this technique by using multiple Unicode characters to obfuscate the command they are executing to bypass signature-based detections.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Obfuscated Files or Information
- **ATT&CK ID:** T1027
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ((parent_process="*cmd.exe" parent_command IN ["^\\^\\^\\^\\^\\^\\", "*set*=*call*%*%*", '*s^e^\\*t*']) OR (command IN ["*?*", "*?*", "*?*", "*/*", "*/*", "*?*", "*_*", "*â*", "*€*", "*£*", "*$*", "*®*", "*µ*", "*¶*"])))
```

2.655 LP_Possible Emotet Activity Detected

- **Trigger Condition:** Process events related to emotet is created.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** Obfuscated Files or Information, PowerShell
- **ATT&CK ID:** T1027, T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (command IN ["* -e* PAA*",
↳ "*JABIAG4AdgA6AHUAcwBIAHIAcABYAG8AZgBpAGwAZQ*",
↳ "*QAZQBuaHYAOgB1AHMAZQByAHAAcgBvAGYAaQBsaGUA*",
↳ "*kAGUAbgB2ADoAdQBzAGUAcgBwAHIAbwBmAGkAbABIA*",
↳ "*IgAoACcAKgAnACkAOwAkA*", "*IAKAAnACoAJwApADsAJA*",
↳ "*iACgAJwAqACcAKQA7ACQA*", "*JABGAGwAeABYAGgAYwBmAGQ*"]) (-command IN [
↳ "fAAgAEMAbwBuAHYAZQByAHQAVABvAC0ASgBzAG8AbgAgAC0ARQByAHIAbwByAEEAYwB0AGkAbwBu",
↳ ",
↳ "wAIABDAG8AbgB2AGUAcgB0AFQAbwAtAEoAcwBvAG4AIAAtAEUAcgByAG8AcgBBAGMAdABpAG8Abg",
↳ ",
↳ "8ACAAQwBvAG4AdgBIAHIAdABUAG8ALQBKAHMABwBuACAALQBFAHIAcgBvAHIAQQBjAHQAaQBvAG",
↳ "]) -user IN EXCLUDED_USERS
```

2.656 LP_Suspicious Use of Control Panel Items

- **Trigger Condition:** Malicious use of a control panel item is detected.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Control Panel
- **ATT&CK ID:** T1218.002
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create (((("process"="*\reg.exe" OR file="reg.exe") command="*add*"
↳ command="*CurrentVersion\Control Panel\CPLs*") OR (command="*.cpl" -(command IN [
↳ "*\System32\*", "%System%*")]) OR (command="*regsvr32 *" command="*/s *" command=
↳ "*igfxCPL.cpl*"))))
```

2.657 LP_Suspicious Use of CSharp Interactive Console Detected

- **Trigger Condition:** The execution of the CSharp interactive console by using PowerShell is detected. Adversaries can run CSharp interactive console from PowerShell and execute their malicious code.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1127 - Trusted Developer Utilities Proxy Execution

- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" "process"="*\csi.exe" file="csi.exe" parent_process=
↳ ".*\powershell.exe"
```

2.658 LP_Suspicious Use of Colorcpl Detected

- **Trigger Condition:** Suspicious usage of colorcpl binary such as execution from non default path and creation of unusual files are detected.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** T1574.001 - DLL Search Order Hijacking
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(label="Process" label="Create" -"process"="C:\Windows\System32\colorcpl.exe" "process"=
↳ ".*\colorcpl.exe") OR (norm_id=WindowsSysmon event_id=11 image=".*\colorcpl.exe" file In [
↳ ".*.icm", ".*.gmmp", ".*.cdmp", ".*.camp"])
```

2.659 LP_Suspicious File Download via Certreq

- **Trigger Condition:** When a file is downloaded using certreq binary. Certreq is a Windows binary used to manage and request a certificate from the certificate authority. Adversaries can use certreq to download payload from their C2 server.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** T1105 - Ingress Tool Transfer
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" "process"="*\certreq.exe" command=".*certreq*" command
↳ IN ["* -Post *", " /Post *"] command IN ["* -config *", "*/config *"] command=".* http*"
↳ command=".* C:\windows\win.ini *
```

2.660 LP_Process Dump via Rundll32 and Comsvcs

- **Trigger Condition:** When LSASS dump using Rundll32 with Comsvcs DLL is detected. *Rundll32.exe* is a Windows binary that loads and runs 32-bit dynamic-link libraries. *comsvcs.dll* is a DLL file used by COM+ Services created by Microsoft. Adversaries can use the binary and DLL to dump the LSASS process.
- **ATT&CK Category:** Defense Evasion, Credential Access
- **ATT&CK Tag:** LSASS Memory, Rundll32
- **ATT&CK ID:** T1003.001, T1218.011
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create ("process"="*\rundll32.exe" or file="RUNDLL32.EXE")
↪command="*comsvcs*" command="*full*" command IN ["*#-*", "*#+*", "*#24*", "*24 *",
↪"*MiniDump*"]
```

2.661 LP_Registry Key Import Detected

- **Trigger Condition:** When registry key import is detected via regedit.exe. Regedit is a Windows binary to access and manipulate the Windows registry. This hierarchical database stores low-level settings for the Microsoft Windows operating system and applications that opt to use the registry. A registry key is an organizational unit in the Windows registry. Adversaries can use Regedit to import their malicious registry key to achieve persistence.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1112 - Modify Registry
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Process" label="Create" "process"="*\regedit.exe" OR file="regedit.exe" command
↪IN ["*/i *", "*/j *"] command="*.reg*" -command IN ["*/e *", "*/a *", "*/c *", "*/-e *", "*/-a *", "*/-
↪c *"]
```

2.662 LP_Suspicious MachineGUID Query Detected

- **Trigger Condition:** When reg.exe is used to detect query machine GUID. Reg.exe is a Windows binary that performs operations on registry subkey information and values in registry entries. MachineGUID is a unique identifier for a machine. Adversaries can use this technique to get MachineGuid information. Also, ransomware abuses this technique to keep track of infected systems using a unique ID.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** T1082 - System Information Discovery
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Process" label="Create" "process"="*reg.exe" command="* query *" command=
↳ "*SOFTWARE\Microsoft\Cryptography*" command IN ["*/v *", "*-v *"] command=
↳ "*MachineGuid*"
```

2.663 LP_Process Injection Via Mavinject Detected

- **Trigger Condition:** When DLL is injected into a running process. Microsoft Application Virtualization Injector (Mavinject) is a Windows utility that can inject code into external processes as part of Microsoft Application Virtualization (App-V). Adversaries can use mavinject to inject malicious DLL to obtain arbitrary code execution.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1218.013 - Mavinject
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Process" label="Create" "process"="*mavinject.exe" command IN ["* /injectrunning*",
↳ "* -injectrunning*", "*.dll*"]
```

2.664 Possible File Transfer Using Finger Detected

- **Trigger Condition:** When the execution of Finger.exe is detected. It is a simple Windows binary that displays user information on a specified remote computer running the Finger service or daemon. It can be abused as a data transfer tool and makeshift C2 channel. However, general administrative use can trigger false positives, but it is still unclear why they use finger.exe.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** T1105 - Ingress Tool Transfer
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label="create" "process"="*\finger.exe"
```

2.665 LP_Suspicious Use of Findstr Detected

- **Trigger Condition:** When suspicious actions such as credential access, file download, or creation of alternate data stream using findstr are detected. Generally, it is used to search for strings in files or to filter command line output. Adversaries can exploit it for defense evasion. However, general administrative use of findstr can trigger false positives.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1218 - Signed Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="create" label="process" "process"="*\findstr.exe" command="*findstr*" ((command=
↪ "*/V*" command="*/L*") OR (command="*/S*" command="*/I*"))
```

2.666 LP_Suspicious File Overwrite Using extrac32 Detected

- **Trigger Condition:** When suspicious actions such as credential access, file download, or creation of alternate data stream using findstr are detected.

Generally, it is used to search for strings in files or to filter command line output. Adversaries can exploit it for defense evasion. However, general administrative use of findstr can trigger false positives.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1218 - Signed Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="create" label="process" "process"="*\findstr.exe" command="*findstr*" ((command=
↪ "*/V*" command="*/L*") OR (command="*/S*" command="*/I*"))
```

2.667 LP_Suspicious Sysmon Driver Unload Detected

- **Trigger Condition:** When suspicious unload of SysmonDrv Filter Driver is detected. Fltmc.exe program is a system-supplied command line utility for mini-filter driver management operations. Adversaries can abuse its functionality to unload the filter driver, which can affect sysmon and stop from collecting the data.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1070 - Indicator Removal on Host, T1562 - Impair Defenses, T1562.002 - Disable Windows Event Logging
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label="create" "process"="*\fltmc.exe" command="*unload*" command =
↪ "*sys*"
```

2.668 LP_Suspicious Execution via IE per User Utility

- **Trigger Condition:** When ie4uinit is executed from unusual file directories. ie4uinit.exe (Internet Explorer (for) Each User Initialization) file is a software component of Internet Explorer by Microsoft Corporation. Adversaries generally abuse ie4uinit.exe to overwrite malicious programs on it and spread them via the internet to execute them on target machines as legitimate processes.
- **ATT&CK Category:** Defense Evasion

- **ATT&CK Tag:** T1218 - Signed Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label="create" ("process"="*\ie4unit.exe" OR file="ie4unit.exe") -(path IN [
↪ "C:\Windows\System32\","C:\Windows\SysWOW64\"])
```

2.669 LP_Proxy Execution via xWizard

- **Trigger Condition:** When the execution of the xWizard tool with runwizard and CLSID arguments are utilized to achieve proxy execution. xWizard is Windows internal binary used to run the Windows component object model (COM). COM is operated to enable inter-process communication. Class ID (CLSID) is a unique number representing a single application component in windows. Adversaries can bypasses the defense mechanism by proxying the execution of malicious content via xWizard.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1218 - System Binary Proxy Execution
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\xwizard.exe" | process regex("(?P<new_
↪command>{\w{8}-\w{4}-\w{4}-\w{4}-\w{12}})",command) | filter new_command=*
```

2.670 LP_Suspicious MSHTA Process Pattern

- **Trigger Condition:** When suspicious *mshta.exe* process patterns, such as binary run from a non-default path, *mshta.exe* binary masquerading as different binary, and execution of HTML application (HTA) masquerading as non-HTA file are detected. Mshta.exe is a utility that executes HTA files. HTAs are standalone applications based on HTML and VBScript that can access local system resources, run scripts and display dynamic content. Adversaries may abuse *mshta.exe* to evade defense by proxy, executing malicious files and Javascript or VBScript through a trusted Windows utility.
- **ATT&CK Category:** Defense Evasion, Execution

- **ATT&CK Tag:** Mshta, Native API
- **ATT&CK ID:** T1218.005, T1106
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\mshta.exe"
((parent_process IN ["*\cmd.exe", "powershell.exe"] OR command IN ["*\AppData\Local*",
↪ "C:\Windows\Temp*", "C:\Users\Public*"]) OR (-"process" IN ["C:\Windows\System32*",
↪ "C:\Windows\SysWOW64*"] ) OR (-command IN ["*\mshta.exe", "mshta"] -command IN ["*.
↪ htm*", "*.hta*"] ))
```

2.671 LP_COM Object Execution via Shell Extension CLSID Verification Host

- **Trigger Condition:** When verclsid.exe is used to run COM object via GUID. Verclsid.exe (Verify COM Shell Extension CLSID) is a Microsoft Windows Native Shell Extension CLSID (Class ID) verification host responsible for verifying each shell extension before Windows Explorer or the Windows Shell uses them. Adversaries may abuse verclsid.exe to execute malicious payloads-COM Scriptlets, by running verclsid.exe and referencing files by Class ID (CLSID), a unique identification number used to identify COM objects.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" "process"="*\verclsid.exe" command="*/C*" command="*/S*"
↪ "
```

2.672 LP_Suspicious Setup Information File Invoked via DefaultInstall

- **Trigger Condition:** When InfDefaultInstall.exe is used to install an INF file. InfDefaultInstall.exe is a Microsoft Windows native tool invoked when an INF (Setup Information) file is selected to install. Adversaries uses InfDefaultInstall to install on the target system through maliciously crafted INF files.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1562.001 - Disable or Modify Tools
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" "process"="*\InfDefaultInstall.exe" command=
↪ "InfDefaultInstall*" command="*.inf"
```

2.673 LP_Creation of Alternate Data Stream

- **Trigger Condition:** When an alternate data stream is created. Alternate Data Stream (ADS) is the ability of an NTFS file system to store different streams of data, in addition to the default stream, which is used for a file. Attackers can leverage a little-known compatibility feature to hide hacking tools, keyloggers, and other malware on a compromised system and subsequently execute them undetected. Also, it can be used for data exfiltration. The alert requires the ADS_FILE_EXTENSIONS list to work.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1564.004 - NTFS File Attributes
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
(label="create" label="process" command IN ADS_FILE_EXTENSIONS ((command="*type *"
↪ command="* > *") OR (command="*makecab*" command="*.cab*") OR (command="*reg
↪ *" command="* export *") OR (command="*diantz.exe*" command="*.cab*") OR
↪ (command="*regedit*" command="*/E *") OR (command="*print*" command IN ["/D:*",
↪ "*/d:*"]) OR (command="*expand*") OR (command="*extrac32*" command="*.cab*") OR
↪ (command="*curl*" command IN ["*--output*", "*-o*"]) OR (command="*certutil*"
↪ command="*-urlcache*") OR (command="*esentutl*" command="*/y*" command="*/d*")
↪ OR (command="*esentutl*" command="*/y*" command="*/d*" command="*/o *"))
↪ OR (label="create" label="file" file in ADS_FILE_EXTENSIONS)
```

2.674 LP_Alternate Data Stream Created using Findstr

- **Trigger Condition:** When findstr is used to create an alternate data stream. Findstr is generally used to search for strings in files or to filter command line output. Adversaries can exploit it to create an alternate data stream for defense evasion. For this alert to work, the ADS_FILE_EXTENSIONS list is required.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1564.004 - NTFS File Attributes
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
[label="create" label="process" "process"="*\findstr.exe" command="*\findstr*" ((command=
↪ "*/V*" command="*/L*") OR (command="*/S*" command="*/I*"))] as s1 followed by [label=
↪ "Create" label="File" file in ADS_FILE_EXTENSIONS] as s2 on s1.process_id=s2.process_id [?]
↪ rename s1.process as "process", s1.log_ts as log_ts, s1.command as command, s1.host as host,
↪ s1.user as user, s1.parent_process as parent_process
```

2.675 LP_Suspicious Download Using Diantz

- **Trigger Condition:** When a remote file is downloaded using diantz.exe and stored by compressing it into a .cab file on a local machine. It performs a similar function as makecab.exe, which compresses a file into a smaller file with a .cab file extension. Adversaries can use diantz.exe for ingress tool transfer to evade the defenses and establish a c2 connection.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** T1105 - Ingress Tool Transfer
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" command="*\diantz.exe*" command="*\*" command="*.*.
↪ cab"
```

2.676 LP_Ngrok RDP Tunnel Detected

- **Trigger Condition:** When it detects the execution of Ngrok utility for tunneling RDP connection. Threat actors often use Ngrok to expose internal services to the internet, like making RDP publicly accessible. 16777216 artifact gets logged when an incoming RDP connection is established via ngrok.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** T1572 - Protocol Tunneling

- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer ((event_source IN ["Microsoft-Windows-TerminalServices-
↳ LocalSessionManager", "Microsoft-Windows-TerminalServices-RemoteConnectionManager
↳"]) OR (channel=Security event_id=4779)) (source_address="::%16777216" OR eventxml.
↳ address="::%16777216") | rename eventxml.address as source_address
```

2.677 LP_Ngrok Execution

- **Trigger Condition:** When it detects the execution of the Ngrok utility used for port forwarding and protocol tunneling. Threat actors often use Ngrok to expose internal services to the internet, like making RDP publicly accessible.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** T1572 - Protocol Tunneling
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="Process" label=Create (("process"="*\ngrok.exe" command IN ["* tcp *", "* http *", "*?
↳ authToken *"]) OR (command="* start *" command="*--all*" command="*.yml*" command=
↳ "*--config*") OR (command IN ["* tcp 139*", "* tcp 445*", "* tcp 3389*", "* tcp 5985*", "*?
↳ tcp 5986*"])))
```

2.678 LP_Windows Defender Uninstall via PowerShell

- **Trigger Condition:** When PowerShell is used to uninstall Windows Defender. PowerShell is a Microsoft task automation and configuration management program consisting of a command-line shell with its scripting language. Microsoft Defender Antivirus is an anti-malware component of Microsoft Windows. Adversaries can use this technique to avoid the detection of their malware.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1562 - Impair Defenses
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\powershell.exe" command="*Uninstall-
↳ WindowsFeature*Name*Windows-Defender*"
```

2.679 LP_Hijacked Binary Execution via Settings Synchronizer

- **Trigger Condition:** When SettingSyncHost is used to run hijacked binaries. SettingSyncHost is a Microsoft Windows host process that synchronizes system settings with other devices, including Internet Explorer, a mail application, OneDrive, Xbox and other application settings. Adversaries can exploit SettingSyncHost to run hijacked binaries and other specified files.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1574.008 - Path Interception by Search Order Hijacking
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" - "process" IN ["C:\Windows\System32\*",
↳ "C:\Windows\SysWOW64\*"] parent_command IN ["*cmd.exe /c*", "*cmd /c*"] parent_
↳ command="*RoamDiag.cmd*" parent_command="*-outputpath*"
```

2.680 LP_Suspicious Execution of Dump64

- **Trigger Condition:** When suspicious use of dump64.exe is detected. dump64.exe is a memory dump tool bundled with Microsoft Visual Studio. Adversaries can leverage it to create a memory dump and parse it offline to retrieve credentials. Adversaries can bypass Microsoft Defender by renaming a tool to dump64.exe and placing it in a Visual Studio folder, for example, procdump.exe. It can trigger false positives if dump64.exe is executed from any folder other than excluded one, even for a legitimate purpose.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** T1003.001 - LSASS Memory
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" "process"="*\dump64.exe" (-("process"=
↪ " *\Installer\Feeback\dump64.exe*") OR command IN ["*-ma *", "*accpeteula*"])
```

2.681 LP_Code Compilation via Visual Basic Command Line Compiler

- **Trigger Condition:** When a successful compilation of code using Visual Basic Command Line Compiler is detected. vbc.exe is Microsoft's Visual Basic compiler used to compile programs within the Visual Studio integrated development environment (IDE). Adversaries can leverage it to collect malicious code on the system to bypass defensive countermeasures. The legitimate use of this tool can trigger false positives, but it is barely used in enterprise environments, so the detection of service is suspicious.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1027.004 - Compile After Delivery
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" parent_process="*\vbc.exe" "process"="*\cvtres.exe"
```

2.682 LP_File Downloaded from Suspicious URL Using GfxDownloadWrapper

- **Trigger Condition:** When downloading files from suspicious (non-standard) URLs using GfxDownloadWrapper.exe is detected. Intel Graphics Executable Download Wrapper (GfxDownloadWrapper) is an application file that allows you to update your graphics card module. It downloads JSON files from <https://gameplayapi.intel.com>. Adversaries can leverage its functionality to download files from other non-standard URLs.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** T1105 - Ingress Tool Transfer
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" "process"="*\GfxDownloadWrapper.exe" - command=
↪ "*gameplayapi.intel.com*" - parent_process="*\GfxDownloadWrapper.exe"
```

2.683 LP_Suspicious CLR Logs File Creation

- **Trigger Condition:** When .NET code is executed via applications, such as mshta, cscript, wscript, regsvr32 and wmic. .NET is a developer platform with tools and libraries for building applications, including web, mobile, desktop, games, IoT, cloud, and microservices. Common Language Runtime in a .NET environment runs code and provides services to make the development process more manageable. The binaries included in the query are Windows internal binary which adversaries can use to execute their malicious scripts.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** T1055 - Process Injection
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=File label=Create label=Overwrite path="*\AppData\Local\Microsoft\CLR*\UsageLogs\*"
↪ " file IN ["mshta*", "cscript*", "wscript*", "regsvr32*", "wmic*"]
```

2.684 LP_CLR DLL Loaded via Scripting Application

- **Trigger Condition:** When Common Language Runtime (CLR) DLL is loaded via scripting applications. mshta.exe, wscript.exe and cscript.exe are Windows internal binary. Common Language Runtime works in the .NET environment, which runs the code and provides services that make the development process more manageable. Adversaries can use this technique to execute malicious scripts.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1218.005 - Mshta
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=image label=load source_image IN ["*\wscript.exe", "cscript.exe", "mshta.exe"] ⓘ
↪ image IN ["*\clr.dll", "mscorlib.dll", "mscorlib.dll"]
```

2.685 LP_Obfuscation Script Usage via MSHTA to Execute Vbscript

- **Trigger Condition:** When execution of invoke-obfuscation PowerShell script with mshta to execute vbscript is detected. mshta.exe file is a software component of Windows Internet Explorer that runs HTML application(HTA) files. Invoke Obfuscation is a PowerShell command and script obfuscation framework. VBScript is an Active Scripting language developed by Microsoft modeled on Visual Basic. Adversaries can use this technique to bypass defensive mechanisms.
- **ATT&CK Category:** Defense Evasion, Execution
- **ATT&CK Tag:** T1027 - Obfuscated Files or Information, T1059.001 - PowerShell
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create command=* | process regex("(?P<new_command>(?!).*(&&
↪).*(mshta).*(vbscript:createobject).*(\\.run).*(\\window\\.close\\.)*",command) | filter new_
↪command=*
```

2.686 LP_Microsoft Defender Logging Disabled

- **Trigger Condition:** When Windows Defender Registry key is modified to disable Windows Defender's logging. Windows Defender is an anti-malware component of Microsoft Windows. Adversaries use this technique to disable logs generated from Windows Defender and avoid detection.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1562 - Impair Defenses
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Registry label=Value label=Set target_object=
↪"*\\SOFTWARE\\Microsoft\\Windows\\CurrentVersion\\WINEVT\\Channels\\Microsoft-Windows-
↪Windows Defender\\Operational\\Enabled" detail="DWORD (0x00000000)"
```

2.687 LP_UAC Bypass via CMLUA or CMSTPLUA

- **Trigger Condition:** When user CMLUA OR CMSTPLUA DLL is loaded to perform user account control (UAC) bypass.
- **ATT&CK Category:** Privilege Escalation
- **ATT&CK Tag:** T1548.002 - Bypass User Account Control
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id="WindowsSysmon" label=Image label=Load image IN ["*\cmlua.dll", ".*\cmstplua.dll",
↪ ".*\cmluautil.dll"] - "process" IN [".*\cmstp.exe", ".*\cmmgr32.exe"] - "process" IN [
↪ ".*\windows\*", ".*\program files\*"]
```

2.688 LP_High Number of Service Stop or Task Kill in Short Span

- **Trigger Condition:** Over ten task kill, service stop or delete events are detected. Adversaries can use this technique to kill, stop or delete services or processes that might otherwise hinder their payload execution. Ransomware is seen as deleting or blocking processes or services before starting the encryption process.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** Service Stop
- **ATT&CK ID:** T1489
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label=create (("process" = ".*\taskkill.exe" (command= ".*f.*" command=".*im.*"
↪ ") OR command=".*IM.*") OR ("process" IN [".*\sc.exe", ".*\net.exe", ".*\net1.exe"]
↪ command=".*stop.*") OR ("process" = ".*\sc.exe" command IN [".*delete.*", ".*disabled.*"]))) -
↪ user IN EXCLUDED_USERS | chart count() as occurrence by user,host,domain,"process",
↪ parent_process | search occurrence > 10
```

2.689 LP_LSA Protected Process Light Disabled

- **Trigger Condition:** When modification of the registry value of Protection Process Light (PPL) to disable, it is detected. Protected Process can be accessed by executables that are digitally signed with a unique Windows Media, with administrator privilege. Protected Process Light is an extension of a protected process where a process can be assigned a different level of protection. Adversaries can use this technique to access the LSASS process and dump it to retrieve credentials.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1112 - Modify Registry
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Registry label=Set label=Value target_object=
→ "*\\System\\CurrentControlSet\\Control\\Lsa\\RunAsPPL " detail="DWORD (0x00000000)"
```

2.690 LP_Suspicious Invocation of Microsoft Workflow Compiler

- **Trigger Condition:** When the use of Microsoft Workflow Compiler is detected. Microsoft Workflow Compiler is a utility included by default in the .NET framework, capable of compiling and executing arbitrary, unsigned C# or VB.net code. Adversaries can leverage it for the proxy execution of executables to evade detection. The use of MWC in an enterprise environment is highly unlikely. However, legitimate use can trigger false positives.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1127 - Trusted Developer Utilities Proxy Execution
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" ("process"="*\\Microsoft.Workflow.Compiler.exe" OR (file=
→ "Microsoft.Workflow.Compiler.exe" command="*.xml/*"))
```

2.691 LP_Process Dump via Sqldumper Detected

- **Trigger Condition:** When a process dump via Sqldumper.exe is detected. The Sqldumper.exe is a debugging utility, included with Microsoft SQL Server, which generates memory dumps of SQL Server and of related processes for debugging purposes. Adversaries can leverage its functionality to dump processes like LSASS. Legitimate MSSQL Server actions can trigger false positives.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** T1003 - OS Credential Dumping, T1003.001 - LSASS Memory
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" "process"="*\sqldumper.exe" command IN ["*0x0110*",
↪ "*0x01100:40*"]
```

2.692 LP_Suspicious Usage of SQLToolsPS Detected

- **Trigger Condition:** When the proxy execution of PowerShell code through the SQLToolsPS.exe is detected. SQLToolsPS.exe is a utility shipped along with Microsoft SQL Server Management Studio that loads SQL Server cmdlts. Adversaries can leverage its functionality to execute malicious powershell codes and bypass the detection methods. Direct execution of PowerShell codes via SQLToolsPS.exe are uncommon. However, the child process sqltoolsps.exe spawned by smss.exe is a legitimate action.
- **ATT&CK Category:** Execution, Defense Evasion
- **ATT&CK Tag:** T1059.001 - PowerShell, T1127 - Trusted Developer Utilities Proxy Execution
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" (("process"="*\sqltoolsps.exe" OR parent_process=
↪ "*\sqltoolsps.exe") OR (file="*\sqltoolsps.exe" -(parent_process="*\smss.exe")))
```

2.693 LP_Proxy Execution of Malicious Payload via Pubprn

- **Trigger Condition:** When proxy execution of malicious payloads via PubPrn.bs is detected. PubPrn.vbs is a signed Visual Basic script that publishes a printer to Active Directory Domain Services. Adversaries can abuse PubPrn to execute malicious payloads hosted on remote sites.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1216.001 - PubPrn
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" command="*\pubprn.vbs*" command="*script:*
```

2.694 LP_File Download via IMEWDBLD

- **Trigger Condition:** When a network connection is detected via the IMEWDBLD.exe binary. IMEWDBLD.EXE is a part of Microsoft Input Method Editor (IME). IME is a software component that enables a user to enter text in a language that can't easily be typed using a standard keyboard. Adversaries can use this technique to download remote system payload.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** T1105 - Ingress Tool Transfer
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Connection label=Network label=Detect "process"="*\IMEWDBLD.exe" is_initiated=true
```

2.695 LP_Memory Dump via Adplus

- **Trigger Condition:** When LSASS process dump via adplus.exe is detected. Local Security Authority Server Service (LSASS) is a process in Microsoft Windows operating systems that is responsible for enforcing the security policy on the system and handles authentication, password change and tokens. ADPlus is a console-based Visual Basic script included with Microsoft Debugging Tools for Windows installation. Adversaries may attempt to access credentials stored in the process memory of the LSASS.

- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** T1003.001 - LSASS Memory
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\adplus.exe" command IN ["*-hang *", "-pn *",
↪ "-pmn *", "-p *", "-po *", "-c *", "-sc *"]
```

2.696 LP_Remote Thread Created via Ttdinject

- **Trigger Condition:** When a remote thread is created by ttdinject binary. Ttdinject is a binary that is a part of the Time Travel Debugging utility, which is used in Windows 10 v1809. Time Travel Debugging is a tool that captures a process trace as it executes and allows to replay it later. Adversaries can use this technique to proxy execute malicious payloads.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1127 - Trusted Developer Utilities Proxy Execution
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create ("process"="*\ttdinject.exe" OR file="TTDInject.exe")
```

2.697 LP_Proxy Download via OneDriveStandaloneUpdater

- **Trigger Condition:** When OneDriveStandaloneUpdater registry value is modified. OneDriveStandaloneUpdater.exe is a binary that belongs to the Standalone Updater process and comes with Microsoft OneDrive. Adversaries can use this technique for transferring tools or other files to the victim system from a URL that is set in the OneDriveStandaloneUpdater registry. Registry auditing must be enabled and permission must be allowed for auditing the OneDriveStandaloneUpdater registry.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** T1105 - Ingress Tool Transfer
- **Minimum Log Source Requirement:** Windows Sysmon

- **Query:**

```
label=registry label=value label=set target_object=
↳ "*"SOFTWARE\Microsoft\OneDrive\UpdateOfficeConfig\UpdateRingSettingURLFromOC*"
```

2.698 LP_Suspicious WMIC ActiveScriptEventConsumer Created

- **Trigger Condition:** When WMIC is executed to create an event consumer. ActiveScriptEventConsumer is a class that runs a predefined script in an arbitrary scripting language when an event is delivered to it. Adversaries may establish persistence and elevate privileges by executing malicious content triggered by a Windows Management Instrumentation (WMI) event subscription.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** T1546.003 - Windows Management Instrumentation Event Subscription
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create command="*ActiveScriptEventConsumer*" command="*?
↳ CREATE *"
```

2.699 LP_Remote Connection Established via Msbuild

- **Trigger Condition:** When a network connection is initiated via MSBuild while building an application is detected. Microsoft Build (MSBuild) Engine is a platform for building applications. Adversaries can use this technique to build their payload and establish a network connection to their controlled server.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** MSBuild
- **ATT&CK ID:** T1127.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=windowssysmon "process"="*\msbuild.exe" event_id=3 destination_port IN ["80",
↪ "443"]
```

2.700 LP_Executables Started in Suspicious Folder

- **Trigger Condition:** When the execution of binaries from a suspicious folder is detected. Paths mentioned in lists are not Windows default paths from where native and internal binaries are executed. Adversaries may attempt to masquerade their payload as legitimate binaries and execute from non-default paths to avoid detection. Legitimate binaries executed from those paths can trigger an alert, so include those binaries in the excluded process list.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1036 - Masquerading
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label="process" label=create "process" IN SUSPICIOUS_FOLDER_EXE_EXECUTION
-"process" IN ["*SpeechUXWiz.exe", "*SystemSettings.exe", "*TrustedInstaller.exe",
↪ "*PrintDialog.exe",
"*MpSigStub.exe", "*LMS.exe", "*mpam-*.exe"]
```

2.701 LP_Windows RDP Port Modified

- **Trigger Condition:** When remote desktop protocol (RDP) for Windows protocol is modified. RDP is a protocol that allows users to have GUI access to a remote desktop. Adversaries can modify the RDP port to evade the defense mechanism used to detect connections in the default RDP port.
- **ATT&CK Category:** Lateral Movement
- **ATT&CK Tag:** T1021.001 - Remote Desktop Protocol
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Registry label=Value label=Set target_object=
↪ "*\System\CurrentControlSet\Control\Terminal Server\WinStations\RDP-Tcp\PortNumber"
```

2.702 LP_Curl Silent Mode Execution Detected

- **Trigger Condition:** When curl is run in silent mode. Client URL (curl) is a command line tool that is used to transfer data to and from a server. Adversaries can use this technique to prevent showing file transfer progress and redirect output to a file.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** T1105 - Ingress Tool Transfer
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command="*curl*" ((command="*-s*" command="*-o*") OR
↪ command="*-s*")
```

2.703 LP_High Volume of File Modification or Deletion in Short Span

- **Trigger Condition:** When 30 file modifications or deletions are detected within a single minute. A large number of file modifications and deletions is an indicator of ransomware. Based on requirements and the number of detected false positives, a user can modify the number of events needed or the time frame. To generate logs, enable the auditing policy of the relevant folders. When a user/software modifies a large number of files this can result in a false positive. To reduce the number of false positives events exclude the process in the query.
- **ATT&CK Category:** Impact
- **ATT&CK Tag:** T1565 - Data Manipulation
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
[30 label=File label=Object label=Storage access IN ["Delete*", "writedata*"] - "process" IN [
↪ "*\tiworker.exe", "*\poqexec.exe", "*\msiexec.exe"] having same host,domain,user, "process
↪ " within 1 minutes]
```

2.704 LP_Non-Existent User Login Attempt Detected

- **Trigger Condition:** When eight non-existent user login attempts on SSH service are detected within a minute. Secure Shell (SSH) is a protocol that provides a secure way to access a computer over a network. Adversaries can perform username brute force to find a valid username. Based on the requirement and false positive, the user can modify the number of invalid login attempts and time frame.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** T1110 - Brute Force
- **Minimum Log Source Requirement:** Unix
- **Query:**

```
[8 label=Invalid label=User "process"=sshd having same source_address within 1 minutes]
```

2.705 LP_Execution of Temporary Files Via Office Application

- **Trigger Condition:** When Office applications creates a child process that executes a file with .tmp extension. Adversaries uses this technique to avoid detection by using the legit application to run a payload that is masquerading as a temporary file.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1036 - Masquerading
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" "parent_process" IN ["*\winword.exe", ".*\powerpnt.exe",  
↪ ".*\excel.exe"] "process"="*.tmp"
```

2.706 LP_Execution of Temporary Files Via Office Application

- **Trigger Condition:** When Office applications creates a child process that executes a file with .tmp extension. Adversaries use this technique to avoid detection by

using the legit application to run a payload that is masquerading as a temporary file.

- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1036 - Masquerading
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" "parent_process" IN ["*\winword.exe", "\powerpnt.exe",
↪ "\excel.exe"] "process"="*.tmp"
```

2.707 LP_Malicious Image Loaded Via Excel

- **Trigger Condition:** When an unsigned image is loaded via Excel. An XLL file is an add-in used by Microsoft Excel. It contains extra functions, templates, or other tools that enhance the capabilities of Excel. Examples of add-ins include custom chart generators and template managers. Adversaries can use this technique to load their malicious unsigned add-ins to execute their payload or download malware from a remote server.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** T1137 - Office Application Startup, T1137.001 - Office Template Macros
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=Image label=Load "process"="*\excel.exe" file IN ["*.xlam ", "*.xla ", "*.xll "] is_sign=false
```

2.708 LP_Malicious Chrome Extension Detected

- **Trigger Condition:** When malicious Chrome extension IDs are detected by Osquery. This analytic relies on chrome_extensions table and requires analysts to keep an up-to-date list of malicious chrome extension IDs.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** T1176 - Browser Extensions

- **Minimum Log Source Requirement:** -
- **Query:**

```
event_source=OSQuery event_type=chrome_extension* columns_identifier IN MALICIOUS_  
↳ CHROME_EXTENSIONS
```

2.709 LP_Chrome Extension Installed Outside of the Webstore

- **Trigger Condition:** When malicious chrome extensions are installed from outside the official Chrome webstore. Adversaries can manually install the browser extension via their batch, PowerShell or VBS scripts. Analysts need to make sure they place the correct event types in the query.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** T1176 - Browser Extensions
- **Minimum Log Source Requirement:** -
- **Query:**

```
event_source=OSQuery event_type="chrome_extension*" columns_from_webstore=false
```

2.710 LP_Chrome Extension Installed with DevTools Permission

- **Trigger Condition:** When OSQuery detects the chrome extension installed with devtools permission. Analyst must check for unusual extensions installed with this permission and also check if the extensions were installed from the webstore.
- **ATT&CK Category:** Persistence
- **ATT&CK Tag:** T1176 - Browser Extensions
- **Minimum Log Source Requirement:** -
- **Query:**

```
event_source=OSQuery event_type="chrome_extension*" columns_permission="*devtools*"
```

2.711 LP_Suspicious WMIC Process Creation

- **Trigger Condition:** When WMIC executes "Process Call Create," suspicious calls to processes such as, rundll32, regsvr32, mshta. The WMI command-line (WMIC) utility provides a command-line interface for Windows Management Instrumentation (WMI). WMI is a Microsoft technology that provides a common framework for managing and monitoring Windows-based systems. Adversaries can use this technique to proxy execute their malicious files and payloads via wmic.exe.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1047 - Windows Management Instrumentation
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create command="process" command=call command=create
command IN ["*rundll32*", "*bitsadmin*", "*regsvr32*", "*cmd.exe /c *", "*cmd.exe /k *", "*cmd.
↪ exe /r *", "*cmd /c *", "*cmd /k *",
"*cmd /r *", "*powershell*", "*pwsh*", "*certutil*", "*cscript*", "*wscript*", "*mshta*",
↪ "*\Users\Public\*", "*\Windows\Temp\*", "*\AppData\Local\*", "*%temp%*", "*%tmp%*", "*
↪ %ProgramData%*", "*%appdata%*", "*%comspec%*", "*%localappdata%"]
```

2.712 LP_Browser Credential Files Accessed

- **Trigger Condition:** When access to a browser (Chrome, Edge & Firefox) using stored credential is detected. When a user saves any credentials in the browser, those credentials are stored in files that are included in the query. Adversaries can access those files in an attempt to retrieve the stored credentials.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1202 - Indirect Command Execution
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=File label=Access ((path IN ["*\\AppData\\Local\\Google\\Chrome\\User
Data\\Default\\Network\\Cookies*", "*\\Appdata\\Local\\Chrome\\User Data\\Default\\Login Data*",
"*\\AppData\\Local\\Google\\Chrome\\User Data\\Local State*"] object_name IN [
"*\\Appdata\\Local\\Microsoft\\Windows\\WebCache\\WebCacheV01.dat", "*\\cookies.sqlite"])
OR object_name IN ["*\\Microsoft\\Edge\\User Data\\Default\\Web Data", "*Firefox*release\\logins.
json", "*firefox*release\\key3.db", "*firefox*release\\key4.db"])
- "process" IN ["*\\firefox.exe", "*\\chrome.exe", "C:\\Program Files\\*", "C:\\Program Files (x86)\\*",
"C:\\WINDOWS\\system32\\*", "*\\MsMpEng.exe", "*\\MpCopyAccelerator.exe", "*\\thor64.exe",
"*\\thor.exe"] -parent_process IN ["C:\\Windows\\System32\\msiexec.exe"] -("process"=system
parent_process=idle) "access"="ReadData"
```

2.713 LP_Windows Defender Antivirus Definitions Removal Detected

- **Trigger Condition:** When Microsoft Defender Antivirus signature definitions are removed from the system. Microsoft Defender Antivirus (formerly Windows Defender) offers protection against all threats on Windows devices. The Malware Protection Command Line Utility (MpCmdRun) is a Microsoft Windows internal command-line tool dedicated to automating and managing Microsoft Defender Antivirus operations on Windows devices. Adversaries leverages this method to remove Antivirus definitions and ultimately avoid detection.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1562.001 - Disable or Modify Tools
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\\MpCmdRun.exe" command="*RemoveDefinitions*"
```

2.714 LP_Exchange ProxyShell Pattern Detected

- **Trigger Condition:** When a URL pattern associated with ProxyShell exploitation attempts (both successful and failure) against Exchange servers is detected. ProxyShell is an attack chain that exploits three known vulnerabilities in Microsoft Exchange: CVE-2021-34473, CVE-2021-34523, and CVE-2021-31207. Adversaries may exploits these vulnerabilities to perform remote code execution.
- **ATT&CK Category:** Initial Access

- **ATT&CK Tag:** T1190 - Exploit Public-Facing Application
- **Minimum Log Source Requirement:** Webserver
- **Query:**

```
norm_id=* ((url="*/autodiscover.json*" url IN ["/powershell*", "*/mapi/nsapi*", "*/EWS*", "X-
↪ Rps-CAT*"]) OR url IN ["*/autodiscover.json?*", "*/autodiscover.json%3f@*", "*/%3f@foo.com*
↪ ", "*/Email=autodiscover/autodiscover.json*", "*/json?@foo.com*"])
```

2.715 LP_Successful Exchange ProxyShell Attack

- **Trigger Condition:** When a URL pattern and status code associated with a successful ProxyShell exploitation attack against Exchange servers are detected. ProxyShell is an attack chain that exploits three known vulnerabilities in Microsoft Exchange: CVE-2021-34473, CVE-2021-34523, and CVE-2021-31207. Adversaries may exploit these vulnerabilities to perform remote code execution.
- **ATT&CK Category:** Initial Access
- **ATT&CK Tag:** T1190 - Exploit Public-Facing Application
- **Minimum Log Source Requirement:** Webserver
- **Query:**

```
norm_id=* (url="*/autodiscover.json*" url IN ["/powershell*", "*/mapi/nsapi*", "*/EWS*", "X-
↪ Rps-CAT*"] status_code IN [200, 301])
```

2.716 LP_Malicious Base64 Encoded PowerShell Keywords in Command Lines Detected

- **Trigger Condition:** When base64 encoded strings are used in hidden malicious Command and Scripting Interpreter and PowerShell command lines. Adversaries hides their activities by encoding commands to bypass detection with this technique.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1059 - Command and Scripting Interpreter, T1059.001 - PowerShell
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

- **Query:**

```
label="process" label=create "process"="*\powershell.exe" command IN ["* hidden *",
↳ "*AGkAdABzAGEAZABtAGkAbgAgAC8AdABYAGEAbgBzAGYAZQByA*",
↳ "*aXRzYWRtaW4gL3RyYW5zMVY*",
↳ "*IAaQB0AHMAYQBkAG0AaQBuACAALwB0AHIAyQBuaHMAZgBIAHIA*",
↳ "*JpdHNhZG1pbIAvdHJhbnNmZX*",
↳ "*YgBpAHQAacwBhAGQAbQBpAG4AIAAvAHQAacgBhAG4AcwBmAGUAacg*",
↳ "*Yml0c2FkbWlucC90cmFuc2Zlc*", "*AGMAaAB1AG4AawBfAHMAaQB6AGUA*",
↳ "*JABjAGgAdQBuaGsAXwBzAGkAegBIA*", "*JGNodW5rX3Npem*",
↳ "*QAYwBoAHUAbgBrAF8AcwBpAHoAZQ*", "*RjaHVua19zaXpl*", "*Y2h1bmtfc2l6Z*",
↳ "*AE8ALgBDAG8AbQBwAHIAZQBzAHMAaQBvAG4A*",
↳ "*kATwAuAEMAbwBtAHAacgBIAHMAcwbPAG8Abg*", "*IPLkNvbXByZXNzaW9u*",
↳ "*SQBPAC4AQwBvAG0AcABYAGUAacwBzAGkAbwBuA*", "*SU8uQ29tcHJlc3Npb2*",
↳ "*Ty5Db21wcmVzc2lvc*", "*AE8ALgBNAGUAbQBvAHIAeQBTahQAacgBIAgEAbQ*",
↳ "*kATwAuAE0AZQBtAG8AcgB5AFMAcABYAGUAYQBtA*", "*IPLk1lbW9yeVN0cmVhb*",
↳ "*SQBPAC4ATQBIAG0AbwByAHkAUwB0AHIAZQBhAG0A*", "*SU8uTWVtb3J5U3RyZWFT*",
↳ "*Ty5NZW1vcnltDhJlYW*", "*4ARwBIAHQAQwBoAHUAbgBrA*", "*5HZXRDaHVua*",
↳ "*AEcAZQB0AEMAaAB1AG4Aaw*", "*LgBHAGUAdABDAGgAdQBuaGsA*",
↳ "*LkdldENodW5r*", "*R2V0Q2h1bm*", "*AEgAUgBFAEEARABfAEkATgBGAE8ANgA0A*",
↳ "*QASABSAEUAAQQBEAF8ASQBOAEYATwA2ADQA*", "*RIUkVBRF9JTkZPNj*",
↳ "*SFJFQURfSU5GTzY0*", "*VABIAFIARQBBAEQAXwBJAE4ARgBPADYANA*",
↳ "*VEhSRUFEX0lOrk82N*",
↳ "*AHIAZQBhAHQAQZQBSAGUAbQBvAHQAQZQBUAGgAcgBIAgEAZA*",
↳ "*cmVhdGVSZW1vdGVUaHJlYW*",
↳ "*MAcgBIAgEAdABIAFIAZQBtAG8AdABIAFQAaABYAGUAYQBkA*",
↳ "*NyZWFOZVJlbW90ZVRocmVhZ*", "*Q3JIYXRlUmVtb3RlVGhyZWFK*",
↳ "*QwByAGUAYQB0AGUAUgBIAg0AbwB0AGUAUVABoAHIAZQBhAGQA*",
↳ "*0AZQBtAG0AbwB2AGUA*", "*1lbW1vdm*", "*AGUAbQBtAG8AdgBIA*",
↳ "*bQBIAG0AbQBvAHYAZQ*", "*bWVtbW92Z*", "*ZW1tb3Zl"] -user IN EXCLUDED_USERS
```

2.717 LP_DLL Loaded Via AllocConsole and RunDLL32

- **Trigger Condition:** When DLL loading through allocconsole function and rundll32. AllocConsole is a Windows internal function that allocates a new console for the calling process. Rundll32.exe is a Windows internal binary that loads and runs 32-bit dynamic-link libraries (DLLs). Adversaries can use this technique to execute their payload using rundll32 to load a malicious DLL by invoking the AllocConsole function.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1218.011 - Rundll32
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

- **Query:**

```
label="process" label=create "process" = "*\\rundll32.exe" command="*.dll*" command=
↳ "*allocconsole*"
```

2.718 LP_Active Directory Database Dump Attempt

- **Trigger Condition:** When an attempt to dump the *ntds.dit* file is detected. *NTDS.dit* file is a database that stores the Active Directory data (including users, groups, security descriptors and password hashes). Adversaries can use this technique to retrieve credentials and obtain other domain information.
- **ATT&CK Category:** Credential Access
- **ATT&CK Tag:** T1003.003 - NTDS
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create(("process" IN ["*\\NTDSDump.exe", "*\\NTDSDumpEx.exe"]) OR
(command="*ntds.dit*" command="*system.hiv*") OR (command="*NTDSgrab.ps1*")) OR
↳ (command="*ac i ntds*"
command="*create full*") OR (command="*/c copy *" command="*\\windows\\ntds\\ntds.dit*")
↳ OR
(command="*activate instance ntds*" command="*create full*") OR (command="*powershell*"
↳ " command="*ntds.dit*") OR
(command="*ntds.dit*" "process" IN
["*\\apache*", "*\\tomcat*", "*\\AppData\\*", "*\\Temp\\*", "*\\Public\\*", "*\\PerfLogs\\*"] OR
↳ "parent_process" IN
["*\\apache*", "*\\tomcat*", "*\\AppData\\*", "*\\Temp\\*", "*\\Public\\*", "*\\PerfLogs\\*"])
```

2.719 LP_Suspicious Child Process Creation via OneNote

- **Trigger Condition:** When the creation of suspicious child processes, execution of binaries from non-default paths and script file execution through OneNote are detected. Adversaries can use malicious OneNote files to social engineer users to execute it and drop their malicious payload or execute commands in the victim system.
- **ATT&CK Category:** Initial Access, Execution
- **ATT&CK Tag:** T1204.002 - Malicious File, T1566.001 - Spearphishing Attachment

- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=1 parent_image="*\onenote.exe"
(file IN ["RUNDLL32.exe", "REGSVR32.exe", "bitsadmin.exe", "CertUtil.exe", "InstallUtil.exe",
↪ "schtasks.exe", "wmic.exe", "cscript.exe", "wscript.exe", "CMSTP.EXE", "Microsoft.Workflow.
↪ Compiler.exe", "RegAsm.exe", "RegSvcs.exe", "MSHTA.EXE", "Msxsl.exe", "IEExec.exe", "Cmd.
↪ Exe", "PowerShell.EXE", "HH.exe", "javaw.exe", "pcalua.exe", "curl.exe", "ScriptRunner.exe",
↪ "CertOC.exe", "WorkFolders.exe", "odbcconf.exe", "msiexec.exe", "msdt.exe"] OR
(image="*\explorer.exe" command IN ["*.hta*", "*.vb*", "*.wsh*", "*.js*", "*.ps*", "*.scr*", "*.pif*",
↪ "*.bat", "*.cmd*"]) OR image IN ["*\AppData\*", ".*\Users\Public\*", ".*\ProgramData\*",
↪ ".*\Windows\Tasks\*", ".*\Windows\Temp\*", ".*\Windows\System32\Tasks\*"])
```

2.720 LP_Usage of Web Request Command

- **Trigger Condition:** Various web request commands used with command line tools and Windows PowerShell cmdlets (including aliases) via CommandLine are detected. Adversaries use this technique to download malicious payloads. However, the Usage of Get-Command and Get-Help modules referencing Invoke-WebRequest and Start-BitsTransfer might trigger false positives. Script Block Logging must be enabled for this alert rule to work.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** PowerShell
- **ATT&CK ID:** T1059.001
- **Minimum Log Source Requirement:** Windows, Windows Sysmon, PowerShell
- **Query:**

```
(label="Create" label="Process" command IN ["*Invoke-WebRequest*", "*iwr*", "*wget*",
↪ "*curl*", "*Net.WebClient*", "*Start-BitsTransfer*", "*Resume-BitsTransfer*", "*[System.Net.
↪ WebRequest]::create*", "*Invoke-RestMethod*", "*WinHttp.WinHttpRequest*", "*new-
↪ object system.net.webclient).downloadstring*", "*new-object system.net.webclient).
↪ downloadfile*", "*new-object net.webclient).downloadstring*", "*new-object net.webclient).
↪ downloadfile*", ".*.Download*", "*Net.WebClient*"] -user IN EXCLUDED_USERS) OR (norm_
↪ id=WinServer event_id= 4104 script_block IN ["*Invoke-WebRequest*", "*iwr*", "*wget*",
↪ "*curl*", "*Net.WebClient*", "*Start-BitsTransfer*", "*Resume-BitsTransfer*", "*[System.Net.
↪ WebRequest]::create*", "*Invoke-RestMethod*", "*WinHttp.WinHttpRequest*", "*new-object
↪ system.net.webclient).downloadstring*", "*new-object system.net.webclient).downloadfile*",
↪ "*new-object net.webclient).downloadstring*", "*new-object net.webclient).downloadfile*",
↪ ".*.Download*", "*Net.WebClient*" ] -path="C:\Packages\Plugins\Microsoft.
↪ GuestConfiguration.ConfigurationforWindows\*")
```

2.721 LP_Reconnaissance Activity with Nltest

- **Trigger Condition:** When possible reconnaissance activity via nltest binary is detected. Nltest is a Windows command-line utility that comes with a Windows Server, which is used to list domain controllers and enumerate domain trusts. The binary is available if you have installed the AD DS or the AD LDS server role. It is also available if you install the Active Directory Domain Services Tools that are part of the Remote Server Administration Tools (RSAT). Adversaries can use this technique to discover domain controllers, users and query the domain trust relationship.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** T1016 - System Network Configuration Discovery, T1482 - Domain Trust Discovery
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\nltest.exe" file="nltestrk.exe" ((command = "*/
↪server*" command="*/query*") OR command IN ["*/dclist:*", "*/domain_trusts*", "*/trusted_
↪domains*", "*/user*", "*/parentdomain*"])
```

2.722 LP_Regsvr32 Network Activity Detected

- **Trigger Condition:** When network connections and Application Layer Protocol, DNS queries initiated via regsvr32 binary are detected. Regsvr32 is a command-line utility to register and unregister the Windows Registry's OLE controls, such as DLLs and ActiveX controls. Adversaries utilized regsvr32 to run their malicious DLL, which downloads their other stager payload.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** Regsvr32
- **ATT&CK ID:** T1218.010
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon "process"="*\regsvr32.exe" event_id IN ["3", "22"]
```

2.723 LP_Possible Reconnaissance Activity

- **Trigger Condition:** Possible reconnaissance activity via nltest binary is detected. Nltest is a Windows command-line utility with a Windows server that lists domain controllers and enumerates domain trusts. Adversaries use this technique to discover the OS, user, network, subnets, file shares and domain trust, which will be used for further actions.
- **ATT&CK Category:** Discovery
- **ATT&CK Tag:** System Network Configuration Discovery, Domain Trust Discovery
- **ATT&CK ID:** T1016, T1482
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create " process="*\nltest.exe" file="nltestrk.exe" ((command="*/
↪server*" command="*/query*") OR command IN ["*/dclist:*", "*/domain_trusts*", "*/trusted_
↪domains*", "*/user*", "*/parentdomain*"])
```

2.724 LP_Privilege Escalation via Kerberos KrbRelayUp

- **Trigger Condition:** KrbRelayUp performs a universal no-fix local privilege escalation in Windows domain environments where LDAP signing is not enforced. KrbRelayUp is a wrapper that can streamline the use of some features in Rubeus, KrbRelay, SCMUACBypass, PowerMad/SharpMad, Whisker and ADCSPwn tools in attacks.
- **ATT&CK Category:** Credential Access, Lateral Movement
- **ATT&CK Tag:** Pass the Ticket, Kerberoasting
- **ATT&CK ID:** T1550.003, T1558.003
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create
(parent_image="KrbRelayUp.exe" OR image="KrbRelayUp.exe" OR
(command=" relay " AND command=" -Domain " AND command=" -ComputerName ") OR
(command=" krbscm " AND command=" -sc ") OR
(command=" spawn " AND command=" -d " AND command=" -cn " AND command=" -cp *"))
```

2.725 LP_Suspicious Execution of LNK File

- **Trigger Condition:** When the execution of suspicious LNK files that either spawns Powershell or command prompt and has high entropy in the command field is detected. A LNK file is a Windows Shortcut that is a pointer to open a file, folder or application. Adversaries can utilize LNK files to embed their malicious scripts and commands and lure victims into executing the payload to gain initial access and evade defense. For this alert to work, an entropy plugin is required. Analysts can set the entropy value depending on the environment to filter out false positives. In our environment, legitimate use entropy was below five, so we used an entropy value greater than five to filter out false positives. The baseline time for using the process entropy command to detect such events is 90 days.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** T1204.002 - Malicious File
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create parent_process="*\explorer.exe" "process" IN ["*\cmd.exe",
↪ " *\powershell.exe"]
| process entropy(command) as command_entropy
| search command_entropy > 5
```

2.726 LP_Insecure Policy Set via Set-ExecutionPolicy

- **Trigger Condition:** Set-ExecutionPolicy command utilized to set insecure policies such as Unrestricted, bypass and RemoteSigned is detected. Adversaries can utilize this technique to change the execution policy in order to execute their choice of malicious powershell scripts.
- **ATT&CK Category:** Execution
- **ATT&CK Tag:** PowerShell
- **ATT&CK ID:** T1059.001
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WinServer event_id=4104 script_block="*Set-ExecutionPolicy*" script_block IN [
↪ "*Unrestricted*", "*bypass*", "*RemoteSigned*"] -script_block IN [
↪ "*\AppData\Roaming\Code\*"]
```

2.727 LP_Network Connection to Suspicious Server

- **Trigger Condition:** Communication between hosts and domains mentioned in the query's list is detected. The query will search for logs generated from the Windows system or proxies and firewalls. The mentioned sites are either file storing or hosting sites. Adversaries have utilized such sites in many campaigns to upload and download data.
- **ATT&CK Category:** Command and Control
- **ATT&CK Tag:** Ingress Tool Transfer
- **ATT&CK ID:** T1105
- **Minimum Log Source Requirement:** Windows Sysmon, Firewall, Proxy Server, WAF
- **Query:**

```
(norm_id=WindowsSysmon event_id=3 "image" IN ["C:\Windows\*", "C:\Users\Public\*"]?
↪ destination_host IN ["*dl.dropboxusercontent.com*", "*.pastebin.com*", "*.githubusercontent.
↪ com*", "*.cdn.discordapp.com/attachments*", "*.mediafire.com*", "*.mega.nz*", "*.ddns.net*",
↪ "*.paste.ee*", "*.hastebin.com/raw/*", "*.ghostbin.co/*", "*.ufile.io*", "*.anonfiles.com*",
↪ "*send.exploit.in*", "*.transfer.sh*", "*.privatlab.net*", "*.privatlab.com*", "*.sendspace.com*",
↪ "*pastetext.net*", "*.pastebin.pl*", "*.paste.ee*", "*.api.telegram.org*"]) OR (device_category?
↪ IN ["Firewall", "ProxyServer"] url IN ["*dl.dropboxusercontent.com*", "*.pastebin.com*", "*.
↪ githubusercontent.com*", "*.cdn.discordapp.com/attachments*", "*.mediafire.com*", "*.mega.
↪ nz*", "*.ddns.net*", "*.paste.ee*", "*.hastebin.com/raw/*", "*.ghostbin.co/*", "*.ufile.io*",
↪ "*anonfiles.com*", "*.send.exploit.in*", "*.transfer.sh*", "*.privatlab.net*", "*.privatlab.com*",
↪ "*sendspace.com*", "*.pastetext.net*", "*.pastebin.pl*", "*.paste.ee*", "*.api.telegram.org*"])
```

NON-MITRE ATT&CK ANALYTICS

The NON-MITRE ATT&CK alerts available in Alert Rules are:

3.1 LP_Windows Login Attempt on Disabled Account

- **Trigger condition:** A user attempts to log in using a disabled account.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer* label=User label=Login label=Fail sub_status_code= "0xC0000072" -  
↪ target_user=*-user = ?-user IN EXCLUDED_USERS | rename user as target_user,?  
↪ domain as target_domain,reason as failure_reason
```

3.2 LP_VMware Link Up

- **Trigger condition:** VMware connection is up.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** VMware
- **Query:**

```
norm_id=VmwareESX label = Link label=Up | chart count() by log_ts, host, switch, port_
↪group, network_adapter
```

3.3 LP_VMware Link Down

- **Trigger condition:** VMware's connection is down.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** VMware
- **Query:**

```
norm_id=VmwareESX label = Link label=Down | chart count() by log_ts, host, switch, port_
↪group, network_adapter
```

3.4 LP_LogPoint License Expiry Status

- **Trigger condition:** Logpoint license is about to expire.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Logpoint
- **Query:**

```
norm_id=LogPoint label=Audit object='License checker' days_remaining=*
```

3.5 LP_Mitre Initial Access Using Spearphishing link Detected

- **Trigger condition:** Malicious URL is detected.
- **ATT&CK Category:** N/A

- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Mimecast
- **Query:**

```
norm_id=Mimecast label=Detect label=Malicious label=URL | process eval("attack_class=
↪ 'Initial Access'") | process eval("technique='Spearphishing Link'")
```

3.6 LP_Mitre Command and Control Using Standard Application Layer Protocol Detected

- **Trigger condition:** Command and control activity using standard application layer protocol is detected.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Proxy server
- **Query:**

```
norm_id=*proxy source_address=* destination_address=* destination_port IN[?]
↪ STANDARD_APPLICATION_PORTS | process ti(destination_address) | rename et_
↪ category as ti_category | process eval("attack_class='Command and Control'") | process[?]
↪ eval("technique='Standard Application Layer Protocol'") | search ti_category=
↪ "*Command and Control*"
```

3.7 LP_Endpoint Protect Threat Content Detected

- **Trigger condition:** Threat content is detected.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Endpoint Protector

- **Query:**

```
norm_id=EndPointProtector label=Threat label=Content (label=Detect OR label=Block)
↪ file=* user=*
```

3.8 LP_Endpoint Protect Device Disconnect

- **Trigger condition:** A USB device is disconnected.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Endpoint Protector
- **Query:**

```
norm_id = EndPointProtector label=disconnect user=* device_type="USB Storage Device"
```

3.9 LP_Endpoint Protect File Delete

- **Trigger condition:** A file is deleted.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Endpoint Protector
- **Query:**

```
norm_id=EndPointProtector label=File label=Delete file=* user=*
```

3.10 LP_Endpoint Protect File Copied To USB Device

- **Trigger condition:** A file is copied to external USB drive.
- **ATT&CK Category:** N/A

- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Endpoint Protector
- **Query:**

```
norm_id=EndPointProtector label=File label=Copy device_type="USB Storage Device"
↪ file=* user=*
```

3.11 LP_System Owner or User Discovery Process Detected

- **Trigger condition:** An attack *Discovery* is performed using the attack technique *System Owner or User Discovery*.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer label="Process" label=Create (commandline="*whoami*" OR
↪ commandline="*quser*" OR commandline="*wmic.exe*useraccount get*" OR
↪ command="*whoami*" OR command="*quser*" OR command="*wmic.
↪ exe*useraccount get*") -user IN EXCLUDED_USERS | rename commandline as command
```

3.12 LP_System Services Discovery Detected

- **Trigger condition:** An attack *Discovery* is performed using the attack technique *System Service Discovery*.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Windows

- **Query:**

```
norm_id=WinServer label="Process" label=Create (commandline="*net.exe*start*" OR
↪ commandline="*tasklist.exe*" OR command="*net.exe*start*" OR command="*tasklist.
↪ exe*" ) -user IN EXCLUDED_USERS | rename commandline as command
```

3.13 LP_SolarisLDAP Password Spraying Attack Detected

- **Trigger condition:** Password spraying attack is detected.
- **ATT&CK Category:** N/A
- **ATT&CK Tag:** N/A
- **ATT&CK ID:** N/A
- **Minimum Log Source Requirement:** Solaris LDAP
- **Query:**

```
norm_id=SolarisLDAP label=User (label=Login OR label=Authentication) label=Fail | chart
↪ distinct_count(user) as UserCount, distinct_list(user) as Users | search UserCount > 5
```

3.14 LP_Microsoft Defender AMSI Trigger

- **Trigger Condition:** Logpoint detects Microsoft Defender with AMSI as the detection source. The Windows Antimalware Scan Interface (AMSI) is a versatile interface standard that allows your applications and services to integrate with any antimalware product on a machine.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id=1116 source_name=AMSI event_source="Microsoft-
↪ Windows-Windows Defender"
```

3.15 LP_Petitpotam - Anonymous RPC and File Share

- **Trigger Condition:** Events related to Petitpotam are logged.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
[event_id=4624 package="NTLM*" (user="ANONYMOUS LOGON" or -workstation=*)]
↪ as stream1 join [event_id=5145 share_name=IPC$ access="*ReadData (or ListDirectory)
↪ WriteData (or AddFile)*" relative_target IN ["lsarpc", "efsrpc", "lsass", "samr",
↪ "netlogon"]] as stream2 on stream1.source_address = stream2.source_address and
↪ stream1.host = stream2.host | rename stream1.user as user, stream1.host as host,
↪ stream1.domain as domain, stream2.source_address as source_address, stream2.share_
↪ name as share_name, stream2.access as access, stream2.log_ts as log_ts
```

3.16 LP_RDP Sensitive Settings Changed

- **Trigger Condition:** Changes to RDP terminal service sensitive settings are detected.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WindowsSysmon event_id=13 target_object IN [
↪ "*\services\TermService\Parameters\ServiceDll*", "*\Control\Terminal
↪ Server\SingleSessionPerUser*", "*\Control\Terminal Server\DenyTSConnections*"] -
↪ user IN EXCLUDED_USERS
```

3.17 LP_Secure Deletion with SDelete

- **Trigger Condition:** Renamed a file while deleting it with the SDelete tool. Adversaries use various tools to clean traces left after their intrusion activity.
- **ATT&CK Category:** -

- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id=WinServer event_id IN ["4656", "4663", "4658"] object_name IN ["*.AAA", "/*.ZZZ", "/*"] -user IN EXCLUDED_USERS
```

3.18 LP_Suspicious Keyboard Layout Load Detected

- **Trigger Condition:** The keyboard preload installation with a suspicious keyboard layout, for example, Chinese, Iranian, or Vietnamese layout, loads in user sessions on systems that is maintained by US staff only.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=13 target_object IN ["*\\Keyboard Layout\\Preload\\*", "/*\\Keyboard Layout\\Substitutes\\*"] detail IN ["00000804", "00000c04", "00000404", "00001004", "00001404", "00000429", "00050429", "0000042a", "00000401", "00010401", "00020401"] -user IN EXCLUDED_USERS
```

3.19 LP_Remote Code Execution using WMI Win32_Process Class over WinRM

- **Trigger Condition:** When an attempt to execute code or create a service on a remote host via winrm.vbs is detected. WinRM is a windows native script used to manage Windows RM settings. The functionality of the WinRM command is provided through a Visual Basic Script, winrm.vbs. This script can be abused to create a process leading to remote code execution and lateral movement. False positives are uncommon, but legitimate use for administrative purposes such as remote PowerShell execution can trigger this alert.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows

- **Query:**

```
label=Create label="Process" command="*winrm*" command="*invoke Create wmicimv2/
↳ Win32_*" command="*-r:http*"
```

3.20 LP_Remote Code Execution using WMI Win32_Service Class over WinRM

- **Trigger Condition:** Application Whitelisting Bypass and Arbitrary Unsigned Code Execution Technique is attempted using winrm.vbs. It detects the execution of attacker-controlled WsmPty.xml or WsmTxt.xml via winrm.vbs and copied cscript.exe (can be renamed). winrm.vbs (a Windows-signed script) can consume and execute attacker-controlled XSL, which is not subject to enlightened script host restrictions, resulting in the execution of arbitrary, unsigned code execution.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Create label="Process" command="*winrm*" command IN ['*format:pretty*', '*format:
↳ "pretty"*', '*format:"text"*', '*format:text*'] -(image IN ["C:\Windows\System32\*",
↳ "C:\Windows\SysWOW64\*"])
```

3.21 LP_Suspicious Microsoft SQL Server PowerShell Module Use Detected

- **Trigger Condition:** The execution of a PowerShell code by the sqlps.exe utility, which is included in the standard set of utilities supplied with the MSSQL Server is detected. Script blocks are not logged in this case, so this utility helps to bypass protection mechanisms based on the analysis of these logs. As this attack requires sqlps.exe bundled with MSSQL installation, any device without it is not vulnerable. Also, child process sqlps.exe spawned by sqlagent.exe is a legitimate action. Direct PS command execution through SQLPS.exe is rare, but if it occurs, it results in a false positive.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -

- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Create label="Process" ("process"="*\sqlps.exe" OR parent_process="*\sqlps.exe" OR
↪file="*\sqlps.exe" ) -(parent_process="*\sqlagent.exe")
```

3.22 LP_Shadow Copy Deletion Using OS Utilities Detected

- **Trigger Condition:** When shadow copies are deleted using operating systems utilities. Shadow copy is a Microsoft technology that can create backup copies or snapshots of computer files or volumes. Windows internal binaries are PowerShell, wmic, vssadmin, diskshadow, wbadmin, and vssadmin. Adversaries can utilize these binaries to delete shadow copies from the system so that the data recovery and reverting the system to a saved state is impossible after dropping malware.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label="Create" ("process" IN ["*\powershell.exe", "wmic.exe", "vssadmin.
↪exe", "diskshadow.exe"] command="*shadow*" command="*delete*") OR ("process"=
↪"*\wbadmin.exe" command="*delete*" command="*catalog*" command="*quiet*") OR (
↪"process"="*\vssadmin.exe" command="*resize*" command="*shadowstorage*"
↪command="*unbounded*")
```

3.23 LP_Child Process Spawned via Diskshadow Detected

- **Trigger Condition:** When child processes are created using the diskshadow binary. DiskShadow.exe is a Windows internal binary that exposes the functionality offered by the Volume Shadow Copy Service. Volume shadow copy service is a Windows framework that backs up a volume by creating a copy of it. Adversaries can use diskshadow binary's interactive mode and execute other binaries using the exec command to bypass defensive countermeasures.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -

- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "parent_process"="*\diskshadow.exe" -command="*conhost.  
↪exe"
```

3.24 LP_Code Execution Via Diskshadow Detected

- **Trigger Condition:** When diskshadow binary is used to execute code from a file. DiskShadow.exe is Windows internal binary that exposes the functionality offered by the Volume Shadow Copy Service. Volume shadow copy service is a framework in Windows that provides the function to backup a volume by creating a copy of it. Adversaries can use diskshadow with -s or /s tag to execute a command from a file and bypass detection.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\diskshadow.exe" command IN ["*/s *", "*-s *"]
```

3.25 LP_Process Pattern Match For CVE-2021-40444 Exploitation

- **Trigger Condition:** The process pattern for CVE-2021-40444 is detected. CVE-2021-40444 is a remote code execution vulnerability in MSHTML, which is Microsoft's proprietary browser engine for Internet Explorer. Control.exe is a Windows internal binary to access the control panel. Adversaries can rename their malware or payload to control.exe and execute it to escape detection.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "process"="*\control.exe" parent_process IN ["*\winword.exe",
↪ " *\excel.exe", " *\powerpnt.exe"] -command="*\control.exe input.dll"
```

3.26 LP_Suspicious Extexport Execution Detected

- **Trigger Condition:** When a service is created by loading a DLL using the ExtExport service in IE. ExtExport is a module that serves to import/export data from other programs, for example, favorites or bookmarks from other browsers. Attackers can use Extexport.exe to load any DLL using the built-in tool ExtExport.exe which can be found inside the Internet Explorer directory.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label=Create label="Process" command IN ["*ExtExport*", "extexport"]
```

3.27 LP_Proxy Execution via Workfolders

- **Trigger Condition:** When Logpoint detects the use of workfolders binary to execute other process. Workfolders is a Windows internal binary that provides a consistent way for users to access their work files from their PCs and devices. Adversaries can use this technique to evade defensive countermeasures or to hide as a persistence mechanism.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Process" label=Create "parent_process"="*\workfolders.exe" "process"="*\control.exe
↪ " "process"="C:\Windows\System32\control.exe"
```

3.28 LP_Proxy Execution via Windows Update Client

- **Trigger Condition:** When wuauctl.exe is used to proxy execute codes. Wuauctl.exe (Windows Update Auto Update Client) is a Microsoft Windows native AutoUpdate Client used to check for available updates from Microsoft Update. Adversaries may abuse wuauctl.exe to camouflage and execute malicious codes.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" ("process"="*\wuauctl.exe" OR file="wuauctl.exe")
↪(command="*UpdateDeploymentProvider*" command="*.dll*" command=
↪"*RunHandlerComServer*")
- (command IN ["* /UpdateDeploymentProvider UpdateDeploymentProvider.dll *", "* wuaueng.
↪dll *"])
```

3.29 LP_Suspicious DLL Execution Using Windows Address Book

- **Trigger Condition:** When a suspicious DLL is executed using wab.exe. Windows Address Book stores addresses, contact details, and e-mail addresses by programs like Outlook. When wab.exe executes, it tries to load DLL pointed by the registry key. But adversaries leverage this functionality to load their custom malicious DLL from a path other than the default by modifying the path pointed by the registry key.
- **ATT&CK Category:** Defense Evasion
- **ATT&CK Tag:** T1564.004 - NTFS File Attributes
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="registry" label="set" target_object="*\Software\Microsoft\WAB\DLLPath*" - detail="
↪%CommonProgramFiles%\System\wab32.dll"
```

3.30 LP_Suspicious Use of Dotnet Detected

- **Trigger Condition:** When the execution of either suspicious DLL or unsigned code using dotnet.exe is detected. dotnet.exe is a command line tool for managing .NET source codes and binaries. Adversaries can use it to execute DLL or some unsigned code and can bypass default AppLocker rules. dotnet.exe might trigger false positives if used for penetrating testing or system administration.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="create" label="process" command IN ["*.dll", "*.csproj"] "process"="*\dotnet.exe"
```

3.31 LP_Execution of Arbitrary Executable Using Storddiag

- **Trigger Condition:** When a renamed arbitrary executable is executed using storddiag.exe. storddiag.exe collects storage and file system diagnostic logs and outputs to a folder. Generally, storddiag.exe performs schtasks.exe, systeminfo.exe and fltmc.exe after it is executed. Adversaries can abuse its functionality by copying it into a random folder, renaming the malicious executables as schtasks.exe, systeminfo.exe and fltmc.exe, and running them. It might trigger false positives for legitimate use of storddiag.exe.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="Create" label="Process" parent_process="*\storddiag.exe" "process" IN ["*\schtasks.exe",
↪ "\systeminfo.exe", "\fltmc.exe"] - parent_process IN ["C:\windows\system32\*",
↪ "C:\windows\syswow64\*"]
```

3.32 LP_Process Creation via Time Travel Tracer

- **Trigger Condition:** When a new child process is spawned via tttracer.exe. Microsoft Time Travel Tracing Tool (Tttracer) is a diagnostic tool to collect time travel traces of given processes. Later, traces are analyzed by Microsoft Support for troubleshooting purposes. Adversaries can use this binary to launch their malicious binary and create a dump of a process.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "parent_process"="*\tttracer.exe"
```

3.33 LP_Time Travel Debugging Utility DLL Loaded

- **Trigger Condition:** When loading of time travel debugging utility DLLs are detected. Ttdrecord.dll, ttdwriter.dll and ttdloader.dll are part of a time travel debugging utility. Time Travel Debugging is a tool that captures a trace of a process as it executes and replays it later, forward and backward. DLL adversaries can run other binaries or dump a process by loading.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
label=image label=load image IN ["*\ttdrecord.dll", "*\ttdwriter.dll", "*\ttdloader.dll"]
```

3.34 LP_File Execution via Msdeploy

- **Trigger Condition:** When MSDeploy is used to execute files. Microsoft Deploy (MSDeploy) is a binary that allows users to deploy Web Applications. Adversaries can use this technique to bypass application whitelisting.
- **ATT&CK Category:** -

- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\msdeploy.exe" command="*verb:sync*"
↪ command="*-source:RunCommand*" command="*-dest:runCommand"
```

3.35 LP_CVE-2022-40684 Exploitation Detected

- **Trigger Condition:** When an exploitation attempt of CVE-2022-40684 is detected. CVE-2022-40684 is an authentication bypass using an alternate path or channel vulnerability [CWE-288] in FortiOS, FortiProxy and FortiSwitchManager that may allow an unauthenticated attacker to perform operations on the administrative interface via specially crafted HTTP or HTTPS requests. Adversaries can use this technique to gain remote access to a system. The affected versions are: FortiOS v7.2.0-7.2.1, FortiOS v7.0.0-7.0.6, FortiProxy v7.2.0, FortiProxy v7.0.0-7.0.6, FortiSwitchManager v7.2.0 and FortiSwitchManager v7.0.0.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Firewall, Proxy Server, Web Server
- **Query:**

```
(url="*/api/v2/cmd/db/system/admin/*" OR resource="*/api/v2/cmd/db/system/admin/*") user_
↪ agent IN ["report runner", "Node.js"]
```

3.36 LP_Possible Proxy Execution of Malicious Code

- **Trigger Condition:** When the possible use of TE.exe for proxy execution of malicious scripts is detected. TE.exe is a testing tool included with Microsoft Test Authoring and Execution Framework (TAEF). TAEF allows users to run automation by executing test files written in different languages (C, C#, Microsoft COM Scripting interfaces). Adversaries can leverage its functionality to execute malicious codes (such as WSC files with VBScript or DLL) directly by running te.exe. It is not unusual to use te.exe directly to execute legal TAEF tests, so legitimate use can trigger false positives.
- **ATT&CK Category:** -

- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label="create" "process"="*\te.exe" OR parent_process="*\te.exe" OR file=
↪ "\te.exe"
```

3.37 LP_Suspicious Usage of BitLocker Management Script

- **Trigger Condition:** When proxy execution of malicious payloads via Manage-bde.wsf is detected. Manage-bde.wsf is a BitLocker management script file that is generally used to turn BitLocker, specify unlock mechanisms, update recovery methods and unlock BitLocker-protected data drives. Adversaries can use it for the proxy execution of malicious payloads.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows, Windows Sysmon
- **Query:**

```
label="process" label="create" command="*cscript*" command="*manage-bde.wsf"
```

3.38 LP_Proxy Execution of Payloads via Microsoft Signed Script

- **Trigger Condition:** When proxy execution of PowerShell code via Microsoft signed script CL_Mutexverifiers.ps1 is detected. Adversaries can execute payloads via runAfterCancelProcess in CL_Mutexverifiers.ps1 module. Script block logging must have been enabled for the alert to work.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
norm_id="WinServer" event_id=4104 script_block IN ["*\CL_Mutexverifiers.ps1*",
↪ "*runAfterCancelProcess *"]
```

3.39 LP_Execution of Windows Defender Offline Shell from Suspicious Folder

- **Trigger Condition:** When OfflineScannerShell.exe is executed from a folder other than the default. Microsoft Defender Offline is an antimalware scanning tool that lets you boot and run a scan from a trusted environment. Adversaries can use OfflineScannerShell.exe to execute the mpclient.dll library in the current working directory and execute arbitrary codes.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows
- **Query:**

```
label="create" label="process" ("process"="*\OfflineScannerShell.exe" -((path="C:\Program
↪ Files\Windows Defender\Offline\") OR (-path=*))
```

3.40 LP_DLL Loaded Via AccCheckConsole

- **Trigger Condition:** When DLL loading through AccCheckConsole binary is detected. AccCheckConsole is a command-line tool for verifying the accessibility implementation of your application's UI. Adversaries can use this technique to load their malicious DLL.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\AccCheckConsole.exe" command="*-window*.dll*"
↪ "
```

3.41 LP_Proxy Execution via Appvlp

- **Trigger Condition:** When proxy execution of binaries via appvlp.exe is detected. Appvlp, also known as Application Virtualization Utility, is included with Microsoft Office 2016, which makes applications available to end-user computers without having to install applications directly on those computers. Adversaries can use this technique to bypass process or signature-based defenses by proxying the execution of malicious content with signed or otherwise trusted binaries.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\appvlp.exe" command IN ["*cmd.exe",
↪ "*powershell.exe*"] command IN ["*.sh*", "*.exe*", "*.dll*", "*.bin*", "*.bat*", "*.cmd*", "*.js*",
↪ "*.msh*", "*.reg*", "*.scr*", "*.ps*", "*.vb*", "*.jar*", "*.pl*", "*.inf*"]
```

3.42 LP_Proxy DLL Execution via UtilityFunctions

- **Trigger Condition:** When the use of UtilityFunctions script to execute a managed DLL is detected. UtilityFunctions is one of several powershell scripts from Microsoft for diagnostic and maintenance work. Adversaries can use this technique to proxy execute malicious files.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create command IN ["*UtilityFunctions.ps1*", "*RegSnapin*"]
```

3.43 LP_Suspicious Usage of Squirrel Binary

- **Trigger Condition:** When squirrel.exe is run via using arguments download, update and updateRollback arguments. Squirrel.exe is a binary to update the existing

installed NuGet or squirrel package. NuGet is a package manager designed to enable developers to share reusable code. Adversaries can use this technique to download and execute malicious NuGet package.

- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label="create" "process"="*\Squirrel.exe" command IN ["*download*",
↪ "*update*"]
```

3.44 LP_Suspicious File Share Permission

- **Trigger Condition:** When the execution of binaries from a suspicious folder is detected. Paths mentioned in the lists are not Windows default paths from where native and internal binaries are executed. Adversaries may attempt to masquerade their payload as legitimate binaries and execute from non-default paths to avoid detection. Legitimate binaries executed from those paths can trigger an alert, so include those binaries in the excluded process list.
- **ATT&CK Category:** -
- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon, Windows
- **Query:**

```
label="process" label=create "process"="*\net.exe" command="* share *grant:*FULL*"
```

3.45 LP_Legitimate Application Dropping Script File

- **Trigger Condition:** When the creation of a new script file by those applications which should not create one such as office applications, Wordpad. Script files contain a set of instructions or commands and are executed by a script interpreter or runtime environment. Adversaries can use this technique to drop their payload in the system and execute it.
- **ATT&CK Category:** -

- **ATT&CK Tag:** -
- **Minimum Log Source Requirement:** Windows Sysmon
- **Query:**

```
norm_id=WindowsSysmon event_id=11 file IN [ "*.ps1", "*.bat", "*.vbs", "*.scf", "*.wsf", "*.wsh" ]  
↪ "process" IN [ "*\\onenote.exe", "*\\winword.exe", "*\\excel.exe", "*\\powerpnt.exe",  
↪ "*\\msaccess.exe", "*\\mspub.exe", "*\\eqnedt32.exe", "*\\visio.exe", "*\\wordpad.exe",  
↪ "*\\wordview.exe", "*\\certutil.exe", "*\\certoc.exe", "*\\CertReq.exe", "*\\Desktopimgdownldr.exe",  
↪ "*\\esentutl.exe", "*\\finger.exe", "*\\AcroRd32.exe", "*\\RdrCEF.exe", "*\\mshta.exe", "*\\hh.exe",  
↪ "]"
```

ALERT RULES DASHBOARDS

4.1 LP_Mitre Attack Analytics Overview

This dashboard consists of the following widgets:

Widget Name	Description
Triggered Attack Tactics	The count of tactics that the attacker may use to perform an attack. The tactics are Initial Access, Execution, Persistence, Privilege Escalation, Defense Evasion, Credential Access, Discovery, Lateral Movement, Collection, Command and Control, Exfiltration and Impact.
Triggered Attack Tactics - Timetrend	A time trend for the attack tactics that the attacker used to perform an attack.
Mitre Att&ck Matrix	An ATT&CK chart, a heatmap describing the attacks carried out in a system in the form of attack tactics, techniques and procedures defined by MITRE.
Top Recurring Attacks	The most recurring attacks, their attack category and the count of attacks. For example, Console History Discover Detected is an attack, Collection is its attack category and the attack occurred three times.
Top Users by Attack Tactics	The top users based on attack tactics.
Top Hosts in Attack	The count of top hosts by attack category.

4.2 Adding the Alert Rules Dashboard

1. Go to *Settings >> Knowledge Base* from the navigation bar and click **Dashboards**.
2. Select **VENDOR DASHBOARD** from the drop-down.
3. Click **Add** from **Actions**.

The screenshot shows the LogPoint Vendor Dashboard interface. At the top, there's a navigation bar with 'LOGPOINT', 'DASHBOARD', 'SEARCH', 'REPORT', 'INCIDENT', and 'SETTINGS'. The 'SETTINGS' tab is active. Below the navigation bar, the 'Vendor Dashboard' section is visible. A table lists widgets, with the first one being 'LP_Mitre Attack Analytics Overview'. The 'Widgets Info' column for this widget is expanded, showing details like 'widget_name', 'description', 'query', 'display_type', 'repos', and 'time_range'. The 'query' field contains a complex LogQL query for MITRE attack tactics. The 'repos' field is set to 'No repos selected'. At the bottom of the dashboard, there are tabs for 'USER ACCOUNTS', 'CONFIGURATION', 'KNOWLEDGE BASE', 'SYSTEM', and 'VENDOR DASHBOARD'.

Fig. 1: Adding the Alert Rules Dashboard

4. Click **Choose Repos.**

The screenshot shows a dialog box titled 'ASK REPOS'. It has a table with columns 'S.N.', 'Dashboard', and 'Repos'. The first row is selected, showing '1' in the S.N. column and 'LP_Mitre Attack Analytics Overview' in the Dashboard column. A red box highlights the 'Choose Repos' button in the top right corner. Below the table, there is a yellow note: 'Note: Using all repos in all the widgets of all dashboards may hit on performance'. At the bottom right, there are 'Ok' and 'Cancel' buttons.

Fig. 2: Selecting Repos

5. Select the repo and click **Done.**




Fig. 3: Selecting Repos

6. Click **Ok**.




Fig. 4: Confirmation for Repo

You can find the Alert Rules dashboard under **Dashboards**.




Fig. 5: Alert Rules Dashboard




Fig. 6: Alert Rules Dashboard




Fig. 7: Alert Rules Dashboard

KB-LISTS

- ABNORMAL_FILES
- ACTINIUM_DOMAINS
- ADMIN_GROUPS
- ADMIN_SOURCES
- ADMINS
- ALERT_IRC_PORT
- ALERT_OPEN_PORTS
- ALERT_PRESENT_EMPLOYEES
- ALERT_UNUSUAL_SOURCE
- ALLOWED_PORTS
- ATTACK_COMMANDS
- BAD_RABBIT_FILE
- BAD_RABBIT_HASH
- BLACKLIST_IPS
- BLACKLISTED_DOMAIN
- BLACKLISTED_IP
- BLACKLISTED_PORTS
- BLOCKED_APPLICATION
- CLOUD_APP
- CLOUD_APPLICATION_IP

- CLOUD_APPLICATIONS
- CONCERNED_CONTENT
- CRIMINAL_CONTENT
- CRITICAL_FILE
- CRITICAL_FILES
- CRITICAL_FOLDER
- DEFAULT_USERS
- DOMAIN
- DOPPELPAYMER_RANSOMWARE_CVE
- DRAGONFLY_CNC_REQUEST
- DYNAMIC_CATEGORIES
- EXCLUDED_USERS
- EXECUTABLES
- EXISTING_USERS
- EXTREMIST_CONTENT
- GHOSTWRITER_DOMAINS
- GHOSTWRITER_IPS
- HERMETIC_WIPER_DRIVER_HASHES
- HERMETIC_WIPER_HASHES
- HIDDEN_COBRA_FILE
- HIDDEN_COBRA_HASH
- HIDDEN_COBRA_IP
- HOME_DIR
- HOME_DOMAIN
- HOME_FOLDER
- HOMENET
- HTTP_ERROR

- INACTIVE_USERS
- INVISIMOLE_MALWARE_HASHES
- ISAAC_WIPER_HASHES
- KASPERSKY_DETECTED_MALWARE_HASHES
- KASPERSKY_UPDATE_FAILURES
- KNOWN_APPLICATIONS
- KNOWN_DOMAINS
- KNOWN_FILE
- KNOWN_SERVER_HOST
- LOCKERGOGA_FILES
- MAGECART_DOMAINS
- MAIL_SERVER_IP
- MAIL_SERVERS
- MALICIOUS_POWERSHELL_COMMANDLET_NAMES
- MALICIOUS_TOOLS_IMPHASH
- MALWARE_EMAILS
- MALWARE_FILES
- MALWARE_HASH
- MALWARE_IP
- MATRIX_FILE
- MAZE_RANSOMWARE_DOMAINS
- MAZE_RANSOMWARE_EMAILS
- MOST_EXPLOITABLE_CVE
- MOST_EXPLOITABLE_DOMAINS
- MOST_EXPLOITABLE_EMAILS
- MOST_EXPLOITABLE_HASHES
- MOST_EXPLOITABLE_IPS

- NEFILIM_RANSOMWARE_EMAILS
- NEFILIM_RANSOMWARE_HASHES
- NON_EXISTING_USERS
- NON_PCI_COMPLIANT_PORT
- POWERSPLOIT_RECON_MODULES
- PRIVILEGED_USER
- PROWLI_CVE
- PROWLI_DOMAIN
- PROWLI_EMAIL
- PROWLI_FILE
- PROWLI_HASH
- SERVER_ADDRESS
- SQL_INJECTION_CHARACTER
- SQL_INJECTION_CHARACTERS
- SUSPICIOUS_COUNTRY
- UNAPPROVED_PORT
- VULNERABLE_CONTENT
- VULNERABLE_WORKSTATIONS
- WANNACRY_DOMAIN
- WANNACRY_EXTENSION
- WEBSERVER_SYSTEMS
- WHISPERGATE_HASHES
- WINADMINS
- WINDOWS_DC
- XSS_TAG
- YOUTUBE

For more details on Lists, go to the [Lists](#) section in the *Logpoint Data Integration guide*.