

# Integrations

## StixTaxii For Director Console API

V6.2.0

# CONTENTS

|          |                                                                               |           |
|----------|-------------------------------------------------------------------------------|-----------|
| <b>1</b> | <b>StixTaxii</b>                                                              | <b>1</b>  |
| <b>2</b> | <b>Installing StixTaxii</b>                                                   | <b>2</b>  |
| 2.1      | Prerequisites . . . . .                                                       | 2         |
| 2.2      | Uploading StixTaxii to the Fabric Storage . . . . .                           | 2         |
| 2.3      | Listing StixTaxii in the Fabric Storage . . . . .                             | 4         |
| 2.4      | Installing StixTaxii . . . . .                                                | 4         |
| <b>3</b> | <b>Uninstalling StixTaxii</b>                                                 | <b>6</b>  |
| <b>4</b> | <b>Configuring StixTaxii</b>                                                  | <b>7</b>  |
| 4.1      | Uploading a SSL Certificate File in the Fabric Storage . . . . .              | 7         |
| 4.2      | Listing the SSL Certificate File in the Fabric Storage . . . . .              | 8         |
| 4.3      | Configuring the STIX/TAXII Enrichment Source for STIX v1.0 . . . . .          | 9         |
| 4.4      | Configuring the STIX/TAXII Enrichment Source for STIX v2.0 and v2.1 . . . . . | 13        |
| 4.5      | General Information . . . . .                                                 | 17        |
| 4.6      | Listing all the StixTaxii Enrichment Source Configurations . . . . .          | 17        |
| 4.7      | Editing the STIX/TAXII Enrichment Source Configuration . . . . .              | 18        |
| 4.8      | Deleting the STIX/TAXII Enrichment Source Configuration . . . . .             | 22        |
| 4.9      | Deleting the SSL Certificate File from the Fabric Storage . . . . .           | 22        |
| <b>5</b> | <b>StixTaxii - RefreshList</b>                                                | <b>25</b> |
| 5.1      | Refreshing the list for StixTaxii Collections . . . . .                       | 25        |
| <b>6</b> | <b>StixTaxii - Trash</b>                                                      | <b>26</b> |
| 6.1      | Deleting StixTaxii from the Fabric Storage . . . . .                          | 26        |

## STIXTAXII

StixTaxii is a [threat intelligence](#) source that fetches Cyber Threat Intelligence (CTI) data written in *STIX* format from a *TAXII* server. You can enrich incoming logs of Logpoint with this fetched data by using the Threat Intelligence [process command](#).

StixTaxii support *STIX/TAXII* versions 1.0, 2.0 and 2.1.

## INSTALLING STIXTAXII

### 2.1 Prerequisites

- Director Fabric v1.4.0 or later
- Director Console v1.6.0 or later
- Logpoint v6.12.2 or later
- Threat Intelligence v5.0.0 or later

### 2.2 Uploading StixTaxii to the Fabric Storage

#### 2.2.1 Private Storage

You can upload StixTaxii to a private storage in the Fabric Storage using the **Upload - Upload** API.

**Endpoint URL:**

`https://api-server-host-name/configapi/Uploads/{pool_UUID}/`

**Method:**

`POST`

**Header:**

| FIELD        | DESCRIPTION                                                                             |
|--------------|-----------------------------------------------------------------------------------------|
| file_name    | Name of the StixTaxii .pak file.                                                        |
| Content-Type | Content type of the StixTaxii .pak file. It must be <i>(application/octet-stream)</i> . |

**Parameters:**

| FIELD | TYPE     | DESCRIPTION                             | REQUIRED  |
|-------|----------|-----------------------------------------|-----------|
| file  | [Object] | The StixTaxii .pak file to be uploaded. | Mandatory |

**Success Response:**

```
{
  "status": "Success",
  "message": "StixTaxii_6.2.0.pak successfully uploaded in the private storage. "
}
```

## 2.2.2 Public Storage

You can upload StixTaxii to a public storage in the Fabric Storage using the **Upload - UploadPublic files** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/Uploads/PublicUpload
```

**Method:**

```
POST
```

**Header:**

| FIELD        | DESCRIPTION                                                                     |
|--------------|---------------------------------------------------------------------------------|
| file_name    | Name of the StixTaxii .pak file.                                                |
| Content-Type | Content type of the StixTaxii .pak file. It must be (application/octet-stream). |

**Parameters:**

| FIELD | TYPE     | DESCRIPTION                             | REQUIRED  |
|-------|----------|-----------------------------------------|-----------|
| file  | [Object] | The StixTaxii .pak file to be uploaded. | Mandatory |

**Success Response:**

```
{
  "status": "Success",
  "message": "StixTaxii_6.2.0.pak successfully uploaded in the public storage. "
}
```

## 2.3 Listing StixTaxii in the Fabric Storage

### 2.3.1 Private Storage

You can list the StixTaxii file uploaded in the private storage using the **Upload - List** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/Uploads/{pool_UUID}/list
```

**Method:**

```
GET
```

**Success Response:**

```
[  
  "StixTaxii_6.2.0.pak"  
]
```

### 2.3.2 Public Storage

You can list the StixTaxii file uploaded in the public storage using the **Upload - ListPublic** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/Uploads/list
```

**Method:**

```
GET
```

**Success Response:**

```
[  
  "StixTaxii_6.2.0.pak"  
]
```

## 2.4 Installing StixTaxii

You can install StixTaxii using the **Upload - Install** API. You must upload it to the Fabric Storage before the installation.

**Endpoint URL:**

```
https://api-server-host-name/configapi/Uploads/{pool_UUID}/{logpoint_identifier}/install
```

**Method:**

```
POST
```

**Parameters:**

| FIELD            | LABEL IN UI | TYPE   | DESCRIPTION                                                                       | REQUIRED  |
|------------------|-------------|--------|-----------------------------------------------------------------------------------|-----------|
| application_type | –           | String | Type of the application. Must be <i>Application</i> .                             | Mandatory |
| file_name        | File        | String | Name of the application file.                                                     | Mandatory |
| file_location    | –           | String | Location of the application file. Can be either <i>private</i> or <i>public</i> . | Mandatory |

**Request Example:**

```
{
  "data": {
    "application_type": "Application",
    "file_name": "stixtaxii_6.2.0.pak",
    "file_location": "private"
  }
}
```

**Success Response:**

```
{
  "status": "Success",
  "message": "/monitorapi/{pool_UUID}/{logpoint_identifier}/orders/{request_id}"
}
```

## UNINSTALLING STIXTAXII

You can uninstall StixTaxii in a Fabric-enabled Logpoint using the **Plugins - Uninstall** API. You must first *remove* the StixTaxii configuration to uninstall it.

### Endpoint URL:

```
https://api-server-host-name/configapi/{pool_UUID}/{logpoint_identifier}/Plugins/{id}
```

### Method:

```
DELETE
```

### Parameters:

| FIELD | TYPE   | DESCRIPTION                                                                    | REQUIRED  |
|-------|--------|--------------------------------------------------------------------------------|-----------|
| id    | String | StixTaxii ID. Obtain it using the <b>StixTaxiiEnrichmentSource - List</b> API. | Mandatory |

### Success Response:

```
{
  "status": "Success",
  "message": "/monitorapi/{pool_UUID}/{logpoint_identifier}/orders/{request_id}"
}
```



## CONFIGURING STIXTAXII

### 4.1 Uploading a SSL Certificate File in the Fabric Storage

#### 4.1.1 Private Storage

You can upload a SSL certificate file to a private storage in the Fabric storage using the **PluginConfiguration-Upload** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/{pool_UUID}/PluginConfiguration/  
↪StixTaxiiEnrichmentSource/upload
```

**Method:**

```
POST
```

**Header:**

| FIELD        | LABEL IN UI | DESCRIPTION                                                                   |
|--------------|-------------|-------------------------------------------------------------------------------|
| Content-Type | –           | Content type of the certificate file. It must be <i>Multipart/Form-data</i> . |

**Parameters:**

| FIELD     | LABEL IN UI | TYPE   | DESCRIPTION          | REQUIRED  |
|-----------|-------------|--------|----------------------|-----------|
| file_name | –           | Object | File to be uploaded. | Mandatory |

**Success Response:**

```
{  
  "status": "Success",  
}
```

(continues on next page)

(continued from previous page)

```
{
  "message": "certificate.crt successfully uploaded in private storage."
}
```

## 4.1.2 Public Storage

You can upload a SSL certificate file to a public storage in the Fabric storage using the **PluginConfiguration-UploadPublic** API.

### Endpoint URL:

```
https://api-server-host-name/configapi/PluginConfiguration/StixTaxiiEnrichmentSource/
↪publicupload
```

### Method:

```
POST
```

### Header:

| FIELD        | LABEL IN UI | DESCRIPTION                                                                   |
|--------------|-------------|-------------------------------------------------------------------------------|
| Content-Type | –           | Content type of the certificate file. It must be <i>Multipart/Form-data</i> . |

### Parameters:

| FIELD     | LABEL IN UI | TYPE   | DESCRIPTION          | REQUIRED  |
|-----------|-------------|--------|----------------------|-----------|
| file_name | –           | Object | File to be uploaded. | Mandatory |

### Success Response:

```
{
  "status": "Success",
  "message": "certificate.crt successfully uploaded in public storage."
}
```

## 4.2 Listing the SSL Certificate File in the Fabric Storage

### 4.2.1 List Private Uploads

You can list the uploaded files to a private storage in the Fabric storage using the **PluginConfiguration-ListPrivateUploads** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/{pool_UUID}/PluginConfiguration/  
↪ StixTaxiiEnrichmentSource/list
```

**Method:**

```
GET
```

**Success Response:**

```
[  
  "certificate.crt",  
  "privateKey.key"  
]
```

## 4.2.2 List Public Uploads

You can list the uploaded files to a public storage in the Fabric storage using the **PluginConfiguration-ListPublicUploads** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/PluginConfiguration/StixTaxiiEnrichmentSource/list
```

**Method:**

```
GET
```

**Success Response:**

```
[  
  "certificate.crt",  
  "privateKey.key"  
]
```

## 4.3 Configuring the STIX/TAXII Enrichment Source for STIX v1.0

You can configure the StixTaxii Enrichment Source using the **PluginConfiguration - Create** API.

**Endpoint URL:**

[https://api-server-host-name/configapi/{pool\\_UUID}/{logpoint\\_identifier}/PluginConfiguration/StixTaxiiEnrichmentSource](https://api-server-host-name/configapi/{pool_UUID}/{logpoint_identifier}/PluginConfiguration/StixTaxiiEnrichmentSource)

**Method:**

POST

**Parameters:**

| FIELD               | LABEL IN UI          | TYPE    | DESCRIPTION                                                                                                                                                                                           | REQUIRED  |
|---------------------|----------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| st_enable_source    | Enable Source        | boolean | Parameter to enable or disable fetching of STIX data from a TAXII server.                                                                                                                             | Mandatory |
| discovery_url       | Base URL             | String  | Location of the discovery service in the TAXII server.                                                                                                                                                | Mandatory |
| begin               | Fetch From           | int     | Parameter to fetch data from the last selected month, hour, or day.                                                                                                                                   | Mandatory |
| begin_unit          | Fetch From           | String  | Unit of the begin.                                                                                                                                                                                    | Mandatory |
| fetch_interval      | Fetch Interval       | int     | An interval between the adjacent fetches.                                                                                                                                                             | Mandatory |
| fetch_interval_unit | Fetch Interval       | String  | Unit of the fetch interval.                                                                                                                                                                           | Mandatory |
| stix_version        | Version              | String  | STIX Version.                                                                                                                                                                                         | Mandatory |
| basic_auth_mode     | Basic Authentication | JSON    | Basic Authentication:<br><br><b>basic_auth_status:</b> Parameter to enable or disable the basic authentication.<br><b>username:</b> TAXII server username.<br><b>password:</b> TAXII server password. | Mandatory |

Continued on next page

Table 1 – continued from previous page

| FIELD         | LABEL IN UI         | TYPE   | DESCRIPTION                                                                                                                                                                                                                                     | REQUIRED  |
|---------------|---------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| ssl_mode      | SSL Authentication  | JSON   | SSL Authentication:<br><br><b>ssl_status:</b><br>Parameter to enable or disable the SSL authentication.<br><b>key_pass:</b><br>Password used to decrypt the SSL key.                                                                            | Mandatory |
| file_location | –                   | String | File location.                                                                                                                                                                                                                                  | Mandatory |
| files         | Files               | JSON   | TAXII server SSL configuration:<br><br><b>cert_file:</b> SSL certificate.<br><b>cert_key:</b> SSL key.                                                                                                                                          | Mandatory |
| st_proxy      | Proxy Configuration | JSON   | TAXII server Proxy configuration:<br><br><b>status:</b> Parameter to enable or disable the proxy server.<br><b>ip:</b> Proxy server IP.<br><b>port:</b> Proxy server port.<br><b>protocol:</b> HTTP or HTTPS protocol used by the proxy server. | Mandatory |

**Request Example:**

```
{
```

(continues on next page)

(continued from previous page)

```

"data":{
  "st_enable_source": true,
  "discovery_url": "https://open.taxiistand.com/services/discovery",
  "fetch_interval": 2,
  "fetch_interval_unit": "Days",
  "begin":20,
  "begin_unit": "Days",
  "st_proxy": {
    "status": false,
    "ip": "127.0.0.1",
    "protocol": "http",
    "port": 22
  },
  "ssl_mode":{
    "ssl_status": false,
    "key_pass": "12345"
  },
  "file_location": "public",
  "files": {
    "cert_file": "client.crt",
    "cert_key": "client.key"
  },
  "stix_version": "1",
  "basic_auth_mode": {
    "username": "guest",
    "basic_auth_status": false,
    "password": "guest"
  }
}
}

```

**Success Response:**

```

{
  "status": "Success",
  "message": "/monitorapi/{pool_UUID}/{logpoint_identifier}/orders/{request_id}"
}

```

## 4.4 Configuring the STIX/TAXII Enrichment Source for STIX v2.0 and v2.1

You can configure the StixTaxii Enrichment Source using the **PluginConfiguration - Create** API.

### Endpoint URL:

```
https://api-server-host-name/configapi/{pool_UUID}/{logpoint_identifier}/PluginConfiguration/  
↪ StixTaxiiEnrichmentSource
```

### Method:

POST

### Parameters:

| FIELD             | LABEL IN UI       | TYPE    | DESCRIPTION                                                                                                                     | REQUIRED  |
|-------------------|-------------------|---------|---------------------------------------------------------------------------------------------------------------------------------|-----------|
| st_enable_source  | Enable Source     | boolean | Parameter to enable or disable fetching of STIX data from a TAXII server.                                                       | Mandatory |
| discovery_url     | Base URL          | String  | Location of the discovery service in the TAXII server.                                                                          | Mandatory |
| enable_pagination | Enable Pagination | boolean | Enable Pagination to separate data fetching into pages.<br><br><b>fetch-per_page:</b> Number of data to be retrieved in a page. | Optional  |
| begin             | Fetch From        | int     | Parameter to fetch data from the last selected month, hour, or day.                                                             | Mandatory |
| begin_unit        | Fetch From        | String  | Unit of the begin.                                                                                                              | Mandatory |
| fetch_interval    | Fetch Interval    | int     | An interval between the adjacent fetches.                                                                                       | Mandatory |

Continued on next page

Table 2 – continued from previous page

| FIELD               | LABEL IN UI          | TYPE   | DESCRIPTION                                                                                                                                                                                           | REQUIRED  |
|---------------------|----------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| fetch_interval_unit | Fetch Interval       | String | Unit of the fetch interval.                                                                                                                                                                           | Mandatory |
| stix_version        | Version              | String | STIX Version.                                                                                                                                                                                         | Mandatory |
| basic_auth_mode     | Basic Authentication | JSON   | Basic Authentication:<br><br><b>basic_auth_status:</b> Parameter to enable or disable the basic authentication.<br><b>username:</b> TAXII server username.<br><b>password:</b> TAXII server password. | Mandatory |
| ssl_mode            | SSL Authentication   | JSON   | SSL Authentication:<br><br><b>ssl_status:</b> Parameter to enable or disable the SSL authentication.<br><b>key_pass:</b> Password used to decrypt the SSL key.                                        | Mandatory |
| file_location       | –                    | String | File location.                                                                                                                                                                                        | Mandatory |
| files               | Files                | JSON   | TAXII server SSL configuration:<br><br><b>cert_file:</b> SSL certificate.<br><b>cert_key:</b> SSL key.                                                                                                | Mandatory |

Continued on next page



Table 2 – continued from previous page

| FIELD    | LABEL IN UI         | TYPE | DESCRIPTION                                                                                                                                                                                                                                                                      | REQUIRED  |
|----------|---------------------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| st_proxy | Proxy Configuration | JSON | <p>TAXII server Proxy configuration:</p> <p><b>status:</b> Parameter to enable or disable the proxy server.</p> <p><b>ip:</b> Proxy server IP.</p> <p><b>port:</b> Proxy server port.</p> <p><b>protocol:</b> <i>HTTP</i> or <i>HTTPS</i> protocol used by the proxy server.</p> | Mandatory |

**Request Example:**

```
{
  "data":{
    "st_enable_source": true,
    "discovery_url": "https://open.taxiistand.com/services/discovery",
    "enable_pagination": true,
    "fetch_per_page":1000,
    "fetch_interval": 2,
    "fetch_interval_unit": "Days",
    "begin":20,
    "begin_unit": "Days",
    "st_proxy": {
      "status": false,
      "ip": "127.0.0.1",
      "protocol": "http",
      "port": 22
    },
    "ssl_mode":{
      "ssl_status": false,
      "key_pass": "12345"
    },
    "file_location": "public",
    "files": {
      "cert_file": "client.crt",
      "cert_key": "client.key"
    },
    "stix_version": "2",
    "basic_auth_mode": {
      "username": "guest",
      "basic_auth_status": false,
      "password": "guest"
    }
  }
}
```

**Success Response:**

```
{
  "status": "Success",
  "message": "/monitorapi/{pool_UUID}/{logpoint_identifier}/orders/{request_id}"
}
```

## 4.5 General Information

You can find the details about the fetched data in **PluginConfiguration-List** API.

### Endpoint URL:

```
https://api-server-host-name/configapi/{pool_UUID}/{logpoint_identifier}/PluginConfiguration/
↪ Ti_general
```

### Method:

```
GET
```

### Success Response:

```
[
  {
    "services": {
      "stix_taxii": {
        "last_successful_fetch": 0,
        "name": "Stix Taxii",
        "error": null,
        "fetch_status": "Completed",
        "no_of_entries": 0,
        "last_fetch_attempt": 1569403863
      },
    },
    "no_of_entries": 0,
    "type": "ti_general",
    "tid": "",
    "id": "5c81f48e10959135395cabea"
  }
]
```

## 4.6 Listing all the StixTaxii Enrichment Source Configurations

You can list the StixTaxii configurations using the **PluginConfiguration - List** API.

### Endpoint URL:

```
https://api-server-host-name/configapi/{pool_UUID}/{logpoint_identifier}/PluginConfiguration/
↪ Ti_stixtaxii
```

### Method:

GET

**Success Response:**

```
[
  {
    "st_proxy": {
      "status": true,
      "ip": "127.0.0.1",
      "protocol": "http",
      "port": 22
    },
    "begin": 1,
    "ssl_mode": {
      "key_pass": "pass1",
      "ssl_status": True
    },
    "cert_file": "certificate.crt",
    "cert_key": "privateKey.key",
    "id": "5d8b2a522be2374b84949c82",
    "basic_auth_mode": {
      "username": "user1",
      "basic_auth_status": true,
      "password": "psw1"
    },
    "stix_version": "2",
    "fetch_interval": 1,
    "st_enable_source_confirmed": false,
    "tid": "",
    "discovery_url": "http://taxiiserver.com/taxii-discovery-service",
    "fetch_interval_unit": "Hours",
    "st_enable_source": true
  }
]
```

## 4.7 Editing the STIX/TAXII Enrichment Source Configuration

You can edit a StixTaxii configuration using the **PluginConfiguration - Edit** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/{pool_UUID}/{logpoint_identifier}/PluginConfiguration/
↪ StixTaxiiEnrichmentSource/{id}
```

**Method:**

PUT

**Parameters:**

| FIELD               | LABEL IN UI          | TYPE    | DESCRIPTION                                                                                                                                                                                                            | REQUIRED  |
|---------------------|----------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| st_enable_source    | Enable Source        | boolean | Parameter to enable or disable fetching of <i>STIX</i> data from a <i>TAXII</i> server.                                                                                                                                | Mandatory |
| discovery_url       | Base URL             | String  | Location of the discovery service in the <i>TAXII</i> server.                                                                                                                                                          | Mandatory |
| enable_pagination   | Enable Pagination    | boolean | Enable Pagination to separate data fetching into pages.<br><br><b>fetch-per_page:</b><br>Number of data to be retrieved in a page.                                                                                     | Optional  |
| begin               | Fetch From           | int     | Parameter to fetch data from the last selected month, hour or day.                                                                                                                                                     | Mandatory |
| begin_unit          | Fetch From           | String  | Unit of the begin.                                                                                                                                                                                                     | Mandatory |
| fetch_interval      | Fetch Interval       | int     | An interval between the adjacent fetches.                                                                                                                                                                              | Mandatory |
| fetch_interval_unit | Fetch Interval       | String  | Fetch interval unit.                                                                                                                                                                                                   | Mandatory |
| stix_version        | Version              | String  | <i>STIX</i> Version.                                                                                                                                                                                                   | Mandatory |
| basic_auth_mode     | Basic Authentication | JSON    | Basic Authentication:<br><br><b>basic_auth_status:</b><br>Parameter to enable or disable the basic authentication.<br><b>username:</b> <i>TAXII</i> server username.<br><b>password:</b> <i>TAXII</i> server password. | Mandatory |

Continued on next page

Table 3 – continued from previous page

| FIELD         | LABEL IN UI         | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                            | REQUIRED  |
|---------------|---------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| ssl_mode      | SSL Authentication  | JSON   | SSL Authentication:<br><br><b>ssl_status</b> : Parameter to enable or disable the SSL authentication.<br><b>key_pass</b> : Password used to decrypt the SSL key.                                                                                                       | Mandatory |
| file_location | –                   | String | File location.                                                                                                                                                                                                                                                         | Mandatory |
| files         | Files               | JSON   | TAXII server SSL configuration:<br><br><b>cert_file</b> : SSL certificate.<br><b>cert_key</b> : SSL key.                                                                                                                                                               | Mandatory |
| st_proxy      | Proxy Configuration | JSON   | TAXII server Proxy configuration:<br><br><b>status</b> : Parameter to enable or disable the proxy server.<br><b>ip</b> : IP of the proxy server.<br><b>port</b> : Port of the proxy server.<br><b>protocol</b> : <i>HTTP</i> or <i>HTTPS</i> used by the proxy server. | Mandatory |
| id            | –                   | String | Existing StixTaxii Enrichment Source ID . Obtain it using the <b>StixTaxiiEnrichmentSource - List</b> API.                                                                                                                                                             | Mandatory |

**Request Example:**

```
{
  "data":{
    "st_enable_source": true,
    "discovery_url": "https://open.taxiistand.com/services/discovery",
    "fetch_interval": 2,
    "fetch_interval_unit": "Days",
    "begin": 20,
    "begin_unit": "Days",
    "st_proxy": {
      "status": false,
      "ip": "127.0.0.1",
      "protocol": "http",
      "port": 22
    },
    "ssl_mode":{
      "ssl_status": false,
      "key_pass": "12345"
    },
    "file_location": "public",
    "files": {
      "cert_file": "client.crt",
      "cert_key": "client.key"
    },
    "stix_version": "2",
    "basic_auth_mode": {
      "username": "guest",
      "basic_auth_status": false,
      "password": "guest"
    }
  }
}
```

**Success Response:**

```
{
  "status": "Success",
  "message": "/monitorapi/{pool_UUID}/{logpoint_identifier}/orders/{request_id}"
}
```

## 4.8 Deleting the STIX/TAXII Enrichment Source Configuration

You can delete a StixTaxii configuration using the **PluginConfiguration - Trash** API.

### Endpoint URL:

```
https://api-server-host-name/configapi/{pool_UUID}/{logpoint_identifier}/PluginConfiguration/
↪StixTaxiiEnrichmentSource/{id}
```

### Method:

Delete

### Parameters:

| FIELD | LABEL IN UI | TYPE   | DESCRIPTION                                                                                            | REQUIRED  |
|-------|-------------|--------|--------------------------------------------------------------------------------------------------------|-----------|
| id    | –           | String | Existing StixTaxiiEnrichmentSource ID. Obtain it using the <b>StixTaxiiEnrichmentSource - List</b> API | Mandatory |

### Success Response:

```
{
  "status": "Success",
  "message": "/monitorapi/{pool_UUID}/{logpoint_identifier}/orders/{request_id}"
}
```

## 4.9 Deleting the SSL Certificate File from the Fabric Storage

### 4.9.1 Trash Private Uploads

You can delete the uploaded certificate files in a private storage in the Fabric storage using the **PluginConfiguration-TrashPrivateUploads** API.

### Endpoint URL:

```
https://api-server-host-name/configapi/{pool_UUID}/PluginConfiguration/
↪StixTaxiiEnrichmentSource/{file_name}
```

### Method:



DELETE

**Parameters:**

| FIELD     | LABEL IN UI | TYPE   | DESCRIPTION         | REQUIRED  |
|-----------|-------------|--------|---------------------|-----------|
| file_name | –           | String | File to be deleted. | Mandatory |

**Success Response:**

```
{
  "status": "Success",
  "message": "certificate.crt successfully deleted."
}
```

## 4.9.2 Trash Public Uploads

You can delete the certificate uploaded files in a public storage in the Fabric storage using the **PluginConfiguration-TrashPublicUploads** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/PluginConfiguration/StixTaxiiEnrichmentSource/{file_
↪ name}
```

**Method:**

DELETE

**Header:**

| FIELD        | LABEL IN UI | DESCRIPTION                                                                   |
|--------------|-------------|-------------------------------------------------------------------------------|
| Content-Type | –           | Content type of the certificate file. It must be <i>Multipart/Form-data</i> . |

**Parameters:**

| FIELD     | LABEL IN UI | TYPE   | DESCRIPTION         | REQUIRED  |
|-----------|-------------|--------|---------------------|-----------|
| file_name | –           | String | File to be deleted. | Mandatory |

**Success Response:**

```
{  
  "status": "Success",  
  "message": "certificate.crt successfully deleted."  
}
```

## STIXTAXII - REFRESHLIST

### 5.1 Refreshing the list for StixTaxii Collections

You can refresh the updated collections of StixTaxii using the **PluginConfiguration - RefreshList** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/{pool_UUID}/{logpoint_identifier}/PluginConfiguration/  
↪ StixTaxiiEnrichmentSource/refreshlist
```

**Method:**

```
POST
```

**Request Example:**

```
{  
  "data": {  
  }  
}
```

**Success Response:**

```
{  
  "status": "Success",  
  "message": "/monitorapi/{pool_UUID}/{logpoint_identifier}/orders/{request_id}"  
}
```

## STIXTAXII - TRASH

## 6.1 Deleting StixTaxii from the Fabric Storage

### 6.1.1 Private Uploads

You can delete StixTaxii from a private storage in the Fabric Storage using the **Upload - TrashPrivate** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/Uploads/{pool_UUID}/{file_name}
```

**Method:**

```
DELETE
```

**Parameters:**

| FIELD | TYPE   | DESCRIPTION                                                              | REQUIRED  |
|-------|--------|--------------------------------------------------------------------------|-----------|
| id    | String | StixTaxii application ID. Obtain it using the <b>Plugins - List</b> API. | Mandatory |

**Success Response:**

```
{
  "status": "Success",
  "message": "monitorapi/{pool_UUID}/{logpoint_identifier}/orders/{request_id} "
}
```

### 6.1.2 Public Uploads

You can delete StixTaxii from a public storage in the Fabric Storage using the **Upload - TrashPrivate** API.

**Endpoint URL:**

```
https://api-server-host-name/configapi/Uploads/{file_name}
```

**Method:**

```
DELETE
```

**Parameters:**

| FIELD | TYPE   | DESCRIPTION                                                              | REQUIRED  |
|-------|--------|--------------------------------------------------------------------------|-----------|
| id    | String | StixTaxii application ID. Obtain it using the <b>Plugins - List</b> API. | Mandatory |

**Success Response:**

```
{
  "status": "Success",
  "message": "monitorapi/{pool_UUID}/{logpoint_identifier}/orders/{request_id}"
}
```